

### TYPICAL INDICATOR ORDERING EXAMPLE

**LB 01 G W01 — 5C 12 — JC**

**Shapes**

|    |             |
|----|-------------|
| 01 | Square      |
| 02 | Round       |
| 03 | Rectangular |

**Housing**

|   |       |
|---|-------|
| K | Black |
| G | Gray  |

**Terminals**

|     |                                                   |
|-----|---------------------------------------------------|
| W01 | Silver Solder Lug/<br>Quick Connect<br>Terminals* |
|-----|---------------------------------------------------|

**Lamps**

**Incandescent Lamp Used with Solid Cap**

|    |         |
|----|---------|
| 05 | 5-volt  |
| 12 | 12-volt |

**Incandescent or Neon Used with Insert Cap**

|    |                      |
|----|----------------------|
| 01 | 110-volt Neon        |
| 05 | 5-volt Incandescent  |
| 12 | 12-volt Incandescent |

**Bright LED Used with LED Cap**

| Colors   | Resistor            |
|----------|---------------------|
| 5C Red   | No Code No Resistor |
| 5D Amber | 05 5-volt           |
|          | 12 12-volt          |
| 5F Green | 24 24-volt          |

**Super Bright LED Used with LED Cap**

|    |       |
|----|-------|
| 6B | White |
| 6F | Green |
| 6G | Blue  |

**Cap Types & Colors**

**Solid Cap: Lens/Filter Colors**

|    |              |
|----|--------------|
| BJ | White/Clear  |
| CJ | Red/Clear    |
| EJ | Yellow/Clear |
| FJ | Green/Clear  |
| GJ | Blue/Clear   |

**Insert Cap: Lens/Filter Colors**

|     |              |
|-----|--------------|
| JB  | Clear/White  |
| JC  | Clear/Red    |
| JE  | Clear/Yellow |
| *JF | Clear/Green  |
| *JG | Clear/Blue   |

\*JF & JG not suitable with neon.

**LED Cap: Lens/Diffuser Colors**

|    |             |
|----|-------------|
| JB | Clear/White |
| JC | Clear/Red   |
| JD | Clear/Amber |
| JF | Clear/Green |


**LED Cap: Lens/Diffuser Colors**

|    |             |
|----|-------------|
| JB | Clear/White |
|----|-------------|

\* Wire harness & cable assemblies offered only in Americas

### DESCRIPTION FOR TYPICAL ORDERING EXAMPLE



**LB01GW01-5C12-JC**



SHAPES & PANEL CUTOUTS


01

.622" (15.8mm)  
Square





02

.854" (21.7mm)  
Round



03

.622" x .866" (15.8mm x 22.0mm)  
Rectangular



Panel Thickness: .039" ~ .157" (1.0 ~ 4.0mm)

HOUSING

Housing Colors Available:

K

Black


G

Gray

TERMINALS

W01

Silver Solder Lug/.110" (2.8mm) Quick Connect



LAMP CODES & SPECIFICATIONS

Incandescent Lamp for Solid Colored and Colored Insert Caps

|                                                                                                                                       |                     |               |                |        |
|---------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------------|----------------|--------|
| <div>AT607</div> <div></div> <div>T-1 Bi-pin</div> |                     | <div>05</div> | <div>12</div>  |        |
|                                                                                                                                       | Voltage             | V             | 5V AC          | 12V AC |
|                                                                                                                                       | Current             | I             | 115mA          | 60mA   |
|                                                                                                                                       | Endurance           | Hours         | 10,000 average |        |
|                                                                                                                                       | Ambient Temp. Range |               | -25°C ~ +50°C  |        |

Neon Lamp for Colored Insert Cap

|                                                                                                                                        |                                                                    |               |                |
|----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|---------------|----------------|
| <div>AT607N</div> <div></div> <div>T-1 Bi-pin</div> |                                                                    | <div>01</div> |                |
|                                                                                                                                        | Voltage                                                            | V             | 110V AC        |
|                                                                                                                                        | Current                                                            | I             | 1.5mA          |
|                                                                                                                                        | Endurance                                                          | Hours         | 10,000 average |
|                                                                                                                                        | Ambient Temp. Range                                                |               | -25°C ~ +50°C  |
|                                                                                                                                        | Recommended Resistors: 33K ohms for 110V AC; 100K ohms for 220V AC |               |                |

The electrical specifications shown are determined at a basic temperature of 25°C.

### LED COLORS & SPECIFICATIONS

The electrical specifications shown are determined at a basic temperature of 25°C. Polarity marks are on the device.

If the source voltage exceeds the rated voltage, a ballast resistor is required.

The resistor value can be calculated by using the formula in the Supplement section.

Additional lamp detail is shown in the Accessories & Hardware section.


#### Bright LED without Resistor

| AT635                                                                                                                                                                                                                      | Color Codes                       | Red          | Amber | Green | No Resistor  |             |           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|--------------|-------|-------|--------------|-------------|-----------|
|                                                                                                                                                                                                                            |                                   | 5C           | 5D    | 5F    | No Code      | No Resistor |           |
| LEDs are colored in OFF state.<br><br><br>T-1 1/2 Bi-pin | Forward Peak Current              | $I_{FM}$     |       |       | 30mA         | 30mA        | 30mA      |
|                                                                                                                                                                                                                            | Continuous Forward Current        | $I_F$        |       |       | 20mA         | 20mA        | 20mA      |
|                                                                                                                                                                                                                            | Forward Voltage                   | $V_F$        |       |       | 1.9V         | 2.0V        | 2.1V      |
|                                                                                                                                                                                                                            | Reverse Peak Voltage              | $V_{RM}$     |       |       | 5V           | 5V          | 5V        |
|                                                                                                                                                                                                                            | Current Reduction Rate Above 25°C | $\Delta I_F$ |       |       | 0.42mA/°C    | 0.42mA/°C   | 0.42mA/°C |
|                                                                                                                                                                                                                            | Ambient Temperature Range         |              |       |       | -25° ~ +50°C |             |           |


#### Bright LED with Resistor

| AT627 with Resistor                                                                               | Color Codes:                      | Red          | Amber | Green | Resistor Codes |      |      |
|---------------------------------------------------------------------------------------------------|-----------------------------------|--------------|-------|-------|----------------|------|------|
|                                                                                                   |                                   | 5C           | 5D    | 5F    | 05             | 12   | 24   |
| <br>T-1 Bi-pin | Forward Peak Current              | $I_{FM}$     |       |       | —              | —    | —    |
|                                                                                                   | Continuous Forward Current        | $I_F$        |       |       | 52mA           | 26mA | 13mA |
|                                                                                                   | Forward Voltage                   | $V_F$        |       |       | 5V             | 12V  | 24V  |
|                                                                                                   | Reverse Peak Voltage              | $V_{RM}$     |       |       | 4V             | 8V   | 16V  |
|                                                                                                   | Current Reduction Rate Above 25°C | $\Delta I_F$ |       |       | 0.50mA/°C      |      |      |
|                                                                                                   | Ambient Temperature Range         |              |       |       | -25° ~ +50°C   |      |      |


AT627  
5-volt  
4-element  
with Resistor



AT627  
12-volt  
4-element  
with Resistor



AT627  
24-volt  
4-element  
with Resistor



#### Super Bright Single Element LED


| AT625G Blue<br>AT631B White<br>AT632F Green                                                                                                                                              | Color                             | ATTENTION<br>ELECTROSTATIC<br>SENSITIVE DEVICES |       |      | 6B           | 6F   | 6G   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------------------------|-------|------|--------------|------|------|
|                                                                                                                                                                                          |                                   | White                                           | Green | Blue |              |      |      |
| <br><br>T-1 Bi-pin | Forward Peak Current              | $I_{FM}$                                        |       |      | 30mA         | 30mA | 30mA |
|                                                                                                                                                                                          | Continuous Forward Current        | $I_F$                                           |       |      | 20mA         | 20mA | 20mA |
|                                                                                                                                                                                          | Forward Voltage                   | $V_F$                                           |       |      | 3.6V         | 3.5V | 3.6V |
|                                                                                                                                                                                          | Reverse Peak Voltage              | $V_{RM}$                                        |       |      | 5V           | 5V   | 5V   |
|                                                                                                                                                                                          | Current Reduction Rate Above 25°C | $\Delta I_F$                                    |       |      | 0.50mA/°C    |      |      |
|                                                                                                                                                                                          | Ambient Temperature Range         |                                                 |       |      | -25° ~ +50°C |      |      |

## CAP TYPES & COLOR COMBINATIONS


Color Codes: B White C Red D Amber E Yellow F Green G Blue J Clear

### Solid Cap for Incandescent Lamp


Lens/Filter  
Colors Available:




**AT476**  
Square




**AT4012**  
Round



**AT4026**  
Rectangular



Translucent Colored Lens



Transparent Clear Filter




Lamp AT607


Material: Polycarbonate Finish: Glossy

### Insert Cap for Incandescent or Neon Lamp


Lens/Filter  
Colors Available:




**AT477**  
Square




**AT4013**  
Round



**AT4027**  
Rectangular



Transparent Clear Lens



Translucent Colored Filter



Lamp AT607 or 607N

Material: Polycarbonate Finish: Glossy


JF and JG not suitable with neon lamp.

### Cap for Bright LED without Resistor


Lens/Diffuser  
Colors Available:




**AT4176**  
Square




**AT4178**  
Round




**AT4177**  
Rectangular



Transparent Clear Lens



Translucent Colored Diffuser



Bright LED  
AT635


Material: Polycarbonate Finish: Glossy

### Cap for Bright LED with Resistor


Lens/Diffuser  
Colors Available:




**AT4162**  
Square




**AT4164**  
Round




**AT4163**  
Rectangular



Transparent Clear Lens



Translucent Colored Diffuser



Bright LED  
AT627

Material: Polycarbonate Finish: Glossy

### CAP TYPES & COLOR COMBINATIONS

#### Cap for Super Bright LEDs




**Clear Lens  
White Diffuser**


**AT4129  
Square**

**AT4128  
Round**

**AT4130  
Rectangular**



**Transparent  
Clear Lens**






**Translucent  
White Diffuser**






**LEDs AT625  
AT631 AT632**

Material:  
Polycarbonate  
Finish: Glossy






### TYPICAL INDICATOR DIMENSIONS

#### Square






**LB01KW01-12-CJ**

#### Round



**LB02KW01-12-CJ**

#### Rectangular



**LB03KW01-12-CJ**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)