

Fusing Equipment

Electrical Apparatus

240-61

NXC® Full Range Current-Limiting Capacitor Fuse

GENERAL

Greater latitude in capacitor bank design is now possible with the Cooper Power Systems NXC® outdoor, current-limiting capacitor fuse. It allows safe fusing of at least 50,000 joules of parallel connected energy.

Fast, full-range clearing capability, inherent advantage of the NXC® current-limiting fuse line, allows the NXC to perform effectively under both high and low fault currents.

Typical applications include use in high fault areas, fusing of individual capacitors, capacitive circuits requiring positive isolation, circuits where let-through current must be restricted, areas where burning debris cannot be tolerated and where high noise levels are undesirable.

The NXC fuse makes use of an automatic leader wire ejection feature for positive interruption and capacitor isolation. Another feature is the visible indication of a sensed fault. Both clearing and indicating operations take place without the functioning of hinges, flippers or other mechanical devices. See Table 1 for fusing recommendations.

APPLICATION

Table 1 lists the individual fusing recommendations for applying NXC fuses in outdoor capacitor banks. The fusing tables are based on the following:

$$I_{\text{Capacitor}} = \frac{\text{kVar unit}}{\text{kV unit}}$$

$$I_{\text{Fuse}} = I_{\text{Capacitor}} \times 1.35 \text{ Protective Margin}$$

The protective margin accounts for normal overvoltages, harmonics, capacitor tolerances and a 25° C. ambient.

TEMPERATURE DERATING

Temperature derating is required when NXC fuses are applied in ambient conditions exceeding 25° C. The derating formula is:

$$A_T = A_{25} [1 - .0065 (T-25)]$$

A_T = Amp rating of fuse at "T"° C.

A₂₅ = Amp rating of fuse at 25° C.

T = Temperature of maximum ambient the fuse will be subjected to at any time.



Figure 1. NXC outdoor capacitor fuse, available in voltage ratings of 8.3, 15.5 and 23 kV, offers positive leader wire ejection for reliable interruption and elimination of electrical stress to circuit apparatus. Top end cap has provision for convenient bus bar mounting.

TABLE 1
Fusing Recommendations

Capacitor or Unit Voltage Rating	Fuse Voltage Rating (kV)	50 kVar*	100 kVar	150 kVar	200 kVar	300 kVar	400 kVar
2400	8.3	30	65	90**	—	—	—
2770	8.3	25	65	80**	—	—	—
4160	8.3	18	40	65	65	—	—
4800	8.3	18	30	45	65	—	—
6640	8.3	18	25	40	45	65	90**
7200	8.3	18	25	30	40	65	80**
7620	8.3	18	18	30	40	65	80**
7960	8.3	18	18	30	40	65	80**
8320	15.5	10	18	25	35	50**	70**
9960	15.5	10	18	25	30	50**	60**
12470	15.5	—	12	18	25	35	50**
13280	15.5	—	12	18	25	35	50**
13800	15.5	—	10	18	25	30	50**
14400	15.5	—	10	18	25	30	50**
19920	23.0	—	12	12	18	25	36**
21600	23.0	—	12	12	18	25	25

*For 50 kVar capacitors, it is difficult to choose reasonably sized fuses which will withstand the I²t outrush. This occurs due to the fact that I²t withstand goes down exponentially with fuse link rating rather than linearly. Consequently, the 50 kVar capacitor fusing recommendations only cover those units with voltages up to 9960 V.

**Indicates 2 fuses in parallel.

Example:

Select proper fuse rating for a 7200V 200 kVar capacitor to be used in an enclosed bank with maximum ambient of 55° C.

$$I_{\text{Capacitor}} = \frac{\text{kVar unit}}{\text{kV unit}} = \frac{200}{7.2} = 27.7 \text{ A}$$

$$I_{\text{Fuse}} = I_{\text{Capacitor}} \times 1.35 = 27.7 \times 1.35 = 37.39 \text{ A}$$

Choose 40A NXC and derate for 55° C. ambient

$$A_T = A_{25} [1 - .0065 (T-25)]$$

$$A_{55} = 40 [1 - .0065 (55-25)]$$

$$A_{55} = 40 [.805]$$

$$A_{55} = 32.2$$

32.2 is less than required 37.39. The fuse is not adequate.

Choose 45 A NXC and derate for 55° C. ambient.

$$A_{55} = 45 [.805] = 36.23$$

36.23 is less than required 37.39.

The 45 A NXC fuse is not adequate.

Choose 65 A NXC and derate for 55° C. ambient.

$$A_{55} = 65 [.805] = 52.32$$

52.32 exceeds 37.38 amps. 65 A

NXC is proper choice.

TABLE 2
Ratings and Ordering Information

Voltage (kV)	Continuous Current (amps)	Interrupting Symmetrical (amps)	Catalog Number	Dimensions (in.)		Approx. Weight (lb)
				A	B	
8.3	10	50,000	FA5J10	8	2 1/8	2.5
	18		FA5J18			
	25		FA5J25			
	30		FA5J30			
	40		FA5J40			
	45		FA5J45*			
65	FA5J65*	9 3/16	3 9/16	7.8		
15.5	10	50,000	FA6J10	12 11/32	2 1/8	3.4
	12		FA6J12			
	18		FA6J18			
	25		FA6J25			
	30		FA6J30			
	35		FA6J35*			
43	FA6J43*	2 1/8	4.3			
23	12	50,000	FA7J12*	15 5/32	2 1/8	3.9
	18		FA7J18	15 5/32	2 1/8	3.9
	25		FA7J25*	18 3/16	2 1/8	5.3

* Contact your Cooper Power Systems representative for information on pricing and availability.

ADDITIONAL INFORMATION

Cooper Power Systems offers a variety of additional literature and reference material on NXC fuses to assist in application and coordination.

Bulletin 76051 Production I²t Testing of Current-Limiting Fuses
 R240-91-37 8.3 kV NXC Capacitor Fuse-TCC Curves
 R240-91-38 15.5 kV NXC Capacitor Fuse-TCC Curves
 R240-91-39 23 kV NXC Capacitor Fuse-TCC Curves
 S240-61-1 Type NXC Current-Limiting-Fuse – Installation Instructions

Contact your Cooper Power Systems representative for further information or other applications.

DIMENSIONS




Figure 2.
Typical Installation.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cooper Bussmann:](#)

[NXC-20](#) [NXC-30](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru