

Is Now Part of



## **ON Semiconductor**®

# To learn more about ON Semiconductor, please visit our website at <u>www.onsemi.com</u>

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at <a href="https://www.onsemi.com">www.onsemi.com</a>. Please email any questions regarding the system integration to <a href="https://www.onsemi.com">Fairchild\_questions@onsemi.com</a>.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized applications, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an equif prese

September 2015



## FAN4800AU / FAN4800CU PFC/ PWM Controller Combination

## Features

- Pin-to-Pin Compatible with ML4800, FAN4800, CM6800, and CM6800A
- PWM Configurable for Current-Mode or Feed-Forward Voltage-Mode Operation
- Internally Synchronized Leading-Edge PFC and Trailing-Edge PWM in One IC
- Low Operating Current
- Innovative Switching-Charge Multiplier Divider
- Average-Current-Mode for Input-Current Shaping
- PFC Over-Voltage and Under-Voltage Protections
- PFC Feedback Open-Loop Protection
- Cycle-by-Cycle Current Limiting for PFC/PWM
- Power-on Sequence Control and Soft-Start
- Line Sagging Protection
- f<sub>RTCT</sub>=4•f<sub>PFC</sub>=4•f<sub>PWM</sub> for FAN4800AU
- f<sub>RTCT</sub>=4•f<sub>PFC</sub>=2•f<sub>PWM</sub> for FAN4800CU

## **Applications**

- Desktop PC Power Supply
- Internet Server Power Supply
- LCD TV/ Monitor Power Supply
- UPS
- Battery Charger
- DC Motor Power Supply
- Monitor Power Supply
- Telecom System Power Supply
- Distributed Power

## **Related Resources**

AN-8027 — FAN480X PFC+PWM Combination Controller Application

## Description

The highly integrated FAN4800AU/CU parts are specially designed for power supplies that consist of boost PFC and PWM. They require very few external components to achieve versatile protections and compensation. They are available in 16-pin DIP and SOP packages.

The PWM can be used in current or Voltage Mode. In Voltage Mode, feed-forward from the PFC output bus can reduce secondary output ripple.

To evaluate FAN4800AU/CU for replacing existing FAN4800A/C, FAN4800AS/CS, old version FAN4800 and ML4800 boards, six things must be completed before the fine-tuning procedure:

- 1. Change  $R_{AC}$  resistor from the old value to a higher resistor value: 6 M $\Omega$  to 8 M $\Omega$ .
- 2. Change RT/CT pin from the existing values to  $R_T$ =6.8 k $\Omega$  and  $C_T$ =1000 pF to have f<sub>PFC</sub>=64 kHz and f<sub>PWM</sub>=64 kHz.
- 3. The VRMS pin needs to be 1.224 V at V<sub>IN</sub>=85 V<sub>AC</sub> for universal input application with line input from 85 V<sub>AC</sub> to 270 V<sub>AC</sub>.
- 4. Change ISENSE pin filter from the exiting values to  $R_{Filter}=51 \Omega$  and  $C_{Filter}=0.01 \mu F$  for higher bandwidth.
- 5. At full load, the average  $V_{\text{VEA}}$  must be ~4.5 V and ripple on  $V_{\text{VEA}}$  needs to be less than 400 mV.
- 6. For the SS pin, the soft-start current has been reduced to half the FAN4800 capacitor.

There are two differences from FAN4800AS/CS to FAN4800AU/CU:

- Add Line Sagging Protection
- Fix Inductance Current Instability during AC Cycle Drop Test

FAN4800AU/CU — PFC/ PWM Controller Combination

## **Ordering Information**

Part Number	Operating Temperature Range	PFC:PWM Frequency Ratio	Package	Packing Method
FAN4800AUN		1:1	16 Pin Dual Inlina Backaga (DIP)	Tuba
FAN4800CUN	40°C to 1105°C	1:2	To-Fill Dual Inline Fackage (DIF)	Tube
FAN4800AUM	-40 °C 10 +105 °C	1:1	16 Din Small Outling Dockage (SOD)	
FAN4800CUM		1:2	To-Fill Small Outline Package (SOP)	Tape & Reel

## **Block Diagram**







## **Pin Configuration**



Figure 6. Pin Configuration (Top View)

## **Pin Definitions**

Pin #	Name	Description
1	IEA	<b>Output of PFC Current Amplifier</b> . The signal from this pin is compared with an internal sawtooth to determine the pulse width for the PFC gate drive.
2	IAC	<b>Input AC Current</b> . For normal operation, this input provides a current reference for the multiplier. The suggested maximum $I_{AC}$ is 65 $\mu$ A.
3	ISENSE	<b>PFC Current Sense</b> . The inverting input of the PFC current amplifier and the output of multiplier and PFC ILIMIT comparator.
4	VRMS	Line-Voltage Detection. The pin is used for the PFC multiplier.
5	SS	<b>PWM Soft-Start</b> . During startup, the SS pin charges an external capacitor with a 10 μA constant current source. The voltage on FBPWM is clamped by SS during startup. If a protection condition occurs and/or PWM is disabled, the SS pin is quickly discharged.
6	FBPWM	PWM Feedback Input. The control input for voltage-loop feedback of PWM stage.
7	RT/CT	<b>Oscillator RC Timing Connection</b> . Oscillator timing node; timing set by $R_T$ and $C_T$ .
8	RAMP	<b>PWM RAMP Input</b> . In Current Mode, this pin functions as the current-sense input. In Voltage Mode, it is the feed-forward sense input from PFC output 380 V (feed-forward ramp).
9	ILIMIT	Peak Current Limit Setting for PWM. The peak current limit setting for PWM.
10	GND	Ground
11	OPWM	<b>PWM Gate Drive</b> . The totem-pole output drive for the PWM MOSFET. This pin is internally clamped under 19 V to protect the MOSFET.
12	OPFC	<b>PFC Gate Drive</b> . The totem-pole output drive for PFC MOSFET. This pin is internally clamped under 15 V to protect the MOSFET.
13	VDD	<b>Supply</b> . The power supply pin. The threshold voltages for startup and turn-off are 11 V and 9.3 V, respectively. The operating current is lower than 10 mA.
14	VREF	Reference Voltage. Buffered output for the internal 7.5 V reference.
15	FBPFC	<b>Voltage Feedback Input for PFC</b> . The feedback input for PFC voltage loop. The inverting input of PFC error amplifier. This pin is connected to the PFC output through a divider network.
16	VEA	Output of PFC Voltage Amplifier. The error amplifier output for PFC voltage feedback loop. A compensation network is connected between this pin and ground.

## **Absolute Maximum Ratings**

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter			Max.	Unit	
V <sub>DD</sub>	DC Supply Voltage			30	V	
V <sub>H</sub>	Voltage on SS, FBPWM, RAMP, VREF Pins	3	-0.3	30.0	V	
V <sub>PFC-OUT</sub>	Voltage on OPFC Pin			V <sub>DD</sub> +0.3V	V	
V <sub>PWM-OUT</sub>	Voltage on OPWM Pin			V <sub>DD</sub> +0.3V	V	
VL	Voltage on IAC, VRMS, RT/CT, ILIMIT, FBF	PFC, VEA Pins	-0.3	7.0	V	
VIEA	Voltage on IEA Pin		0	$V_{VREF}$ +0.3	V	
V <sub>N</sub>	Voltage on ISENSE Pin		-5.0	0.7	V	
I <sub>AC</sub>	Input AC Current			1	mA	
I <sub>REF</sub>	VREF Output Current			5	mA	
I <sub>PFC-OUT</sub>	Peak PFC OUT Current, Source or Sink			0.5	Α	
I <sub>PWM-OUT</sub>	Peak PWM OUT Current, Source or Sink			0.5	А	
PD	Power Dissipation T <sub>A</sub> < 50°C			800	mW	
0	Thermal Desistance (Junction to Air)	DIP		80.80	°C/W	
Θ <sub>JA</sub>	mermai Resistance (Junction to Air)	SOP		104.10		
0	Thermal Desistance (Junction to Case)	DIP		35.38	°C 44/	
OlC	SOP			40.41	-0/00	
TJ	Operating Junction Temperature		-40	+125	°C	
T <sub>STG</sub>	Storage Temperature Range			+150	°C	
TL	Lead Temperature(Soldering)			+260	°C	
FOD	Electrostatia Discharge Carability	Human Body Model, JESD22-A114		6.0		
ESD		Charged Device Model, JESD22-C101		2.0	κv	

#### Notes:

1. All voltage values, except differential voltage, are given with respect to GND pin.

2. Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device.

## **Recommended Operating Conditions**

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Min.	Max.	Unit
T <sub>A</sub>	Operating Ambient Temperature	-40	+105	°C

## **Electrical Characteristics**

Symbol	Parameter	Condition	Min.	Тур.	Max.	Unit
V <sub>DD</sub> Section		•	1			
I <sub>DD-ST</sub>	Startup Current	V <sub>DD</sub> =V <sub>TH-ON</sub> -0.1V, OPFC OPWM Open		30	80	μA
I <sub>DD-OP</sub>	Operating Current	V <sub>DD</sub> =13 V, OPFC OPWM Open	2.0	2.6	5.0	mA
V <sub>TH-ON</sub>	Turn-on Threshold Voltage		10	11	12	V
$ riangle V_{TH}$	Hysteresis		1.3		1.9	V
V <sub>DD-OVP</sub>	V <sub>DD</sub> OVP		27	28	29	V
$ riangle V_{\text{DD-OVP}}$	V <sub>DD</sub> OVP Hysteresis			1		V
Oscillator						
fosc-rt/ct	RT/CT Frequency		240	256	268	kHz
4	PFC & PWM Frequency	R <sub>T</sub> =6.8 kΩ, C <sub>T</sub> =1000 pF	60	64	67	
TOSC	FAN4800CU PWM Frequency		120	128	134	КНZ
f <sub>DV</sub>	Voltage Stability <sup>(3)</sup>	$11 \text{ V} \leq \text{V}_{\text{DD}} \leq 22 \text{ V}$			2	%
f <sub>DT</sub>	Temperature Stability <sup>(3)</sup>	-40°C ~ +105°C			2	%
f <sub>TV</sub>	Total Variation (PFC & PWM) <sup>(3)</sup>	Line, Temperature	58		70	kHz
f <sub>RV</sub>	Ramp Voltage	Valley to Peak		2.8		V
IOSC-DIS	Discharge Current	V <sub>RAMP</sub> =0 V, V <sub>RT/CT</sub> =2.5 V	6.5		15.0	mA
<b>f</b> RANGE	Frequency Range		50		75	kHz
t <sub>PFC-DEAD</sub>	PFC Dead Time	R <sub>T</sub> =6.8 kΩ, C <sub>T</sub> =1000 pF	400	600	800	ns
V <sub>VREF</sub>						
V <sub>VREF</sub>	Reference Voltage	$I_{VREF}=0$ mA, $C_{VREF}=0.1 \ \mu F$	7.4	7.5	7.6	V
$ riangle V_{VREF1}$	Load Regulation of Reference Voltage	$C_{VREF}$ =0.1 µF, $I_{VREF}$ =0 mA to 3.5 mA V <sub>DD</sub> =14 V, Rise/Fall Time > 20 µs		30	50	mV
$ riangle V_{VREF2}$	Line Regulation of Reference Voltage	$C_{\text{VREF}}\text{=}0.1~\mu\text{F},~\text{V}_{\text{DD}}\text{=}11\text{V}$ to 22 V			25	mV
$\bigtriangleup V_{\text{VREF-DT}}$	Temperature Stability <sup>(3)</sup>	-40°C ~ +105°C		0.4	0.5	%
$ riangle V_{VREF-TV}$	Total Variation <sup>(3)</sup>	Line, Load, Temperature	7.35		7.65	V
$\bigtriangleup V_{\text{VREF-LS}}$	Long-Term Stability <sup>(3)</sup>	T <sub>J</sub> =125°C, 0 ~ 1000 Hours	5		25	mV
IVREF-MAX.	Maximum Current	V <sub>VREF</sub> > 7.35 V	5			mA
PFC OVP Co	omparator					
V <sub>PFC-OVP</sub>	Over-Voltage Protection		2.70	2.75	2.80	V
$\bigtriangleup V_{\text{PFC-OVP}}$	PFC OVP Hysteresis		200	250	300	mV
Low-Power I	Detect Comparator					
VVEAOFF	VEA Voltage OFF OPFC		0.2	0.3	0.4	V
V <sub>IN</sub> OK Com	parator					
V <sub>RD-FBPFC</sub>	Voltage Level on FBPFC to Enable OPWM During Startup		2.3	2.4	2.5	V
$ riangle V_{RD-FBPFC}$	Hysteresis		1.0	1.1	1.2	V

Unless otherwise noted,  $V_{DD}$ =15 V,  $T_A$ = 25°C,  $T_A$ =TJ, RT=6.8 k $\Omega$ , and CT=1000 pF.

Continued on the following page ...

## Electrical Characteristics (Continued)

Symbol	Parameter	Condition	Min.	Тур.	Max.	Unit
Voltage Erro	or Amplifier	L	1			
V <sub>REF</sub>	Reference Voltage		2.45	2.50	2.55	V
Av	Open-Loop Gain <sup>(3)</sup>		35	42		dB
Gmv	Transconductance	V <sub>NONINV</sub> =V <sub>INV</sub> , V <sub>VEA</sub> =3.75 V	50	70	90	µmho
I <sub>FBPFC-L</sub>	Maximum Source Current	V <sub>FBPFC</sub> =2 V, V <sub>VEA</sub> =1.5 V	40	50		μA
I <sub>FBPFC-H</sub>	Maximum Sink Current	V <sub>FBPFC</sub> =3 V, V <sub>VEA</sub> =6 V		-50	-40	μA
I <sub>BS</sub>	Input Bias Current		-1		1	μA
$V_{VEA-H}$	Output High Voltage on $V_{VEA}$		5.8	6.0		V
$V_{VEA-L}$	Output Low Voltage on VVEA			0.1	0.4	V
Current Erro	or Amplifier					
Gmı	Transconductance	V <sub>NONINV</sub> =V <sub>INV</sub> , V <sub>IEA</sub> =3.75 V	70	88	105	µmho
VOFFSET	Input Offset Voltage	V <sub>VEA</sub> =0 V, IAC Open	-10		10	mV
V <sub>IEA-H</sub>	Output High Voltage		6.8	7.4	7.8	V
V <sub>IEA-L</sub>	Output Low Voltage			0.1	0.4	V
١L	Source Current	V <sub>ISENSE</sub> = -0.6 V, V <sub>IEA</sub> =1.5 V	35	50		μA
I <sub>H</sub>	Sink Current	V <sub>ISENSE</sub> = +0.6 V, V <sub>IEA</sub> =4.0 V		-50	-35	μA
Aı	Open-Loop Gain <sup>(3)</sup>		40	50		dB
TriFault Dete	ect™			-		
t <sub>FBPFC-OPEN</sub>	Time to FBPFC Open	V <sub>FBPFC</sub> =V <sub>PFC-UVP</sub> to FBPFC OPEN, 470 pF from FBPFC to GND		2	4	ms
Vpfc-uvp	PFC Feedback Under-Voltage Protection		0.4	0.5	0.6	V
Gain Modula	ator					
I <sub>AC</sub>	Input for AC Current <sup>(3)</sup>	Multiplier Linear Range	0		65	μA
		$I_{AC}$ =17.67 µA, V <sub>RMS</sub> =1.080 V V <sub>FBPFC</sub> =2.25 V		7.94		
		I <sub>AC</sub> =20 μA, V <sub>RMS</sub> =1.224 V V <sub>FBPFC</sub> =2.25 V		7.02		
GAIN	Gain Modulator <sup>(4)</sup>	I <sub>AC</sub> =25.69 μA, V <sub>RMS</sub> =1.585 V V <sub>FBPFC</sub> =2.25 V		4.18		
		I <sub>AC</sub> =51.62 μA, V <sub>RMS</sub> =3.169 V V <sub>FBPFC</sub> =2.25 V		1.05		
		I <sub>AC</sub> =62.23 μA, V <sub>RMS</sub> =3.803 V V <sub>FBPFC</sub> =2.25 V		0.73		
BW	Bandwidth <sup>(3)</sup>	I <sub>AC</sub> =40 μA			2	kHz
V <sub>O</sub> (gm)	Output Voltage=5.7 kΩ × (I <sub>SENSE</sub> -I <sub>OFF</sub> SET)	I <sub>AC</sub> =50 μA, V <sub>RMS</sub> =1.224 V V <sub>FBPFC</sub> =2.25 V	0.76	0.80	0.84	V
PFC ILIMIT CO	omparator					
V <sub>PFC-ILIMIT</sub>	Peak Current Limit Threshold Voltage, Cycle-by-Cycle Limit		-1.2	-1.3	-1.4	V
$ riangle V_{PK}$	PFC ILIMIT-Gain Modulator	I <sub>AC</sub> =17.67 μA, V <sub>RMS</sub> =1.08 V V <sub>FBPFC</sub> =2.25 V	400			mV
			Continue	d on the	following	page

Unless otherwise noted,  $V_{DD}$ =15 V,  $T_A$ = 25°C,  $T_A$ =TJ, RT=6.8 k $\Omega$ , and CT=1000 pF.

## Electrical Characteristics (Continued)

Symbol	Parameter	Condition	Min.	Тур.	Max.	Unit
PFC Output	Driver					
$V_{\text{GATE-CLAMP}}$	Gate Output Clamping Voltage	V <sub>DD</sub> =22 V	13	15	17	V
V <sub>GATE-L</sub>	Gate Low Voltage	V <sub>DD</sub> =15 V, I <sub>O</sub> =100 mA			1.5	V
$V_{\text{GATE-H}}$	Gate High Voltage	V <sub>DD</sub> =13 V, I <sub>O</sub> =100 mA	8			V
t <sub>R</sub>	Gate Rising Time	V <sub>DD</sub> =15 V, C <sub>L</sub> =4.7 nF, O/P= 2 V to 9 V	40	70	120	ns
t <sub>F</sub>	Gate Falling Time	V <sub>DD</sub> =15 V, C <sub>L</sub> =4.7 nF, O/P=9 V to 2 V	40	60	110	ns
D <sub>PFC-MAX</sub>	Maximum Duty Cycle	V <sub>IEA</sub> <1.2 V	94	97		%
D <sub>PFC-MIN</sub>	Minimum Duty Cycle	V <sub>IEA</sub> >4.5 V			0	%
PWM ILIMIT C	omparator	·				
V <sub>PWM-ILIMIT</sub>	Threshold Voltage		0.95	1.00	1.05	V
t <sub>PD</sub>	Propagation Delay to Output			250		ns
t <sub>PWM-BNK</sub>	Leading-Edge Blanking Time		170	250	350	ns
PWM Output	t Driver					
$V_{\text{GATE-CLAMP}}$	Gate Output Clamping Voltage	V <sub>DD</sub> =22 V	18	19	20	V
$V_{GATE-L}$	Gate Low Voltage	V <sub>DD</sub> =15 V, I <sub>O</sub> =100 mA			1.5	V
$V_{\text{GATE-H}}$	Gate High Voltage	$V_{DD}$ =13 V, I <sub>O</sub> =100 mA	8			V
t <sub>R</sub>	Gate Rising Time	$V_{DD}$ =15 V, C <sub>L</sub> =4.7 nF, O/P=2 V to 9 V	30	60	120	ns
t <sub>F</sub>	Gate Falling Time	$V_{DD}$ =15 V, C <sub>L</sub> =4.7 nF, O/P=9 V to 2 V	30	50	110	ns
D <sub>PWM-MAX</sub>	Maximum Duty Cycle		49.0	49.5	50.0	%
V <sub>PWM-LS</sub>	PWM Comparator Level Shift		1.3	1.5	1.8	V
Soft-Start						
V <sub>SS-MAX</sub>	Maximum Voltage	V <sub>DD</sub> =15 V	9.5	10.0	10.5	V
I <sub>SS</sub>	Soft-Start Current			10		μA
Brownout						
$V_{RMS-UVL}$	VRMS Threshold LOW		1.00	1.05	1.10	V
$V_{RMS-UVH}$	VRMS Threshold HIGH		1.85	1.90	1.95	V
$\bigtriangleup V_{\text{RMS-UVP}}$	Hysteresis		750	850	950	mV
t <sub>UVP</sub>	Under- Voltage Protection Delay		750	1000	1250	ms
Sagging Pro	tection	-			•	•
$V_{RMS-SAG}$	VRMS Threshold SAG LOW		0.80	0.85	0.90	V
t <sub>SAG</sub>	SAG Protection Delay		28	33	38	ms

Unless otherwise noted, V\_DD=15 V, T\_A=25°C, T\_A=T\_J, R\_T=6.8 k\Omega, and C\_T=1000 pF.

Notes:

3. This parameter, although guaranteed by design, is not 100% production tested.

4. This gain is the maximum gain of modulation with a given  $V_{RMS}$  voltage when  $V_{VEA}$  is saturated to HIGH.





Figure 17. V<sub>RMS-UVP</sub> vs. Temperature

Figure 18. ΔV<sub>RMS-UVP</sub> vs. Temperature

FAN4800AU/CU — PFC/ PWM Controller Combination

## **Typical Characteristics**



Figure 19. V<sub>GATE-CLAMP-PFC</sub> vs. Temperature







Figure 23. Iss vs. Temperature



Figure 20. V<sub>GATE-CLAMP-PWM</sub> vs. Temperature



Figure 22. D<sub>PWM-MAX</sub> vs. Temperature



Figure 24. V<sub>RMS-SAG</sub> vs. Temperature

## **Functional Description**

#### Oscillator

The internal oscillator frequency is determined by the timing resistor and capacitor on the RT/CT pins as shown in Figure 25. The frequency of the internal oscillator is given:

$$f_{OSC} = \frac{1}{0.56 \cdot R_T \cdot C_T + 360C_T}$$
(1)

Because the PWM stage generally uses a forward converter, it is necessary to limit the maximum duty cycle at 50%. To have a small tolerance of the maximum duty cycle, a frequency divider with toggle flip-flops is used, as illustrated in Figure 25. The operation frequency of PFC and PWM stage is 1/4 of oscillator frequency. (For FAN4800CU, the operation frequencies for PFC and PWM stages are 1/4 and 1/2 of oscillator frequency, respectively).

The dead time for the PFC gate drive signal is determined by:

$$t_{DEAD} = 360C_T \tag{2}$$

The dead time should be smaller than 2% of the switching period to minimize line current distortion around the line zero crossing.





Figure 27 shows the interleaved leading / trailing edge modulation, where the turn-off of the PFC drive signal is synchronized to the turn-on of the PWM drive signal. This technique allows the PFC output diode current to flow directly into the downstream DC/DC converter, minimizing the current ripple of PFC output capacitor.

#### **Gain Modulator**

Gain modulator is the key block for the PFC stage because it provides the reference to the current control error amplifier for the input current shaping, as shown in Figure 28. The output current of the gain modulator is a function of V<sub>EA</sub>, I<sub>AC</sub>, and V<sub>RMS</sub>. The gain of the gain modulator is given as a ratio between I<sub>MO</sub> and I<sub>AC</sub> with a given V<sub>RMS</sub> when V<sub>EA</sub> is saturated to HIGH. The gain is inversely proportional to V<sub>RMS</sub><sup>2</sup>, as shown in Figure 29, to implement line feed-forward. This automatically adjusts the reference of current control error amplifier according to the line voltage, such that the input power of PFC converter is not changed with line voltage (as shown in Figure 30).



© 2011 Fairchild Semiconductor Corporation FAN4800AU/CU • Rev. 1.4

www.fairchildsemi.com



Figure 29. Modulation Gain Characteristics



Figure 30. Line Feed-Forward Operation

To sense the RMS value of the line voltage, averaging circuit with two poles is typically employed, as shown in Figure 28. Notice that the input voltage of the PFC is clamped at the peak of the line voltage once the PFC stops switching because the junction capacitance of the bridge diode is not discharged, as shown in Figure 31. Therefore, the voltage divider for VRMS should be designed considering the brownout protection trip-point and minimum operation line voltage.



The rectified sinusoidal signal is obtained by the current flowing into the IAC pin. The resistor  $R_{IAC}$  should be large enough to prevent saturation of the gain modulator, calculating as:

$$\frac{\sqrt{2}V_{LINE}}{R_{LAC}} \cdot G^{MAX} < 140 \mu A \tag{3}$$

where V<sub>LINEMIN</sub> is the line voltage that trips brownout protection, G<sub>MAX</sub> is the maximum modulator gain when V<sub>RMS</sub> is 1.08 V (which can be found in the datasheet), and 140  $\mu$ A is the maximum output current of the gain modulator.

#### **Current Control of Boost Stage**

The FAN4800AU/CU employs two control loops for power factor correction, as shown in Figure 32: a current-control loop and a voltage-control loop. The current-control loop shapes inductor current as shown in Figure 33 based on the reference signal obtained at the IAC pin calculated as:

$$I_L \cdot R_{CS1} = I_{MO} \cdot R_M = I_{AC} \cdot G \cdot R_M$$
(4)



Figure 32. Gain Modulation Block



Figure 33. Inductor Current Shaping

The current-control feedback loop also has a pulse-bypulse current limit comparator that forces the PFC switch to turn off until the next switching cycle if the ISENSE pin voltage drops below -1.3 V.

### Voltage Control of Boost Stage

The voltage-control loop regulates PFC output voltage using an internal error amplifier such that the FB voltage is the same as the internal reference of 2.5 V.

#### **Brownout Protection**

The built-in internal brownout protection comparator monitors the voltage of the VRMS pin. Once VRMS pin voltage is lower than 1.05 V, the PFC stage is shut down to protect the system from over current. FAN4800AU/CU starts up the boost stage once VRMS voltage increases above 1.9 V.

#### TriFault Detect™

To improve power supply reliability, reduce system component count, and simplify compliance to UL 1950 safety standards, the FAN4800AU/CU includes Fairchild's TriFault Detect technology.

In a feedback path failure, the output voltage of the PFC can exceed safe operating limits. TriFault Detect protects the power supply from a failure related to the output feedback by monitoring the FBPFC voltage.

TriFault Detect is an entirely internal circuit. It requires no external components to serve its protective function.



Figure 34. TriFault Detect™

#### **PWM Stage**

The PWM stage is capable of Current Mode or Voltage Mode operation. In Current-Mode, the PWM ramp (RAMP) is usually derived directly from a current-sensing resistor or current transformer in the primary side of the output stage, and is thereby representative of the current flowing in the converter's output stage. ILIMIT, which provides cycle-by-cycle current limiting, is typically connected to RAMP in such applications.

For Voltage-Mode operation, RAMP can be connected to a separate RC timing network to generate a voltage ramp against which the FBPWM voltage is compared. Under these conditions, the voltage feed-forward from the PFC bus can be used for better line transient response.

No voltage error amplifier is included in the PWM stage, as this function is generally performed by KA431, in the secondary side. To facilitate the design of opto-coupler feedback circuitry, an offset voltage is built into the inverting input of PWM comparator. This allows FBPWM to command a zero percent duty cycle when its pin voltage is below 1.5 V.



Figure 35. PWM Ramp Generation Circuit

## **PWM Current Limit**

The ILIMIT pin is a direct input to the cycle-by-cycle current limiter for the PWM section. If the input voltage at this pin exceeds 1 V, the output of the PWM is disabled for until the start of the next PWM clock cycle.

## **VIN OK Comparator**

The V<sub>IN</sub> OK comparator monitors the output of the PFC stage and inhibits the PWM stage if this voltage is less than 2.4 V (96% of its nominal value). Once this voltage goes above 2.4 V, the PWM stage begins soft-start. The PWM stage is shut down when FBPFC voltage drops below 1.3 V.

#### **PWM Soft-Start (SS)**

PWM startup is controlled by the soft-start capacitor. A current source of 10  $\mu$ A supplies the charging current for the soft-start capacitor. PWM startup is prohibited until the soft-start capacitor voltage reaches 1.5 V.

## AC Line Drops Out

FAN4800AU/CU is designed such that the operation of PFC part is not perturbed by AC line dropout. Once line voltage disappears, the error amplifier can be saturated, resulting in abnormal current waveforms when the line voltage is recovered if proper preventive measures are not employed.

With a limited gain modulator operation, FAN4800AU /CU guarantees stable PFC operation even when AC line is recovered from dropout, as shown in Figure 36.



Figure 36. AC Cycle Drop

#### **Line Sag Protection**

When the line sags below its normal operational range, the PFC part keeps operating until the brownout protection is triggered, which has 1 s debounce time. Due to the low line voltage, the gain modulator for current loop is saturated and input current of PFC is limited, resulting in a drop of the PFC output voltage at heavy-load condition. Since the PWM part has a V<sub>IN</sub> OK comparator that shuts down PWM operation when the FBPFC voltage drops below 1.3 V, the downstream DC-DC converter can stop operation while the PFC output voltage drops during line sag. Once the downstream converter stops operation, even the limited PFC input current can charge up the PFC output since the PFC part has no load current. Because this can cause repeated startup and shutdown of downstream converter during line sag, FAN4800AU/CU has line sag protection.

There are two conditions that trigger line sag protection, as shown in Figure 37 and Figure 38. The first condition is when  $V_{RMS}$  is lower than  $V_{RMS-SAG}$  (0.85 V) for longer than  $t_{SAG}$  (33 ms), as shown in Figure 37. The second condition is when  $V_{RMS}$  is lower than  $V_{RMS-SAG}$  (0.85 V) and  $VF_{BPFC}$  is lower than  $V_{IN-OFF}$  (1.3 V), as shown in Figure 38. Once line sag protection is triggered, the PWM and the PFC stop operation until  $V_{RMS}$  increases above 1.9 V.



Figure 37. The First Condition of Sag Protection



Figure 38. The Second condition of Sag Protection





SCALE: 2:1



ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <u>www.onsemi.com/site/pdf/Patent-Marking.pdf</u>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor has against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death ass

#### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910

Japan Customer Focus Center Phone: 81-3-5817-1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

© Semiconductor Components Industries, LLC

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor: FAN4800CUM FAN4800CUN



#### ООО "ЛайфЭлектроникс"

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru

#### www.lifeelectronics.ru