

## Important notice

Dear Customer,

On 7 February 2017 the former NXP Standard Product business became a new company with the tradename **Nexperia**. Nexperia is an industry leading supplier of Discrete, Logic and PowerMOS semiconductors with its focus on the automotive, industrial, computing, consumer and wearable application markets

In data sheets and application notes which still contain NXP or Philips Semiconductors references, use the references to Nexperia, as shown below.

Instead of <http://www.nxp.com>, <http://www.philips.com/> or <http://www.semiconductors.philips.com/>, use **<http://www.nexperia.com>**

Instead of [sales.addresses@www.nxp.com](mailto:sales.addresses@www.nxp.com) or [sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com), use **[salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)** (email)

Replace the copyright notice at the bottom of each page or elsewhere in the document, depending on the version, as shown below:

- © NXP N.V. (year). All rights reserved or © Koninklijke Philips Electronics N.V. (year). All rights reserved

Should be replaced with:

- © **Nexperia B.V. (year). All rights reserved.**

If you have any questions related to the data sheet, please contact our nearest sales office via e-mail or telephone (details via **[salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)**). Thank you for your cooperation and understanding,

Kind regards,

Team Nexperia

# PDTC115T series

NPN resistor-equipped transistors; R1 = 100 k $\Omega$ , R2 = open

Rev. 04 — 17 February 2005

Product data sheet

## 1. Product profile

### 1.1 General description

NPN resistor-equipped transistors.

Table 1: Product overview

| Type number                   | Package       |        | PNP complement |
|-------------------------------|---------------|--------|----------------|
|                               | Philips       | JEITA  |                |
| PDTC115TE                     | SOT416        | SC-75  | PDTA115TE      |
| PDTC115TK                     | SOT346        | SC-59A | PDTA115TK      |
| PDTC115TM                     | SOT883        | SC-101 | PDTA115TM      |
| PDTC115TS <a href="#">[1]</a> | SOT54 (TO-92) | SC-43A | PDTA115TS      |
| PDTC115TT                     | SOT23         | -      | PDTA115TT      |
| PDTC115TU                     | SOT323        | SC-70  | PDTA115TU      |

[1] Also available in SOT54A and SOT54 variant packages (see [Section 2](#)).

### 1.2 Features

- Built-in bias resistor
- Reduces component count
- Simplifies circuit design
- Reduces pick and place costs

### 1.3 Applications

- General-purpose switching and amplification
- Circuit drivers
- Inverter and interface circuits

### 1.4 Quick reference data











Table 2: Quick reference data

| Symbol           | Parameter                 | Conditions | Min | Typ | Max | Unit       |
|------------------|---------------------------|------------|-----|-----|-----|------------|
| V <sub>CEO</sub> | collector-emitter voltage | open base  | -   | -   | 50  | V          |
| I <sub>O</sub>   | output current (DC)       |            | -   | -   | 100 | mA         |
| R1               | bias resistor 1 (input)   |            | 70  | 100 | 130 | k $\Omega$ |

PHILIPS

2. Pinning information

Table 3: Pinning

| Pin                           | Description        | Simplified outline                                                                                            | Symbol                                                                                             |
|-------------------------------|--------------------|---------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| SOT54                         |                    |                                                                                                               |                                                                                                    |
| 1                             | input (base)       | <br>001aab347              | <br>006aaa218   |
| 2                             | output (collector) |                                                                                                               |                                                                                                    |
| 3                             | GND (emitter)      |                                                                                                               |                                                                                                    |
| SOT54A                        |                    |                                                                                                               |                                                                                                    |
| 1                             | input (base)       | <br>001aab348              | <br>006aaa218  |
| 2                             | output (collector) |                                                                                                               |                                                                                                    |
| 3                             | GND (emitter)      |                                                                                                               |                                                                                                    |
| SOT54 variant                 |                    |                                                                                                               |                                                                                                    |
| 1                             | input (base)       | <br>001aab447            | <br>006aaa218 |
| 2                             | output (collector) |                                                                                                               |                                                                                                    |
| 3                             | GND (emitter)      |                                                                                                               |                                                                                                    |
| SOT23, SOT323, SOT346, SOT416 |                    |                                                                                                               |                                                                                                    |
| 1                             | input (base)       | <br>006aaa144            | <br>sym012    |
| 2                             | GND (emitter)      |                                                                                                               |                                                                                                    |
| 3                             | output (collector) |                                                                                                               |                                                                                                    |
| SOT883                        |                    |                                                                                                               |                                                                                                    |
| 1                             | input (base)       | <br>Transparent top view | <br>sym012    |
| 2                             | GND (emitter)      |                                                                                                               |                                                                                                    |
| 3                             | output (collector) |                                                                                                               |                                                                                                    |

### 3. Ordering information

Table 4: Ordering information

| Type number              | Package |                                                                               |         |
|--------------------------|---------|-------------------------------------------------------------------------------|---------|
|                          | Name    | Description                                                                   | Version |
| PDTC115TE                | SC-75   | plastic surface mounted package; 3 leads                                      | SOT416  |
| PDTC115TK                | SC-59A  | plastic surface mounted package; 3 leads                                      | SOT346  |
| PDTC115TM                | SC-101  | leadless ultra small plastic package; 3 solder lands; body 1.0 × 0.6 × 0.5 mm | SOT883  |
| PDTC115TS <sup>[1]</sup> | SC-43A  | plastic single-ended leaded (through hole) package; 3 leads                   | SOT54   |
| PDTC115TT                | -       | plastic surface mounted package; 3 leads                                      | SOT23   |
| PDTC115TU                | SC-70   | plastic surface mounted package; 3 leads                                      | SOT323  |

[1] Also available in SOT54A and SOT54 variant packages (see [Section 2](#) and [Section 9](#)).

### 4. Marking

Table 5: Marking codes

| Type number | Marking code <sup>[1]</sup> |
|-------------|-----------------------------|
| PDTC115TE   | 17                          |
| PDTC115TK   | 28                          |
| PDTC115TM   | G5                          |
| PDTC115TS   | TC115T                      |
| PDTC115TT   | *AK                         |
| PDTC115TU   | *17                         |

[1] \* = -: made in Hong Kong  
 \* = p: made in Hong Kong  
 \* = t: made in Malaysia  
 \* = W: made in China

## 5. Limiting values

**Table 6: Limiting values**

*In accordance with the Absolute Maximum Rating System (IEC 60134).*

| Symbol           | Parameter                 | Conditions                       | Min | Max  | Unit |
|------------------|---------------------------|----------------------------------|-----|------|------|
| V <sub>CBO</sub> | collector-base voltage    | open emitter                     | -   | 50   | V    |
| V <sub>CEO</sub> | collector-emitter voltage | open base                        | -   | 50   | V    |
| V <sub>EBO</sub> | emitter-base voltage      | open collector                   | -   | 5    | V    |
| I <sub>O</sub>   | output current (DC)       |                                  | -   | 100  | mA   |
| I <sub>CM</sub>  | peak collector current    |                                  | -   | 100  | mA   |
| P <sub>tot</sub> | total power dissipation   |                                  |     |      |      |
|                  | SOT416                    | T <sub>amb</sub> ≤ 25 °C [1]     | -   | 150  | mW   |
|                  | SOT346                    | T <sub>amb</sub> ≤ 25 °C [1]     | -   | 250  | mW   |
|                  | SOT883                    | T <sub>amb</sub> ≤ 25 °C [2] [3] | -   | 250  | mW   |
|                  | SOT54                     | T <sub>amb</sub> ≤ 25 °C [1]     | -   | 500  | mW   |
|                  | SOT23                     | T <sub>amb</sub> ≤ 25 °C [1]     | -   | 250  | mW   |
|                  | SOT323                    | T <sub>amb</sub> ≤ 25 °C [1]     | -   | 200  | mW   |
| T <sub>stg</sub> | storage temperature       |                                  | -65 | +150 | °C   |
| T <sub>j</sub>   | junction temperature      |                                  | -   | 150  | °C   |
| T <sub>amb</sub> | ambient temperature       |                                  | -65 | +150 | °C   |

[1] Refer to standard mounting conditions.

[2] Reflow soldering is the only recommended soldering method.

[3] Refer to SOT883 standard mounting conditions; FR4 printed-circuit board with 60  $\mu$ m copper strip line.

## 6. Thermal characteristics

**Table 7: Thermal characteristics**

| Symbol               | Parameter                                   | Conditions  | Min     | Typ | Max | Unit |
|----------------------|---------------------------------------------|-------------|---------|-----|-----|------|
| R <sub>th(j-a)</sub> | thermal resistance from junction to ambient | in free air |         |     |     |      |
|                      | SOT416                                      |             | [1]     | -   | 833 | K/W  |
|                      | SOT346                                      |             | [1]     | -   | 500 | K/W  |
|                      | SOT883                                      |             | [2] [3] | -   | 500 | K/W  |
|                      | SOT54                                       |             | [1]     | -   | 250 | K/W  |
|                      | SOT23                                       |             | [1]     | -   | 500 | K/W  |
|                      | SOT323                                      |             | [1]     | -   | 625 | K/W  |

[1] Refer to standard mounting conditions.


[2] Reflow soldering is the only recommended soldering method.

[3] Refer to SOT883 standard mounting conditions; FR4 printed-circuit board with 60  $\mu$ m copper strip line.


## 7. Characteristics

**Table 8: Characteristics**
 $T_{amb} = 25\text{ }^{\circ}\text{C}$  unless otherwise specified.

| Symbol      | Parameter                            | Conditions                                                                  | Min | Typ | Max | Unit          |
|-------------|--------------------------------------|-----------------------------------------------------------------------------|-----|-----|-----|---------------|
| $I_{CBO}$   | collector-base cut-off current       | $V_{CB} = 50\text{ V}; I_E = 0\text{ A}$                                    | -   | -   | 100 | nA            |
| $I_{CEO}$   | collector-emitter cut-off current    | $V_{CE} = 30\text{ V}; I_B = 0\text{ A}$                                    | -   | -   | 1   | $\mu\text{A}$ |
|             |                                      | $V_{CE} = 30\text{ V}; I_B = 0\text{ A}; T_j = 150\text{ }^{\circ}\text{C}$ | -   | -   | 50  | $\mu\text{A}$ |
| $I_{EBO}$   | emitter-base cut-off current         | $V_{EB} = 5\text{ V}; I_C = 0\text{ A}$                                     | -   | -   | 100 | nA            |
| $h_{FE}$    | DC current gain                      | $V_{CE} = 5\text{ V}; I_C = 1\text{ mA}$                                    | 100 | -   | -   |               |
| $V_{CEsat}$ | collector-emitter saturation voltage | $I_C = 5\text{ mA}; I_B = 0.25\text{ mA}$                                   | -   | -   | 150 | mV            |
| R1          | bias resistor 1 (input)              |                                                                             | 70  | 100 | 130 | k $\Omega$    |
| $C_c$       | collector capacitance                | $I_E = I_e = 0\text{ A}; V_{CB} = 10\text{ V}; f = 1\text{ MHz}$            | -   | -   | 2.5 | pF            |


 $V_{CE} = 5\text{ V}$ 

- (1)  $T_{amb} = 100\text{ }^{\circ}\text{C}$
- (2)  $T_{amb} = 25\text{ }^{\circ}\text{C}$
- (3)  $T_{amb} = -40\text{ }^{\circ}\text{C}$

**Fig 1. DC current gain as a function of collector current; typical values**

 $I_C/I_B = 20$ 

- (1)  $T_{amb} = 100\text{ }^{\circ}\text{C}$
- (2)  $T_{amb} = 25\text{ }^{\circ}\text{C}$
- (3)  $T_{amb} = -40\text{ }^{\circ}\text{C}$

**Fig 2. Collector-emitter saturation voltage as a function of collector current; typical values**

8. Package outline




Fig 3. Package outline SOT416 (SC-75)




Fig 4. Package outline SOT346 (SC-59A/TO-236)




Fig 5. Package outline SOT883 (SC-101)




Fig 6. Package outline SOT54 (SC-43A/TO-92)




Fig 7. Package outline SOT54A




Fig 8. Package outline SOT54 variant




Fig 9. Package outline SOT23 (TO-236AB)




Fig 10. Package outline SOT323 (SC-70)

## 9. Packing information

**Table 9: Packing methods**

The indicated -xxx are the last three digits of the 12NC ordering code. [\[1\]](#)

| Type number | Package       | Description                    | Packing quantity |      |       |
|-------------|---------------|--------------------------------|------------------|------|-------|
|             |               |                                | 3000             | 5000 | 10000 |
| PDTC115TE   | SOT416        | 4 mm pitch, 8 mm tape and reel | -115             | -    | -135  |
| PDTC115TK   | SOT346        | 4 mm pitch, 8 mm tape and reel | -115             | -    | -135  |
| PDTC115TM   | SOT883        | 2 mm pitch, 8 mm tape and reel | -                | -    | -315  |
| PDTC115TS   | SOT54         | bulk, straight leads           | -                | -412 | -     |
| PDTC115TS   | SOT54A        | tape and reel, wide pitch      | -                | -    | -116  |
| PDTC115TS   | SOT54A        | tape ammopack, wide pitch      | -                | -    | -126  |
| PDTC115TS   | SOT54 variant | bulk, delta pinning            | -                | -112 | -     |
| PDTC115TT   | SOT23         | 4 mm pitch, 8 mm tape and reel | -215             | -    | -235  |
| PDTC115TU   | SOT323        | 4 mm pitch, 8 mm tape and reel | -115             | -    | -135  |

[1] For further information and the availability of packing methods, see [Section 14](#).

## 10. Revision history

**Table 10: Revision history**

| Document ID    | Release date                                                                                                                                                                                                                                                                                                               | Data sheet status    | Change notice | Doc. number    | Supersedes  |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------|----------------|-------------|
| PDTC115T_SER_4 | 20050217                                                                                                                                                                                                                                                                                                                   | Product data sheet   | -             | 9397 750 14021 | PDTC115TT_3 |
| Modifications  | <ul style="list-style-type: none"><li>• The types PDTC115TE, PDTC115TK, PDTC115TM, PDTC115TS and PDTC115TU were added.</li><li>• <a href="#">Table 1 "Product overview"</a> added</li><li>• <a href="#">Figure 1</a> and <a href="#">2</a> added</li><li>• <a href="#">Section 9 "Packing information"</a> added</li></ul> |                      |               |                |             |
| PDTC115TT_3    | 20040727                                                                                                                                                                                                                                                                                                                   | Product data sheet   | -             | 9397 750 13505 | PDTC115TT_2 |
| PDTC115TT_2    | 20040510                                                                                                                                                                                                                                                                                                                   | Objective data sheet | -             | 9397 750 13206 | PDTC115TT_1 |
| PDTC115TT_1    | 20040305                                                                                                                                                                                                                                                                                                                   | Objective data sheet | -             | 9397 750 12554 | -           |

## 11. Data sheet status

| Level | Data sheet status <sup>[1]</sup> | Product status <sup>[2] [3]</sup> | Definition                                                                                                                                                                                                                                                                                     |
|-------|----------------------------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| I     | Objective data                   | Development                       | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.                                                                                                    |
| II    | Preliminary data                 | Qualification                     | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.             |
| III   | Product data                     | Production                        | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). |

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

## 12. Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

## 13. Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

## 14. Contact information

For additional information, please visit: <http://www.semiconductors.philips.com>

For sales office addresses, send an email to: [sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com)



15. Contents

|     |                              |   |
|-----|------------------------------|---|
| 1   | Product profile .....        | 1 |
| 1.1 | General description.....     | 1 |
| 1.2 | Features .....               | 1 |
| 1.3 | Applications .....           | 1 |
| 1.4 | Quick reference data.....    | 1 |
| 2   | Pinning information.....     | 2 |
| 3   | Ordering information.....    | 3 |
| 4   | Marking .....                | 3 |
| 5   | Limiting values.....         | 4 |
| 6   | Thermal characteristics..... | 4 |
| 7   | Characteristics.....         | 5 |
| 8   | Package outline .....        | 6 |
| 9   | Packing information.....     | 7 |
| 10  | Revision history.....        | 8 |
| 11  | Data sheet status .....      | 9 |
| 12  | Definitions .....            | 9 |
| 13  | Disclaimers.....             | 9 |
| 14  | Contact information .....    | 9 |



© Koninklijke Philips Electronics N.V. 2005

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 17 February 2005  
Document number: 9397 750 14021

Published in The Netherlands

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)