



Product: [83333E](#)

Electronic, 3 C #24 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

 Request Sample

Product Description

High Temperature Electronic, 3 Conductor 24AWG (19x36) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Product Overview

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | MIL-W-16878/4 (Type E) Spec; Extreme High/Low Temperature Environments; up to 600V analog signals & voltage control |
|------------------------|---------------------------------------------------------------------------------------------------------------------|

Construction Details

Conductor

| Element      | Number of Element | AWG | Stranding | Material             |
|--------------|-------------------|-----|-----------|----------------------|
| Conductor(s) | 3                 | 24  | 19x36     | SC - Silvered Copper |

Insulation

| Element      | Material                       | Thickness [in] | Color Code        |
|--------------|--------------------------------|----------------|-------------------|
| Conductor(s) | PTFE - Polytetrafluoroethylene | 0.010          | White, Black, Red |

Outer Shield Material

| Type  | Material             | Coverage |
|-------|----------------------|----------|
| Braid | SC - Silvered Copper | 85%      |

Outer Jacket Material

| Material                       | Thickness | Diameter |
|--------------------------------|-----------|----------|
| PTFE - Polytetrafluoroethylene | 0.011 in  | 0.137 in |

Electrical Characteristics

Electricals

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                |
|--------------|--------------------|-------------------------------|-------------------------------------------------|-----------------------------|
| Conductor(s) | 22.9 Ohm/1000ft    | 21.9 pF/ft                    | 36.8 pF/ft                                      | 4 Amps per conductor @ 25°C |

Voltage

| Non-UL Voltage Rating |
|-----------------------|
| 600 V                 |

Mechanical Characteristics

Temperature

| Operating       |
|-----------------|
| -65°C to +200°C |

Bend Radius

| Stationary Min. |
|-----------------|
| 1.5 in          |

|                    |               |
|--------------------|---------------|
| Max. Pull Tension: | 42.5 lbs      |
| Bulk Cable Weight: | 17 lbs/1000ft |

Standards and Compliance

|                                 |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Sustainability:                 | CA Prop 65                                                                                              |
| Flammability / Fire Resistance: | IEC 60332-1-2                                                                                           |
| NEMA Compliance:                | NEMA HP3                                                                                                |
| Military Compliance:            | MIL-W-16878/4 (Type E except stranding), (insulated conductors)                                         |
| CPR Euroclass:                  | Fca                                                                                                     |
| European Directive Compliance:  | EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                | China RoHS II (GB/T 26572-2011)                                                                         |

Product Notes

|        |                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------|
| Notes: | Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---------------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.329 Revision Date: 06-15-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)