

# MC74HCT132A

## Quad 2-Input NAND Gate with Schmitt-Trigger Inputs with LSTTL Compatible Inputs

### High-Performance Silicon-Gate CMOS

The MC74HCT132A is identical in pinout to the LS132. The device inputs are compatible with standard CMOS outputs; with pull-up resistors, they are compatible with LSTTL outputs.

The MC74HCT132A can be used to enhance noise immunity or to square up slowly changing waveforms.

#### Features

- Output Drive Capability: 10 LSTTL Loads
- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2.0 to 6.0 V
- Low Input Current: 1.0  $\mu$ A
- High Noise Immunity Characteristic of CMOS Devices
- In Compliance with the Requirements as Defined by JEDEC Standard No. 7A
- Chip Complexity: 72 FETs or 18 Equivalent Gates
- These are Pb-Free Devices







Figure 1. Pin Assignment



ON Semiconductor®

<http://onsemi.com>

#### MARKING DIAGRAMS



A = Assembly Location  
L, WL = Wafer Lot  
Y, YY = Year  
W, WW = Work Week  
G or ■ = Pb-Free Package

(Note: Microdot may be in either location)

#### FUNCTION TABLE

| Inputs |   | Output |
|--------|---|--------|
| A      | B | Y      |
| L      | L | H      |
| L      | H | H      |
| H      | L | H      |
| H      | H | L      |

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

# MC74HCT132A




Figure 2. Logic Diagram

## ORDERING INFORMATION

| Device           | Package                | Shipping <sup>†</sup> |
|------------------|------------------------|-----------------------|
| MC74HCT132ANG    | PDIP-14<br>(Pb-Free)   | 25 / Tape & Ammo Box  |
| MC74HCT132ADG    | SOIC-14<br>(Pb-Free)   | 55 Units / Rail       |
| MC74HCT132ADR2G  | SOIC-14<br>(Pb-Free)   | 2500 / Tape & Reel    |
| MC74HCT132ADTR2G | TSSOP-14*              | 2500 / Tape & Reel    |
| MC74HCT132AFELG  | SOEIAJ-14<br>(Pb-Free) | 2000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*This package is inherently Pb-Free.

# MC74HCT132A

## MAXIMUM RATINGS

| Symbol         | Parameter                                                                                                     | Value                                     | Unit |
|----------------|---------------------------------------------------------------------------------------------------------------|-------------------------------------------|------|
| $V_{CC}$       | Positive DC Supply Voltage                                                                                    | – 0.5 to + 7.0                            | V    |
| $V_{IN}$       | Digital Input Voltage                                                                                         | – 0.5 to + 7.0                            | V    |
| $V_{OUT}$      | DC Output Voltage<br>Output in 3-State<br>High or Low State                                                   | – 0.5 to + 7.0<br>– 0.5 to $V_{CC}$ + 0.5 | V    |
| $I_{IK}$       | Input Diode Current                                                                                           | – 20                                      | mA   |
| $I_{OK}$       | Output Diode Current                                                                                          | ± 20                                      | mA   |
| $I_{OUT}$      | DC Output Current, per Pin                                                                                    | ± 25                                      | mA   |
| $I_{CC}$       | DC Supply Current, $V_{CC}$ and GND Pins                                                                      | ± 75                                      | mA   |
| $I_{GND}$      | DC Ground Current per Ground Pin                                                                              | ± 75                                      | mA   |
| $T_{STG}$      | Storage Temperature Range                                                                                     | – 65 to + 150                             | °C   |
| $T_L$          | Lead Temperature, 1 mm from Case for 10 Seconds                                                               | 260                                       | °C   |
| $T_J$          | Junction Temperature Under Bias                                                                               | + 150                                     | °C   |
| $\theta_{JA}$  | Thermal Resistance<br>14-PDIP<br>14-SOIC<br>14-TSSOP                                                          | 78<br>125<br>170                          | °C/W |
| $P_D$          | Power Dissipation in Still Air at 85°C<br>PDIP<br>SOIC<br>TSSOP                                               | 750<br>500<br>450                         | mW   |
| MSL            | Moisture Sensitivity                                                                                          | Level 1                                   |      |
| $F_R$          | Flammability Rating<br>Oxygen Index: 30% – 35%                                                                | UL 94 V0 @ 0.125 in                       |      |
| $V_{ESD}$      | ESD Withstand Voltage<br>Human Body Model (Note 1)<br>Machine Model (Note 2)<br>Charged Device Model (Note 3) | > 2000<br>> 100<br>> 500                  | V    |
| $I_{Latch-Up}$ | Latch-Up Performance<br>Above $V_{CC}$ and Below GND at 85°C (Note 4)                                         | ± 300                                     | mA   |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Tested to EIA/JESD22-A114-A.
2. Tested to EIA/JESD22-A115-A.
3. Tested to JESD22-C101-A.
4. Tested to EIA/JESD78.

## RECOMMENDED OPERATING CONDITIONS

| Symbol            | Parameter                                            | Min  | Max                  | Unit |
|-------------------|------------------------------------------------------|------|----------------------|------|
| $V_{CC}$          | DC Supply Voltage (Referenced to GND)                | 2.0  | 6.0                  | V    |
| $V_{IN}, V_{OUT}$ | DC Input Voltage, Output Voltage (Referenced to GND) | 0    | $V_{CC}$             | V    |
| $T_A$             | Operating Temperature, All Package Types             | – 55 | + 125                | °C   |
| $t_r, t_f$        | Input Rise and Fall Time (Figure 3)                  | –    | No Limit<br>(Note 5) | ns   |

5. When  $V_{IN} \sim 0.5 V_{CC}$ ,  $I_{CC} \gg$  quiescent current.
6. Unused inputs may not be left open. All inputs must be tied to a high-logic voltage level or a low-logic input voltage level.

# MC74HCT132A

## DC ELECTRICAL CHARACTERISTICS (Voltages Referenced to GND)

| Symbol                         | Parameter                                      | Test Conditions                                                                               | V <sub>CC</sub><br>V | Guaranteed Limit |            |            | Unit |
|--------------------------------|------------------------------------------------|-----------------------------------------------------------------------------------------------|----------------------|------------------|------------|------------|------|
|                                |                                                |                                                                                               |                      | −55°C to 25°C    | ≤ 85°C     | ≤ 125°C    |      |
| V <sub>T+</sub> max            | Maximum Positive-Going Input Threshold Voltage | V <sub>OUT</sub> = 0.1 V<br> I <sub>OUT</sub>   ≤ 20 μA                                       | 4.5<br>5.5           | 1.9<br>2.1       | 1.9<br>2.1 | 1.9<br>2.1 | V    |
| V <sub>T+</sub> min            | Minimum Positive-Going Input Threshold Voltage | V <sub>OUT</sub> = 0.1 V<br> I <sub>OUT</sub>   ≤ 20 μA                                       | 4.5<br>5.5           | 1.2<br>1.4       | 1.2<br>1.4 | 1.2<br>1.4 | V    |
| V <sub>T−</sub> max            | Maximum Negative-Going Input Threshold Voltage | V <sub>OUT</sub> = V <sub>CC</sub> − 0.1 V<br> I <sub>OUT</sub>   ≤ 20 μA                     | 4.5<br>5.5           | 1.2<br>1.4       | 1.2<br>1.4 | 1.2<br>1.4 | V    |
| V <sub>T−</sub> min            | Minimum Negative-Going Input Threshold Voltage | V <sub>OUT</sub> = V <sub>CC</sub> − 0.1 V<br> I <sub>OUT</sub>   ≤ 20 μA                     | 4.5<br>5.5           | 0.5<br>0.6       | 0.5<br>0.6 | 0.5<br>0.6 | V    |
| V <sub>H</sub> min<br>(Note 7) | Minimum Hysteresis Voltage                     | V <sub>OUT</sub> = 0.1 V or V <sub>CC</sub> − 0.1 V<br> I <sub>OUT</sub>   ≤ 20 μA            | 4.5<br>5.5           | 0.4<br>0.4       | 0.4<br>0.4 | 0.4<br>0.4 | V    |
| V <sub>OH</sub>                | Minimum High-Level Output Voltage              | V <sub>IN</sub> ≤ V <sub>T−</sub> min or V <sub>T+</sub> max<br> I <sub>OUT</sub>   ≤ 20 μA   | 4.5<br>5.5           | 4.4<br>5.4       | 4.4<br>5.4 | 4.4<br>5.4 | V    |
|                                |                                                | V <sub>IN</sub> ≤ −V <sub>T−</sub> min or V <sub>T+</sub> max<br> I <sub>OUT</sub>   ≤ 4.0 mA | 4.5                  | 3.98             | 3.84       | 3.7        |      |
| V <sub>OL</sub>                | Maximum Low-Level Output Voltage               | V <sub>IN</sub> ≥ V <sub>T+</sub> max<br> I <sub>OUT</sub>   ≤ 20 μA                          | 4.5<br>5.5           | 0.1<br>0.1       | 0.1<br>0.1 | 0.1<br>0.1 | V    |
|                                |                                                | V <sub>IN</sub> ≥ V <sub>T+</sub> max  I <sub>OUT</sub>   ≤ 4.0 mA                            | 4.5                  | 0.26             | 0.33       | 0.4        |      |
| I <sub>IN</sub>                | Maximum Input Leakage Current                  | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                      | 5.5                  | ± 0.1            | ± 1.0      | ± 1.0      | μA   |
| I <sub>CC</sub>                | Maximum Quiescent Supply Current (per Package) | V <sub>IN</sub> = V <sub>CC</sub> or GND<br>I <sub>OUT</sub> = 0 μA                           | 5.5                  | 1.0              | 10         | 40         | μA   |

7. V<sub>H</sub>min > (V<sub>T+</sub>min) − (V<sub>T−</sub>max); V<sub>H</sub>max = (V<sub>T+</sub>max) + (V<sub>T−</sub>min).

## AC ELECTRICAL CHARACTERISTICS (C<sub>L</sub> = 50 pF, Input t<sub>r</sub> = t<sub>f</sub> = 6.0 ns, V<sub>CC</sub> = 5.0 V ± 10%)

| Symbol                                 | Parameter                                                                | V <sub>CC</sub><br>V                    | Guaranteed Limit |        |         | Unit |
|----------------------------------------|--------------------------------------------------------------------------|-----------------------------------------|------------------|--------|---------|------|
|                                        |                                                                          |                                         | −55°C to 25°C    | ≤ 85°C | ≤ 125°C |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Input A or B to Output Y<br>(Figures 3 and 4) | 5.0                                     | 25               | 31     | 38      | ns   |
| t <sub>TLH</sub> ,<br>t <sub>THL</sub> | Maximum Output Transition Time, Any Output<br>(Figures 3 and 4)          | 5.0                                     | 15               | 19     | 22      | ns   |
| C <sub>in</sub>                        | Maximum Input Capacitance                                                | —                                       | 10               | 10     | 10      | pF   |
| C <sub>PD</sub>                        | Power Dissipation Capacitance (per Gate) (Note 8)                        | Typical @ 25°C, V <sub>CC</sub> = 5.0 V |                  |        |         | pF   |
|                                        |                                                                          | 24                                      |                  |        |         |      |

8. Used to determine the no-load dynamic power consumption: P<sub>D</sub> = C<sub>PD</sub> V<sub>CC</sub><sup>2</sup>f + I<sub>CC</sub> V<sub>CC</sub>.

# MC74HCT132A




Figure 3. Switching Waveforms




Figure 4. Test Circuit





Figure 5. Typical Schmitt-Trigger Applications

# MC74HCT132A

## PACKAGE DIMENSIONS

**PDIP-14**  
CASE 646-06  
ISSUE P



### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.715     | 0.770 | 18.16       | 19.56 |
| B   | 0.240     | 0.260 | 6.10        | 6.60  |
| C   | 0.145     | 0.185 | 3.69        | 4.69  |
| D   | 0.015     | 0.021 | 0.38        | 0.53  |
| F   | 0.040     | 0.070 | 1.02        | 1.78  |
| G   | 0.100 BSC |       | 2.54 BSC    |       |
| H   | 0.052     | 0.095 | 1.32        | 2.41  |
| J   | 0.008     | 0.015 | 0.20        | 0.38  |
| K   | 0.115     | 0.135 | 2.92        | 3.43  |
| L   | 0.290     | 0.310 | 7.37        | 7.87  |
| M   | ---       | 10 °  | ---         | 10 °  |
| N   | 0.015     | 0.039 | 0.38        | 1.01  |

# MC74HCT132A

## PACKAGE DIMENSIONS

SOIC-14  
CASE 751A-03  
ISSUE J




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

|     | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
| DIM | MIN         | MAX  | MIN       | MAX   |
| A   | 8.55        | 8.75 | 0.337     | 0.344 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.054     | 0.068 |
| D   | 0.35        | 0.49 | 0.014     | 0.019 |
| F   | 0.40        | 1.25 | 0.016     | 0.049 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| J   | 0.19        | 0.25 | 0.008     | 0.009 |
| K   | 0.10        | 0.25 | 0.004     | 0.009 |
| M   | 0°          | 7°   | 0°        | 7°    |
| P   | 5.80        | 6.20 | 0.228     | 0.244 |
| R   | 0.25        | 0.50 | 0.010     | 0.019 |

### SOLDERING FOOTPRINT\*




DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HCT132A

## PACKAGE DIMENSIONS

### TSSOP-14 CASE 948G-01 ISSUE B




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.50        | 0.60 | 0.020     | 0.024 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |

#### SOLDERING FOOTPRINT\*




\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HCT132A

## PACKAGE DIMENSIONS

SOEIAJ-14  
CASE 965-01  
ISSUE B



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

| DIM            | MILLIMETERS |       | INCHES    |       |
|----------------|-------------|-------|-----------|-------|
|                | MIN         | MAX   | MIN       | MAX   |
| A              | ---         | 2.05  | ---       | 0.081 |
| A <sub>1</sub> | 0.05        | 0.20  | 0.002     | 0.008 |
| b              | 0.35        | 0.50  | 0.014     | 0.020 |
| c              | 0.10        | 0.20  | 0.004     | 0.008 |
| D              | 9.90        | 10.50 | 0.390     | 0.413 |
| E              | 5.10        | 5.45  | 0.201     | 0.215 |
| e              | 1.27 BSC    |       | 0.050 BSC |       |
| H <sub>E</sub> | 7.40        | 8.20  | 0.291     | 0.323 |
| L              | 0.50        | 0.85  | 0.020     | 0.033 |
| L <sub>E</sub> | 1.10        | 1.50  | 0.043     | 0.059 |
| M              | 0 °         | 10 °  | 0 °       | 10 °  |
| Q <sub>1</sub> | 0.70        | 0.90  | 0.028     | 0.035 |
| Z              | ---         | 1.42  | ---       | 0.056 |

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

MC74HCT132A/D

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)