







P.C.B Layout(Top View)

N= Number of poles Δ

$$\text{Dim.A} = (N-1) \times 6.35 + 7.75$$

$$\text{Dim.B} = (N-1) \times 6.35$$

POLE	2P~8P	9P~16P	17P~24P	25P~30P
Dim.B	±0.20	±0.30	±0.40	±0.50
Dim.A	±0.30	±0.40	±0.50	±0.60

SIGN	DATE	APPROVER
Δ	2/07'06	Part No. changed Tony
Δ	10/20'06	Demention A changed Steady
Δ	10/28'10	Rated voltage is chaged form 250 V to 300 V Aaron
Δ	10/28'10	Torque is changed from 6.1 Lb-In to 6.5 Lb-In Aaron
Δ	10/28'10	Tolerance is changed Aaron
Δ	12/05'12	Change the screw plating specification Jacky
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY Y!!!		

MATERIALS ELECTRICAL

- Δ RATED VOLTAGE & CURRENT: 300 V, 10 A
 WITHSTAND VOLTAGE: AC 2000 V/Min
 INSULATION RESISTANCE: 1000 M Ω OR MORE AT DC 500 V
 OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C
 Δ SCREW TORQUE VALUE: 6.5 Lb-In.
 WIRE RANGE: 22 - 16AWG
 1) MOLDED PARTS: POLYIMIDE 66, UL 94 V-0 BLACK
 2) TERMINAL: BRASS, 0.8t, Tin PLATED
 Δ 3) TERMINAL SCREWS: STEEL, M3

APPROVAL: 
 PART NO.:
 Critical dimension: ∇

YK 211 xx 0 x x 00G

NO. OF POLES
 02: 2 POLES
 03: 3 POLES
 04: 4 POLES
 ...
 30: 30 POLES

G: RoHS compliant (lead<4%)
 In copper Alloy

MARK
 0: "@" MARK
 1: "ANY" MARK

TERMINAL & SCREW PLATED
 0: TERMINAL & SCREW: G/F
 Δ 1: TERMINAL: G/F, SCREW: Zinc
 2: TERMINAL: Sn, SCREW: G/F
 Δ 3: TERMINAL: Sn, SCREW: Zinc

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	YK-211 Series 2P-30P			
PART NO.	YK211xx0xx00G			DWG NO. 8YK0001-211
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
		Jacky 2012.12.05	Jacky 2012.12.05	
SHEET: 01/01				UNIT: mm SCALE: NONE REV.: F
				Tolerance X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru