

| ASSY. NO. (CAT. NO.) | LED COLOR | |
|-------------------------|------------|------------|
| | POSITION 1 | POSITION 2 |
| 553-0101F | BLANK | RED |
| 553-0102F | BLANK | GREEN |
| 553-0103F | BLANK | YELLOW |
| 553-0107F | BLANK | ORANGE |
| 553-0108F | BLANK | BLUE |
| 553-0110F | RED | BLANK |
| 553-0111F | RED | RED |
| 553-0112F | RED | GREEN |
| 553-0113F | RED | YELLOW |
| 553-0118F | RED | BLUE |
| 553-0120F | GREEN | BLANK |
| 553-0121F | GREEN | RED |
| 553-0122F | GREEN | GREEN |
| 553-0123F | GREEN | YELLOW |
| 553-0127F | GREEN | ORANGE |
| 553-0128F | GREEN | BLUE |
| 553-0130F | YELLOW | BLANK |
| 553-0131F | YELLOW | RED |
| 553-0132F | YELLOW | GREEN |
| 553-0133F | YELLOW | YELLOW |
| 553-0171F | ORANGE | RED |
| 553-0172F | ORANGE | GREEN |
| 553-0173F | ORANGE | YELLOW |
| 553-0177F | ORANGE | ORANGE |
| 553-0181F | BLUE | RED |
| 553-0182F | BLUE | GREEN |
| 553-0188F | BLUE | BLUE |
| 553-0199F | WHITE | WHITE |
| 553-0201F | BLANK | RED |
| 553-0202F | BLANK | GREEN |
| 553-0203F | BLANK | YELLOW |
| 553-0210F | RED | BLANK |
| 553-0211F | RED | RED |
| 553-0212F | RED | GREEN |
| 553-0213F | RED | YELLOW |
| 553-0220F | GREEN | BLANK |
| 553-0221F | GREEN | RED |
| 553-0222F | GREEN | GREEN |
| 553-0223F | GREEN | YELLOW |
| 553-0230F | YELLOW | BLANK |
| 553-0231F | YELLOW | RED |
| 553-0232F | YELLOW | GREEN |
| 553-0233F | YELLOW | YELLOW |
| 553-0301F | BLANK | RED |
| 553-0302F | BLANK | GREEN |
| 553-0303F | BLANK | YELLOW |
| 553-0310F | RED | BLANK |
| 553-0311F | RED | RED |
| 553-0312F | RED | GREEN |
| 553-0313F | RED | YELLOW |
| 553-0320F | GREEN | BLANK |
| 553-0321F | GREEN | RED |
| 553-0322F | GREEN | GREEN |
| 553-0323F | GREEN | YELLOW |
| 553-0331F | YELLOW | RED |
| 553-0332F | YELLOW | GREEN |
| 553-0333F | YELLOW | YELLOW |



RoHS COMPLIANT 553-0XXXF
 Part Numbers with the "F" suffix ending are RoHS Compliant.
 For example: 553-0101F
 Packaging is marked with "RoHS Compliant" label or equivalent markings. Parts can be wave soldered, dip soldered or hand soldered using typical lead-free soldering process with max 260°C temp. for 5 sec.

| BIN | LIMITS (WHITE LED) (CHROMATICITY COORDINATES) | | | |
|-----|--|-------|-------|-------|
| | X | Y | Z | U |
| A3 | 0.270 | 0.270 | 0.250 | 0.250 |
| | 0.275 | 0.325 | 0.300 | 0.250 |
| A4 | 0.270 | 0.250 | 0.250 | 0.270 |
| | 0.275 | 0.250 | 0.200 | 0.225 |
| B3 | 0.290 | 0.290 | 0.270 | 0.270 |
| | 0.300 | 0.350 | 0.325 | 0.275 |
| B4 | 0.290 | 0.270 | 0.270 | 0.290 |
| | 0.300 | 0.275 | 0.225 | 0.250 |
| C3 | 0.310 | 0.310 | 0.290 | 0.290 |
| | 0.325 | 0.375 | 0.350 | 0.300 |
| C4 | 0.310 | 0.290 | 0.290 | 0.310 |
| | 0.325 | 0.300 | 0.250 | 0.275 |
| D3 | 0.330 | 0.330 | 0.310 | 0.310 |
| | 0.350 | 0.400 | 0.375 | 0.325 |
| D4 | 0.330 | 0.310 | 0.310 | 0.330 |
| | 0.350 | 0.325 | 0.275 | 0.300 |




SCALE 2.000



ATTENTION:
 OBSERVE PRECAUTIONS FOR
 HANDLING ELECTROSTATIC
 SENSITIVE DEVICES

NOTES:

- (FOR ORANGE: LEADS .018 SQ. NOM.), LED BODY \varnothing .115±.010 AND THE PC BOARD TOLERANCE ON LEAD THICKNESS TO BE ±.003.
- LED LEAD DIMENSIONS SHOWN ARE MEASURED AT HOUSING EXIT.
- LEADS TO FIT INTO HOLES SPACED AS PER PATTERN.
- PIN NUMBERS FOR REFERENCE ONLY, DESIGNATION NON-EXISTENT ON PART.
- DIALIGHT PART NUMBERS: 553-0XXXF.
- THIS ASSEMBLY CONTAINS ELECTROSTATIC DISCHARGE SENSITIVE DEVICES (ESDS). MAINTAIN ALL PRECAUTIONARY MEASURES DURING ASSEMBLY, HANDLING, AND STORAGE IN ACCORDANCE WITH IPC-A-610.



| 553-01XXXF | | | | | | |
|--|--------|------|------|------|---------|-----------------|
| OPERATING CHARACTERISTICS AT 25 °C AMBIENT: 10 mA LEDs | | | | | | |
| LED CHARACTERISTICS | COLOR | MIN. | TYP. | MAX. | UNITS | TEST CONDITIONS |
| LUMINOUS INTENSITY | RED | 2.5 | 8.7 | 18 | mcd | $I_F = 10$ mA |
| | YELLOW | 1.7 | 5.6 | — | | |
| | GREEN | 5.6 | 12.6 | 29 | | |
| | BLUE | 11 | 16 | 23 | | |
| | ORANGE | 3.4 | 7.0 | 10.8 | | |
| | WHITE | 400 | 1100 | 1900 | | |
| PEAK WAVELENGTH | RED | | 635 | | nm | $I_F = 10$ mA |
| | YELLOW | | 588 | | | |
| | GREEN | | 565 | | | |
| | BLUE | | 468 | | | |
| | ORANGE | | 600 | | | |
| | WHITE | | | | | |
| DOMINANT WAVELENGTH | RED | 615 | 625 | 632 | nm | $I_F = 10$ mA |
| | YELLOW | 585 | 590 | 595 | | |
| | GREEN | 564 | 568 | 573 | | |
| | BLUE | 460 | 467 | 475 | | |
| | ORANGE | 597 | 602 | 616 | | |
| | WHITE | | | | | |
| FORWARD VOLTAGE | RED | | 2.0 | 2.6 | V | $I_F = 10$ mA |
| | YELLOW | | 2.1 | 2.6 | | |
| | GREEN | | 2.1 | 2.6 | | |
| | BLUE | 2.0 | 2.7 | 4.1 | | |
| | ORANGE | 1.5 | 1.9 | 3.5 | | |
| | WHITE | | 3.5 | 4.0 | | |
| REVERSE CURRENT | RED | | | 100 | μ A | $V_R = 5V$ |
| | YELLOW | | | 100 | | |
| | GREEN | | | 100 | | |
| | BLUE | | | 10 | | |
| | ORANGE | | | 100 | | |
| | WHITE | | | 100 | | |
| VIEWING ANGLE | RED | | 60 | | DEGREE | $I_F = 20$ mA |
| | YELLOW | | 60 | | | |
| | GREEN | | 60 | | | |
| | BLUE | | 100 | | | |
| | ORANGE | | 60 | | | |
| | WHITE | | 45 | | | |

| 553-03XXXF | | | | | | |
|--|--------|------|------|------|---------|-----------------|
| OPERATING CHARACTERISTICS AT 25 °C AMBIENT: 5 V INTEGRAL RESISTOR LEDs | | | | | | |
| LED CHARACTERISTICS | COLOR | MIN. | TYP. | MAX. | UNITS | TEST CONDITIONS |
| LUMINOUS INTENSITY | RED | 8.7 | 29.0 | | mcd | $V_F = 5V$ |
| | YELLOW | 3.7 | 12.6 | | | |
| | GREEN | 5.6 | 19.0 | | | |
| PEAK WAVELENGTH | RED | | 635 | | nm | $I_F = 10$ mA |
| | YELLOW | | 585 | | | |
| | GREEN | | 565 | | | |
| FORWARD CURRENT | RED | | 10 | 20 | mA | $V_F = 5V$ |
| | YELLOW | | 10 | 20 | | |
| | GREEN | | 10 | 20 | | |
| REVERSE CURRENT | RED | | | 100 | μ A | $V_R = 5V$ |
| | YELLOW | | | 100 | | |
| | GREEN | | | 100 | | |
| VIEWING ANGLE | ALL | | 60 | | DEGREE | |

| 553-02XXXF | | | | | | |
|---|--------|------|------|------|---------|-----------------|
| OPERATING CHARACTERISTICS AT 25 °C AMBIENT: 2 mA LOW CURRENT LEDs | | | | | | |
| LED CHARACTERISTICS | COLOR | MIN. | TYP. | MAX. | UNITS | TEST CONDITIONS |
| LUMINOUS INTENSITY | RED | 0.75 | 2.5 | | mcd | $I_F = 2$ mA |
| | YELLOW | 0.4 | 4.5 | | | |
| | GREEN | 0.4 | 1.1 | | | |
| PEAK WAVELENGTH | RED | | 635 | | nm | $I_F = 2$ mA |
| | YELLOW | | 585 | | | |
| | GREEN | | 565 | | | |
| FORWARD VOLTAGE | RED | 1.7 | 2.2 | | V | $I_F = 2$ mA |
| | YELLOW | 1.8 | 2.2 | | | |
| | GREEN | 1.9 | 2.2 | | | |
| REVERSE CURRENT | ALL | | | 10 | μ A | $V_R = 5V$ |
| VIEWING ANGLE | ALL | | 60 | | DEGREE | |

| 553-03XXXF | | | | |
|---|-------------|-------|--------|-------|
| ABSOLUTE MAXIMUM RATINGS AT 25 °C AMBIENT | | | | |
| | COLOR | | | UNITS |
| | RED | GREEN | YELLOW | |
| CONTINUOUS FORWARD VOLTAGE | 7.5 | | | V |
| REVERSE VOLTAGE | 5 | | | V |
| LINEAR DERATING FROM 50 °C | 0.071 | | | V/°C |
| LEAD SOLDERING TEMPERATURE (.063" [1.6mm] FROM BODY) FOR 5 SEC. | 260 | | | °C |
| OPERATING TEMPERATURE | -40 TO +85 | | | °C |
| STORAGE TEMPERATURE | -55 TO +100 | | | °C |

| 553-01XXXF | | | | | | | |
|---|-------------|--------|-------------|------|-------------|-------|-------|
| ABSOLUTE MAXIMUM RATINGS AT 25 °C AMBIENT | | | | | | | |
| | COLOR | | | | | | UNITS |
| | RED | YELLOW | GREEN | BLUE | ORANGE | WHITE | |
| POWER DISSIPATION | 100 | 60 | 120 | 120 | 135 | 120 | mW |
| PEAK FORWARD CURRENT (1/5 DUTY CYCLE, 1 ms PULSE WIDTH) (1/10, .1ms FOR BLUE) ($t_c < 10 \mu$ s D=.005 FOR ORANGE) | 90 | 60 | 90 | 100 | 500 | 100 | mA |
| CONTINUOUS FORWARD CURRENT | 30 | 20 | 30 | 30 | 30 | 30 | mA |
| LINEAR DERATING FROM 50 °C (30 °C FOR BLUE, 30 °C FOR WHITE) | 0.40 | 0.25 | 0.40 | .5 | 0.50 | .45 | mA/°C |
| REVERSE VOLTAGE | 5 | | | | | | V |
| LEAD SOLDERING TEMPERATURE (.063" [1.6mm] FROM BODY) FOR 5 SEC. | 260 | | | | | | °C |
| OPERATING TEMPERATURE | -55 TO +100 | | -40 TO +85 | | -55 TO +100 | | °C |
| STORAGE TEMPERATURE | -55 TO +100 | | -55 TO +100 | | -40 TO +100 | | °C |

| 553-02XXXF | | | | |
|---|-------------|-------|--------|-------|
| ABSOLUTE MAXIMUM RATINGS AT 25 °C AMBIENT: | | | | |
| | COLOR | | | UNITS |
| | RED | GREEN | YELLOW | |
| POWER DISSIPATION | 20 | | | mW |
| PEAK FORWARD CURRENT (1/10 DUTY CYCLE, 0.1ms PULSE WIDTH) | 500 | | | mA |
| CONTINUOUS FORWARD CURRENT | 7 | | | mA |
| LINEAR DERATING FROM 95 °C | 0.7 | | | mA/°C |
| REVERSE VOLTAGE | 5 | | | V |
| LEAD SOLDERING TEMPERATURE (.063" [1.6mm] FROM BODY) FOR 5 SEC. | 260 | | | °C |
| OPERATING TEMPERATURE | -55 TO +100 | | | °C |
| STORAGE TEMPERATURE | -55 TO +100 | | | °C |

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT CORP. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT CORP.

SCALE: 6.000

DRAWING NUMBER: **C-17277**

REV: **K**

TOLERANCES: UNLESS OTHERWISE SPECIFIED

FRACTIONS: ±1/64

DECIMALS (.XX): ±.02

DECIMALS (.XXX): ±.015

ANGLES: ±3°

FINISH

TITLE: **3mm LED BI-LEVEL CBI**

MATERIAL: **RoHS COMPLIANT**

Dialight

1501 ROUTE 34 SOUTH
 FARMINGDALE, NJ 07727
 (732) 919-3119
 www.dialight.com

FSCM 83330

SHEET 1 OF 1

FAMILY TABLES:

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.

