

# C3D03060F–Silicon Carbide Schottky Diode

## Z-REC™ RECTIFIER (FULL-PAK)

$$\begin{aligned} V_{RRM} &= 600 \text{ V} \\ I_{F(AVG)} &= 3 \text{ A} \\ Q_c &= 6.7 \text{ nC} \end{aligned}$$

### Features

- 600-Volt Schottky Rectifier
- Optimized for PFC Boost Diode Application
- Zero Reverse Recovery Current
- Zero Forward Recovery Voltage
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Extremely Fast Switching
- Positive Temperature Coefficient on  $V_F$


### Benefits

- Replace Bipolar with Unipolar Rectifiers
- Essentially No Switching Losses
- Higher Efficiency
- Reduction of Heat Sink Requirements
- Parallel Devices Without Thermal Runaway

### Applications

- Switch Mode Power Supplies
- Power Factor Correction
  - Typical PFC  $P_{out}$  : 150W-300W

### Package



TO-220-F2



| Part Number | Package   | Marking  |
|-------------|-----------|----------|
| C3D03060F   | TO-220-F2 | C3D03060 |

### Maximum Ratings

| Symbol         | Parameter                                  | Value          | Unit             | Test Conditions                                                                                                                                 | Note |
|----------------|--------------------------------------------|----------------|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|------|
| $V_{RRM}$      | Repetitive Peak Reverse Voltage            | 600            | V                |                                                                                                                                                 |      |
| $V_{RSM}$      | Surge Peak Reverse Voltage                 | 600            | V                |                                                                                                                                                 |      |
| $V_{DC}$       | DC Blocking Voltage                        | 600            | V                |                                                                                                                                                 |      |
| $I_{F(AVG)}$   | Average Forward Current                    | 3.0            | A                | $T_c=105^\circ\text{C}$                                                                                                                         |      |
| $I_{FRM}$      | Repetitive Peak Forward Surge Current      | 20<br>15       | A                | $T_c=25^\circ\text{C}$ , $t_p=10 \text{ mS}$ , Half Sine Wave $D=0.3$<br>$T_c=110^\circ\text{C}$ , $t_p=10 \text{ mS}$ , Half Sine Wave $D=0.3$ |      |
| $I_{FSM}$      | Non-Repetitive Peak Forward Surge Current  | 28<br>22       | A                | $T_c=25^\circ\text{C}$ , $t_p=10 \text{ mS}$ , Half Sine Wave $D=0.3$<br>$T_c=110^\circ\text{C}$ , $t_p=10 \text{ mS}$ , Half Sine Wave $D=0.3$ |      |
| $I_{FSM}$      | Non-Repetitive Peak Forward Surge Current  | 100            | A                | $T_c=25^\circ\text{C}$ , $t_p=10 \mu\text{S}$ , Pulse                                                                                           |      |
| $P_{tot}$      | Power Dissipation                          | 12.5<br>5.4    | W                | $T_c=25^\circ\text{C}$<br>$T_c=110^\circ\text{C}$                                                                                               |      |
| $T_J, T_{stg}$ | Operating Junction and Storage Temperature | -55 to<br>+175 | $^\circ\text{C}$ |                                                                                                                                                 |      |
|                | TO-220 Mounting Torque                     | 1<br>8.8       | Nm<br>lbf-in     | M3 Screw<br>6-32 Screw                                                                                                                          |      |

## Electrical Characteristics

| Symbol | Parameter               | Typ.            | Max.       | Unit          | Test Conditions                                                                                                                                                                                                    | Note |
|--------|-------------------------|-----------------|------------|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| $V_F$  | Forward Voltage         |                 | 1.7<br>2.4 | V             | $I_F = 3\text{ A}$ $T_J = 25^\circ\text{C}$<br>$I_F = 3\text{ A}$ $T_J = 175^\circ\text{C}$                                                                                                                        |      |
| $I_R$  | Reverse Current         | 10<br>20        | 50<br>100  | $\mu\text{A}$ | $V_R = 600\text{ V}$ $T_J = 25^\circ\text{C}$<br>$V_R = 600\text{ V}$ $T_J = 175^\circ\text{C}$                                                                                                                    |      |
| $Q_C$  | Total Capacitive Charge | 6.7             |            | nC            | $V_R = 600\text{ V}$ , $I_F = 3\text{ A}$<br>$di/dt = 500\text{ A}/\mu\text{S}$<br>$T_J = 25^\circ\text{C}$                                                                                                        |      |
| C      | Total Capacitance       | 155<br>13<br>12 |            | pF            | $V_R = 0\text{ V}$ , $T_J = 25^\circ\text{C}$ , $f = 1\text{ MHz}$<br>$V_R = 200\text{ V}$ , $T_J = 25^\circ\text{C}$ , $f = 1\text{ MHz}$<br>$V_R = 400\text{ V}$ , $T_J = 25^\circ\text{C}$ , $f = 1\text{ MHz}$ |      |

Note:

1. This is a majority carrier diode, so there is no reverse recovery charge.

## Thermal Characteristics

| Symbol          | Parameter                                                  | Typ. | Unit                      |
|-----------------|------------------------------------------------------------|------|---------------------------|
| $R_{\theta JC}$ | TO-220-F2 Package Thermal Resistance from Junction to Case | 12.0 | $^\circ\text{C}/\text{W}$ |

## Typical Performance




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics

## Typical Performance




Figure 3. Current Derating




Figure 4. Capacitance vs. Reverse Voltage




Figure 5. Transient Thermal Impedance

## Typical Performance





Figure 6. Power Derating

## Package Dimensions

Package TO-220-F2




| POS | Inches |      | Millimeters |       |
|-----|--------|------|-------------|-------|
|     | Min    | Max  | Min         | Max   |
| A   | .177   | .193 | 4.5         | 4.9   |
| B   | .092   | .108 | 2.34        | 2.74  |
| C   | .248   | .272 | 6.3         | 6.9   |
| D   | .098   | .114 | 2.5         | 2.9   |
| E   | .390   | .406 | 9.9         | 10.3  |
| F   | .118   | .134 | 3.0         | 3.4   |
| G   | .122   | .137 | 3.1         | 3.5   |
| H   | .617   | .633 | 15.67       | 16.07 |
| L   | .039   | .055 | 1.0         | 1.4   |
| M   | .016   | .031 | 0.4         | 0.8   |
| N   | .185   | .217 | 4.7         | 5.5   |
| P   | 0      | .154 | 0           | 3.9   |
| S   | .476   | .508 | 12.1        | 12.9  |
| T   | .016   | .031 | 0.4         | 0.8   |

NOTE:

1. Dimension L, M, T apply for Solder Dip Finish


## Recommended Solder Pad Layout



TO-220-2

| Part Number | Package   | Marking  |
|-------------|-----------|----------|
| C3D03060F   | TO-220-F2 | C3D03060 |

## Diode Model



$$V_{f_T} = V_T + I_f * R_T$$

$$V_T = 1.01 + (T_j * -1.26 * 10^{-3})$$

$$R_T = 0.14 + (T_j * 1.13 * 10^{-3})$$

**Note:**  $T_j$  = Diode Junction Temperature In Degrees Celcius

"The levels of environmentally sensitive, persistent biologically toxic (PBT), persistent organic pollutants (POP), or otherwise restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS), as amended through April 21, 2006.

This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, air traffic control systems, or weapons systems.

Copyright © 2009-2011 Cree, Inc. All rights reserved. The information in this document is subject to change without notice. Cree and the Cree logo are registered trademarks and Z-Rec is a trademark of Cree, Inc.

Cree, Inc.  
4600 Silicon Drive  
Durham, NC 27703  
USA Tel: +1.919.313.5300  
Fax: +1.919.313.5451  
[www.cree.com/power](http://www.cree.com/power)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)