


Product: [9764](#) 

CATV Video, RG11, 14 AWG BCCS, Tri Shield, Polyethylene Jacket



Product Description

CATV, Series 11, 14 AWG solid .064" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond Plus®; aluminum braid shield (75% coverage), polyethylene jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | Nominal Diameter | No. of Coax |
|-----|-----------|----------------------------------|------------------|-------------|
| 14 | Solid | BCCS - Bare Copper Covered Steel | 0.064 in | 1 |

| | |
|------------------|---|
| Conductor Count: | 1 |
|------------------|---|

Insulation

| Material | Nominal Diameter |
|--------------------------|------------------|
| PE - Polyethylene (Foam) | 0.28 in |

| | |
|-------------------------|--------------|
| Insulation, Table Note: | Gas Injected |
|-------------------------|--------------|

Outer Shield Material

| Type | Layer | Material | Material Trade Name | Coverage [%] |
|-------|-------|--------------------|---------------------|--------------|
| Tape | 1 | Alum / Poly / Alum | Duobond® II | 100 % |
| Braid | 2 | Aluminum | | 75 % |
| Tape | 3 | Alum / Poly | | 100 % |

| | |
|--------------------------|--|
| Outer Shield Table Note: | Tape has shorting fold and is bonded to jacket |
|--------------------------|--|

Outer Jacket Material

| Material | Nominal Diameter |
|-------------------|------------------|
| PE - Polyethylene | 0.4 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|--------------------------|---------------------|
| 11 Ohm/1000ft | 3.8 Ohm/1000ft | 3.8 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Shield |
|--------------------------------------|
| 16.2 pF/ft |

Inductance

| Nominal Inductance |
|--------------------|
| 0.097 µH/ft |

Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 75 Ohm |

Return Loss (RL)

| Frequency [MHz] | Min. Structural Return Loss (SRL) |
|-----------------|-----------------------------------|
| 5-1000 MHz | 20 dB |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.2 ns/ft | 83 % |

High Freq

| Frequency [MHz] | Max. Insertion Loss (Attenuation) |
|-----------------|-----------------------------------|
| 5 MHz | 0.38 dB/100ft |
| 55 MHz | 0.96 dB/100ft |
| 211 MHz | 1.9 dB/100ft |
| 270 MHz | 2.13 dB/100ft |
| 300 MHz | 2.25 dB/100ft |
| 350 MHz | 2.42 dB/100ft |
| 400 MHz | 2.6 dB/100ft |
| 450 MHz | 2.75 dB/100ft |
| 550 MHz | 3.04 dB/100ft |
| 750 MHz | 3.65 dB/100ft |
| 870 MHz | 4.06 dB/100ft |
| 1000 MHz | 4.35 dB/100ft |

Voltage

| Non-UL Voltage Rating |
|-----------------------|
| 300 V RMS |

Temperature Range

| | |
|-----------------------|----------------|
| Non-UL Temp Rating: | 80°C |
| Operating Temp Range: | -55°C To +80°C |

Mechanical Characteristics

| | |
|----------------------------------|---------------|
| Bulk Cable Weight: | 52 lbs/1000ft |
| Max Recommended Pulling Tension: | 276 lbs |
| Min Bend Radius/Minor Axis: | 4 in |

Standards

| | |
|--------------|-----------|
| RG Type: | 11/U Type |
| Series Type: | Series 11 |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| Environmental Space: | Outdoor - Water Exposure |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| MII Order #39 (China RoHS): | Yes |

Suitability

| | |
|------------------------|-----|
| Suitability - Burial: | Yes |
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|--------------|--------|------------|----------|--------------|
| 9764 0101000 | Black | Reel | 1,000 ft | 612825258452 |
| 9764 0031000 | Orange | Reel | 1,000 ft | 612825258278 |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.291 Revision Date: 04-28-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru