Desiccant is a drying agent used to lower the moisture content of air inside a closed space, such as a Moisture Barrier Bag (ANSI/ESD S11.4 Level 1 and Level 2 Static Control Bags). Desiccant is packaged in fractional units in order to facilitate its usage with a variety of bag sizes. One full "unit" of packaged desiccant will absorb the following quantities of water at equilibrium with air at 77°F (25°C): 3.00 grams @ 20% rH and 6.00 grams @ 40% rH, when tested to MIL-D-3464.

In order to provide a complete moisture barrier packaging assembly, desiccant must be inserted into the bag, prior to having the bag vacuum sealed. The recommended amount of desiccant is dependent on the interior surface area of the bag to be used. The table is a reference indicating recommended minimum amounts of desiccant that should be used with Moisture Barrier Bags.







13840 & 13850

INTERIOR BAG	NUMBER OF DESICCANT UNITS			
SURFACE AREA*	**MIH <20%	MIH <30%	MIH < 40%	
100 og in	1 E	1.0	1.0	
100 sq. in.	1.5	1.0	1.0	
130 sq. in.	2.0	1.5	1.0	
160 sq. in.	2.0	1.5	1.5	
200 sq. in.	2.5	2.0	1.5	
240 sq. in.	3.0	2.0	1.5	
290 sq. in.	4.0	2.5	2.0	
340 sq. in.	4.5	3.0	2.5	
390 sq. in.	5.0	3.5	2.5	
450 sq. in.	5.5	4.0	3.0	
510 sq. in.	6.5	4.5	3.5	
580 sq. in.	7.5	5.0	4.0	
650 sq. in.	8.0	5.5	4.0	
720 sq. in.	9.0	6.0	4.5	

Table for recommended desiccant usage. Information taken out of EIA-583, Table 1, Page 8.

Desiccant paks are available from Desco in the following unit sizes and standard packages:

Item #	Unit Size	Std. Package	Dimensions
<u>13840</u>	1/2 unit	Box of 700	1.5" x 3"
<u>13843</u>	1 unit	Box of 450	2" x 4"
<u>13844</u>	1 unit	Pail of 300	2" x 4"
13850	1/2 unit	Pail of 550	1.5" x 3"

As packaged Desco 13850 meets MIL-D-3464, Type II and is on the QPL (Qualified Product List). Click <u>here</u> to see Desi-Pak (supplier Cage Code 00334).

Fill Contents: Activated Clay

Paper: Tyvek

Warranty: 3 Years from date of manufacture



Made in the United States of America

Specifications and procedures subject to change without notice.

Desiccant Pak

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEBSITE: <u>Desco.com</u> PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 13850 DATE: December 2013

[&]quot;...it is important to take possible temperature exposure into account when shipping electronic parts. It is particularly important to consider what happens to the interior of a package if the environment has high humidity. If the temperature varies across the dew point of the established interior environment of the package, condensation may occur. The interior of a package should either contain desiccant or the air should be evacuated from the package during the sealing process. The package itself should have a low WVTR." (ESD Handbook ESD TR20.20 section 5.4.3.2.2)

^{*}To measure interior bag surface area, multiply length x width x 2

^{**}MIH = Maximum Interior Humidity (%)

DESCO SAFETY DATA SHEET =

May be used to comply with ANSI Z400.1-2004, and Globally Harmonized System (OSHA Hazcom 29 CFR 1910.1200, (EU) No.453/2010 and Japan JIS 7253:2012). Standards must be consulted for specific

requirements.

Revision Date: 2018-02-27

SECTION 1 — IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifiers

Product Name: Desi Pak
EC No.: None
REACH Registration No.: None
CAS No.: None

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use: Desiccant

1.3 Details of the supplier of the safety data sheet

Supplier: Desco

3651 Walnut Ave Chino, CA 91710 (909) 627-8178

Email Address: <u>Service@Desco.com</u>

1.4 Emergency telephone number

Emergency Number: (909) 627-8178

SECTION 2 — HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

No reportable hazardous components as defined by the Globally Harmonized System (OSHA Hazcom 29 CFR 1910.1200, (EU) No.453/2010 and Japan JIS 7253:2012).

2.2 Label elements

Not a dangerous substance according to GHS.

2.3 Other hazards

None known.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

No reportable hazardous components as defined by the Globally Harmonized System (OSHA Hazcom 29 CFR 1910.1200, (EU) No.453/2010 and Japan JIS 7253:2012).

SECTION 4 — FIRST AID MEASURES

4.1 Description of first aid measures

General advice No known delayed effects. Consult a physician for all exposures except for

minor instances.

If inhaled INHALATION: If exposed to excessive levels of dust or fumes, remove

to fresh air and get medical attention. Get medical attention if cough and other symptoms develop. If you feel unwell, seek medical advice (show the

label where possible).

In case of skin contact Wash off immediately with plenty of water for at least 15 minutes.

Use a mild soap if available.

In case of eye contact Do not rub affected area. Rinse immediately with plenty of lukewarm

water, also under the eyelids, for at least 15 minutes. Obtain medical

attention.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: <u>Desco.com</u>

If swallowed Normally not needed. If whole canisters or sachets are ingested, call a

physician or your local Poison Control Center (1-800-222-1222 in the

United States).

4.2 Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed

The possible symptoms known are those derived from the labelling (see

section 2). No additional symptoms are known.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5 — FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media The product itself does not burn.

Use extinguishing measures that are appropriate to local circumstances

and the surrounding environment.

Water spray jet Dry powder Foam

Carbon dioxide (CO2)

Unsuitable Extinguishing Media No restrictions

5.2 Special hazards arising from the substance or mixture

The product is not flammable. Does not sustain combustion.

No hazardous decomposition products are known.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

Special sliding risk through leaking of spilled product in connection with water.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid dust formation.

Evacuate personnel to safe areas.

Avoid contact with skin, eyes and clothing.

Wear personal protective equipment.

Avoid breathing dust.

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Special sliding risk through leaking of spilled product in connection with water.

Wearing appropriate personal protective equipment, contain spill and collect into a suitable container.

No special precautions required.

6.2 Environmental precautions

No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Pick up and transfer to properly labelled containers.

If product is released from trucks in roads, place signposts and remove the spill using vacuum cleaning systems.

6.4 Reference to other sections

See SECTION 8 and SECTION 13.

SECTION 7 — HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handlingUse of proper hygiene practices in the workplace is recommended.

Hygiene measures Wash hands before breaks and at the end of workday.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: <u>Desco.com</u>

Page 2 of 7 © 2018 DESCO INDUSTRIES, INC

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas Minimize airborne dust generation and prevent wind dispersal during

and containers loading and unloading. Keep containers closed and store packaged

products so as to prevent accidental bursting.

Advice on storage compatibility No conditions to be specially mentioned.

Storage stability Store in a dry place.

7.3 Specific end uses Not relevant

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures Use ventilation adequate to keep exposures below recommended

exposure limits. See the safety datasheet.

8.2 Exposure controls

Personal protective equipment

Respiratory protection Use local exhaust if dusting occurs. Good general ventaliation is adequate

in the absence of dusts.

Hand protection Wear protective gloves. Wash thoroughly after handling.

Eye protection Safety glasses with side-shields. Skin and Body protection Wear suitable protective equipment.

Hygiene measures Wash hands before breaks and at the end of workday.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance lumpy, granular, powder

Color: bright to earthy

Odor: None

Odor Threshold: Not determined 6.0 - 11.0 (20°C) :Hg

Method: aquaous suspension

Melting point/range: > 450°C

Method: EU A.1

Boiling point/boiling range: not applicable (solid with a melting point > 450°C)

Flash point: Not applicable Evaporation rate: Not applicable Flammability (solid, gas): Does not ignite Method: EU A.1

Self-ignition: Method: 92/69/EEC, A.6.

No relative self-ignition temperature below 400°C

Upper explosion limit: Not applicable

Lower explosive limit: Non explosive (void of any chemical structures commonly associated with

explosive properties)

not applicable (solid with a melting point > 450°C) Vapor pressure:

Vapor density relative to air: Non applicable 2.6 g/cm3 Density:

Bulk density: 500 - 1,100 kg/m3 Solubility (Water): < 0.9 a/l (20°C)

Method: Tested according to Directive 92/69/EEC.

No applicable inorganic Partition coefficient (n-octanol/water):

Auto-ignition temperature: Not determined

Decomposition temperature: No decomposition if used as directed.

Viscosity (dynamic): Not applicable Viscosity (kinematic): Not applicable

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

Oxidizing properties: No oxidizing properties (Based on the chemical structure, the substance

does not contain a surplus of oxygen or any structural groups known to be

correlated with a tendency to react exothermally with combustible material).

9.2 Other information

None known.

SECTION 10 — STABILITY AND REACTIVITY

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Forms slippery/greasy layers with water.

10.5 Incompatible materials

Inert, not reactive. Avoid storing together with materials that may be affected by dust.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11 — TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure

Eye contact. Ingestion

Acute toxicity

Acute oral toxicity LD50 (Rat): > 2 g/kg

Method: OECD Test Guideline 420

Acute inhalation toxicity No data available Acute dermal toxicity No data available

Bentonite is almost insoluble and has a low absorption through the skin.

Skin corrosion/irritation

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation

Species: Rabbit

Method: OECD Test Guideline 405

Result: No skin irritation

Respiratory or skin sensitisation

No data available

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

Germ cell mutagenicity

Genotoxicity in vitro Test Type: In vitro gene mutation study in bacteria

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro gene mutation study in mammalian cells

Method: OECD Test Guideline 476

Result: negative

Carcinogenicity

IARC Not listed **OSHA** Not listed **NTP** Not listed

Reproductive toxicity

Effects on fertility Based on available data, the classification criteria are not met.

STOT - Single exposure

No organ toxicity observed in acute tests.

Aspiration toxicity

No aspiration toxicity classification.

Experience with human exposure

General Information The possible symptoms known are those derived from the labelling (see

section 2).

SECTION 12 — ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 16 g/l

Exposure time: 96 h

LC50 (Marine water fish): 2.8 - 3.2 g/l

Exposure time: 24 h

Toxicity to daphnia and other aquatic

EC50 (Daphnia magna (Water flea)): > 100 mg/l

invertebrates

Exposure time: 48 h

Method: OECD Test Guideline 202 EC50 (Metacarcinus magister): 81.6 mg/l

Exposure time: 96 h

EC50 (Pandalus danae): 24.8 mg/l

Exposure time: 96 h

Toxicity to algae EC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 100

Exposure time: 72 h

Plant toxicity (Phaseolus vulgaris): 84.4 mg/kg

Remarks: No effect on the growth was observed.

(Zea mays): 84.4 mg/kg

Remarks: No effect on the growth was observed.

12.2 Persistence and degradability

Biodegradability The methods for determining biodegradability are not applicable to

inorganic substances.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

12.3 Bioaccumulative potential

Bioaccumulation Not relevant for inorganic substances.

12.4 Mobility in soil

Distribution among environmental

Medium: Soil compartments Bentonite is almost insoluble and thus presents a low mobility in most

soils.

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

According to experience and to the information currently available, the Additional ecological information

product has no harmful effects on the environment if used correctly as

intended.

SECTION 13 — DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

RCRA - Resource Conservation and

Recovery Authorization Act

No -- Not as sold.

NONE Water Code

Waste from residues This product, if discarded as sold, is not a Federal RCRA hazardous

> waste. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may

differ from federal disposal regulations.

Contaminated packaging No specific requirements.

SECTION 14 — TRANSPORT INFORMATION

DOT Not restricted **IATA** Not restricted **IMDG** Not restricted

14.1 UN Number N/A

14.2 UN proper shipping name N/A

14.3 Transport hazard class(es) N/A

14.4 Packing group N/A

14.5 Environmental hazards N/A 14.6 Special precautions for user N/A

14.7 Transport in bulk according to Annex II

of MARPOL and the IBC Code N/A

SECTION 15 — REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards No SARA Hazards

SARA 313 This product is not subject to SARA Title III Section 313 reporting

requirements under 40 CFR 372.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: Desco.com

Page 6 of 7 © 2018 DESCO INDUSTRIES, INC

Clean Water Act

Contains no known priority pollutants at concentrations greater than 0.1%.

The components of this product are reported in the following inventories:

TSCA All components of this product are listed or excluded from listing on the

United States Environmental Protection Agency Toxic Substances Control

Act (TSCA) Inventory.

15.2 Chemical Safety Assessment Not relevant

SECTION 16 — OTHER INFORMATION

HMIS RATING Health 0, Flammability 0, Reactivity 0, Personal Protection B
NFPA RATING Special Hazard: N/A, Health: 0, Flammability: 0, Instability: 0

SDS Updated 2018-02-27

Disclaimer

OTHER INFORMATION: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.

DESCO - 3651 Walnut Ave., Chino, CA 91710 • (909) 627-8178 • Website: <u>Desco.com</u>



OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru