



# Western Digital® PC SN520 NVMe™ SSD

## Fueling Innovation

### Design Flexibility

With future-ready, scalable NVMe architecture, the Western Digital PC SN520 NVMe SSD offers a robust solution to fuel generations of innovative IoT applications. Scalable NVMe offers a significant performance increase over SATA SSDs while further optimizing low power consumption to the low level of 2.5mW.

This NVMe SSD enables greater design flexibility for IoT and embedded customers, who seek a cost effective, small form factor, reliable and rugged storage device with low capacity points from 128GB to 512GB.

### Robust Construction Suited for IoT

The Western Digital PC SN520 NVMe SSD, supporting PCIe Gen3 x2, is designed for applications that have a limited number of PCIe lanes available for storage, however, require both high performance and low power. Partners that could benefit from NVMe technology include:

- **Commercial:** Interactive kiosks, ATMs and Point-of-Sales (POS), Multi-Functional Printers (MFP) and industries that require high-volume transaction processing
- **Edge Equipment and IoT Gateway:** Such as network equipment, industrial machinery, medical equipment, or embedded PC that need the high capacities to capture the floor's and sensors' data and the high IOPS to support the system's data analytics
- **Media Content Delivery and Streaming:** In-flight entertainment systems, train control and monitoring systems, data recorder and video surveillance that require high capacity and reliability

### Versatile Options for IoT

Equipped with a fully integrated solution which includes in-house controller, 64-layer 3D NAND, firmware, and testing, Western Digital provides longevity, supply and a robust and reliable design.

Designed with Western Digital's in-house tiered-caching NVMe architecture, the Western Digital PC SN520 NVMe SSD delivers high performance with sequential read and write speeds up to 1,700MB/s and 1,400MB/s respectively and high endurance up to 300 TBW, all of which are available in a variety of small form factors: M.2 2230, M.2 2242, M.2 2280.

### Summary

Western Digital PC SN520 NVMe SSD, in variety of small, single-sided form factors such as M.2 2230, M.2 2242 and M.2 2280, enables customers to build ultra-thin, ultra-small boards and systems that address multiple IoT segments, without sacrificing performance and power consumption.



### WESTERN DIGITAL PC SN520 NVMe SSD KEY BENEFITS & FEATURES

**READ SPEEDS UP TO 1,700MB/S AND LOW POWER CONSUMPTION LEVERAGES BOTH THE PCIe GEN3 x2 INTERFACE, AS WELL AS SOPHISTICATED NVMe POWER MANAGEMENT**

**128GB-512GB CAPACITIES AVAILABLE IN THREE SMALL FORM FACTORS: M.2 2230, M.2 2242, M.2 2280**

**ENDURANCE OF UP TO 300 TBW**

**5 YEAR LIMITED WARRANTY**

# Western Digital PC SN520 NVMe SSD

Specifications are subject to change

<b>Form Factors</b>	M.2 2230, M.2 2242, M.2 2280		
<b>Interface</b>	PCIe Gen3 x2 NVMe v1.3		
<b>Formatted Capacities<sup>1</sup></b>	128GB, 256GB, 512GB		
<b>Performance<sup>2</sup></b>	128GB	256GB	512GB
Sequential Read up to (MB/s)	1,500	1,700	1,700
Sequential Write up to (MB/s)	800	1,300	1,400
Random Read up to (IOPS)	95K	220K	270K
Random Write up to (IOPS)	90K	175K	280K
Endurance <sup>3</sup> (TBW)	100	200	300
<b>Power</b>	128GB	256GB	512GB
Peak Power (10µs) (A)	1.2	1.4	1.8
Avg. Active Power <sup>4,5</sup> (mW)	75	75	75
Low Power (PS3) <sup>5</sup> (mW)	25	25	25
Sleep (PS4) <sup>5</sup> (mW)	2.5	2.5	2.5
Supply Voltage (V / ±5%)	3.3	3.3	3.3
<b>Reliability</b>	Up to 1.752M hours		
MTTF <sup>6</sup>	Up to 1.752M hours		
<b>Environmental</b>			
Operating Temperature <sup>7</sup>	32°F to 158°F (0°C to 70°C)		
Non-operating Temperature <sup>8</sup>	-67°F to 185°F (-55°C to 85°C)		
Operating Vibration	5 gRMS, 10–2000 Hz, 3 axes		
Non-operating Vibration	4.9 gRMS, 7–800 Hz, 3 axes		
Shock	1,500G @0.5 ms half sine		
Certifications	FCC, UL, TUV, KCC, BSMI, VCCI, C-Tick		
Limited Warranty <sup>9</sup>	5 years		
<b>Physical Dimensions</b>			
Width	22mm ±0.15mm		
Length	2230: 30mm ±0.15mm; 2242: 42mm ±0.15mm; 2280: 80mm ±0.15mm		
Thickness (max)	2.38mm		
Weight	2230: 3.5g ±1g; 2242: 4.0g ±1g; 2280: 6.5g ±1g		

SKU	Form Factor	Capacity
SDAPTUW-128G	M.2 2230 S3-B-M	128GB
SDAPTUW-256G	M.2 2230 S3-B-M	256GB
SDAPTUW-512G	M.2 2230 S3-B-M	512GB
SDAPMUW-128G	M.2 2242 S3-B-M	128GB
SDAPMUW-256G	M.2 2242 S3-B-M	256GB
SDAPMUW-512G	M.2 2242 S3-B-M	512GB
SDAPNUW-128G	M.2 2280 S3-B-M	128GB
SDAPNUW-256G	M.2 2280 S3-B-M	256GB
SDAPNUW-512G	M.2 2280 S3-B-M	512GB



## Western Digital

Western Digital  
5601 Great Oaks Parkway  
San Jose, CA 95119, USA  
www.wdc.com

Western Digital and the Western Digital logo are the registered trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. All marks are the property of their respective owners. Pictures shown may vary from actual products. The NVMe™ word mark is a trademark of NVM Express, Inc.

<sup>1</sup> As used for storage capacity, one gigabyte (GB) = one billion bytes and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.  
<sup>2</sup> Test Conditions: Performance is based on the CrystalDiskMark 5.2.2 benchmark using a 1000MB LBA range ASUS Z170A desktop with Intel® i7-6700K 4.0GHz, 8GB 2133MHz DDR4. Windows 10 Pro 64-bit using Microsoft StorNVMe driver, secondary drive. Performance may vary based on host device. 1 MB = 1,000,000 bytes. IOPS = input/output operations per second.  
<sup>3</sup> TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity.  
<sup>4</sup> Measured using MobileMark™ 2014 on HP EliteBook X360 1030 G2 with i7-7600U, 8GB RAM. Windows 10 Pro, 64-bit RS3 using Microsoft StorNVMe driver, primary drive.  
<sup>5</sup> Power measurements at 25°C.  
<sup>6</sup> MTTF = Mean Time To Failure based on internal testing using Telcordia stress part testing. MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty. (Telcordia SR-332, GB, 40°C)  
<sup>7</sup> Operational temperature as reported by device (composite temperature).  
<sup>8</sup> Non-operational storage temperature does not guarantee data retention.  
<sup>9</sup> 5 years or Max Endurance (TBW) limit, whichever occurs first. 5 year warranty in regions not recognizing "limited." See <http://support.wdc.com> for more details.

Product specifications subject to change without notice. Not all products are available in all regions of the world.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)