





PRODUCT NO. ④	DIM. A	DIM. B	DIM. C	STYLE	POSITIONS LOADED	CONTACT PLATING ①	NOTES
69255-X01YLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	-
-X02YLF	1.25 /0.050	2.69 /0.106	15.62/0.615	KEYED	ALL	5u" Au + high performance lubricant	-
-X03YLF	-	-	15.62/0.615	UNKEYED	2,3,4,5,6,7	5u" Au + high performance lubricant	-
-X04YLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	-
-X05YLF	-	-	15.62/0.615	UNKEYED	ALL	1.27um /50u" GXT	-
-X06YLF	1.25 /0.050	2.69 /0.106	15.62/0.615	KEYED	ALL	1.27um /50u" GXT	-
-X07YLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	NOTE 5
-X08YLF	-	-	15.62/0.615	UNKEYED	3,4,5,6	5u" Au + high performance lubricant	-
-X09YLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	NOTE 6
-X10YLF	-	-	13.62/0.536	UNKEYED	ALL	5u" Au + high performance lubricant	NOTE 6



KEYWAY OPTION ON
69255-002LF & -006LF ONLY.



SPECIAL BEND REQUIRED BY
CUSTOMER FOR P/N 69255-001BLF



NOTES :

① SPECIAL PACKAGING.

② SOLDER TAIL LENGTH :

X = 0 [3.18 ±0.51 / 0.125 ±0.020]

X = 1 [8.13 ±0.51 / 0.320 ±0.020]

X = 2 [5.30 ±0.51 / 0.208 ±0.020]

X = 3 [3.70 ±0.51 / 0.145 ±0.020]

X = 4 [4.50 ±0.51 / 0.177 ±0.020]

[FOR X = 1 TO 4 , IF WIRE TRUE POSITION IS NOT APPLICABLE.]

[PACKAGING SPEC. IS GS-14-428

③ COLOR OF HOUSING :

Y = NIL (BLACK HOUSING)

Y = W (WHITE, RAL1013 HOUSING)

Y = G (GRAY, HOUSING)

④ SPECIAL REQUIREMENT :

SEE DETAIL C FOR P/N 69255-001B

FOR FEATURE DETAILS.

⑤ NO PANEL STOPS ON -X09Y AND -X10Y.

⑥ THIS PIN NUMBERING OPPOSITE TO

FCC, PART 68, SUB-PART F REQUIREMENTS

⑦ PART NUMBERS WITH LF IN THE END ARE LEAD FREE.

8 THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATION AS DESCRIBED IN GS-22-008.

9 THE HOUSING TEMPERATURE WITHSTAND EXPOSURE TO 260°C PEAK
TEMPERATURE FOR 15 SECONDS IN A WAVE SOLDER APPLICATION WITH A
1.5 MM MINIMUM THICK CIRCUIT BOARD. SEE APPLICATION NOTES/PROCEDURES
IF THEY ARE AVAILABLE.

⑩ PLATING OPTION:

MAY BE EITHER GOLD OR GXT PLATED AT MANUFACTURER'S OPTION.

mat'l. code				surface	tolerance	projection	product family	
				ISO1302	ISO1101 ISO406		MOD JACK	
ltr	ecn no	dr	date	tolerances unless otherwise specified			title	
AJ	ELX-N-15334	Henry	07/18/13	angles	0.X±0.3		8 POS VERTICAL	
-	-	-	-	length	0.XX±0.15	mm	PC.B. MOD JACK ASSY	
AD	N08-0239	MHT	11/10/08	0°±2'	0.XXX±0.05	scale 2.0		
AE	N09-0092	SH MNO	01/13/10	dr	JANET	2/22/00	dwg no	
AF	ELX-N-010675	SH MNO	3/14/12	enfr	M.CHENG	12/19/00	sheet, 2 of 3 size	
AG	ELX-N-13786	Henry	01/02/13	chr	M.CHENG	12/19/00	69255	
AH	ELX-N-14061	Henry	02/18/13	appd	M.CHENG	12/19/00	A4	
sheet	revision						type Product Customer Drawing	
index	sheet							

PRODUCT NO. ④	DIM. A	DIM. B	DIM. C	STYLE	POSITIONS LOADED	CONTACT PLATING ①	NOTES
69255-X01YHLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	-
-X02YHLF	1.25 /0.050	2.69 /0.106	15.62/0.615	KEYED	ALL	5u" Au + high performance lubricant	-
-X03YHLF	-	-	15.62/0.615	UNKEYED	2,3,4,5,6,7	5u" Au + high performance lubricant	-
-X04YHLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	-
-X05YHLF	-	-	15.62/0.615	UNKEYED	ALL	1.27um /50u" GXT	-
-X06YHLF	1.25 /0.050	2.69 /0.106	15.62/0.615	KEYED	ALL	1.27um /50u" GXT	-
-X07YHLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	NOTE 1
-X08YHLF	-	-	15.62/0.615	UNKEYED	3,4,5,6	5u" Au + high performance lubricant	-
-X09YHLF	-	-	15.62/0.615	UNKEYED	ALL	5u" Au + high performance lubricant	NOTE 6
-X10YHLF	-	-	13.62/0.536	UNKEYED	ALL	5u" Au + high performance lubricant	NOTE 6

MEETS PIP PROCESS PRODUCT NO.

mat'l. code				surface ISO1302		tolerance ISO1101 ISO406		projection 		product family MOD JACK											
litr		ecr no		dr		date		tolerances unless otherwise specified		title											
AJ		ELX-N-15334		Henry		7/18/13		angles		0.X±0.3				8 POS VERTICAL PC.B. MOD JACK ASSY							
-		-		-		-		0.XX±0.15													
AD		N08-0239		MHT		11/10/08		0'±2"		0.XXX±0.05											
AE		N09-0092		SH		MMO		01/13/10		dr		JANET		2/22/00		dwg no		sheet, 3 of 3		size	
AF		ELX-N-010675		SH		MMO		3/14/12		enfr		M.CHENG		12/19/00				69255		A4	
AG		ELX-N-13786		Henry		01/02/13		chr		M.CHENG		12/19/00									
AH		ELX-N-14061		Henry		02/18/13		appd		M.CHENG		12/19/00									
sheet		revision																			
index		sheet																			

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru