

# Features

# Regulated Converters

- Wide input range 85-305Vac
- Full load temperature range: -40°C to +65°C
- Ultra-high efficiency over entire load range
- No external components necessary
- International EMC compliant
- Lowest total cost of ownership
- 140% Peak Load Capability



# RAC10-K/277

**10 Watt**  
**2" x 1"**  
**Single and Dual Output**



UL/IEC/EN62368-1 (pending)  
 UL/IEC/EN60950-1 (pending)  
 IEC/EN60335-1 (pending)  
 CSA C22.2 No. 60950-1-07 (pending)  
 CSA C22.2 No. 62368-1-14 (pending)  
 EN61204-3 (pending)  
 EN55022/EN55024 (pending)  
 FCC Part 15 (pending)

## Description

The RAC10-K/277 series are highly efficient PCB-Mount power conversion modules with ultra-low energy losses even in light load conditions. Built for worldwide usage, the AC/DC units cover an enhanced mains input range of 85Vac up to 305Vac and come with international safety certifications for both industrial and household standards. These AC/DC modules offer fully protected single or dual outputs as well as EMC class B compliance without the need of any external components. The 150% peak power capability makes the RAC10-K/277 series suitable for inductive, high start-up current or nonlinear loads. With a full load temperature range of -40°C to +65°C, they are ideal for always-on and standby mode operations in process automation, IoT and smart building applications.


## Selection Guide

| Part Number     | Input Voltage Range [VAC] | Output Voltage [VDC] | Output Current [mA] | Efficiency typ. <sup>(1)</sup> [%] | Max. Capacitive Load [µF] |
|-----------------|---------------------------|----------------------|---------------------|------------------------------------|---------------------------|
| RAC10-3.3SK/277 | 85-305                    | 3.3                  | 2500                | 79                                 | 10000                     |
| RAC10-05SK/277  | 85-305                    | 5                    | 2000                | 82                                 | 8000                      |
| RAC10-12SK/277  | 85-305                    | 12                   | 840                 | 84                                 | 1500                      |
| RAC10-15SK/277  | 85-305                    | 15                   | 670                 | 85                                 | 1000                      |
| RAC10-24SK/277  | 85-305                    | 24                   | 420                 | 84                                 | 330                       |
| RAC10-12DK/277  | 85-305                    | ±12                  | ±420                | 82                                 | ±1200                     |
| RAC10-15DK/277  | 85-305                    | ±15                  | ±340                | 83                                 | ±1000                     |

### Notes:

Note1: Efficiency is tested at 25°C with constant resistant mode at full load and 230VAC

## Model Numbering





**Specifications** (measured @  $t_a = 25^\circ\text{C}$ , nominal input voltage (115/230VAC), full load and after warm-up)

| BASIC CHARACTERISTICS                                |   |                          |                 |              |                      |
|--|---|--------------------------|-----------------|--------------|----------------------|
| Parameter  | Condition   |                          | Min.            | Typ.         | Max.                 |
| Internal Input Filter                                |   |                          | Pi Type         |              |                      |
| Input Voltage Range <sup>(2)</sup>                   | (refer to line derating graph on PA-5)                  |                          | 85VAC<br>120VDC |              | 305VAC<br>430VDC     |
| Input Current  | 115VAC<br>230VAC  |                          |                 |              | 0.25A<br>0.21A       |
| Inrush Current                                       | 230VAC  |                          |                 |              | 0.06A <sup>2</sup> s |
| No load Power Consumption                            |   |                          |                 | 150mW        | 250mW                |
| ErP Standby Mode Conformity (Output Load Capability) | 0.5W<br>Input Power= 1.0W<br>2.0W                       |                          |                 |              | 0.3W<br>0.7W<br>1.4W |
| Input Frequency Range                                |   |                          | 47Hz            |              | 63Hz                 |
| Overload Capability                                  | peak duty cycle: 10%; $T_{AMB} + 50^\circ\text{C}$ max. |                          |                 |              | 140%/10s             |
| Start-up Time  |   |                          |                 | 30ms         |                      |
| Rise Time  |   |                          |                 |              | 25ms                 |
| Hold-up time   | 115VAC<br>230VAC  |                          |                 | 15ms<br>90ms |                      |
| Minimum Load   |   |                          | 0%              |              |                      |
| Internal Operating Frequency                         |   |                          |                 |              | 100kHz               |
| Output Ripple and Noise                              | 20MHz BW  | 3.3Vout, 5Vout<br>others |                 | 60mVp-p      | 1% of Vout           |
| Power Factor   | 115VAC<br>230VAC  |                          | 0.6<br>0.5      |              |                      |

**Notes:**


Note2: The products were submitted for safety files at AC-Input operation.

**Efficiency vs. Load**



continued on next page

**Specifications** (measured @  $t_a = 25^\circ\text{C}$ , nominal input voltage (115/230VAC), full load and after warm-up)




## REGULATIONS

| Parameter          | Condition             |            | Value      |
|--------------------|-----------------------|------------|------------|
| Output Accuracy    |                       |            | ±1.0% typ. |
| Line Regulation    | low line to high line |            | ±0.5% typ. |
| Load Regulation    | 0-100% load           | 3.3, 5Vout | ±1.5% typ. |
|                    |                       | others     | ±1.0% typ. |
| Transient Response | 25% load step change  |            | 4.0% max.  |
|                    | Recovery Time         |            | 500µs      |

continued on next page

**Specifications** (measured @  $t_a = 25^\circ\text{C}$ , nominal input voltage (115/230VAC), full load and after warm-up)



## PROTECTIONS


| Parameter                      | Type                                 | Value                     |
|--------------------------------|--------------------------------------|---------------------------|
| Internal Input Fuse            |                                      | T2A, slow blow            |
| Short Circuit Protection (SCP) |                                      | Hiccup, automatic restart |
| Over Voltage Protection (OVP)  |                                      | 150% - 195%, Hiccup Mode  |
| Over Load Protection (OLP)     |                                      | 150% - 195%, Hiccup Mode  |
| Over Voltage Category (OVC)    |                                      | OVC II                    |
| Isolation Voltage              | tested for 1 minute                  | 4KVAC                     |
| Isolation Resistance           | I/P to O/P, Isolation Voltage 500VDC | 1GΩ min.                  |
| Isolation Capacitance          | I/P to O/P, 100kHz/0.1V              | 100pF max.                |
| Insulation Grade               |                                      | reinforced                |
| Leakage Current                |                                      | 0.25mA max.               |

## ENVIRONMENTAL

| Parameter                   | Condition                          | Value   |
|-----------------------------|------------------------------------|---|
| Operating Temperature Range | with derating (see graph)          | -40°C to +80°C  |
| Maximum Case Temperature    |                                    | +100°C  |
| Temperature Coefficient     |                                    | ±0.05%/°C   |
| Operating Altitude          |                                    | 3000m   |
| Operating Humidity          | non-condensing                     | 20% to 90% RH   |
| Design Lifetime             | 115VAC/60Hz and full load at +25°C | >10 x 10 <sup>3</sup> hours                                     |
| MTBF                        | according to MIL-HDBK-217F, G.B.   | +25°C   |
|                             |                                    | +65°C   |
| Pollution Degree            |                                    | PD2   |
| Vibration                   |                                    | 10-500Hz, 2G 10min./1cycle, period 60min. each along x,y,z axes |

continued on next page

**Specifications** (measured @  $t_a = 25^\circ\text{C}$ , nominal input voltage (115/230VAC), full load and after warm-up)







| SAFETY AND CERTIFICATIONS  |   |  |
|--|---|--|
| Certificate Type (Safety)  | Report / File Number                      | Standard   |
| Information Technology Equipment, General Requirements for Safety  | pending                                   | UL60950-1, 2nd Edition, 2014<br>CSA C22.2 No. 60950-1-07, 2nd Ed. 2014 |
| Audio/Video, information and communication technology equipment - Safety requirements                    | pending                                   | UL62368-1, 2nd Edition, 2014<br>CSA C22.2 Nr. 62368-1-14, 2nd Ed. 2014 |
| Information Technology Equipment, General Requirements for Safety (CB)                                   | pending                                   | IEC60950-1:2005, 2nd Edition +A2:2013                                  |
| Household and similar electrical appliances - Safety - Part 1: General requirements                      | pending                                   | IEC60335-1,2010+A1,2013<br>EN60335-1,2012+A11,2014                     |
| Information Technology Equipment, General Requirements for Safety (LVD)                                  | pending                                   | IEC60950-1, 2nd Edition + AM2, 2013<br>EN60950-1, 2nd Edition, 2014    |
| Audio/Video, information and communication technology equipment - Safety requirements (CB)               | pending                                   | IEC/EN62368-1, 2nd Edition, 2014                                       |
| Risk-Analysis  |   | ISO 14121-2  |
| RoHS2  | pending                                   | RoHS 2011/65/EU + AM2015/863   |
| EMC Compliance   | Conditions                                | Standard / Criterion   |
| Low-voltage power supplies DC output - Part 3: Electromagnetic compatibility                             |   | EN61204-3:2000   |
| Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement | pending                                   | AZS/NZS CSPR 22:2009 + A1:2010, Class B                                |
| ESD Electrostatic discharge immunity test  | ±8kV Air; ±4kV Contact                    | EN61000-4-2:2009, Criteria B   |
| Radiated, radio-frequency, electromagnetic field immunity test   | 10V/m                                     | EN61000-4-3:2006 + A2:2010, Criteria A                                 |
| Fast Transient and Burst Immunity  | AC In Port: ±2kV                          | EN61000-4-4:2012, Criteria B   |
| Surge Immunity   | AC In Port: ±1.0kV<br>DC Out Port: ±2.0kV | EN61000-4-5:2014, Criteria B   |
| Immunity to conducted disturbances, induced by radio-frequency fields                                    | 10Vrms                                    | EN61000-4-6:2014, Criteria A   |
| Power Magnetic Field Immunity  | 50Hz/ 1A/m                                | EN61000-4-8:2010, Criteria A   |
| Voltage Dips   | >90%<br>>30%                              | EN61000-4-11:2004, Criteria B<br>EN61000-4-11:2004, Criteria C         |
| Voltage Interruptions  | >95%                                      | EN61000-4-11:2004, Criteria C  |
| Voltage Fluctuations and Flicker in Public Low-Voltage Systems <=16A per phase                           |   | EN61000-3-3:2013   |

**Specifications** (measured @  $t_a = 25^\circ\text{C}$ , nominal input voltage (115/230VAC), full load and after warm-up)

| DIMENSION and PHYSICAL CHARACTERISTICS |           |                         |
|--|-----------|-------------------------|
| Parameter                              | Type      | Value                   |
| Material                               | Case      | black plastic (UL94V-0) |
|  | Potting   | silicone (UL94V-0)      |
|  | PCB       | FR4 (UL94V-0)           |
|  | Baseplate | plastic (UL94V-0)       |
| Package Dimension (LxWxH)              |           | 52.5 x 27.4 x 23.0mm    |
| Package Weight                         |           | 65g typ.                |



### Dimension Drawing (mm)



### Pin Connections

| Pin # | Single     | Dual       |
|-------|------------|------------|
| 1     | VAC in (N) | VAC in (N) |
| 2     | VAC in (L) | VAC in (L) |
| 3     | No Pin     | -Vout      |
| 4     | -Vout      | COM        |
| 5     | +Vout      | +Vout      |

NC= no connection  
 Tolerance: xx.x= ±0.5mm  
 xx.xx= ±0.25mm



### PACKAGING INFORMATION

| Parameter                   | Type           | Value                 |
|-----------------------------|----------------|-----------------------|
| Packaging Dimension (LxWxH) | tube           | 490.0 x 56.0 x 40.0mm |
| Packaging Quantity          |                | 15pcs                 |
| Storage Temperature Range   | non-condensing | -40°C to +85°C        |
| Storage Humidity            |                | 20% to 90% RH         |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)