

## 8458 Multi-Conductor - Audio, Control and Instrumentation Cable



For more Information  
please call

1-800-Belden1

**General Description:**

22 AWG stranded (7x30) tinned copper conductors, conductors cabled, PVC insulation, PVC Jacket.

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 15           | 22  | 7x30      | TC - Tinned Copper |

Total Number of Conductors:

15

**Insulation**

Insulation Material:

| Insulation Material      | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | 0.011                |

**Outer Shield**

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    | Nom. Wall Thickness (in.) |
|--------------------------|---------------------------|
| PVC - Polyvinyl Chloride | .040                      |

**Overall Cable**

Overall Cabling Color Code Chart:

| Color        |
|--------------|
| Black        |
| White        |
| Red          |
| Green        |
| Orange       |
| Blue         |
| White/Black  |
| Red/Black    |
| Green/Black  |
| Orange/Black |
| Blue/Black   |
| Black/White  |
| Red/White    |
| Green/White  |
| Blue/White   |

Overall Nominal Diameter:

0.315 in.

**Mechanical Characteristics (Overall)**

|                                   |                          |
|-----------------------------------|--------------------------|
| Operating Temperature Range:      | -20°C To +80°C           |
| UL Temperature Rating:            | 80°C (UL AWM Style 2576) |
| Bulk Cable Weight:                | 64 lbs/1000 ft.          |
| Max. Recommended Pulling Tension: | 135 lbs.                 |
| Min. Bend Radius/Minor Axis:      | 3.250 in.                |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                          |     |
|--------------------------|-----|
| NEC/(UL) Specification:  | CMG |
| CEC/C(UL) Specification: | CMG |

## 8458 Multi-Conductor - Audio, Control and Instrumentation Cable

|                                       |                            |
|---------------------------------------|----------------------------|
| AWM Specification:                    | UL Style 2576 (150 V 80°C) |
| CSA Specification:                    | FT4                        |
| EU Directive 2011/65/EU (ROHS II):    | Yes                        |
| EU CE Mark:                           | Yes                        |
| EU Directive 2000/53/EC (ELV):        | Yes                        |
| EU Directive 2002/95/EC (RoHS):       | Yes                        |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005                 |
| EU Directive 2002/96/EC (WEEE):       | Yes                        |
| EU Directive 2003/11/EC (BFR):        | Yes                        |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                        |
| MII Order #39 (China RoHS):           | Yes                        |

## Flame Test

|                 |                    |
|-----------------|--------------------|
| UL Flame Test:  | UL1685 FT4 Loading |
| CSA Flame Test: | FT4                |

## Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

## Electrical Characteristics (Overall)

## Nom. Inductance:

|                    |
|--------------------|
| Inductance (µH/ft) |
| .17                |

## Nom. Capacitance Conductor to Conductor:

|                     |
|---------------------|
| Capacitance (pF/ft) |
| 34                  |

## Nom. Conductor DC Resistance:

|                          |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 15.6                     |

## Max. Operating Voltage - UL:

|                               |
|-------------------------------|
| Voltage                       |
| 300 V RMS (CMG)               |
| 150 V RMS (UL AWM Style 2576) |

## Max. Recommended Current:

|                               |
|-------------------------------|
| Current                       |
| 2.1 Amps per conductor @ 25°C |

## Put Ups and Colors:

| Item #       | Putup    | Ship Weight | Color  | Notes | Item Desc      |
|--------------|----------|-------------|--------|-------|----------------|
| 8458 060100  | 100 FT   | 7.300 LB    | CHROME |       | 15 #22 PVC PVC |
| 8458 0601000 | 1,000 FT | 72.000 LB   | CHROME | C     | 15 #22 PVC PVC |
| 8458 060500  | 500 FT   | 35.500 LB   | CHROME | C     | 15 #22 PVC PVC |
| 8458 0605000 | 5,000 FT | 345.000 LB  | CHROME | C     | 15 #22 PVC PVC |

## Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 08-31-2012

© 2014 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)