




3M™ HM PRESS-FIT HEADER, 8-ROW, HM SERIES
FOR HARD METRIC APPLICATIONS




HM-H200E1-8CX1
HM-H244E2-8BX1




HM-H200DE1-8CX1
HM-H244DE2-8BX1




HM-H176D1-8CX1
HM-H220D2-8BX1




HM-H176DG1-8CX1
HM-H220DG2-8BX1



HM-H176DPWR1-8CX1
HM-H220DPWR2-8BX1



HM-H088FL1-8CX1
HM-H110FL2-8BX1



HM-H088FR1-8CX1
HM-H110FR2-8BX1

(UNLESS OTHERWISE SHOWN)
ORDERING INFORMATION
(ROWS I AND Z NOT LOADED)

HM-HXXXXX1-8CX1-XXXXX

HEADER POSITION AND TYPE

TAIL STYLE:
P = PRESS-FIT TAIL
S = SOLDER TAIL

PLATING

(UNLESS OTHERWISE SHOWN)
ORDERING INFORMATION
(ROWS I AND Z LOADED, 8.3MM MATE LENGTH)

HM-HXXXXX2-8BX1-XXXXX

HEADER POSITION AND TYPE

TAIL STYLE:
P = PRESS-FIT TAIL
S = SOLDER TAIL

PLATING

PLATING SPECIFICATIONS:

- TG30L = .76µM [30µIN] MIN. GOLD ON CONTACT AREA, LUBRICATED
2.54µM [100µIN] MIN. TIN/LEAD ON TERMINAL AREA (RIA C2 & E2 APPLY)
1.27µM [50µIN] MIN. NICKEL ALL OVER.
TYPICALLY HIGHER MAKE ORDER QUANTITIES AS COMPARED TO TG30.
- TG30 = .76µM [30µIN] MIN. GOLD ON CONTACT AREA
2.54µM [100µIN] MIN. TIN/LEAD ON TERMINAL AREA (RIA C2 & E2 APPLY)
1.27µM [50µIN] MIN. NICKEL ALL OVER.
STANDARD OPTION.
- TG50 = 1.27µM [50µIN] MIN. GOLD ON CONTACT AREA, LUBRICATED
2.54µM [100µIN] MIN. TIN/LEAD ON TERMINAL AREA (RIA C2 & E2 APPLY)
1.27µM [50µIN] MIN. NICKEL ALL OVER.
NON-STANDARD OPTION (AVAILABLE WITH LONGER LEAD TIMES AND
HIGHER MAKE ORDER QUANTITIES, MOQ)
- KR = .76µM [30µIN] MIN. GOLD ON CONTACT AREA
2.54µM [100µIN] MIN. MATTE TIN ON TERMINAL AREA (RIA C2 & E2 APPLY)
1.27µM [50µIN] MIN. NICKEL ALL OVER.

- * MODULAR/SCALABLE FORMAT IEC 61076-4-101
- * PRESS-FIT OF SOLDER TAIL VERSION
- * 101 MATED LINES PER INCH
- * SHIPS WITH PROTECTIVE CAP, WHICH ALSO SERVES AS AN INSERTION TOOL
- * END-TO-END STACKABLE WITH 8 ROW 3M™ HM AND HSHM PRODUCTS
- * INTEGRATED GUIDE AND GUIDE PIN
- * MULTI-PURPOSE CENTER (MPC) KEYING AND GUIDANCE
- * FOUR INTEGRATED 8.25 A POWER CONTACTS AND GUIDE PIN

- NOTES
1. MATERIAL:
PLASTIC: HIGH TEMP LCP, UL94V-0
PINS: COPPER ALLOY.
 2. REGULATORY INFORMATION:
ROHS COMPLIANT. SEE THE REGULATORY INFORMATION APPENDIX (RIA) IN THE "ROHS COMPLIANCE" SECTION OF WWW.3MCONNECTORS.COM FOR COMPLIANCE INFORMATION (RIA E1 & C1 APPLY)
 3. IN THE EVENT OF CONFLICT BETWEEN THIS DATA AND THAT CONTAINED IN THE PRODUCT SPECIFICATION, THE PRODUCT SPECIFICATION TAKES PRECEDENT.

3 MECHANICAL:

NORMAL FORCE (NOMINAL): .57N [58g] SIGNAL
ENGAGEMENT FORCE (NOMINAL): .32N [33g] SIGNAL
SEPARATION FORCE (NOMINAL): .20N [20g] SIGNAL
WIPE (NOMINAL, SHORTEST CONTACT): 2.67 [.105] SIGNAL
MATE/UNMATE CYCLES: 250
APPLICATION: THIS MODULE IS NOT SUITABLE FOR STAND-ALONE USE. (REFER TO IEC-61076-4-101)

3 ELECTRICAL:

CURRENT RATING (FULLY LOADED): 1A @ 70°C SIGNAL
INSULATION RESISTANCE: $1 \times 10^4 \text{ M}\Omega$ @ 100 V_{DC}
WITHSTANDING VOLTAGE: 750V_{RMS}

3 ENVIRONMENTAL:

TEMPERATURE RATING: -55°C TO 125°C
PROCESS RATING: MAX. 260°C (PER J-STD-020C)
WITHSTANDING VOLTAGE: 1 (PER J-STD-020C)



3M™ ELECTRONIC SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3mconnectors.com>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373



cAUs
UL FILE NO: E68080

DIMENSIONS: MM [INCHES]		A	39815	MAR 28,2012		JNC	TS
DESIGN REFERENCE		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
NEXT ASSEMBLY		CSTIGLIONE		MAR 28,2012		MFG	
DIVISION		INTERconnect Solutions		ISD		T. SUNIGA	
DO NOT SCALE DRAWING		SCALE 5/2		TOLERANCES EXCEPT AS NOTED		INCHES	
THIRD ANGLE PROJECTION		INTERPRET PER ASME Y14.5 - 1994		MILLIMETERS		.00 ± .01 .000 ± .005 .0000 ± .0000	
MAX SURFACE ROUGHNESS		SURFACES		.00 ± .03 .000 ± .013		.000 ± .000	
MARKED ONLY		ANGLES		3M		© 3M COPYRIGHT 2012	
TITLE		HM PRESS-FIT HEADER, 8-ROW, HM SERIES		CAGE NUMBER		D78-5100-2517-0	
MODEL		REV. A		SHT 1 OF 4		DET	

3M™ HM PRESS-FIT HEADER, 8-ROW, HM SERIES
FOR HARD METRIC APPLICATIONS





NOTES
1 CAPS TO BE REMOVED AFTER PRESS-FIT INSTALLATION PROCESS.




HM-H200E1-8CX1
HM-H244E2-8BX1

HM-H200DE1-8CX1
HM-H244DE2-8BX1



HM-H176D1-8CX1
HM-H220D2-8BX1



TYPICAL SIDE VIEW
DIMENSIONS FOR THE
HEADERS ON THIS DRAWING




STANDARD CONFIGURATION

DIM. "A"	5.3 [.21]	FOR ROWS A THRU H
DIM. "B"	4.4 [.17]	EXCEPT AS NOTED




FOR NON-STANDARD CONFIGURATIONS
CONTACT A 3M SALES REPRESENTATIVE

DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
10123456789	10123456789	1	2	3	4	5
DIVISION	INTERCONNECT SOLUTIONS	SCALE	3	TOLERANCES EXCEPT AS NOTED	INCHES	MILLIMETERS
DO NOT SCALE DRAWING	1	0.00 ± .01	0.00 ± .005	0.000 ± .0000	0 ± .03	0 ± .13
THIRD ANGLE PROJECTION	INTERPRET PER ASME Y14.5 - 1994	MAX SURFACE ROUGHNESS	0.00 ± .000	0.000 ± .000	0.000 ± .000	0.000 ± .000
MARKED ONLY	ANGLES	MODEL	1	2	3	4
3M	3M Center St. Paul, MN 55144	© 3M COPYRIGHT 2012	3M	3M	3M	3M
TITLE	HM PRESS-FIT HEADER, 8-ROW, HM SERIES	CAGE NUMBER	D	78-5100-2517-0	REV.	A
DET	1	2	3	4	5	6




3M™ HM PRESS-FIT HEADER, 8-ROW, HM SERIES
FOR HARD METRIC APPLICATIONS



HM-H176DG1-8CX1
HM-H220DG2-8BX1






HM-H088FL1-8CX1
HM-H110FL2-8BX1



POWER TAILS
(4 CONTACTS,
12 LEADS)

HM-H176DPWR1-8CXX
HM-H220DPWR2-8BXX




HM-H088FR1-8CX1
HM-H110FR2-8BX1

DIM. "B" TAIL LENGTH
1 = 4.4 [.17] PIN, 2.0 [.08] POWER
AND 2.0 [.08] ESD
2 = 4.4 [.17] PIN, 4.4 [.17] POWER
AND 2.0 [.08] ESD





DESIGN REFERENCE		NEXT ASSEMBLY		A 39815		MAR 28, 2012		JNC	TS
REV		ECO		ISSUE DATE AND DESCRIPTION		DRFT		CHKD	
DISTRIBUTION CODES		DIVISION CODE		CAGI		DATE		DATE	
Interconnect Solutions		ISD		CASTIGLIONE		MAR 28, 2012		MAR 28, 2012	
DO NOT SCALE DRAWING		SCALE 3/1		TOLERANCES EXCEPT AS NOTED		INCHES		MILLIMETERS	
THIRD ANGLE PROJECTION		INTERPRET PER ASME Y14.5 - 1994		MAX SURFACE ROUGHNESS		0.00 ± .01		0.00 ± .005	
MAX SURFACE ROUGHNESS		0.00 ± .01		0.00 ± .005		0.00 ± .01		0.00 ± .005	
MARKED ONLY		ANGLES		TITLE		HM PRESS-FIT HEADER, 8-ROW, HM SERIES		CAGE NUMBER	
MODEL		DRAWING NO.		REV.		D 78-5100-2517-0		A	
LISTS		YES		NO		SHT 3 OF 4			

3M™ HM PRESS-FIT HEADER, 8-ROW, HM SERIES
FOR HARD METRIC APPLICATIONS



HOLE PLATING TABLE				
HOLE	(FINISHED HOLE)	Cu THICKNESS	SnPb THICKNESS	DRILLED HOLE DIA.
DIM. "B"	.690-.790 [.0270-.0310]	.025-.045 [.0010-.0018]	.008-.018 [.0003-.0007]	.810-.860 [.0320-.0340]
DIM. "D"	.550-.650 [.0217-.0256]	.025-.045 [.0010-.0018]	.008-.018 [.0003-.0007]	.686-.727 [.0270-.0286]

1 ROW 1 AND 2 HOLES ARE ONLY USED FOR HM-HXXXX2-8BX1 STYLE HEADER.



RECOMMENDED PCB MOUNTING HOLE PATTERN
(VIEWED FROM COMPONENT SIDE)

DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
INTERCONNECT SOLUTIONS	ISD	CASTIGLIONE	MAR 28, 2012	MFG DATE		
DO NOT SCALE DRAWING	SCALE 3/1	TOLERANCES EXCEPT AS NOTED				
THIRD ANGLE PROJECTION						
MAX SURFACE ROUGHNESS						
MARKED ONLY						

A	39815	MAR 28, 2012	JNC	TS
REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
CASTIGLIONE	MAR 28, 2012	MFG DATE		
CHKD		DATE		
APPR	T. SUNIGA	DATE		
DATE	MAR 28, 2012			

3M 3M Center St. Paul, MN 55144

© 3M COPYRIGHT 2012
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.

TITLE
HM PRESS-FIT HEADER, 8-ROW, HM SERIES

CAGE NUMBER
D 78-5100-2517-0

REV.
A

MODEL
SHT 4 OF 4

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru