

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC

DIST

AD00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AL2	REVISED PER ECO-11-004820	11MAR11	RK	HMR

DATE CODE

AMP XXXX
3-435802-8
OFF

PIN 1 IDENT DOT

.38±.02

.022±.002 TYP

.100 TYP

A±.02

DATE CODE

AMP XXXX
435802-1
OFF

PIN 1 IDENT DOT

.38±.02

.022±.002 TYP

.100 TYP

A±.02

CLOSE
OPEN

.14±.02 TYP

.012 TYP

.19±.01

.315±.010

.02^{+.01}_{-.00}
STANDOFF, 4 PLC

.29±.02 TYP

MOUNTING SURFACE

FIG 1

CLOSE
OPEN

.14±.02 TYP

.012 TYP

.19±.01

.315±.010

.02^{+.01}_{-.00}
STANDOFF, 4 PLC

.29±.02 TYP

MOUNTING SURFACE

FIG 2

CONTACT ARRANGEMENT

7 NO POSITION MARKING.

8 NO PART NO. MARKING.

9 STRIPPABLE TAPE SEAL, SEE FIGURE 8.

10 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

1 FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7519.

2 SWITCH SHOWN IN OPEN POSITION.

3 ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLACK.

4 STAMPING WILL VARY ON 2 AND 3 POSITION TOPS DUE TO SPACE RESTRICTIONS.

5 STRIPPABLE TRANSPARENT SEAL, SEE FIG 6.

6 .315 DIMENSION APPLIES AT TERMINAL TIPS. TERMINALS ARE .300^{+.010}_{-.000} AT MOUNTING SURFACE.

	FIG 2	FIG 3A& 7		1.08	10	6-435802-3
SUPSD BY 1-435802-6	FIG 1	FIG 3B	9	.88	8	3-435802-8
10 OBSOLETE	FIG 2	7 8	5	.58	5	3-435802-1
SUPSD BY 2-5435802-9	FIG 2	7 8	5	.88	8	3-435802-0
SUPSD BY 1-435802-0	FIG 2	7 8	5	.48	4	2-435802-9
OBSOLETE	FIG 1	7	5	.28	2	2-435802-8
OBSOLETE	FIG 2	7	5	.28	2	2-435802-7
OBSOLETE	FIG 2	FIG 4	5	1.08	10	2-435802-6
OBSOLETE	FIG 2	7	5	.88	8	2-435802-5
OBSOLETE	FIG 2	FIG 3A& 5	5	.88	8	2-435802-4
	FIG 2			.48	4	2-435802-3
	FIG 2			1.28	12	2-435802-2
	FIG 2			1.18	11	2-435802-1
	FIG 2			1.08	10	2-435802-0
	FIG 2	FIG 3A	5	.98	9	1-435802-9
	FIG 2			.78	7	1-435802-8
	FIG 2			.68	6	1-435802-7
	FIG 2			.58	5	1-435802-6
	FIG 2			.48	4	1-435802-5
SUPSD BY 435802-2	FIG 2		5	.38	3	1-435802-4
SUPSD BY 3-1437590-2	FIG 1	FIG 3B	5	.28	2	1-435802-3
10 OBSOLETE	FIG 2			1.28	12	1-435802-2
	FIG 1	FIG 3B	5	.28	2	1-435802-0
	FIG 2		5	.88	8	435802-9
	FIG 2			1.08	10	435802-8
10 SUPSD BY 5435802-7	FIG 2	FIG 3A		.98	9	435802-7
	FIG 2			.78	7	435802-6
	FIG 2			.68	6	435802-5
	FIG 2			.58	5	435802-4
	FIG 2			.48	4	435802-3
	FIG 2	FIG 3A		.38	3	435802-2
	FIG 2	FIG 3A		.88	8	435802-1
	HOUSING	MARKING	PROTECTIVE SEAL	A	NO OF POSN	PART NO.

435802-1 SHOWN

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

MATERIAL: HOUSING & ROCKERS: POLYESTER CONTACTS: BERYLLIUM COPPER

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± -
1 PLC	± -
2 PLC	± -
3 PLC	± .005
4 PLC	± -
ANGLES	± -

FINISH: CONTACTS: PLATED .000030 MIN GOLD IN CONTACT AREA OVER .000050 MIN NICKEL

DWN: R. TALLEY 9-19-89

CHK: R. MILLER 9-19-89

APVD: H. LEITER 9-19-89

PRODUCT SPEC

APPLICATION SPEC

WEIGHT: -

CUSTOMER DRAWING

TE Connectivity

SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED

SIZE: A2 CAGE CODE: 00779 DRAWING NO: C=435802

RESTRICTED TO: -

SCALE: 4:1 SHEET: 1 of 2 REV: AL2




FIG 3A




FIG 3B




FIG 4





FIG 5



PROTECTIVE SEAL

FIG 6






FIG 7



PROTECTIVE SEAL

FIG 8

 $.010 \pm .010$ $.005^{+.010}_{-.005}$
TYP

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. TALLEY 9-19-89	 TE Connectivity			
		CHK R. MILLER 9-19-89				
DIMENSIONS: INCHES		APVD H. LEITER 9-19-89	NAME SWITCH ASSY, DIP, TYPE C, 7000 SERIES, SPST, SIDE ACTUATED			
		PRODUCT SPEC —				
		APPLICATION SPEC —				
		SIZE A2	CAGE CODE 00779	DRAWING NO C-435802	RESTRICTED TO —	
		CUSTOMER DRAWING				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		WEIGHT —	SCALE 4:1			
0 PLC ± —		SHEET 2 of 2				
1 PLC ± —		REV AL2				
2 PLC ± —						
3 PLC ± .005						
4 PLC ± —						
ANGLES ± —						
FINISH						
MATERIAL SEE SHEET 1						

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru