



RECOMMENDED P.C. BOARD HOLE LAYOUT

- 1 "AMP", "CSA", "D-C", AND "DATE CODE" WITH .062±.015 HIGH CHARACTERS WHERE SIZE PERMITS.
- 2 HOUSING: 1-70 POSITION SIZES MAY BE PPS, GLASS-FILLED OR PCT, GLASS-FILLED. POSITION SIZES GREATER THAN 70 WILL BE PPS, GLASS-FILLED.
- 3 CONTACT: PHOSPHOR BRONZE.
- 4 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] BRIGHT TIN-LEAD ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 5 THESE DIMENSIONS PERTAIN TO CAVITY C'S ONLY, NOT TO CONTACT LOCATIONS.
- 6 POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE CONTACT BEAMS).
- 7 CSA LOGO INK STAMPED WHITE ON HOUSING.
- 8 PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- 9 CONTACT FINISH: DUPLEX PLATED 0.00076 [.000030] GOLD IN CONTACT AREA, 0.00127-0.00254 [.000050-.000100] MATTE TIN ON SOLDER TAILS, ALL OVER 0.00127 [.000050] NICKEL.
- 10 ROHS 2002/95/EC COMPLIANT.
- 11 RECESSED AREA AROUND MOLD GATE IS OPTIONAL. THIS FEATURE IS ALLOWABLE ON EITHER SIDE OF HOUSING OR MAY NOT BE PRESENT AT ALL.
- 12 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER
OBSOLETE	34.49 [1.358]	10	22	8-532956-0	OBSOLETE	34.49 [1.358]	10	22	3-532956-0
OBSOLETE	39.57 [1.558]	12	26	7-532956-9	OBSOLETE	39.57 [1.558]	12	26	2-532956-9
OBSOLETE	62.43 [2.458]	21	44	7-532956-8	OBSOLETE	62.43 [2.458]	21	44	2-532956-8
OBSOLETE		79	160	7-532956-7	OBSOLETE				2-532956-7
OBSOLETE	24.33 [.958]	6	14	7-532956-6	OBSOLETE	24.33 [.958]	6	14	2-532956-6
OBSOLETE	24.33 [.958]	6	14	7-532956-5	OBSOLETE	24.33 [.958]	6	14	2-532956-5
OBSOLETE	235.15 [9.258]	89	180	7-532956-4	OBSOLETE	235.15 [9.258]	89	180	2-532956-4
OBSOLETE	260.55 [10.258]	99	200	7-532956-3	OBSOLETE	260.55 [10.258]	99	200	2-532956-3
OBSOLETE	194.51 [7.658]	73	148	7-532956-2	OBSOLETE	194.51 [7.658]	73	148	2-532956-2
OBSOLETE	184.35 [7.258]	69	140	7-532956-1	OBSOLETE	184.35 [7.258]	69	140	2-532956-1
OBSOLETE	171.65 [6.758]	64	130	7-532956-0	OBSOLETE	171.65 [6.758]	64	130	2-532956-0
OBSOLETE	169.11 [6.658]	63	128	6-532956-9	OBSOLETE	169.11 [6.658]	63	128	1-532956-9
OBSOLETE	158.95 [6.258]	59	120	6-532956-8	OBSOLETE	158.95 [6.258]	59	120	1-532956-8
OBSOLETE	146.25 [5.758]	54	110	6-532956-7	OBSOLETE	146.25 [5.758]	54	110	1-532956-7
OBSOLETE	133.55 [5.258]	49	100	6-532956-6	OBSOLETE	133.55 [5.258]	49	100	1-532956-6
OBSOLETE	128.47 [5.058]	47	96	6-532956-5	OBSOLETE	128.47 [5.058]	47	96	1-532956-5
OBSOLETE	120.85 [4.758]	44	90	6-532956-4	OBSOLETE	120.85 [4.758]	44	90	1-532956-4
OBSOLETE	113.23 [4.558]	42	86	6-532956-3	OBSOLETE	113.23 [4.558]	42	86	1-532956-3
OBSOLETE	108.15 [4.258]	39	80	6-532956-2	OBSOLETE	108.15 [4.258]	39	80	1-532956-2
OBSOLETE	97.99 [3.858]	35	72	6-532956-1	OBSOLETE	97.99 [3.858]	35	72	1-532956-1
OBSOLETE	95.45 [3.758]	34	70	6-532956-0	OBSOLETE	95.45 [3.758]	34	70	1-532956-0
OBSOLETE	82.75 [3.258]	29	60	5-532956-9	OBSOLETE	82.75 [3.258]	29	60	532956-9
OBSOLETE	70.05 [2.758]	24	50	5-532956-8	OBSOLETE	70.05 [2.758]	24	50	532956-8
OBSOLETE	57.35 [2.258]	19	40	5-532956-7	OBSOLETE	57.35 [2.258]	19	40	532956-7
OBSOLETE	52.27 [2.058]	17	36	5-532956-6	OBSOLETE	52.27 [2.058]	17	36	532956-6
OBSOLETE	44.65 [1.758]	14	30	5-532956-5	OBSOLETE	44.65 [1.758]	14	30	532956-5
OBSOLETE	37.03 [1.458]	11	24	5-532956-4	OBSOLETE	37.03 [1.458]	11	24	532956-4
OBSOLETE	31.95 [1.258]	9	20	5-532956-3	OBSOLETE	31.95 [1.258]	9	20	532956-3
OBSOLETE	26.87 [1.058]	7	16	5-532956-2	OBSOLETE	26.87 [1.058]	7	16	532956-2
OBSOLETE	21.79 [.858]	5	12	5-532956-1	OBSOLETE	21.79 [.858]	5	12	532956-1
FINISH	B	A	NO OF POSN	PART NUMBER	FINISH	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. 17JAN01

DIN: K.L.CLOUSER/UTA
CHK: DOUG SARVER
APVD: DON FORKER 05/15/91

TE Connectivity

RECEPTACLE ASSY, MOD II, DBL ROW,
2.54 X 2.54 [.100 X .100] CL, GUIDE PIN EARS,
CLOSED ENTRY, SHORT-POINT-OF-CONTACT

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 532956

WEIGHT: --

CUSTOMER DRAWING SCALE: 6:1 SHEET: 1 OF 1 REV: AF3

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru