

# UP5

## High power, drum inductors



### Description

- 18.54 x 15.24 x 7.11mm maximum surface mount package
- Ferrite core material
- Inductance range from 1.0 $\mu$ H to 1000 $\mu$ H
- Current range from 0.56 to 20 Amps
- Frequency range up to 1MHz
- RoHS compliant

### Applications

- Buck or boost inductor
- Desktop computer
- Workstations/servers
- DVD Players
- Portable power devices
- Base stations
- Industrial power supplies
- Output filter chokes
- Test equipment instrumentation

### Environmental Data

- Storage temperature range: -40°C to +125°C
- Operating temperature range: -40°C to +125°C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020D compliant



## Product Specifications

| Part Number <sup>5</sup> | OCL <sup>1</sup> $\mu\text{H} \pm 20\%$ | I <sub>rms</sub> <sup>2</sup> (amps) | sat <sup>3</sup> (amps)<br>@25°C | SRF MHz typical | DCR m $\Omega$ @ 20°C<br>Maximum | K-factor <sup>4</sup> |
|--------------------------|-----------------------------------------|--------------------------------------|----------------------------------|-----------------|----------------------------------|-----------------------|
| UP5-1R0-R                | 1.0                                     | 8.6                                  | 20.0                             | 140             | 9.0                              | 73.61                 |
| UP5-1R5-R                | 1.5                                     | 7.5                                  | 18.0                             | 110             | 12.0                             | 60.22                 |
| UP5-2R2-R                | 2.2                                     | 7.1                                  | 16.0                             | 75.0            | 14.0                             | 50.96                 |
| UP5-3R3-R                | 3.3                                     | 6.2                                  | 14.0                             | 70.0            | 18.0                             | 44.16                 |
| UP5-5R6-R                | 5.6                                     | 5.3                                  | 12.0                             | 45.0            | 20.0                             | 31.55                 |
| UP5-100-R                | 10.0                                    | 4.3                                  | 10.0                             | 21.0            | 31.0                             | 24.54                 |
| UP5-150-R                | 15.0                                    | 4.0                                  | 8.0                              | 16.0            | 36.0                             | 20.07                 |
| UP5-220-R                | 22.0                                    | 3.5                                  | 7.0                              | 13.0            | 47.0                             | 16.99                 |
| UP5-330-R                | 33.0                                    | 3.0                                  | 5.5                              | 11.0            | 66.0                             | 14.09                 |
| UP5-470-R                | 47.0                                    | 2.6                                  | 4.5                              | 9.0             | 86.0                             | 11.62                 |
| UP5-680-R                | 68.0                                    | 2.3                                  | 3.5                              | 6.5             | 130                              | 9.60                  |
| UP5-101-R                | 100                                     | 1.8                                  | 3.0                              | 5.7             | 190                              | 7.98                  |
| UP5-151-R                | 150                                     | 1.5                                  | 2.6                              | 4.5             | 250                              | 6.56                  |
| UP5-221-R                | 220                                     | 1.2                                  | 2.4                              | 3.7             | 380                              | 5.39                  |
| UP5-331-R                | 330                                     | 1.0                                  | 1.9                              | 3.0             | 560                              | 4.39                  |
| UP5-471-R                | 470                                     | 0.82                                 | 1.4                              | 2.7             | 850                              | 3.70                  |
| UP5-681-R                | 680                                     | 0.72                                 | 1.2                              | 2.2             | 1100                             | 3.08                  |
| UP5-102-R                | 1000                                    | 0.56                                 | 1.0                              | 2.0             | 1800                             | 2.54                  |

1. OpenCircuitInductance(OCL)TestParameters:100kHz,0.25Vrms,0.0Adc

2. I<sub>rms</sub>: DC current for an approximate  $\Delta T$  rise of 40°C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow and proximity of other heat generating components will affect the temperature rise. It is recommended the part temperature not exceed 125°C under worst case operating conditions verified in the end application.

3. Isat: Peak current for approximately 10% rolloff at 25°C.


4. K-factor:UsedtodetermineBp-pforcoreloss(see graph).  $B_p-p = K \cdot L \cdot \Delta I$ , Bp-p:(Gauss), K: (K-factor from table), L: (inductance in  $\mu\text{H}$ ),  $\Delta I$  (peak-to-peak ripple current in amps).

5. Part Number Definition: UP5-xxx-R


- UP5 = Product code and size
- xxx= Inductance value in  $\mu\text{H}$ , R = decimal point. If no R is present, then third digit equals the number of zeros.
- "-R" suffix = RoHS compliant

## Dimensions (mm)


Top View




Side View




Bottom View



Recommended Pad Layout



Schematic




xxx = Inductance value in  $\mu\text{H}$  (R = Decimal point).

If no "R" is present, then the third digit equals the number of zeros.

wwlllyy = Date code R = Revision level

Packaging information


Supplied in tape-and-reel packaging, 250 parts per reel, 13" diameter reel.




Temperature rise vs. total loss



Core loss



Inductance characteristics



## Solder reflow profile




**Table 1 - Standard SnPb Solder ( $T_C$ )**

| Package Thickness | Volume mm <sup>3</sup> <350 | Volume mm <sup>3</sup> ≥350 |
|-------------------|-----------------------------|-----------------------------|
| <2.5mm)           | 235°C                       | 220°C                       |
| ≥2.5mm            | 220°C                       | 220°C                       |

**Table 2 - Lead (Pb) Free Solder ( $T_C$ )**

| Package Thickness | Volume mm <sup>3</sup> <350 | Volume mm <sup>3</sup> 350 - 2000 | Volume mm <sup>3</sup> >2000 |
|-------------------|-----------------------------|-----------------------------------|------------------------------|
| <1.6mm            | 260°C                       | 260°C                             | 260°C                        |
| 1.6 – 2.5mm       | 260°C                       | 250°C                             | 245°C                        |
| >2.5mm            | 250°C                       | 245°C                             | 245°C                        |

## Reference JEDEC J-STD-020D

| Profile Feature                                                                    | Standard SnPb Solder | Lead (Pb) Free Solder |
|------------------------------------------------------------------------------------|----------------------|-----------------------|
| Preheat and Soak                                                                   |                      |                       |
| • Temperature min. ( $T_{smin}$ )                                                  | 100°C                | 150°C                 |
| • Temperature max. ( $T_{smax}$ )                                                  | 150°C                | 200°C                 |
| • Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )                                      | 60-120 Seconds       | 60-120 Seconds        |
| Average ramp up rate $T_{smax}$ to $T_p$                                           | 3°C/ Second Max.     | 3°C/ Second Max.      |
| Liquidous temperature ( $T_L$ )                                                    | 183°C                | 217°C                 |
| Time at liquidous ( $t_L$ )                                                        | 60-150 Seconds       | 60-150 Seconds        |
| Peak package body temperature ( $T_p$ )*                                           | Table 1              | Table 2               |
| Time ( $t_p$ )** within 5 °C of the specified classification temperature ( $T_C$ ) | 20 Seconds**         | 30 Seconds**          |
| Average ramp-down rate ( $T_p$ to $T_{smax}$ )                                     | 6°C/ Second Max.     | 6°C/ Second Max.      |
| Time 25°C to Peak Temperature                                                      | 6 Minutes Max.       | 8 Minutes Max.        |

\* Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum.

\*\* Tolerance for time at peak profile temperature ( $t_p$ ) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
**Electronics Division**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
www.eaton.com/elx

© 2015 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 4409 BU09493  
December 2015

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)