

A

B

C

D

E

F

1 0 1 1 5 0 9 1 - X 0 E - X X X L F

8-COLUMN
DIFFERENTIAL
SIGNAL

LEAD-FREE DESIGNATION
ONLY WITH APPLICABLE
PLATING CODES

LETTER	PLATING (SEE NOTE 6)	
	APPLICATION	TYPE (REFERENCE)
B	TELCORDIA CO	0.76um GOLD or GXT
C	TELCORDIA UE	1.27um GOLD
D	TELCORDIA CO	0.76um GOLD or GXT, LEAD-FREE
E	TELCORDIA UE	1.27um GOLD, LEAD-FREE

NUMBER	GUIDE PIN STYLE (SEE NOTE 8)
0	STANDARD GUIDE PIN, MACHINED
1	STANDARD GUIDE PIN, ROLLED


MODULE DESCRIPTION	LETTER DESIGNATION REPRESENTED IN DASH NUMBER										BASE MODULE
LEFT POLARIZING GUIDANCE MODULE (SEE SHEET 6)	N	J	A	B	C	D	E	F	G	H	
	NO KEY NO GUIDE PIN										
RIGHT POLARIZING GUIDANCE MODULE (SEE SHEET 7)	Z	Y	P	Q	R	S	T	U	V	W	
	NO KEY NO GUIDE PIN										
OPEN MODULE (TWO WALL) (SEE SHEET 2)	0 (ZERO)										
LEFT WALL MODULE (SEE SHEET 3)	L										
RIGHT WALL MODULE (SEE SHEET 4)	M										
FOUR WALL MODULE (SEE SHEET 5)	1 (ONE)										


NUMBER	CONTACT MATING WIPE LENGTH		COMPLIANT TAIL TYPE (SEE NOTE 9)
	SIGNAL	GROUND	
1	2 MM	4 MM	0.55 (0.0217") DRILL
2	3 MM	4 MM	0.55 (0.0217") DRILL
3	2 MM	4 MM	0.45 MICRO (0.0177") DRILL
4	3 MM	4 MM	0.45 MICRO (0.0177") DRILL
5	2 MM	3 MM	0.55 (0.0217") DRILL
6	3 MM	3 MM	0.55 (0.0217") DRILL
7	2 MM	3 MM	0.45 MICRO (0.0177") DRILL
8	3 MM	3 MM	0.45 MICRO (0.0177") DRILL
FOR CUSTOM-LOADED MODULES, SEE INDIVIDUAL CUSTOM DRAWINGS WITH THE DRAWING-NUMBER FORMAT OF 10115091-XXXX, WHERE: "X" DENOTES MODULE TYPE PER CHART ON THIS SHEET "YYYY" IS A SEQUENTIAL NUMBER BEGINNING WITH "0001".			

TABLE 1 (SEE NOTE 11)		
	UNGROUNDED	GROUNDED
FHS	Ø2.35-Ø2.55	Ø2.35-Ø2.55
PAD	N/A	Ø5.50
PLATED	NO	YES
DRILL(mm)	2.44mm	2.58mm
DRILL(in)	0.096"	0.1015"

TABLE 2 (SEE NOTE 12)		
SCREW P/N	DESCRIPTION	BOARD THICKNESS
10091790-002LF	#2-56 X 0.375" LG. PHILIPS PANHEAD W/SQ CONICAL WASHER	1.60-5.00mm
10091790-003LF	#2-56 X 0.375" LG. PHILIPS PANHEAD W/SQ CONICAL WASHER	5.00-10.00mm

spec ref	-		
tolerance std	TOLERANCES UNLESS OTHERWISE SPECIFIED		
ISO 406			
ISO 1101			
surface 	linear	0.X	±0.3
		0.XX	±0.10
		0.XXX	±0.05
	ISO 1302	angular	0°





dr	Collins Lu	2011/07/27	projection		mm		size	A2	scale	1:1
eng	Sandar Soe	2016/03/07					ecn no	ELX-S-17624-1		
chr	-	-	product family	-	-	-	rel level	Released		
appr	Chen-Hong Tan	2016/03/17								
Amphenol FCI		title	MODULE ASSEMBLY, XCEDE HD				dwg no	10115091		rev
			Vertical Header, 4 Pair 8 Column							E
www.fci.com		cat. no.	-	Product - Customer Drw				sheet 1 of 8		




SEE NOTE 5

PIN AI

OPEN WALL MODULE



BP HOLE PATTERN COMPONENT SIDE
OPEN WALL MODULE BACKPLANE FOOTPRINT


spec ref		-		dr		Collins Lu		2011/07/27		projection		mm		size		A2		scale		1:1	
tolerance std		ISO 406		eng		Sandar Soe		2016/03/07						ecn no		ELX-S-17624-1		rel level		Released	
ISO 1101		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		-		-													
surface		ISO 1302		appr		Chen-Hong Tan		2016/03/17		product family		-		rel level		Released		rev		E	
		linear		0.X		±0.3		Amphenol FCI		title		MODULE ASSEMBLY, XCEDE HD		dwg no		10115091		rev		E	
		0.XX		±0.10																	
		0.XXX		±0.05																	
angular		0°		±2°		www.fci.com		cat. no.		-		Product - Customer Drw		sheet 2 of 8							

PDS: Rev :E






STATUS:Released

Printed: Mar 17, 2016

Printed: Mar 17, 2016




RIGHT WALL MODULE








RIGHT WALL MODULE BACKPLANE FOOTPRINT

spec ref	-	dr	Collins Lu	2011/07/27	projection	mm	size	A2	scale	1:1
tolerance std	ISO 406 ISO 1101	eng	Sandar Soe	2016/03/07	chr	-	ecn no	ELX-S-17624-1	rel level	
surface	ISO 1302	appr	Chen-Hong Tan	2016/03/17	product family	-	rel level	Released		
TOLERANCES UNLESS OTHERWISE SPECIFIED		linear	0.X	±0.3	Amphenol FCi		MODULE ASSEMBLY, XCEDE HD Veritcal Header, 4 Pair 8 Column		dwg no 10115091	
			0.XX	±0.10						
			0.XXX	±0.05						
	angular	0°	±2°		www.fci.com	cat. no.	-	Product - Customer Drw	sheet 4 of 8	rev E



FOUR WALL MODULE



FOUR WALL MODULE BACKPLANE FOOTPRINT

spec ref	-	dr	Collins Lu	2011/07/27	projection	mm	size	A2	scale	1:1
tolerance std	ISO 406 ISO 1101	eng	Sandar Soe	2016/03/07	chr	-	ecn no	ELX-S-17624-1	rel level	Released
surface	ISO 1302	appr	Chen-Hong Tan	2016/03/17	product family	-	cat. no.	Product - Customer Drw	sheet 5 of 8	rev
linear	0.X ±0.3 0.XX ±0.10 0.XXX ±0.05	Amphenol FCI	title	MODULE ASSEMBLY, XCEDE HD	dwg no	10115091	rev	E		
angular	0° ±2°	www.fci.com	cat. no.	-	Product - Customer Drw	sheet 5 of 8				

LEFT POLARIZING/GUIDE MODULE



BP HOLE PATTERN COMPONENT SIDE
LEFT POLARIZING GUIDE MODULE
BACKPLANE FOOTPRINT

Optional Key See Sheet 1
Part Number Tree

SEE NOTE 5

SEE NOTE 11 & TABLE 1





SEE DETAIL A
OnSheet 8 For Details

spec ref		-		dr		Collins Lu		2011/07/27		projection		mm		size		A2		scale		1:1									
tolerance std		ISO 406 ISO 1101		eng		Sandar Soe		2016/03/07						ecn no		ELX-S-17624-1		Released											
TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		-		-		appr						Chen-Hong Tan		2016/03/17				product family		-							
		surface		ISO 1302		linear		0.X ±0.3 0.XX ±0.10 0.XXX ±0.05		angular		0° ±2°		Amphenol FCi		www.fci.com		cat. no.		-		Product - Customer Drw		sheet 6 of 8		rev		E	
																title		MODULE ASSEMBLY, XCEDE HD		dwg no		10115091							

PDS: Rev :E

STATUS:Released

Printed: Mar 17, 2016







TABLE 3		
	COMPLIANT PIN DRILL $\varnothing 0.55[0.0217"]$	COMPLIANT PIN DRILL $\varnothing 0.45[0.0177"]$
PTH	$\varnothing 0.45 \pm 0.05$	$\varnothing 0.36 \pm 0.05$
DRILL	$\varnothing 0.55 [0.0217"]$	$\varnothing 0.45 [0.0177"]$
PAD	$\varnothing 0.85$	$\varnothing 0.75$

NOTES:

- CONNECTOR MATERIALS
SHROUD : HIGH-TEMP POLYMER, COLOR : BLACK, UL94V-0
CONTACTS : HIGH PREFORMANCE COPPER ALLOY
- PRODUCT SPECIFICATION : GS-12-0936
- APPLICATION SPECIFICATION : GS-20-0348
- PRODUCT MARKING :
PART NUMBER (10115091-XOE-XXXLF)
"FCI" AND DATE CODE (FCI P#####)
- NOTCH DESIGNATES "ROW A" SIDE OF CONNECTOR. NOTCH FEATURE ON OPPOSITE FOR PRODUCT MARKING.
- PLATING THICKNESS OF SIGNAL & GROUND CONTACT ARE DETERMINED BY PLATING CODE, REFER TO P/N TREE ON SHEET 1.
- PACKAGING MEETS GS-14-920 LEAD-FREE LABELING SPECIFICATION.
- GUIDE-PIN STYLE DESIGNATION ONLY APPLIES TO MODULE VERSIONS THAT REQUIRE GUIDE-PIN HARDWARE. FOR ALL NON-GUIDE-PIN VERSIONS, THE DEFAULT DASH-NUMBER DIGIT IN THAT LOCATION IS STILL '0'.
- SEE APPLICATION SPECIFICATION FOR ROUTING GUIDELINES, ADDITIONAL PTH GUIDELINES, MATED DIMENSIONS, GUIDE PIN SELECTION, ETC.
- A $\triangle$ SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE THAT HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.
- OPTIONAL HOLE LOCATION FOR GROUNDED PIN OR ADDITIONAL GUIDE-PIN SUPPORT. SEE TABLE 1 SHEET 1 FOR ADDITIONAL DETAILS.
- SCREW IS OPTIONAL AND ENGAGES WITH BOTTOM OF GUIDE PIN FROM BENEATH THE PCB FOR ADDITIONAL GUIDE-PIN SUPPORT.

spec ref -		dr Collins Lu		2011/07/27		projection		mm		size A2		scale 1:1	
tolerance std		eng Sandar Soe		2016/03/07						ecn no		ELX-S-17624-1	
ISO 406 ISO 1101		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr -						appr Chen-Hong Tan		2016/03/17	
surface 		linear		0.X ±0.3 0.XX ±0.10 0.XXX ±0.05		Amphenol FCI		title MODULE ASSEMBLY, XCEDE HD Veritical Header, 4 Pair 8 Column		dwg no 10115091		rev E	
ISO 1302		angular 0° ±2°		www.fci.com									

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru