
Continental Device India Limited

An ISO/TS16949 and ISO 9001 Certified Company

HIGH SPEED SILICON SWITCHING DIODES

CLL4148
CLL4448

SOD - 80C
Mini MELF (LL- 34)



Polarity: Cathode is indicated by a black band

Hermetically Sealed, Glass Silicon Diodes

ABSOLUTE MAXIMUM RATINGS

DESCRIPTION	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
Reverse Voltage (Continuous)	V_R	75	V
Average Rectified Forward Current	I_F (av)	150	mA
Forward Current (DC)	I_F	200	mA
Repetitive Peak Forward Current	I_{FRM}	450	mA
Non Repetitive Peak Surge Current t=1 ms	I_{FSM}	2000	mA
t=1 s	I_{FSM}	500	mA
Power Dissipation up to Tamb=25 ºC	P_{tot}	500	mW
Derating factor		2.85	mW/K
Operating & Storage Junction Temperature Range	T_j, T_{stg}	- 65 to +200	ºC


ELECTRICAL CHARACTERISTICS (Ta=25 ºC Unless Otherwise Specified)


DESCRIPTION	SYMBOL	TEST CONDITION		MIN	MAX	UNIT
Forward Voltage	V_F	I_F=10mA	**CLL4148**		1.0	V
		I_F=5mA	**CLL4448**	0.62	0.72	
		I_F=100mA	**CLL4448**		1.0	
Reverse Current	I_R	V_R=20V			25	nA
		V_R=75V			5.0	µA
		V_R=20V, T_j=100º C,	**CLL4448**		3.0	µA
		V_R=20V, T_j=150º C			50	µA
Reverse Breakdown Voltage	V_{BR}	I_R=100µA		100		V

DYNAMIC CHARACTERISTICS


Diode Capacitance	C_d	V_R=0V, f=1MHz		4.0	pF
Forward Recovery Voltage	V_{fr}	I_F=50mA, t_r=20ns		2.5	V
Reverse Recovery Time	t_{rr}	I_F=10mA, to I_R=60mA R_L=100 Ω Measured @ I_R=1mA	.	4.0	ns

SOD 80C (LL-34) Mini MELF Hermetically Sealed Glass Package





All dimensions are in mm



Notes :-

1. Maximum of 0.5% of the total number of components per reel may be missing- exclusively at the beginning and at the end of the reel.
2. A maximum of three consecutive components may be missing, provided this gap is followed by six consecutive components.

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
SOD-80C T&R	2.5K/reel	100 gm/3K pcs	3" x 7.5" x 7.5"	10.0K	17" x 15" x 13.5"	160.0K	10 kgs
	10K/reel	400 gm/10K pcs	13" x 13" x 0.5"	10.0K	17" x 15" x 13.5"	300.0K	15 kgs

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.

CDIL is a registered Trademark of
Continental Device India Limited
C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119
email@cdil.com www.cdilsemi.com

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru