

### FEATURES

- ±4000 V HBM ESD
- High common-mode voltage range
  - 2 V to +65 V operating
  - 3 V to +68 V survival
- Buffered output voltage
- Wide operating temperature range
  - 5-lead SOT: –40°C to +125°C
- Excellent ac and dc performance
  - 5  $\mu\text{V}/^\circ\text{C}$  typical offset drift
  - 13 ppm/°C typical gain drift
  - 120 dB typical CMRR at dc

### APPLICATIONS

- High-side current sensing
  - Motor controls
  - Transmission controls
  - Engine management
  - Suspension controls
  - Vehicle dynamic controls
  - DC-to-dc converters

### GENERAL DESCRIPTION

The AD8211 is a high voltage, precision current shunt amplifier. It features a set gain of 20 V/V, with a typical  $\pm 0.5\%$  gain error over the entire temperature range. The buffered output voltage directly interfaces with any typical converter. Excellent common-mode rejection from –2 V to +65 V is independent of the 5 V supply. The AD8211 performs unidirectional current measurements across a shunt resistor in a variety of industrial and automotive applications, such as motor control, solenoid control, or battery management.

### FUNCTIONAL BLOCK DIAGRAM




Figure 1.

Special circuitry is devoted to output linearity being maintained throughout the input differential voltage range of 0 mV to 250 mV, regardless of the common-mode voltage present. The AD8211 has an operating temperature range of –40°C to +125°C and is offered in a small 5-lead SOT package.

#### Rev. 0

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

TABLE OF CONTENTS

|                                                   |   |                                                      |    |
|---------------------------------------------------|---|------------------------------------------------------|----|
| Features .....                                    | 1 | Theory of Operation .....                            | 10 |
| Applications .....                                | 1 | Application Notes .....                              | 11 |
| Functional Block Diagram .....                    | 1 | Output Linearity .....                               | 11 |
| General Description .....                         | 1 | Applications Information .....                       | 12 |
| Revision History .....                            | 2 | High-Side Current Sense with a Low-Side Switch ..... | 12 |
| Specifications .....                              | 3 | High-Side Current Sensing .....                      | 12 |
| Absolute Maximum Ratings .....                    | 4 | Low-Side Current Sensing .....                       | 12 |
| ESD Caution .....                                 | 4 | Outline Dimensions .....                             | 13 |
| Pin Configuration and Function Descriptions ..... | 5 | Ordering Guide .....                                 | 13 |
| Typical Performance Characteristics .....         | 6 |                                                      |    |

REVISION HISTORY

7/07—Revision 0: Initial Version

## SPECIFICATIONS

$T_{OPR} = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ ,  $T_A = 25^{\circ}\text{C}$ ,  $V_S = 5\text{ V}$ ,  $R_L = 25\text{ k}\Omega$  ( $R_L$  is the output load resistor), unless otherwise noted.

Table 1.

| Parameter                          | Min | Typ        | Max        | Unit                           | Conditions                                               |
|------------------------------------|-----|------------|------------|--------------------------------|----------------------------------------------------------|
| <b>GAIN</b>                        |     |            |            |                                |                                                          |
| Initial                            |     | 20         |            | V/V                            |                                                          |
| Accuracy                           |     |            | $\pm 0.25$ | %                              | $V_O \geq 0.1\text{ V dc}$                               |
| Accuracy Over Temperature          |     | $\pm 0.35$ |            | %                              | $T_{OPR}$                                                |
| Gain vs. Temperature               |     | -13        |            | ppm/ $^{\circ}\text{C}$        | $T_{OPR}^1$                                              |
| <b>VOLTAGE OFFSET</b>              |     |            |            |                                |                                                          |
| Offset Voltage (RTI)               |     |            | $\pm 1$    | mV                             | $25^{\circ}\text{C}$                                     |
| Over Temperature (RTI)             |     | $\pm 2.2$  |            | mV                             | $T_{OPR}$                                                |
| Offset Drift                       |     | 5          |            | $\mu\text{V}/^{\circ}\text{C}$ | $T_{OPR}^2$                                              |
| <b>INPUT</b>                       |     |            |            |                                |                                                          |
| Input Impedance                    |     |            |            |                                |                                                          |
| Differential                       |     | 5          |            | k $\Omega$                     |                                                          |
| Common Mode                        |     | 5          |            | M $\Omega$                     |                                                          |
|                                    |     | 3.5        |            | k $\Omega$                     | Common-mode voltage > 5 V                                |
| Common-Mode Input Voltage Range    | -2  |            | +65        | V                              | Common-mode voltage < 5 V                                |
| Differential Input Voltage Range   |     | 250        |            | mV                             | Common-mode continuous                                   |
| Common-Mode Rejection              | 100 | 120        |            | dB                             | Differential input voltage                               |
|                                    | 80  | 90         |            | dB                             | $T_A, f = \text{dc}, V_{CM} > 5\text{ V}$ , see Figure 5 |
|                                    |     |            |            |                                | $T_A, f = \text{dc}, V_{CM} < 5\text{ V}$ , see Figure 5 |
| <b>OUTPUT</b>                      |     |            |            |                                |                                                          |
| Output Voltage Range Low           | 0.1 | 0.05       |            | V                              |                                                          |
| Output Voltage Range High          |     | 4.95       | 4.9        | V                              |                                                          |
| Output Impedance                   |     | 2          |            | $\Omega$                       |                                                          |
| <b>DYNAMIC RESPONSE</b>            |     |            |            |                                |                                                          |
| Small Signal -3 dB Bandwidth       |     | 500        |            | kHz                            |                                                          |
| Slew Rate                          |     | 4.5        |            | V/ $\mu\text{s}$               |                                                          |
| <b>NOISE</b>                       |     |            |            |                                |                                                          |
| 0.1 Hz to 10 Hz, RTI               |     | 7          |            | $\mu\text{V p-p}$              |                                                          |
| Spectral Density, 1 kHz, RTI       |     | 70         |            | nV/ $\sqrt{\text{Hz}}$         |                                                          |
| <b>POWER SUPPLY</b>                |     |            |            |                                |                                                          |
| Operating Range                    | 4.5 |            | 5.5        | V                              |                                                          |
| Quiescent Current Over Temperature |     | 1.2        | 2.0        | mA                             | $V_{CM} > 5\text{ V}^3$ , see Figure 12                  |
| Power Supply Rejection Ratio       | 76  |            |            | dB                             |                                                          |
| <b>TEMPERATURE RANGE</b>           |     |            |            |                                |                                                          |
| For Specified Performance          | -40 |            | +125       | $^{\circ}\text{C}$             |                                                          |

<sup>1</sup> The mean of the gain drift distribution is typically  $-13\text{ ppm}/^{\circ}\text{C}$ , with a  $\sigma = 3\text{ ppm}/^{\circ}\text{C}$ .

<sup>2</sup> The mean of the offset drift distribution is typically  $+5\text{ }\mu\text{V}/^{\circ}\text{C}$ , with a  $\sigma = 3\text{ }\mu\text{V}/^{\circ}\text{C}$ .

<sup>3</sup> When the input common-mode voltage is less than 5 V, the supply current increases, which can be calculated by  $I_S = -0.275(V_{CM}) + 2.5$ .

ABSOLUTE MAXIMUM RATINGS

Table 2.

| Parameter                             | Rating          |
|---------------------------------------|-----------------|
| Supply Voltage                        | 12.5 V          |
| Continuous Input Voltage              | –3 V to +68 V   |
| Reverse Supply Voltage                | –0.3 V          |
| HBM (Human Body Model) ESD Rating     | ±4000 V         |
| CDM (Charged Device Model) ESD Rating | ±1000 V         |
| Operating Temperature Range           | –40°C to +125°C |
| Storage Temperature Range             | –65°C to +150°C |
| Output Short-Circuit Duration         | Indefinite      |

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ESD CAUTION



**ESD (electrostatic discharge) sensitive device.** Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS




Figure 2. Metallization Diagram




Figure 3. Pin Configuration

Table 3. Pin Function Descriptions

| Pin No. | Mnemonic         | X    | Y    | Description         |
|---------|------------------|------|------|---------------------|
| 1       | OUT              | −277 | +466 | Buffered Output.    |
| 2       | GND              | −140 | +466 | Ground.             |
| 3       | V <sub>IN+</sub> | −228 | −519 | Noninverting Input. |
| 4       | V <sub>IN−</sub> | +229 | −519 | Inverting Input.    |
| 5       | V+               | +264 | +466 | Supply.             |

## TYPICAL PERFORMANCE CHARACTERISTICS




Figure 4. Typical Offset vs. Temperature




Figure 7. Typical Small Signal Bandwidth ( $V_{OUT} = 200 \text{ mV p-p}$ )




Figure 5. Typical CMRR vs. Frequency




Figure 8. Total Output Error vs. Differential Input Voltage




Figure 6. Typical Gain Error vs. Temperature




Figure 9. Input Bias Current vs. Differential Input Voltage,  $V_{CM} = 0 \text{ V}$




Figure 10. Input Bias Current vs. Differential Input Voltage,  $V_{CM} = 5\text{ V}$




Figure 11. Input Bias Current vs. Input Common-Mode Voltage




Figure 12. Supply Current vs. Common-Mode Voltage




Figure 13. Fall Time




Figure 14. Rise Time




Figure 15. Differential Overload Recovery (Falling)




Figure 16. Differential Overload Recovery (Rising)




Figure 19. Maximum Output Sink Current vs. Temperature




Figure 17. Settling Time (Falling)




Figure 20. Maximum Output Source Current vs. Temperature




Figure 18. Settling Time (Rising)




Figure 21. Output Voltage Range vs. Output Source Current






Figure 22. Output Voltage Range from GND vs. Output Sink Current

## THEORY OF OPERATION

In typical applications, the AD8211 amplifies a small differential input voltage generated by the load current flowing through a shunt resistor. The AD8211 rejects high common-mode voltages (up to 65 V) and provides a ground-referenced, buffered output that interfaces with an analog-to-digital converter (ADC). Figure 23 shows a simplified schematic of the AD8211.




Figure 23. Simplified Schematic

A load current flowing through the external shunt resistor produces a voltage at the input terminals of the AD8211. The input terminals are connected to Amplifier A1 by Resistor R and Resistor R1. The inverting terminal, which has very high input impedance is held to

$$(V_{CM}) - (I_{SHUNT} \times R_{SHUNT})$$

because negligible current flows through Resistor R. Amplifier A1 forces the noninverting input to the same potential. Therefore, the current that flows through Resistor R1, is equal to

$$I_{IN} = (I_{SHUNT} \times R_{SHUNT})/R1$$

This current ( $I_{IN}$ ) is converted back to a voltage via  $R_{OUT}$ . The output buffer amplifier has a gain of 20 V/V and offers excellent accuracy as the internal gain setting resistors are precision trimmed to within 0.01% matching. The resulting output voltage is equal to

$$V_{OUT} = (I_{SHUNT} \times R_{SHUNT}) \times 20$$

## APPLICATION NOTES

### OUTPUT LINEARITY

In all current sensing applications, and especially in automotive and industrial environments where the common-mode voltage can vary significantly, it is important that the current sensor maintain the specified output linearity, regardless of the input differential or common-mode voltage. The AD8211 contains specific circuitry on the input stage, which ensures that even when the differential input voltage is very small, and the common-mode voltage is also low (below the 5 V supply), the input-to-output linearity is maintained. Figure 24 shows the input differential voltage vs. the corresponding output voltage at different common modes.




Figure 24. Gain Linearity Due to Differential and Common-Mode Voltage

Regardless of the common mode, the AD8211 provides a correct output voltage when the input differential is at least 2 mV, which is due to the voltage range of the output amplifier that can go as low as 33 mV typical. The specified minimum output amplifier voltage is 100 mV to provide sufficient guard-bands. The ability of the AD8211 to work with very small differential inputs, regardless of the common-mode voltage, allows for more dynamic range, accuracy, and flexibility in any current sensing application.

## APPLICATIONS INFORMATION

### HIGH-SIDE CURRENT SENSE WITH A LOW-SIDE SWITCH

In such load control configurations, the PWM-controlled switch is ground referenced. An inductive load (solenoid) is tied to a power supply. A resistive shunt is placed between the switch and the load (see Figure 25). An advantage of placing the shunt on the high side is that the entire current, including the recirculation current, can be measured because the shunt remains in the loop when the switch is off. In addition, diagnostics can be enhanced because shorts to ground can be detected with the shunt on the high side. In this circuit configuration, when the switch is closed, the common-mode voltage moves down to near the negative rail. When the switch is opened, the voltage reversal across the inductive load causes the common-mode voltage to be held one diode drop above the battery by the clamp diode.




Figure 25. Low-Side Switch

### HIGH-SIDE CURRENT SENSING

In this configuration, the shunt resistor is referenced to the battery. High voltage is present at the inputs of the current sense amplifier. In this mode, the recirculation current is again measured and shorts to ground can be detected. When the shunt is battery referenced, the AD8211 produces a linear ground-referenced analog output. An AD8214 can also be used to provide an over-current detection signal in as little as 100 ns. This feature is useful in high current systems where fast shutdown in over-current conditions is essential.




Figure 26. Battery-Referenced Shunt Resistor

### LOW-SIDE CURRENT SENSING

In systems where low-side current sensing is preferred, the AD8211 provides an integrated solution with great accuracy. Ground noise is rejected, CMRR is typically higher than 90 dB, and output linearity is not compromised, regardless of the input differential voltage.





Figure 27. Ground-Referenced Shunt Resistor

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MO-178-AA  
Figure 28. 5-Lead Small Outline Transistor Package [SOT-23]  
(RJ-5)  
Dimensions shown in millimeters

ORDERING GUIDE

| Model                       | Temperature Range | Package Description | Package Option | Branding |
|-----------------------------|-------------------|---------------------|----------------|----------|
| AD8211YRJZ-R2 <sup>1</sup>  | −40°C to +125°C   | 5-Lead SOT-23       | RJ-5           | Y02      |
| AD8211YRJZ-RL <sup>1</sup>  | −40°C to +125°C   | 5-Lead SOT-23       | RJ-5           | Y02      |
| AD8211YRJZ-RL7 <sup>1</sup> | −40°C to +125°C   | 5-Lead SOT-23       | RJ-5           | Y02      |

<sup>1</sup> Z = RoHS Compliant Part.

**AD8211**

**NOTES**

## NOTES

**AD8211**

## **NOTES**



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)