


MKP3V120, MKP3V240



Description

Bidirectional devices designed for direct interface with the ac power line. Upon reaching the breakover voltage in each direction, the device switches from a blocking state to a low voltage on-state. Conduction will continue like a Triac until the main terminal current drops below the holding current. The plastic axial lead package provides high pulse current capability at low cost. Glass passivation insures reliable operation.

Features

- High Pressure Sodium Vapor Lighting
- Strobes and Flashers
- Ignitors
- High Voltage Regulators
- Pulse Generators
- Used to Trigger Gates of SCR's and Triac
-  Indicates UL Registered – File #E128662
- These are Pb-Free Devices

Axial Lead

AXIAL LEAD
CASE 59
STYLE 2



Functional Diagram



Additional Information



Datasheet



Resources



Samples

Maximum Ratings ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) (– 40 to 125°C, Sine Wave, 50 to 60 Hz, Gate Open)	V_{DRM} V_{RRM}	± 90 ± 180	V
On-State RMS Current (All Conduction Angles; $T_L = 80^\circ\text{C}$, Lead Length = 3/8")	$I_{\text{T (RMS)}}$	± 1.0	A
Peak Non-Repetitive Surge Current (60 Hz One Cycle, Sine Wave, $T_J = 125^\circ\text{C}$)	I_{TSM}	± 20	A
Operating Junction Temperature Range	T_J	-40 to +125	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-40 to +150	$^\circ\text{C}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Thermal Characteristics

Rating	Symbol	Value	Unit
Thermal Resistance, Junction-to-Lead (Lead Length = 3/8")	$R_{\theta\text{JL}}$	15	$^\circ\text{C/W}$
Lead Solder Temperature (Lead Length $\geq 1/16"$ from Case, 10 s Max)	T_L	260	$^\circ\text{C}$

Electrical Characteristics - OFF ($T_j = 25^\circ\text{C}$ unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit
Repetitive Peak Off–State Current (50 to 60 Hz Sine Wave) $V_{\text{DRM}} = 90\text{V}$, MKP3V120 $V_{\text{DRM}} = 180\text{V}$, MKP3V240	I_{DRM}	-	-	10	μA

Electrical Characteristics - ON ($T_j = 25^\circ\text{C}$ unless otherwise noted; Electricals apply in both directions)

Characteristic	Symbol	Min	Typ	Max	Unit	
Breakover Voltage	V_{BO}	MKP3V120 $I_{\text{BO}} = 200 \mu\text{A}$	110	-	130	V
		MKP3V240 $I_{\text{BO}} = 200 \mu\text{A}$	220	-	250	
Peak On–State Voltage ($I_{\text{TM}} = 1 \text{ A Peak}$, Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2\%$)	V_{TM}	-	1.1	1.5	V	
Dynamic Holding Current (Sine Wave, 60 Hz, $R_L = 100 \Omega$)	I_{H}	-	-	100	mA	
Switching Resistance (Sine Wave, 50 to 60 Hz)	R_s	0.1	-	-	k Ω	

Dynamic Characteristics

Characteristic	Symbol	Min	Typ	Max	Unit
Critical Rate–of–Rise of On–State Current, Critical Damped Waveform Circuit ($I_{\text{PK}} = 130 \Omega$, Pulse Width = 10 μsec)	dv/dt	-	120	-	V/ μs

Voltage Current Characteristic of SCR

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current




Figure 1. Maximum Case Temperature




Figure 2. Maximum Ambient Temperature




Figure 3. Typical Forward Voltage






Figure 4. Typical Power Dissipation



Thermal Characteristics

Figure 5. Thermal Response



Typical Characteristics

Figure 6. Typical Breakover Current






Figure 7. Typical Holding Current



Dimensions




Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.287	0.374	7.30	9.50
B	0.189	0.209	4.80	5.30
D	0.047	0.051	1.20	1.30
K	1.000	---	25.40	---

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. ALL RULES AND NOTES ASSOCIATED WITH JEDEC DO-41 267-04 OBSOLETE, NEW STANDARD 267-05.

STYLE 2: NO POLARITY

Part Marking System



- A= Assembly Location
 - xx = 12 or 24
 - YY, Y= Year
 - WW = Work Week
 - = Pb-Free Package
- (Note: Microdot may be in either location)

Ordering Information

Device	Package	Shipping
MKP3V120G	Axial Lead	500 Units / Box
MKP3V120RLG		1500 / Tape & Reel
MKP3V240G		500 Units / Box
MKP3V240RLG		1500 / Tape & Reel

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru