

		REVISIONS			
REV	DESCRIPTION		DATE	APPROVED	
--	REVISED PER ECN 99-0001		5/13/99	S. Moody	

OSMT JACK
SEE NOTE 1

2338-7350-09 CONNECTOR SUB-ASSEMBLY (TWO PLACES)

9950-48-01 COAX CABLE

100,0±3,0

NOTES

1. CONNECTOR CENTERLINES SHALL BE 180° ± 30° APART AS SHOWN.

ELECTRICAL Frequency DC - 6 GHz Nominal Impedance 50 ohms Voltage Rating 250 Volts (VRMS Max.) @ Sea Level VSWR 1.20:1 Max. @ 2GHz 1.40:1 Max. @ 6GHz Insulation Resistance 1000 Megohms Minimum Dielectric Withstanding Voltage 500 Volts (VRMS Minimum) @ Sea Level MECHANICAL Connector Durability 100 mating cycles ENVIRONMENTAL Temperature Rating -40°C (-40°F) To +105°C (221°F)		<table><tr><td>OUTER CONTACT</td><td>BERYLLIUM COPPER</td><td>GOLD PLATE OVER NICKEL PLATE</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER</td><td>GOLD PLATE OVER NICKEL PLATE</td></tr><tr><td>DIELECTRIC</td><td>POLYPROPYLENE, GF</td><td>N/A</td></tr><tr><td>CABLE JACKET</td><td>POLYVINYLCHLORIDE</td><td>N/A</td></tr><tr><td>SHIELD</td><td>TINNED COPPER WIRE, 38 AWG</td><td>N/A</td></tr><tr><td>DIELECTRIC</td><td>FLUORINATED ETHYLENE PROPYLENE (FEP)</td><td>N/A</td></tr><tr><td>CENTER CONDUCTOR</td><td>TINNED COPPER CLAD STEEL</td><td>N/A</td></tr><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON</td></tr><tr><td>FRAC</td><td>DEC</td><td>ANGLES</td></tr><tr><td>± 1/64</td><td>± 0.13</td><td>± 1°</td></tr><tr><td colspan="3">These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td></tr><tr><td colspan="3">DRAWN BY BB DATE 08/10/92</td></tr><tr><td colspan="3">CHECKED BY</td></tr><tr><td colspan="3">APPROVED BY P. R. 08/14/92</td></tr><tr><td colspan="3">USE ASSY PROCEDURE</td></tr><tr><td colspan="3">NO. A.P. N/A</td></tr><tr><td colspan="3">TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY (180° OFFSET)</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>9950-3100-23</td></tr><tr><td>SCALE 10:1</td><td colspan="2">REV 018</td></tr><tr><td colspan="3">SHEET 1 OF 1</td></tr></table>	OUTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE	CENTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE	DIELECTRIC	POLYPROPYLENE, GF	N/A	CABLE JACKET	POLYVINYLCHLORIDE	N/A	SHIELD	TINNED COPPER WIRE, 38 AWG	N/A	DIELECTRIC	FLUORINATED ETHYLENE PROPYLENE (FEP)	N/A	CENTER CONDUCTOR	TINNED COPPER CLAD STEEL	N/A	COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON			FRAC	DEC	ANGLES	± 1/64	± 0.13	± 1°	These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			DRAWN BY BB DATE 08/10/92			CHECKED BY			APPROVED BY P. R. 08/14/92			USE ASSY PROCEDURE			NO. A.P. N/A			TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY (180° OFFSET)			SIZE B	CODE IDENT NO. 26805	9950-3100-23	SCALE 10:1	REV 018		SHEET 1 OF 1		
OUTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE																																																															
CENTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE																																																															
DIELECTRIC	POLYPROPYLENE, GF	N/A																																																															
CABLE JACKET	POLYVINYLCHLORIDE	N/A																																																															
SHIELD	TINNED COPPER WIRE, 38 AWG	N/A																																																															
DIELECTRIC	FLUORINATED ETHYLENE PROPYLENE (FEP)	N/A																																																															
CENTER CONDUCTOR	TINNED COPPER CLAD STEEL	N/A																																																															
COMPONENT	MATERIAL	FINISH																																																															
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON																																																																	
FRAC	DEC	ANGLES																																																															
± 1/64	± 0.13	± 1°																																																															
These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.																																																																	
DRAWN BY BB DATE 08/10/92																																																																	
CHECKED BY																																																																	
APPROVED BY P. R. 08/14/92																																																																	
USE ASSY PROCEDURE																																																																	
NO. A.P. N/A																																																																	
TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY (180° OFFSET)																																																																	
SIZE B	CODE IDENT NO. 26805	9950-3100-23																																																															
SCALE 10:1	REV 018																																																																
SHEET 1 OF 1																																																																	

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru