


## 60 V field-effect rectifier diode

Datasheet - production data



### Description

The device is based on a proprietary technology that achieves the best in class  $V_F/I_R$  trade-off for a given silicon surface.

This 60 V rectifier has been optimized for use in confined applications where both efficiency and thermal performance are key.

This device is suitable for use in adapters and chargers.

Table 1: Device summary

| Symbol       | Value    |
|--------------|----------|
| $I_{F(AV)}$  | 2 x 15 A |
| $V_{RRM}$    | 60 V     |
| $V_F$ (typ.) | 0.41 V   |
| $T_j$ (max.) | 175 °C   |

### Features

- ST advanced rectifier process
- Stable leakage current over reverse voltage
- Reduced leakage current
- Low forward voltage drop
- High frequency operation

# 1 Characteristics

**Table 2: Absolute ratings (limiting values at 25 °C, per diode, unless otherwise specified)**

| Symbol              | Parameter                                             |                                   |            | Value       | Unit |
|---------------------|-------------------------------------------------------|-----------------------------------|------------|-------------|------|
| V <sub>RRM</sub>    | Repetitive peak reverse voltage                       |                                   |            | 60          | V    |
| I <sub>F(RMS)</sub> | Forward rms current                                   |                                   |            | 60          | A    |
| I <sub>F(AV)</sub>  | Average forward current δ = 0.5, square wave          | T <sub>C</sub> = 155 °C           | Per diode  | 15          | A    |
|                     |                                                       |                                   | Per device | 30          |      |
| I <sub>FSM</sub>    | Surge non repetitive forward current                  | t <sub>p</sub> = 10 ms sinusoidal |            | 250         | A    |
| T <sub>stg</sub>    | Storage temperature range                             |                                   |            | -65 to +175 | °C   |
| T <sub>j</sub>      | Maximum operating junction temperature <sup>(1)</sup> |                                   |            | +175        | °C   |

**Notes:**

<sup>(1)</sup> $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$  condition to avoid thermal runaway for a diode on its own heatsink.

**Table 3: Thermal resistance parameters**

| Symbol        | Parameter        |           | Max. value | Unit |
|---------------|------------------|-----------|------------|------|
| $R_{th(j-c)}$ | Junction to case | Per diode | 1.5        | °C/W |
|               |                  | Total     | 0.9        |      |
| $R_{th(c)}$   | Coupling         |           | 0.25       |      |

**Table 4: Static electrical characteristics, per diode**

| Symbol      | Parameter               | Test conditions       |                      | Min. | Typ.  | Max.  | Unit |
|-------------|-------------------------|-----------------------|----------------------|------|-------|-------|------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25\text{ °C}$  | $V_R = V_{RRM}$      | -    |       | 170   | μA   |
|             |                         | $T_j = 125\text{ °C}$ |                      | -    | 10    | 20    | mA   |
|             |                         | $T_j = 125\text{ °C}$ | $V_R = 45\text{ V}$  | -    | 6     | 12    |      |
| $V_F^{(2)}$ | Forward voltage drop    | $T_j = 25\text{ °C}$  | $I_F = 3\text{ A}$   | -    | 0.355 | 0.395 | V    |
|             |                         | $T_j = 125\text{ °C}$ |                      | -    | 0.295 | 0.335 |      |
|             |                         | $T_j = 25\text{ °C}$  | $I_F = 7.5\text{ A}$ | -    | 0.430 | 0.475 |      |
|             |                         | $T_j = 125\text{ °C}$ |                      | -    | 0.410 | 0.460 |      |
|             |                         | $T_j = 25\text{ °C}$  | $I_F = 15\text{ A}$  | -    | 0.530 | 0.585 |      |
|             |                         | $T_j = 125\text{ °C}$ |                      | -    | 0.540 | 0.600 |      |

**Notes:**

<sup>(1)</sup>Pulse test:  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$


<sup>(2)</sup>Pulse test:  $t_p = 380\text{ μs}$ ,  $\delta < 2\%$

To evaluate the conduction losses use the following equation:


$$P = 0.320 \times I_{F(AV)} + 0.019 \times I_{F(RMS)}^2$$

## 1.1 Characteristics (curves)


**Figure 1: Average forward current versus ambient temperature ( $\delta = 0.5$ , per diode)**




**Figure 2: Relative variation of thermal impedance junction to case versus pulse duration**




**Figure 3: Reverse leakage current versus reverse voltage applied (typical values, per diode)**



**Figure 4: Junction capacitance versus reverse voltage applied (typical values, per diode)**



**Figure 5: Forward voltage drop versus forward current (typical values, per diode)**



**Figure 6: Forward voltage drop versus forward current (typical values, per diode)**





Figure 7: Thermal resistance junction to ambient versus copper surface under tab for D<sup>2</sup>PAK  
(typical values)



## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

- Cooling method: by conduction (C)
- Epoxy meets UL94,V0
- Recommended torque value: 0.55 N·m (for TO-220AB)
- Maximum torque value: 0.6 N·m (for TO-220AB)

## 2.1 TO-220AB package information

Figure 8: TO-220AB package outline




Table 5: TO-220AB package mechanical data

| Ref. | Dimensions  |       |            |       |
|------|-------------|-------|------------|-------|
|      | Millimeters |       | Inches     |       |
|      | Min.        | Max.  | Min.       | Max.  |
| A    | 4.40        | 4.60  | 0.173      | 0.181 |
| b    | 0.61        | 0.88  | 0.024      | 0.035 |
| b1   | 1.14        | 1.70  | 0.045      | 0.067 |
| c    | 0.48        | 0.70  | 0.019      | 0.028 |
| D    | 15.25       | 15.75 | 0.600      | 0.620 |
| E    | 10.00       | 10.40 | 0.394      | 0.409 |
| e    | 2.40        | 2.70  | 0.094      | 0.106 |
| e1   | 4.95        | 5.15  | 0.195      | 0.203 |
| F    | 0.51        | 0.60  | 0.020      | 0.024 |
| J1   | 2.40        | 2.72  | 0.094      | 0.107 |
| H1   | 6.20        | 6.60  | 0.244      | 0.256 |
| L    | 13.00       | 14.00 | 0.512      | 0.551 |
| L1   | 3.50        | 3.93  | 0.138      | 0.155 |
| L20  | 16.40 typ.  |       | 0.646 typ. |       |
| L30  | 28.90 typ.  |       | 1.138      |       |
| Ø P  | 3.75        | 3.85  | 0.148      | 0.156 |
| Q    | 2.65        | 2.95  | 0.104      | 0.116 |

## 2.2 D<sup>2</sup>PAK package information



Figure 9: D<sup>2</sup>PAK package outline

Table 6: D<sup>2</sup>PAK package mechanical data

| Ref. | Dimensions  |      |       |        |       |       |
|------|-------------|------|-------|--------|-------|-------|
|      | Millimeters |      |       | Inches |       |       |
|      | Min.        | Typ. | Max.  | Min.   | Typ.  | Max.  |
| A    | 4.40        |      | 4.60  | 0.173  |       | 0.181 |
| A1   | 0.03        |      | 0.23  | 0.001  |       | 0.009 |
| b    | 0.70        |      | 0.93  | 0.028  |       | 0.037 |
| b2   | 1.14        |      | 1.70  | 0.045  |       | 0.067 |
| c    | 0.45        |      | 0.60  | 0.018  |       | 0.024 |
| c2   | 1.23        |      | 1.36  | 0.048  |       | 0.053 |
| D    | 8.95        |      | 9.35  | 0.352  |       | 0.368 |
| D1   | 7.50        | 7.75 | 8.00  | 0.295  | 0.305 | 0.315 |
| D2   | 1.10        | 1.30 | 1.50  | 0.043  | 0.051 | 0.060 |
| E    | 10          |      | 10.40 | 0.394  |       | 0.409 |
| E1   | 8.50        | 8.70 | 8.90  | 0.335  | 0.343 | 0.346 |
| E2   | 6.85        | 7.05 | 7.25  | 0.266  | 0.278 | 0.282 |
| e    |             | 2.54 |       |        | 0.100 |       |
| e1   | 4.88        |      | 5.28  | 0.190  |       | 0.205 |
| H    | 15          |      | 15.85 | 0.591  |       | 0.624 |
| J1   | 2.49        |      | 2.69  | 0.097  |       | 0.106 |
| L    | 2.29        |      | 2.79  | 0.090  |       | 0.110 |
| L1   | 1.27        |      | 1.40  | 0.049  |       | 0.055 |
| L2   | 1.30        |      | 1.75  | 0.050  |       | 0.069 |
| R    |             | 0.4  |       |        | 0.015 |       |
| V2   | 0°          |      | 8°    | 0°     |       | 8°    |

Figure 10: D<sup>2</sup>PAK recommended footprint (dimensions are in mm)

### 3 Ordering information

Table 7: Ordering information

| Order code     | Marking    | Package            | Weight | Base qty. | Delivery mode |
|----------------|------------|--------------------|--------|-----------|---------------|
| FERD30H60CTS   | FD30H60CTS | TO-220AB           | 1.38 g | 50        | Tube          |
| FERD30H60CG-TR | FD30H60CG  | D <sup>2</sup> PAK | 1.43 g | 1000      | Tape and reel |

### 4 Revision history

Table 8: Document revision history

| Date        | Revision | Changes          |
|-------------|----------|------------------|
| 01-Sep-2017 | 1        | Initial release. |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)