


## Precision micropower shunt voltage reference



SOT323-5L

### Features

- Fixed 2.048 V output voltage
- Ultra low operating current: 10  $\mu$ A at 25 °C
- High initial accuracy:  $\pm$  0.2%
- Stable when used with capacitive loads
- Industrial (-40 to +85 °C) temperature range
- 20 ppm / °C typ., 70 ppm / °C max. temperature coefficient
- Available in SOT323-5L package

### Applications

- Portable, battery-operated equipment
- Data acquisition systems
- Instrumentation

### Description

The **TS4061V** is a low power high accuracy shunt voltage reference providing a stable output voltage over the industrial temperature range, with a maximum temperature coefficient of 70 ppm/°C.

The SOT323-5L package is ideal in applications where space saving is a critical issue.


The very low operating current is a key advantage for power budgeted designs. In addition, the **TS4061V** is very stable and can be used in a broad range of application conditions.

Maturity status link

[TS4061V](#)

## 1 Pin configuration

**Figure 1. Pin connections (top view)**



**Table 1. Order code**

Part number	Cathode-to-anode voltage	Precision	Package	Temperature range
TS4061VIBT-205	2.048 V	0.2%	SOT323-5L	-40 to +85 °C

## 2 Maximum ratings

**Table 2. Absolute maximum ratings**

Symbol	Parameter	Value	Unit
$I_k$	Reverse breakdown current	20	mA
$I_f$	Forward current	15	mA
$P_d$	Power dissipation <sup>(1)</sup> SOT323-5L	500	mW
$T_{std}$	Storage temperature	-65 to +150	°C
ESD	Human body model (HBM)	2	kV
	Charged device model	1500	V
$T_{lead}$	Lead temperature (Soldering) 10 s.	260	°C
$T_j$	Max junction temperature	+150	°C

1.  $P_d$  has been calculated with  $T_{amb} = 25\text{ °C}$  and  $T_{jmax} = 150\text{ °C}$

**Note:** Absolute maximum ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied.

**Table 3. Thermal data**


Symbol	Parameter	Value	Unit
$R_{thJA}$	Thermal resistance junction-ambient	250	°C/W
$R_{thJC}$	Thermal resistance junction-case	171	°C/W

**Table 4. Operating conditions**

Symbol	Parameter	Value	Unit
$I_{kmin}$	Minimum operating current	10	μA
$I_{kmax}$	Maximum operating current	15	mA
$T_{oper}$	Operating free air temperature range	-40 to +85	°C

### 3 Typical application circuit

Figure 2. Application circuit



Note: The value of  $R$  must be chosen in order to ensure  $I_K \geq I_{Kmin}$  in all the operating conditions ( $V_{IN}$ , load and temperature).

## 4 Electrical characteristics

$I_k = 10 \mu\text{A}$ ,  $T_{\text{amb}} = 25 \text{ }^\circ\text{C}$  (unless otherwise specified).

**Table 5. Electrical characteristics**


Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_k$	Initial accuracy TS4061VIBT-205	$I_k = 10 \mu\text{A}$	-0.2		+0.2	%
$I_{k\text{min}}$	Minimum operating current	$T_{\text{amb}} = 25 \text{ }^\circ\text{C}$		7.5	10	$\mu\text{A}$
		$-40 \text{ }^\circ\text{C} < T_{\text{amb}} < +85 \text{ }^\circ\text{C}$			12	
$\Delta V_k / \Delta T$	Average temperature coefficient	$10 \mu\text{A} < I_k < 15 \text{ mA}$ , $-40 \text{ }^\circ\text{C} < T_{\text{amb}} < +85 \text{ }^\circ\text{C}$		20	70	ppm/ $^\circ\text{C}$
$\Delta V_k / \Delta I_k$	Reverse breakdown voltage change with operating current range	$I_{k\text{min}} < I_k < 1 \text{ mA}$ $-40 \text{ }^\circ\text{C} < T_{\text{amb}} < +85 \text{ }^\circ\text{C}$		0.2	1	mV
		$1 \text{ mA} < I_k < 15 \text{ mA}$ $-40 \text{ }^\circ\text{C} < T_{\text{amb}} < +85 \text{ }^\circ\text{C}$		1.7	4	
$R_{ka}$	Static impedance	$I_k = 10 \mu\text{A}$ to $10 \text{ mA}$		0.15	0.3	$\Omega$
Hys	Thermal hysteresis	$I_k = 10 \mu\text{A}$		120		ppm
Noise	Wide band noise	$I_k = 10 \mu\text{A}$ $10 \text{ Hz} < f < 10 \text{ kHz}$		90		$\mu\text{V}_{\text{RMS}}$
	Low frequency noise	$I_k = 10 \mu\text{A}$ $0.1 \text{ Hz} < f < 10 \text{ Hz}$		45		$\mu\text{V}_{\text{p-p}}$

**Note:** Limits are 100% production tested at 25 °C. Limits overtemperature are guaranteed through correlation and by design.


## 5 Typical performance characteristics

The following plots are referred to the typical application circuit and, unless otherwise noted, at  $T_A = 25\text{ }^\circ\text{C}$ .


**Figure 3. Cathode voltage vs. temperature ( $I_K = 10\text{ }\mu\text{A}$ )**




**Figure 4. Cathode voltage vs. temperature ( $I_K = 1\text{ mA}$ )**




**Figure 5. Cathode voltage vs. temperature ( $I_K = 15\text{ mA}$ )**




**Figure 6. Static impedance vs. temperature**











**Figure 7.  $\Delta V_K / \Delta I_K$  vs. temperature ( $I_K = 8\text{ }\mu\text{A}$  to 1 mA)**



**Figure 8.  $\Delta V_K / \Delta I_K$  vs. temperature ( $I_K = 1\text{ mA}$  to 15 mA)**



**Figure 9. Minimum operating cathode current vs. temperature**

**Figure 10. Reverse characteristic**

**Figure 11. Forward characteristic**

**Figure 12. Temperature coefficient**

**Figure 13. Turn-on transient ( $t_{rise} = 10 \mu s$ , no  $C_{OUT}$ )**

**Figure 14. Turn-on transient ( $t_{rise} = 1.2 ms$ , no  $C_{OUT}$ )**


**Figure 15. Turn-on transient ( $t_{rise} = 1.2\text{ ms}$ ,  $C_{OUT} = 100\text{ nF}$ )**

**Figure 16. Turn-on transient ( $t_{rise} = 1.2\text{ ms}$ ,  $C_{OUT} = 1\text{ }\mu\text{F}$ )**





## 6 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

### 6.1 SOT323-5L package information

Figure 17. SOT323-5L package outline



**Table 6. SOT323-5L package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.10
A1	0		0.10
A2	0.80	0.90	1.00
b	0.15		0.30
c	0.10		0.22
D	1.80	2.00	2.20
E	1.80	2.10	2.40
E1	1.15	1.25	1.35
e		0.65	
e1		1.30	
L	0.26	0.36	0.46
$\theta$	0°		8°

## Revision history

**Table 7. Document revision history**

Date	Revision	Changes
07-Jun-2018	1	Initial release.

## Contents

<b>1</b>	<b>Pin configuration</b> .....	<b>2</b>
<b>2</b>	<b>Maximum ratings</b> .....	<b>3</b>
<b>3</b>	<b>Typical application circuit</b> .....	<b>4</b>
<b>4</b>	<b>Electrical characteristics</b> .....	<b>5</b>
<b>5</b>	<b>Typical performance characteristics</b> .....	<b>6</b>
<b>6</b>	<b>Package information</b> .....	<b>9</b>
<b>6.1</b>	<b>SOT323-5L package information</b> .....	<b>9</b>
	<b>Revision history</b> .....	<b>11</b>

## List of tables

<b>Table 1.</b>	Order code . . . . .	2
<b>Table 2.</b>	Absolute maximum ratings . . . . .	3
<b>Table 3.</b>	Thermal data . . . . .	3
<b>Table 4.</b>	Operating conditions . . . . .	3
<b>Table 5.</b>	Electrical characteristics . . . . .	5
<b>Table 6.</b>	SOT323-5L package mechanical data . . . . .	10
<b>Table 7.</b>	Document revision history . . . . .	11

## List of figures

<b>Figure 1.</b>	Pin connections (top view) . . . . .	2
<b>Figure 2.</b>	Application circuit . . . . .	4
<b>Figure 3.</b>	Cathode voltage vs. temperature ( $I_K = 10 \mu A$ ) . . . . .	6
<b>Figure 4.</b>	Cathode voltage vs. temperature ( $I_K = 1 mA$ ) . . . . .	6
<b>Figure 5.</b>	Cathode voltage vs. temperature ( $I_K = 15 mA$ ) . . . . .	6
<b>Figure 6.</b>	Static impedance vs. temperature . . . . .	6
<b>Figure 7.</b>	$\Delta V_K / \Delta I_K$ vs. temperature ( $I_K = 8 \mu A$ to $1 mA$ ) . . . . .	6
<b>Figure 8.</b>	$\Delta V_K / \Delta I_K$ vs. temperature ( $I_K = 1 mA$ to $15 mA$ ) . . . . .	6
<b>Figure 9.</b>	Minimum operating cathode current vs. temperature . . . . .	7
<b>Figure 10.</b>	Reverse characteristic . . . . .	7
<b>Figure 11.</b>	Forward characteristic . . . . .	7
<b>Figure 12.</b>	Temperature coefficient . . . . .	7
<b>Figure 13.</b>	Turn-on transient ( $t_{rise} = 10 \mu s$ , no $C_{OUT}$ ) . . . . .	7
<b>Figure 14.</b>	Turn-on transient ( $t_{rise} = 1.2 ms$ , no $C_{OUT}$ ) . . . . .	7
<b>Figure 15.</b>	Turn-on transient ( $t_{rise} = 1.2 ms$ , $C_{OUT} = 100 nF$ ) . . . . .	8
<b>Figure 16.</b>	Turn-on transient ( $t_{rise} = 1.2 ms$ , $C_{OUT} = 1 \mu F$ ) . . . . .	8
<b>Figure 17.</b>	SOT323-5L package outline . . . . .	9

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2018 STMicroelectronics – All rights reserved

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)