lumbergautomation
A BELDEN BRAND

Mini, 1 1/8”-Round-Plug Connector, Double-Ended Cordsets, Numeric Color Code

RSRK 1201M...1901M

12-, and 19-Poles

Mini, 1 1/8" double-ended cordsets, male straight to female straight connector, 12-, and 19-poles with molded cable, Numeric color code.

RSRK



Pin Assignments

Mini, 1 1/8” - Male / Female

12 poles



1 = black w/ number “1”
2 = black w/ number “2”
3 = black w/ number “3”
4 = black w/ number “4”
5 = black w/ number “5”
6 = black w/ number “6”
7 = black w/ number “7”
8 = black w/ number “8”
9 = green w/yellow tracer
10 = black w/ number “10”
11 = black w/ number “11”
12 = black w/ number “12”

19 poles



1 = black w/ number “1”
2 = black w/ number “2”
3 = black w/ number “3”
4 = black w/ number “4”
5 = black w/ number “5”
6 = black w/ number “6”
7 = black w/ number “7”
8 = black w/ number “8”
9 = black w/ number “9”
10 = black w/ number “10”
11 = black w/ number “11”
12 = green w/yellow tracer
13 = black w/ number “13”
14 = black w/ number “14”
15 = black w/ number “15”
16 = black w/ number “16”
17 = black w/ number “17”
18 = black w/ number “18”
19 = black w/ number “19”

19 poles - current rating

1-4, 6, 8-11, and 13-19 = 3 A
5 and 7 = 8 A
12 = Ground”

Mini, 1 1/8”-Round-Plug Connector, Double-Ended Cordsets, Numeric Color Code

RSRK 1201M...1901M

Technical Data

Environmental

Degree of protection	IP 67 / NEMA 6P
Operating temperature range	-40°C (-40°F) / +90°C (194°F)

Mechanical

Housing / Molded body	TPU, yellow
Insert	TPU, yellow
Contact	CuZn, gold over silver plated
Coupling nut	Aluminum, anodized black

Electrical

Current rating	12 poles: 5 A 19 poles: see pin assignments
Voltage rating	300 V

Cable Specifications - Numeric Color Code

Cable No.	Outer Jacket	Gauge	Jacket Color	OD	Temperature Rating	Agency Approvals
669	**PUR**	18AWG	Yellow	.489” (12.4 mm)	-40°C (-40°F) to +90°C (194°F)	AWM 20233
676	**PUR**	18AWG	Yellow	.390” (9.9 mm)	-40°C (-40°F) to +80°C (176°F)	UL: AWM 20233 / CSA: AWM I/II A/B
769	**TPE**	18AWG	Yellow	.438” (11.1 mm)	-40°C (-40°F) to +90°C (194°F)	UL: PLTC
776	**TPE**	18AWG	Yellow	.438” (11.1 mm)	-40°C (-40°F) to +90°C (194°F)	UL: PLTC

Part Number	Pins	Outer Jacket	Standard Cable Lengths	Characteristics
RSRK 1201M-676/...M	**12**	**PUR**	1 M / 2 M / 3 M / 5 M / 10 M	
RSRK 1201M-776/...M	**12**	**TPE**	1 M / 2 M / 3 M / 5 M / 10 M / 20 M	
RSRK 1901M-669/...M	**19**	**PUR**	1 M / 2 M / 3 M / 5 M / 10 M	
RSRK 1901M-769/...M	**19**	**TPE**	1 M / 2 M / 3 M / 5 M / 10 M / 20 M	

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru