

Cable gland - G-EDSWU-M40-L66L-STES-S - 1411099

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Stainless steel 1.4404, Application: Ex, External cable diameter 27.9 mm ... 40.4 mm, Shielding: Yes, Connecting thread: M40, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	820.0 GRM
Custom tariff number	73269098
Country of origin	United Kingdom

Technical data

Dimensions

Length	101 mm
Length without connecting thread	86 mm
Connecting thread diameter	40 mm
Wrench size, union nut	55 mm
Wrench size, support	55 mm
Hexagon angular dimension GRP	60.5 mm
Length of the connecting thread	15 mm
External cable diameter	27.9 mm ... 40.4 mm
Cable diameter without cable sheath	22 mm ... 32.2 mm

Ambient conditions

Degree of protection	IP66 (using the A-SEW-...P-W flat gasket (e.g., 1411283))
----------------------	---

Cable gland - G-EDSWU-M40-L66L-STES-S - 1411099

Technical data

Ambient conditions

	IP67 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
	IP68 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
Ambient temperature (operation)	-60 °C ... 130 °C

General

Cable gland material	Stainless steel 1.4404
Seal material	Thermoplastic elastomers
O-ring material	Viton
Thread type on connection side	M40
Color	silver
Standards/specifications	EN 60079-0, -1, -7, -15, -31
	IEC 60079-0, -1, -7, -15, -31
	EN 50262
	IEC 62444
	IEC 61241-0:2004
ATEX	Sira 13ATEX1073X
	Sira 13ATEX4079X
	Ex II 2G, II 1D, Ex d IIC Gb, Ex e IIC Gb, Ex ta IIIC Da, Ex II 3G Ex nR IIC Gc, Ex I M2, Ex d I Mb, Ex e I Mb
IECEx	IECEx SIR 13.0028X
	Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex d I Mb, Ex e I Mb

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Cable gland - G-EDSWU-M40-L66L-STES-S - 1411099

Approvals

Approvals

UL Listed

Ex Approvals

IECEEx / ATEX / INMETRO / CSA / CSAus / NEPSI / EAC Ex / CIDET / cCSAus


Approvals submitted

Approval details

UL Listed

Drawings

Dimensional drawing



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru