


REVISIONS			
REV	DESCRIPTION, ECM, EAR NO.	DATE	APP'D
C	PROPOSAL DRAWING	MAY07,2013	L.CHAN
D	CHANGE SHELL SHAPE ON THE TOP FACE	JUN03,2014	L.CHAN
E	ADD LED DESIGNATION AND PACKAGING	MAR.16,2017	L.CHAN
F	FIX THE LED OPTIONS TO INCLUDE 0~8	FEB.6,2018	L.CHAN

NOTES:

- ELECTRICAL:**
1. VOLTAGE RATING : 125 VAC.
 2. CURRENT RATING : 1.25 AMP.
 3. INSULATING RESISTANCE : 500 MEGOHMS MINIMUM.
 4. DIELECTRIC STRENGTH : 1000 VAC 60HZ, 1MIN.
 5. CATEGORY 5e CHARACTERISTIC:

Frequency MHz	Near-End Crosstalk dB, MIN.	Return Loss dB, MIN.	Attenuation dB, MAX.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

MECHANICAL:

1. SHIELD : STAINLESS STEEL, WITH TIN-DIP ON SOLDER TABS.
2. HOUSING : HIGH TEMP THERMOPLASTIC, UL 94V-0.
3. INSERT : HIGH TEMP THERMOPLASTIC UL 94V-0.
4. PCB : FR-4.
5. CONTACT : PHOSPHOR BRONZE.
SELECTIVE GOLD PLATING FOR MATING SURFACE,
SEE AMPHENOL PART NUMBER FOR DETAIL.
100u" NICKEL UNDERPLATE
500u" MATTE TIN PLATING ON CONTACT SOLDER TAIL.

ENVIRONMENTAL:

1. STORAGE : -40° TO +85°.
2. OPERATION : -40° TO +85°.
MATES WITH MODULAR PLUG CONFORMING TO TIA 1096.

RECOMMENDED SOLDER PROCESS: WAVE SOLDER, PEAK TEMPERATURE
260° FOR 5 SECOND MAXIMUM.


AMPHENOL PART NUMBER: RJE72-488-1XXX

GOLD PLATING OPTION _____

1=6u" [0.15 MICRONS] GOLD PLATING

OPTIONS (SEE BELOW TABLE 1)
REFER TO LED OPTIONS
IN NEXT PAGE

1=6u"	[0.15 MICRONS]	GOLD PLATING
2=15u"	[0.38 MICRONS]	GOLD PLATING
3=30u"	[0.76 MICRONS]	GOLD PLATING
4=50u"	[1.27 MICRONS]	GOLD PLATING

TABLE 1

RJE724881XX1	3.18[.125]	2.36[.093]
RJE724881XX2	2.27[.089]	1.57[.062]
RJE724881XX3	2.16[.085]	1.57[.062]
AMPHENOL P/N:	DIM A	RECOMMEND PCB THICKNESS

Amphenol Canada Corp.
www.amphenolcanada.com

MODULAR JACK, 1X4 PORTS, 8 POSITIONS, 8 CONTACTS,
SHIELDED WITH TOP & SIDE TABS, WITH LED,
SINK PCB TYPE, TAB UP, CAT5e

DWG NO.	P-RJE72-488-1XXX	REV F
---------	------------------	----------

CODE ID NO. 03554	DWG SIZE: C	SCALE: N/A	SHEET 1 OF 3
-------------------	-------------	------------	--------------

UNLESS SPECIFIED OTHERWISE	DRAWN	HUGH WANG	FEB 22 2011
PRIMARY UNITS MILLIMETERS	CHECKED	L.CHAN	FEB 22 2011
SECONDARY INCHES	M.E. APP'D		
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES FOR MM	DWG APP'D	ADRIAN.G	FEB 22 2011
1 DECIMAL PLACE ±0.50	ENG. REL. NO.		
2 DECIMAL PLACE ±0.30	REF.		
3 DECIMAL PLACE ±0.10	THIRD ANGLE PROJECTION		DO NOT SCALE DRAWING
ANGULAR DEGREES ±3°			

$\phi 1.12 \pm 0.05$ [$\phi .044 \pm .002$]
 16 HOLES
 $\phi 0.90 \pm 0.05$ [$\phi .035 \pm .002$]
 32 HOLES

14.3 [$.563$]*3=42.90 [1.689]
 2.29 [$.090$] TYP.
 2.29 [$.090$] TYP.
 6.27 [$.247$]
 8.05 [$.317$]
 8.42 [$.331$]
 10.42 [$.410$]


1.02 [$.040$]*7=7.14 [$.281$]
 1.00 [$.039$] TYP. R.0.50 [$R.020$]
 13.04 [$.513$]
 58.10 [2.287]
 58.80 [2.315]
 61.74 [2.431]

12.75 [$.502$]
 5.07 [$.200$]
 2.40 [$.094$]
 5.84 [$.230$]
 5.07 [$.200$]

RECOMMENDED PCB LAYOUT
 TOLERANCE: ± 0.05 [$.002$] mm.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP

REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D



TYPICAL FOR SINGLE & MULTI-PORT

LED SPECIFICATIONS:

FORWARD VOLTAGE: 2.1 VOLTS TYP.
 REVERSE VOLTAGE: 5.0 VOLTS MIN.
 LUMINOUS INTENSITY: 0.5 mCd MIN.
 (AT If=2mA)
 STORAGE TEMPERATURE: -40° TO 85° C
 LEAD SOLDERING TEMPERATURE: 260° C
 (5 SEC, 1/16" FROM CASE)
 PLATING ON TAILS: TIN OR TIN/COPPER
 ALLOY OVER SILVER

EXAMPLE:

PART NUMBER RJE72-X88-1XXX

LED COLOR CODE

CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)
0	BLOCKED	BLOCKED	9	GREEN	BLOCKED	J	BiC RD/GR	YELLOW
1	YELLOW	GREEN	A	BiC GR/YE	BiC GR/YE	K	YELLOW	BiC GR/OR
2	BLOCKED	GREEN	B	BiC RD/GR	BiC RD/GR	L	BiC GR/YE	RED
3	YELLOW	BLOCKED	C	BiC RD/GR	BiC GR/YE	M	RED	YELLOW
4	GREEN	YELLOW	D	GREEN	BiC GR/YE	P	GREEN	BiC RD/GR
5	GREEN	GREEN	E	YELLOW	BiC GR/YE	R	BiC GR/OR	GREEN
6	YELLOW	YELLOW	F	BiC GR/YE	YELLOW	T	RED	RED
7	RED	GREEN	G	BiC GR/OR	BiC GR/OR	V	BiC RD/GR	GREEN
8	GREEN	RED	H	BiC GR/YE	GREEN			

PRIMARY COLOR FOR BI-COLOR

LEDS IN STANDARD ANODE/
 CATHODE CONFIGURATION IS:
 RED-GREEN= RED
 RED-YELLOW= RED
 GREEN-YELLOW= GREEN
 GREEN-ORANGE= GREEN

LEGEND






BiC=BI-COLOR LED
 LOWC=LOW CURRENT LED
 YE=YELLOW
 GR=GREEN
 RD=RED
 OR=ORANGE

NOTE:


THE TWO DIGITS PRECEDING THE
 ADDITIONAL LED CODE MUST BE
 USED IN THE PART NUMBER, WHEN
 ORDERING ANY OF THE ADDITIONAL
 LED OPTIONS.

UNLESS SPECIFIED OTHERWISE			DRAWN HUGH WANG FEB 22.2012		Amphenol Canada Corp. www.amphenolcanada.com
PRIMARY UNITS MILLIMETERS			CHECKED L.CHAN FEB 22.2012		
SECONDARY INCHES			M.E. APP'D		
REFERENCE IN PARENTHESES			Q.A. APP'D		
GENERAL TOLERANCES FOR MM			DWG APP'D ADRIAN.G FEB 22.2012		MODULAR JACK, 1X4 PORTS, 8 POSITIONS, 8 CONTACTS, SHIELDED WITH TOP & SIDE TABS, WITH LED, SINK PCB TYPE, TAB UP, CAT5e
1 DECIMAL PLACE ±0.50			ENG. REL. NO.		
2 DECIMAL PLACE ±0.30			REF.		
3 DECIMAL PLACE ±0.10			THIRD ANGLE PROJECTION		
ANGULAR DEGREES ±3°			DO NOT SCALE DRAWING		DWG NO. P-RJE72-488-1XXX
					REV F
					CODE ID NO. 03554 DWG SIZE: C SCALE: N/A SHEET 2 OF 3

REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D



CARTON
(380*315*290 mm)



SCALE 2:1

- NOTES:
1. FINISHED CONNECTORS (AFTER FINAL INSPECTION) TO BE PACKED INTO CONDUCTIVE HIPS TRAYS, 20 CONNECTORS PER TRAY.
 2. 22 (11X2) TRAYS LOADED WITH 440PCS CONNECTORS TO BE PACKED INTO PE BAG, MUST SEAL PE BAG.
 3. TRAYS & CARTONS MATERIAL MUST BE ABLE TO WITHSTAND IMPACT DURING PRODUCT TRANSPORTATION TO PREVENT ANY DAMAGE TO FINISHED CONNECTORS.
 4. EACH TRAY AND CARTON OF PARTS TO BE LABELLED WITH AMPHENOL CANADA PART NUMBER, DATE CODE, QUANTITY, COUNTRY OF ORIGIN, AND CSA/UL LOGO WHEN APPROVED. THE PART NUMBER AND QUANTITY SHALL BE BOTH HUMAN & BAR CODE READABLE.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS SPECIFIED OTHERWISE		DRAWN	HUGH WANG	FEB 22, 2012	Amphenol Canada Corp. www.amphenolcanada.com	
PRIMARY UNITS MILLIMETERS		CHECKED	L.CHAN	FEB 22, 2012		
SECONDARY INCHES		M.E. APP'D			MODULAR JACK, 1X4 PORTS, 8 POSITIONS, 8 CONTACTS, SHIELDED WITH TOP & SIDE TABS, WITH LED, SINK PCB TYPE, TAB UP, CAT5e	
REFERENCE IN PARENTHESES		Q.A. APP'D				
GENERAL TOLERANCES FOR MM		DWG APP'D		ADRIAN.G	FEB 22, 2012	DWG NO. P-RJE72-488-1XXX
1 DECIMAL PLACE ±0.50		ENG. REL. NO.				
2 DECIMAL PLACE ±0.30		REF.				CODE ID NO. 03554
3 DECIMAL PLACE ±0.10		THIRD ANGLE PROJECTION				
ANGULAR DEGREES ±3°		DO NOT SCALE DRAWING				DWG SIZE: C
						SCALE: N/A
						SHEET 3 OF 3

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru