
STR. FEMALE MODULE 6 CRIMP TYPE INSERTS


R694.252.537

COAX FOR 2.6/50 CABLE

Series: MCC2



All dimensions are in mm.



Issue: 1013 F

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



STR. FEMALE MODULE 6 CRIMP TYPE INSERTS

R694.252.537

COAX FOR 2.6/50 CABLE

Series: MCC2

PACKAGING

Standard	Unit	Other
100	-	Contact us

ELECTRICAL CHARACTERISTICS

Impedance $\mathbf{50}$ Ω Frequency $\mathbf{0-6}$ GHz

VSWR 1.5* + 0,0000 x F(GHz) Maxi Insertion loss 0.2 $\sqrt{F(GHz)}$ dB Maxi RF leakage - (- F(GHz)) dB Maxi

 $\begin{array}{cccc} \mbox{Voltage rating} & & \mbox{500 Veff Maxi} \\ \mbox{Dielectric withstanding voltage} & \mbox{750 Veff mini} \\ \mbox{Insulation resistance} & \mbox{5000 } \mbox{M} \mbox{\Omega} \mbox{mini} \end{array}$

MECHANICAL CHARACTERISTICS

Center contact retention

Axial force – Mating end
Axial force – Opposite end
Torque

NA N mini
NA N mini
NA N.cm mini

Recommended torque

Mating NA N.cm
Panel nut NA N.cm
Clamp nut NA N.cm
A/F clamp nut 0,0000 mm

Mating life 500 Cycles mini

Weight **5,4700** g

ENVIRONMENTAL

Operating temperature -25/+125 ° C

Hermetic seal NA Atm.cm3/s

Panel leakage NA

SPECIFICATION

CABLE ASSEMBLY

Stripping	a	b	С	d	e	f
mm	2,50	5,00	10,5	0,00	8,00	0,00

Assembly instruction: Crimp 02

Recommended cable(s)

RG 316 KX 22A RG 188

Characteristics indicated on this data sheet are those that can be achieved with the highest performance cable. Intrinsic limitations of the cable may diminish the performance of the assembly

Cable retention

- pull off- torqueNA N.cm

TOOLING

Part Number	Description	Hexagon
R282.211.000	CRIMPING TOOL	3.25
. Or spare	-	
tools		
R282.293.000	CRIMPING TOOL	
	M22520/5-01	
R282.235.003	CRIMPING DIES	3.25
	M22520/5-03	
. And - (et)		
R282.281.000	CRIMPING TOOL	2X4 pos
		4
R282.967.030	POSITIONER FOR	
	TOOL R282 281 000	

OTHER CHARACTERISTICS

* 0 to 3 GHz

Issue: 1013 F

In the effort to improve our products, we reserve the right to make changes judged to be necessary.




STR. FEMALE MODULE 6 CRIMP TYPE INSERTS

COAX FOR 2.6/50 CABLE

R694.252.537

Series: MCC2





OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru