FAIRCHILD SEMICONDUCTOR™

February 1990
Revised November 1999

100393
Low Power 9-Bit ECL-to-TTL Translator with Latches

General Description

The 100393 is a 9-bit translator for converting F100K logic levels to TTL logic levels. A LOW on the latch enable (LE) latches the data at the input state. A HIGH on the LE makes the latches transparent. A HIGH on either the ECL or TTL output enable ($\overline{OE}$ ECL or $\overline{OE}$ $\overline{TTL}$), holds the outputs in a high impedance state.

The 100393 is designed with TTL, 64 mA outputs for Bus Driving capability. All ECL inputs have 50 kΩ pull-down resistors. When the inputs are either unconnected or at the same potential, the outputs will go LOW.

Features


- 64 mA I_{OL} drive capability
- 2000V ESD protection
- –4.2V to –5.7V operating range
- Latched outputs
- TTL outputs

Ordering Code:


Order Number	Package Number	Package Description
100393QC	V28A	28-Lead Plastic Lead Chip Carrier (PLCC), JEDEC MO-047, 0.450 Square

Devices also available in Tape and Reel. Specify by appending the suffix letter "X" to the ordering code.

Logic Symbol



Connection Diagram



Pin Descriptions

Pin Names	Description
D_0–D_8	Data Inputs (ECL)
Q_0–Q_8	Data Outputs (TTL)
LE	Latch Enable Input (ECL)
$\overline{OE}$ $\overline{TTL}$	Output Enable (TTL)
$\overline{OE}$ ECL	Output Enable (ECL)


© 1999 Fairchild Semiconductor Corporation

Truth Table

Inputs				Outputs
$\overline{OE}$ $\overline{TTL}$	$\overline{OE}$ $\overline{ECL}$	LE	D_N	Q_N
L	L	H	L	L
L	L	H	H	H
L	L	L	X	Latched
H	X	X	X	Z
X	H	X	X	Z

H = HIGH Voltage Level
L = LOW Voltage Level
X = Don't Care
Z = High Impedance

Logic Diagram



Absolute Maximum Ratings(Note 1)

Storage Temperature (T_{STG})	−65°C to +150°C
Maximum Junction Temperature (T_J)	+150°C
Case Temperature under Bias (T_C)	0°C to +85°C
V_{EE} Pin Potential to Ground Pin	−7.0V to +0.5V
V_{TTL} Pin Potential to Ground Pin	−0.5V to +6.0V
ECL Input Voltage (DC)	V_{EE} to +0.5V
TTL Input Voltage	−0.5V to +7.0V
Output Current (DC Output HIGH)	+130 mA
ESD (Note 2)	≥2000V

Recommended Operating Conditions

Case Temperature (T_C)	0°C to +85°C
Supply Voltage	
V_{EE}	−5.7V to −4.2V
V_{TTL}	+4.5V to +5.5V

Note 1: The "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the absolute maximum rating. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 2: ESD testing conforms to MIL-STD-883, Method 3015.

DC Electrical Characteristics (Note 3)

V_{EE} = −4.2V to −5.7V; V_{CC} = V_{CCA} = GND, V_{TTL} = +4.5V to +5.5V, T_C = 0°C to +85°C

Symbol	Parameter		Min	Typ	Max	Units	Conditions	
V_{OH}	Output HIGH Voltage		2.5 2.0			V	I_{OH} = −1 mA I_{OH} = −15 mA	V_{IN} = V_{IL} (Min) or V_{IH} (Max)
V_{OL}	Output LOW Voltage				0.55 0.50	V	I_{OL} = 64 mA I_{OL} = 24 mA	V_{IN} = V_{IL} (Min) or V_{IH} (Max)
V_{IH}	Input HIGH Voltage	ECL Inputs	−1165		−870	mV	Guaranteed HIGH Signal for All Inputs	
		$\overline{OE}$ $\overline{TTL}$	2.0			V		
V_{IL}	Input LOW Voltage	ECL Inputs	−1830		−1475	mV	Guaranteed LOW Signal for All Inputs	
		$\overline{OE}$ $\overline{TTL}$			0.8	V		
I_{BVI}	Input Breakdown Current				10	µA	V_{BI} = 7.0V	
I_{IH}	ECL Input HIGH Current	ECL Inputs			240	µA	V_{IN} = V_{IH} (Max)	
		$\overline{OE}$ $\overline{ECL}$			350			
	TTL Input HIGH Current	$\overline{OE}$ $\overline{TTL}$			5.0	µA	V_{IN} = 2.7V	
I_{IL}	ECL Input LOW Current	ECL Inputs	0.5			µA	V_{IN} = V_{IL} (Min)	
	TTL Input LOW Current	$\overline{OE}$ $\overline{TTL}$			−50	µA	V_{IN} = 0.5V	
I_{CEX}	Output HIGH Leakage Current				250	µA		
I_{OS}	Output Short-Circuit Current		−100		−225	mA	V_{OUT} = 0.0V, V_{TTL} = +5.5V	
I_{OZH}	3-STATE Current Output HIGH				+50	µA	V_{OUT} = +2.7V	
I_{OZL}	3-STATE Current Output LOW				−50	µA	V_{OUT} = 0.5V	
V_{FCD}	Input Clamp Diode Voltage				−1.2	V	I_{IN} = −18 mA	
I_{EE}	V_{EE} Power Supply Current		−39		−18	mA	Inputs OPEN	
I_{CCH}	V_{TTL} Power Supply Current HIGH				29	mA		
I_{CCL}	V_{TTL} Power Supply Current LOW				65	mA		
I_{CCZ}	V_{TTL} Power Supply Current 3-STATE				49	mA		


Note 3: The specified limits represent the "worst case" value for the parameter. Since these "worst case" values normally occur at the temperature extremes, additional noise immunity and guard banding can be achieved by decreasing the allowable system operating ranges. Conditions for testing shown in the tables are chosen to guarantee operation under "worst case" conditions.

AC Electrical Characteristics

V_{EE} = −4.2V to −5.7V, V_{CC} = GND, V_{TTL} = +4.5V to +5.5V

Symbol	Parameter	T_C = 0°C		T_C = +25°C		T_C = +85°C		Units	Conditions
		Min	Max	Min	Max	Min	Max		
t_{PLH} t_{PHL}	Propagation Delay Data to Output	2.3	4.8	2.3	4.8	2.3	5.3	ns	Figures 1, 2
t_{PLH} t_{PHL}	Propagation Delay LE to Output	2.3	5.6	2.3	5.6	2.3	6.4	ns	Figures 1, 2
t_{PZH} t_{PZL}	Output Enable Time $\overline{OE}$ $\overline{TTL}$ ↓ to Q_N	2.0 3.5	5.5 8.0	2.0 3.5	5.5 8.0	2.0 3.5	5.5 8.0	ns	Figure 3
t_{PHZ} t_{PLZ}	Output Disable Time $\overline{OE}$ $\overline{TTL}$ ↑ to Q_N	2.0 2.0	6.0 5.5	2.0 2.0	6.0 5.0	2.0 2.0	6.0 5.0	ns	Figure 3
t_{PZH} t_{PZL}	Output Enable Time $\overline{OE}$ $\overline{ECL}$ ↑ to Q_N	2.4 3.2	5.6 8.5	2.4 3.2	5.6 8.5	2.4 3.2	5.6 8.5	ns	Figure 4
t_{PHZ} t_{PLZ}	Output Disable Time $\overline{OE}$ $\overline{ECL}$ ↓ to Q_N	2.4 3.2	6.0 7.6	2.4 3.2	6.0 7.6	2.4 3.2	6.0 7.6	ns	Figure 4
t_S	Setup Time, D_N to LE	0.7		0.7		0.7		ns	Figures 1, 2
t_H	Hold Time, D_N to LE	1.3		1.3		1.3		ns	Figures 1, 2
t_{PW} (L)	Pulse Width LOW, LE	2.0		2.0		2.0		ns	Figures 1Figure 2

Test Circuit



Switch Positions
for Parameter Testing

Parameter	S-Position
t_{PLH}, t_{PHL}	Open
t_{PHZ}, t_{PZH}	Open
t_{PLZ}, t_{PZL}	Open

FIGURE 1. AC Test Setup

Switching Waveforms




FIGURE 2. Propagation Delays, Setup and Hold Times, and Pulse Width




FIGURE 3. Enable and Disable Waveforms, $\overline{OE}$ $\overline{TTL}$





FIGURE 4. Enable and Disable Waveforms, $\overline{OE}$ $\overline{ECL}$

Physical Dimensions inches (millimeters) unless otherwise noted



28-Lead Plastic Lead Chip Carrier (PLCC), JEDEC MO-047, 0.450 Square
Package Number V28A

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru