

THE CP1 FAMILY

Compact machine controllers



» Fast programming with Function Blocks

» Flexible Ethernet connectivity

» Easy positioning functionality

Think big... start small!

Omron's vast experience in the field of industrial automation has resulted in the creation of the right products for your applications, ranging from simple to more complex automation solutions. The CP1 family of programmable controllers provides you with a complete product line-up to automate compact machines and perform any other simple automation tasks, quickly and easily. Programming and operation are consistent with Omron's other modular Programmable controllers. And you are guaranteed the same high quality and reliability that you expect from any Omron product, ensuring that your equipment keeps on giving continuous dependable performance.

Scalable solution

The CP1 family is scalable; this means that you can choose the products with the right level of sophistication to meet your automation needs in terms of functionality, flexibility and pricing. Each of the CP1 family models, the CP1E, CP1L and CP1H, offers the functionality required for complete machine control. Benefits include: easy expansion of I/O, fast and versatile communication, and full positioning capabilities via ready-to-use Function Blocks. The CP1 family uses the same instruction set and professional programming software found in Omron's other modular Programmable controllers.



Answering your needs... precisely

Fast and versatile communication

Flexible, fast and yet cost-effective communication is essential in today's competitive market. This applies in particular to compact Programmable controllers, which not only need to connect with devices inside the machine, but also outside the machine for operating, data-logging and remote access. With this in mind, Omron has given the CP1 family excellent communication capabilities for both serial and Ethernet networking. In addition, Omron provides flexible and economical option boards for serial communication.

Flexible Ethernet connectivity

To meet communication needs over different protocols simultaneously and to easily connect for remote access, our latest CP1L Programmable controller features embedded Ethernet with socket services functionality. This offers, among other things, programmable connectivity to third-party devices and makes this outstanding product the best-in-class machine controller on the market.

Easy positioning functions

The CP1 family is designed to fulfill position control tasks. Up to four axes of servo-drives can be controlled with high-speed pulse outputs, while high-speed pulse inputs can allow the connection of up to four encoders. Control is easily achieved with Function Block or standard functions without the need of specialist motion boards or expansion units. Furthermore, thanks to its fast serial ports, the CP1 family is also capable of performing simple positioning tasks. With the use of Modbus Function Blocks, up to 31 inverters can be controlled and monitored in real-time.

Flexible Ethernet connectivity

As simple and quick- as USB!

Thanks to the CP1L-EM's or CP1L-EL's Automatic-Connect function, programming over Ethernet is as simple as using USB on the other models in the CP1 family. This means that you don't need to waste time adjusting the Ethernet settings on the PC, but that you can simply plug and connect, just like USB. The Automatic-Connect function connects instantly over a default IP address to the CP1L, saving you valuable set-up time.

Versatile communication

Omron's CP1L Ethernet models are equipped as standard with Socket Services. This facilitates the easy exchange of data with other Ethernet devices supporting a dedicated protocol. The Socket Services reduce effort and simplify programming and allow Ethernet protocols to be used directly from your Programmable controller program. Ethernet can also be used for applications that require remote access functionality, such as a secure VPN connection with a standard router.

Omron network



Wireless Ethernet



CP1 Programmable controller



Operate and Monitoring



Socket Service



Remote access



Data Logging



Modbus/TCP

More options – greater possibilities!

More analog I/Os

In addition to the two standard embedded analog inputs, Omron's CP1L with embedded Ethernet also supports three new, optional analog I/O boards. These enable you to add extra analog inputs and outputs, and mixed inputs/outputs at minimum cost and without the need for more cabinet space. With its analog I/O modules, auto-tuning PID function, the CP1L is ideal for accurate process control.



CP1 family features at a glance

- 10 to 60 I/O base models, expandable to 320 I/O points
- Digital, analog and temperature sensor I/O expansion units
- 4 to 6 High-speed encoder inputs and 2 to 4 high-speed pulse outputs
- Modbus Master feature for easy inverter or temperature control
- Analog I/O option boards and auto-tuning PID for accurate process control
- Optional boards for RS-232/RS-422/485/Ethernet or LCD display
- Ladder diagram, Function Block or Structured Text programming
- Powerful instructions common within Omron's modular Programmable controller series
- USB or Ethernet port – no special cables needed
- No-Battery mode operation – retains the program and data

Note: The functions that are supported depend on the model.

Maximize efficiency by selecting the optimum CPU unit for your applications



			CP1E											
			E-type					N-type						
			CP1E -E10D_-_	CP1E -E14DR-A	CP1E -E20DR-A	CP1E -E30DR-A	CP1E -E40DR-A	CP1E -N14D_-_	CP1E -N20D_-_	CP1E -NA20D_-_	CP1E -N30D_-_	CP1E -N40D_-_	CP1E -N60D_-_	
I/O	Digital Inputs		6	8	12	18	24	8	12	12	18	24	36	
	Digital Outputs		4	6	8	12	16	6	8	8	12	16	24	
	Removable Terminals		No					No						
	Total I/O Capacity		10	14	20	150	160	14	20	140	150	160	180	
	CP1W Expansion Units		No			Yes (3 max.)		No		Yes (3 max.)				
	CJ-Series Special I/O and CPU Bus Units		No					No						
	Interrupt/Quick/Counter Inputs		4	6					6					
	High Speed Counter Inputs		5 (10 kHz max.)	6 (10 kHz max.)					2 (100 kHz max.) and 4 (10 kHz max.)					
	Pulse Outputs (transistor outputs models only)		No					2 axes (100 kHz max.)						
	Analog I/O (embedded)		No					No		2 inputs, 1 output	No			
	Analog Adjuster (0-255)		Yes (2)					Yes (2)						
	External Analog Settings Input (resolution 1/256)		No					No						
Optional boards	Number of boards supported		0					0		1				
	Serial Communications (CP1W-CIF01/11/12)		No					No		Yes				
	Ethernet (CP1W-CIF41)		No					No		Yes				
	LCD Display (CP1W-DAM01)		No					No						
	Analog I/O boards		No					No						
CPU details	Programming port		USB					USB						
	RS-232C port (embedded)		No					Yes (1)						
	Function Blocks support (Ladder diagrams or ST language)		No					No						
	Processing Speed (minimum)		1.19 μs / Basic instruction, 7.9 μs / Special instruction					1.19 μs / Basic instruction, 7.9 μs / Special instruction						
	Program Capacity		2K steps					8K steps						
	Data Memory Capacity		2K words					8K words						
	Memory Cassette (CP1W-ME05M)		No					No						
	Real-Time Clock		No					Yes (with optional battery)						
	Battery		No					Optional (CP1W-BAT01)						
7-Segment Display		No					No							
Relay Outputs	AC Power Supply		CP1E -E10DR-A	CP1E -E14DR-A	CP1E -E20DR-A	CP1E -E30DR-A	CP1E -E40DR-A	CP1E -N14DR-A	CP1E -N20DR-A	CP1E -NA20DR-A	CP1E -N30DR-A	CP1E -N40DR-A	CP1E -N60DR-A	
	DC Power Supply		CP1E -E10DR-D	-	-	-	-	CP1E -N14DR-D	CP1E -N20DR-D	-	CP1E -N30DR-D	CP1E -N40DR-D	CP1E -N60DR-D	
Transistor Outputs	Sink Type	AC Power Supply	CP1E -E10DT-A	-	-	-	-	CP1E -N14DT-A	CP1E -N20DT-A	-	CP1E -N30DT-A	CP1E -N40DT-A	CP1E -N60DT-A	
		DC Power Supply	CP1E -E10DT-D	-	-	-	-	CP1E -N14DT-D	CP1E -N20DT-D	CP1E -NA20DT-D	CP1E -N30DT-D	CP1E -N40DT-D	CP1E -N60DT-D	
	Source Type	AC Power Supply	CP1E -E10DT1-A	-	-	-	-	CP1E -N14DT1-A	CP1E -N20DT1-A	-	CP1E -N30DT1-A	CP1E- N14DT1-A	CP1E -N60DT1-A	
		DC Power Supply	CP1E -E10DT1-D	-	-	-	-	CP1E -N14DT1-D	CP1E -N20DT1-D	CP1E -NA20DT1-D	CP1E -N30DT1-D	CP1E -N40DT1-D	CP1E -N60DT1-D	

Note: This table is a general overview only. For details, refer to the CP1E datasheet (Cat. No. P061), CP1L datasheet (Cat. No. P081) or CP1H datasheet (Cat. No. P080).



	CP1L									CP1H		
	L-type			M-type			EL-type	EM-type				
	CP1L -L10D_-_	CP1L -L14D_-_	CP1L -L20D_-_	CP1L -M30D_-_	CP1L -M40D_-_	CP1L -M60D_-_	CP1L -EL20D_-_	CP1L -EM30D_-_	CP1L -EM40D_-_	CP1H -Y20DT-D	CP1H -X40D_-_	CP1H -XA40D_-_
	6	8	12	18	24	36	12	18	24	12	24	24
	4	6	8	12	16	24	8	12	16	8	16	16
	No			Yes			No	Yes		Yes		
	10	54	60	150	160	180	60	150	160	300	320	320
	No	Yes (1 max.)		Yes (3 max.)			Yes (1 max.)	Yes (3 max.)		Yes (7 units or 15 input words / 15 output words max.)		
	No						No			Yes (2 max.)		
	2	4	6				6			6	8	
	4 (100 kHz max.)						4 (100 kHz max.)			2 (100 kHz max.) and 2 Line-driver (1 MHz)		4 (100 kHz max.)
	2 axes (100 kHz max.)						2 axes (100 kHz max.)			2 (100 kHz max.) and 2 Line-driver (1 MHz)		4 axes (100 kHz max.)
	No						2 inputs			No		4 inputs, 2 outputs
	Yes (1)						No			Yes (1)		
	Yes (0-10V)						No			Yes (0-10V)		
	0	1		2			1	2		2		
	No	Yes						Yes		Yes		
	No	Yes						No		Yes		
	No	Yes						Yes		Yes		
	No						Yes			No		
	USB						Ethernet			USB		
	No						No			No		
	Yes						Yes			Yes		
	0.55 μs / Basic instruction, 4.1 μs / Special instruction						0.55 μs / Basic instruction, 4.1 μs / Special instruction			0.10 μs / Basic instruction, 0.15 μs / Special instruction		
	5K steps			10K steps			5K (+10K FB) steps	10K (+10K FB) steps		20K steps		
	10K words			32K words			10K words	32K words		32K words		
	Yes						Yes			Yes		
	Yes						Yes			Yes		
	Yes (CJ1W-BAT01)						Yes (CJ1W-BAT01)			Yes (CJ1W-BAT01)		
	No						No			Yes		
	CP1L -L10DR-A	CP1L -L14DR-A	CP1L -L20DR-A	CP1L -M30DR-A	CP1L -M40DR-A	CP1L -M60DR-A	-	-	-	-	CP1H -X40DR-A	CP1H -XA40DR-A
	CP1L -L10DR-D	CP1L -L14DR-D	CP1L -L20DR-D	CP1L -M30DR-D	CP1L -M40DR-D	CP1L -M60DR-D	CP1L -EL20DR-D	CP1L -EM30DR-D	CP1L -EM40DR-D	-	-	-
	CP1L -L10DT-A	CP1L -L14DT-A	CP1L -L20DT-A	CP1L -M30DT-A	CP1L -M40DT-A	CP1L -M60DT-A	-	-	-	-	-	-
	CP1L -L10DT-D	CP1L -L14DT-D	CP1L -L20DT-D	CP1L -M30DT-D	CP1L -M40DT-D	CP1L -M60DT-D	CP1L -EL20DT-D	CP1L -EM30DT-D	CP1L -EM40DT-D	CP1H -Y20DT-D	CP1H -X40DT-D	CP1H -XA40DT-D
	-	-	-	-	-	-	-	-	-	-	-	-
	CP1L -L10DT1-D	CP1L -L14DT1-D	CP1L -L20DT1-D	CP1L -M30DT1-D	CP1L -M40DT1-D	CP1L -M60DT1-D	CP1L -EL20DT1-D	CP1L -EM30DT1-D	CP1L -EM40DT1-D	-	CP1H -X40DT1-D	CP1H -XA40DT1-D

Expansion units

Expansion I/O Units



CP1W-8ED
DC inputs: 8

CP1W-8ER
Relay outputs: 8

CP1W-8ET
Transistor outputs (sinking): 8

CP1W-8ET1
Transistor outputs (sourcing): 8



CP1W-16ER
Relay outputs: 16

CP1W-16ET
Transistor outputs (sinking): 16

CP1W-16ET1
Transistor outputs (sourcing): 16

CP1W-20EDR1
DC inputs: 12
Relay outputs: 8



CP1W-20EDT
DC inputs: 12
Transistor outputs (sinking): 8

CP1W-20EDT1
DC inputs: 12
Transistor outputs (sourcing): 8

CP1W-32ER
Relay outputs: 32

CP1W-32ET
Transistor outputs (sinking): 32

CP1W-32ET1
Transistor outputs (sourcing): 32
CP1W-40EDR
DC inputs: 24
Relay outputs: 16

CP1W-40EDT
DC inputs: 24
Transistor outputs (sinking): 16

CP1W-40EDT1
DC inputs: 24
Transistor outputs (sourcing): 16

Analog I/O Units



Analog Input Unit

CP1W-AD041
Analog inputs: 4 (resolution: 6,000)

Analog Output Unit

CP1W-DA021
Analog outputs: 2 (resolution: 6,000)

CP1W-DA041
Analog outputs: 4 (resolution: 6,000)



Analog I/O Unit

CP1W-MAD11
Analog inputs: 2 (resolution: 6,000)
Analog outputs: 1 (resolution: 6,000)

Temperature Sensor Unit



CP1W-TS001
Thermocouple inputs: 2

CP1W-TS002
Thermocouple inputs: 4

CP1W-TS101
Platinum-resistance thermometer inputs: 2

CP1W-TS102
Platinum-resistance thermometer inputs: 4

CompoBus/S I/O Link Unit



CP1W-SRT21
Inputs: 8 bits
Outputs: 8 bits

Optional Boards



CP1W-CIF01
RS-232C
(15 m max.)



CP1W-CIF11
RS-422A/485
(50 m max.)



CP1W-CIF12
RS-422A/485
(Isolated-type)
(500 m max.)



CP1W-CIF41
Ethernet



CP1W-DAM01
Display 4 rows,
12 characters



CP1W-ADB21
Analog 2 inputs,
0-10 V, 0-20 mA



CP1W-DAB21V
Analog
2 outputs, 0-10 V



CP1W-MAB221
Analog 2 inputs
0-10 V, 0-20 mA &
2 outputs 0-10 V

Memory Cassette



CP1W-ME05M
512K words
(upload/download program)

Battery Set



CJ1W-BAT01
(for CP1L/CP1H)




CP1W-BAT01
(for CP1E)

CJ Unit Adapter



CP1W-EXT01
CJ Unit adapter for use with CP1H.
Includes CJ endplate.

I/O Connecting Cable



CP1W-CN811
Length: 80 cm

CP1W Expansion Units include I/O Connection Cables (in lengths of approx. 6 cm) for side-by-side connection.

Note: This table is a general overview only. For details, refer to the CP1E datasheet (Cat. No. P061), CP1L datasheet (Cat. No. P081) or CP1H datasheet (Cat. No. P080).

Software

The CX-One is a comprehensive software package that integrates Support Software for OMRON PLCs and components. CX-One Ver. 4.□ includes CX-Programmer Ver. 9.□.

CX-One Lite is a subset of the complete CX-One package that provides only the Support Software required for micro PLC applications. CX-One Lite Ver. 4.□ includes Micro PLC (the CP1 family) Edition CX-Programmer Ver. 9.□.

Note 1: The CX-One and CX-One Lite cannot be simultaneously installed on the same computer.

Note 2: This section is a general overview only. For details, refer to the CX-One Catalog (No. R134).

		Media	Order code
FA Integrated Tool Package CX-One Ver.4.□	Single user licence ^{*1}	DVD ^{*2}	CXONE-AL01D-V4
FA Integrated Tool Package CX-One Lite Ver.4.□	Single user licence	CD	CXONE-LT01C-V4


^{*1} Multi licenses are available for the CX-One (3, 10, 30, or 50 licenses).

^{*2} The CX-One is also available on CD (CXONE-AL□□C-V4).

CX-One supported OS: Windows 7, Windows Vista® or Windows XP (SP3 or higher).

Except for Windows XP 64-bit version.

Using CJ-series units and CP1W units with the CP1H



CJ-Series Units for use with CP1H

Description	Unit Name	Model	Description	Unit Name	Model	
Analog I/O and Control Units	Universal Analog Input Unit	CJ1W-AD04U	Motion/Position Control Units	Position Control Units	CJ1W-NC113	
	Analog Input Unit	CJ1W-AD041-V1			CJ1W-NC133	
		CJ1W-AD042			CJ1W-NC213	
		CJ1W-AD081-V1			CJ1W-NC233	
		CJ1W-DA021			CJ1W-NC413	
	CJ1W-DA041	CJ1W-NC433				
	CJ1W-DA042V	MECHATROLINK-II Position Control Unit		CJ1W-NCF71		
	CJ1W-DA08V			CJ1W-NCF71-MA		
	CJ1W-DA08C			CJ1W-NC271		
	CJ1W-MAD42			CJ1W-NC471		
	Universal Analog Input Unit	CJ1W-PH41U		MECHATROLINK-II Motion Control Unit	CJ1W-MCH71	
	Process Input Unit	CJ1W-PDC15	Communication Units		Serial Communication Units	CJ1W-SCU21-V1
	Thermocouple Input Unit	CJ1W-PTS15				CJ1W-SCU22
		CJ1W-PTS51		CJ1W-SCU31-V1		
	Resistance Thermometer Input Unit	CJ1W-PTS16		CJ1W-SCU32		
		CJ1W-PTS52		CJ1W-SCU41-V1		
	Temperature Control Loops, Thermocouple Unit	CJ1W-TC001		CJ1W-SCU42		
		CJ1W-TC002		Ethernet Unit	CJ1W-ETN21	
		CJ1W-TC003			CJ1W-EIP21	
		CJ1W-TC004		FL-net Ethernet Unit	CJ1W-FLN22	
	Temperature Control Loops, RTD	CJ1W-TC101		High-speed Data Storage Unit	CJ1W-SPU01-V2	
		CJ1W-TC102	DeviceNet Master Unit	CJ1W-DRM21		
		CJ1W-TC103	CompoNet Master Unit	CJ1W-CRM21		
		CJ1W-TC104	CompoBus/S Master Unit	CJ1W-SRM21		
Motion/Position Control Units	High Speed Counter Unit	CJ1W-CT021	Control Units	Controller Link Unit	CJ1W-CLK23	
		RFID Sensor Controller Unit		CJ1W-V680C11		
CJ1W-V680C12						
CJ1W-V600C11						
CJ1W-V600C12						

Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Other company names and product names in this document are the trademarks or registered trademarks of their respective companies.

Warranty and Limitations of Liability

WARRANTY

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

LIMITATIONS OF LIABILITY

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall the responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted.

IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRANTY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PRODUCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

- The application examples provided in this catalog are for reference only. Check functions and safety of the equipment before use.
- Never use the products for any application requiring special safety requirements, such as nuclear energy control systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, or other application involving serious risk to life or property, without ensuring that the system as a whole has been designed to address the risks, and that the OMRON products are properly rated and installed for the intended use within the overall equipment or system.

Note: Do not use this document to operate the Unit.

OMRON Corporation Industrial Automation Company
Tokyo, JAPAN

Contact: www.ia.omron.com

Regional Headquarters

OMRON EUROPE B.V.

Wegalaan 67-69-2132 JD Hoofddorp
The Netherlands
Tel: (31) 2356-81-300/Fax: (31) 2356-81-388

OMRON ELECTRONICS LLC

One Commerce Drive Schaumburg,
IL 60173-5302 U.S.A.
Tel: (1) 847-843-7900/Fax: (1) 847-843-7787

OMRON ASIA PACIFIC PTE. LTD.

No. 438A Alexandra Road # 05-05/08 (Lobby 2),
Alexandra Technopark,
Singapore 119967
Tel: (65) 6835-3011/Fax: (65) 6835-2711

OMRON (CHINA) CO., LTD.

Room 2211, Bank of China Tower,
200 Yin Cheng Zhong Road,
PuDong New Area, Shanghai, 200120, China
Tel: (86) 21-5037-2222/Fax: (86) 21-5037-2200

Authorized Distributor:

© OMRON Corporation 2009-2012 All Rights Reserved.
In the interest of product improvement,
specifications are subject to change without notice.

CSM_1_1_0312

Cat. No. P082-E1-01

0312-(0405)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru