


FLORENTINA-2X2-M

~30° medium beam

TECHNICAL SPECIFICATIONS:

Dimensions	89.6 mm
Height	22.2 mm
Fastening	pin, screw
ROHS compliant	yes 


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ROSE-CMC-M	Single lens	PC	clear	
FLORENTINA-2X2-HLD	Holder	PC	black	











ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCP14967_FLORENTINA-2X2-M	Single lens	88	24	8	4.3
» Box size: 476 x 273 x 292 mm					



PHOTOMETRIC DATA (MEASURED):

<p>COMET ELECTRONICS</p> <p>LED EASY-T FLUX 2x2 FLR XG xxx G7 FWHM 30.0° Efficiency 83 % Peak intensity 2.5 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>COMET ELECTRONICS</p> <p>LED EASY-T FLUX 2x2 FLR XT xxx G5 FWHM 30.0° Efficiency 83 % Peak intensity 2.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>CREE</p> <p>LED XHP35 HD FWHM 31.0° Efficiency 77 % Peak intensity 2.3 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>CREE</p> <p>LED XP-L HD FWHM 30.0° Efficiency 75 % Peak intensity 2.4 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		


PHOTOMETRIC DATA (MEASURED):




LED XP-L HD
FWHM 30.0°
Efficiency 75 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14960_FLORENTINA-2X2-SHD-WHT





LED LUXEON MZ
FWHM 29.0°
Efficiency 77 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14960_FLORENTINA-2X2-SHD-WHT











LED LUXEON MZ
FWHM 30.0°
Efficiency 75 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14734_FLORENTINA-2X2-SHD



LED LUXEON TX
FWHM 30.0°
Efficiency 80 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
 C14734_FLORENTINA-2X2-SHD




PHOTOMETRIC DATA (MEASURED):

<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM 30.0° Efficiency 79 % Peak intensity 2.6 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLO Square CSSRM2/CSSRM3 FWHM 30.0° Efficiency 75 % Peak intensity 2.6 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLO Square CSSRM2/CSSRM3 FWHM 30.0° Efficiency 77 % Peak intensity 2.6 cd/lm LEDs/each optic 1 Light colour White Required components: C14960_FLORENTINA-2X2-SHD-WHT</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLO Square EC FWHM 30.0° Efficiency 80 % Peak intensity 2.7 cd/lm LEDs/each optic 1 Light colour White Required components: C14734_FLORENTINA-2X2-SHD</p>		

PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED HiLOM SC16 (LH181B)
FWHM 36.0°
Efficiency 58 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C14734_FLORENTINA-2X2-SHD



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru