



1.6×1.2mm for Consumer Products



RoHS Compliant

**Features**

- Crystal unit for Consumer Products
- Ultra-miniature and low profile  
32000kHz or more accepts 0.33mm-high
- Ceramic package
- Reflow compatible

**Applications**

- 1seg. tuner
- Wearable devices
- True wireless earphones

**How to Order**

CX1612DB 36000 □□ G E J CC  
① ② ③ ④ ⑤ ⑥ ⑦

①Series	②Frequency
③Load Capacitance	④Frequency Tolerance
B0 6 pF	G ±15×10 <sup>-6</sup>
D0 8 pF	
⑤Operating Temp. Range	⑥Frequency Temp. Stability
EJ -10 to +70°C	±15×10 <sup>-6</sup>

⑦Individual Specification  
(STD Specification is "CC".)

Packaging (Tape & Reel 3000/ 20000 pcs./ reel)

**Specifications**

Item	Symbol	Specification	Unit	Remarks
Frequency Range	f <sub>nom</sub>	26000 to 60000	kHz	
Overtone Order	OT	Fundamental	—	
Load Capacitance	CL	8	pF	
Frequency Tolerance	f <sub>tol</sub>	±15	×10 <sup>-6</sup>	25°C±3°C
Motional Series Resistance	R1	Table 1	ohm	
Drive Level	DL	Table 2	μW	
Operating Temp. Range	T <sub>use</sub>	-10 to +70	°C	
Storage Temp. Range	T <sub>stg</sub>	-40 to +85	°C	
Frequency Temp. Characteristics	f <sub>tem</sub>	±15	×10 <sup>-6</sup>	Freq. deviation from the value at 25°C

Please contact us for other specifications.

Table 1 Motional Series Resistance


Frequency Range	Motional Series Resistance
26000≤f <sub>nom</sub> <37400kHz	150 Ω max.
37400≤f <sub>nom</sub> <50000kHz	80 Ω max.
50000≤f <sub>nom</sub> ≤60000kHz	50 Ω max.

Table 2 Level of Drive

Frequency Range	Level of Drive
26000≤f <sub>nom</sub> ≤60000kHz	10μW (100μW max.)


**Dimensions**

(Unit: mm)



**Recommended Land Pattern**

(Unit: mm)



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Kyocera:

[CX1612DB48000D0FPJC1](#) [CX1612DB27120D0FLJCC](#) [CX1612DB38400D0FLJCC](#) [CX1612DB40000B0FLJCC](#)  
[CX1612DB40000H0FLJCC](#) [CX1612DB27120F0FLJCC](#) [CX1612DB48000B0FLJCC](#) [CX1612DB32000H0FLJCC](#)  
[CX1612DB26000B0FLLCC](#) [CX1612DB27120H0FLJCC](#) [CX1612DB27000P0FLJCC](#) [CX1612DB48000F0FLJCC](#)  
[CX1612DB27120B0FLJCC](#) [CX1612DB37400F0FLJCC](#) [CX1612DB26000F0FLLCC](#) [CX1612DB32000D0FLJCC](#)  
[CX1612DB48000D0FLJCC](#) [CX1612DB40000D0FLJCC](#) [CX1612DB32000B0FLJCC](#) [CX1612DB38400B0FLJCC](#)  
[CX1612DB37400H0FLJCC](#) [CX1612DB26000H0FLLCC](#) [CX1612DB32000F0FLJCC](#) [CX1612DB40000F0FLJCC](#)  
[CX1612DB24000D0FLLCC](#) [CX1612DB26000D0FLLCC](#) [CX1612DB38400F0FLJCC](#) [CX1612DB37400B0FLJCC](#)  
[CX1612DB37400D0FLJCC](#) [CX1612DB48000H0FLJCC](#) [CX1612DB38400H0FLJCC](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)