FAIRCHILD
SEMICONDUCTOR®

September 2001

IGBT

FGS15N40L

General Description


Insulated Gate Bipolar Transistors(IGBTs) with trench gate structure have superior performance in conductance and switching to planar gate structure and also have wide noise immunity. These devices are well suitable for strobe application

Features


- High Input Impedance
- High Peak Current Capability (130A)
- Easy Gate Drive

Application

- Strobe Flash



8-SOP



Absolute Maximum Ratings

T_C = 25°C unless otherrwise noted

Symbol	Description	FGS15N40L	Units
V_{CES}	Collector-Emitter Voltage	400	V
V_{GES}	Gate-Emitter Voltage	± 6	V
$I_{CM\ (1)}$	Pulsed Collector Current	130	A
P_C	Maximum Power Dissipation @ T_a = 25°C	2.0	W
T_J	Operating Junction Temperature	-40 to +150	°C
T_{stg}	Storage Temperature Range	-40 to +150	°C
T_L	Maximum Lead Temp. for soldering PurPoses from case for 5 secnds	300	°C

Notes :
(1) Repetitive rating : Pulse width limited by max. junction temperature

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient(PCB Mount)	--	62.5	°C/W

Notes: Mounted on 1" square PCB(FR4 or G-10 Material)

©2001 Fairchild Semiconductor Corporation

Electrical Characteristics of IGBT T_C = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Off Characteristics						
BV_{CES}	Collector-Emitter Breakdown Voltage	V_{GE} = 0V, I_C = 1mA	450	--	--	V
I_{CES}	Collector Cut-off Current	V_{CE} = V_{CES}, V_{GE} = 0V	--	--	10	μA
I_{GES}	G-E leakage Current	V_{GE} = V_{GES}, V_{CE} = 0V	--	--	± 0.1	μA
On Characteristics						
$V_{GE(th)}$	G-E threshold Voltage	I_C = 0V, I_C = 1mA	-	-	1.4	V
$V_{CE(sat)}$	C-E Saturation Voltage	I_C = 130A , V_{GE} = 4.0V	2.0	4.5	8.0	V
Dynamic Characteristics						
C_{ies}	Input Capacitance	V_{GE} = 0V , V_{CE} = 30V f = 1MHz	--	3800	--	pF
C_{oes}	Output Capacitance		--	45	--	pF
C_{res}	Reverse Transfer Capacitance		--	30	--	pF
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	V_{CC} = 300V , I_C = 130A V_{GE} = 4.0V , R_G = 15Ω ∗ Resistive Load	--	0.15	--	us
t_r	Rise Time		--	1.5	--	us
$t_{d(off)}$	Turn-Off Delay Time		--	0.15	0.3	us
t_f	Fall Time		--	1.5	3.0	us

Notes : Recommendation of Rg Value : Rg ≥ 15Ω

©2001 Fairchild Semiconductor Corporation




Fig 1. Typical Output Chacracteristics




Fig 2. Saturation Voltage vs. Case Temerature at Variant Current Level




Fig 3. Saturation Voltage vs. V_{GE}




Fig 4. Saturation Voltage vs. V_{GE}




Fig 5. Saturation Voltage vs. V_{GE}




Fig 6. Capacitance Characteristics

©2001 Fairchild Semiconductor Corporation





Fig 7. Collector Current Limit Vs Gate - Emitter Voltage Limit

©2001 Fairchild Semiconductor Corporation

Package Dimension

8-SOP



Dimensions in Millimeters

©2001 Fairchild Semiconductor Corporation

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FAST®	OPTOLOGIC™	SMART START™	VCX™
Bottomless™	FASTr™	OPTOPLANAR™	STAR*POWER™	
CoolFET™	FRFET™	PACMAN™	Stealth™	
CROSSVOLT™	GlobalOptoisolator™	POP™	SuperSOT™-3	
DenseTrench™	GTO™	Power247™	SuperSOT™-6	
DOME™	HiSeC™	PowerTrench®	SuperSOT™-8	
EcoSPARK™	ISOPLANAR™	QFET™	SyncFET™	
E^2CMOS™	LittleFET™	QS™	TruTranslation™	
EnSigna™	MicroFET™	QT Optoelectronics™	TinyLogic™	
FACT™	MicroPak™	Quiet Series™	UHC™	
FACT Quiet Series™	MICROWIRE™	SLIENT SWITCHER®	UltraFET®	

STAR*POWER is used under license

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

©2001 Fairchild Semiconductor Corporation

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru