

.075 Centers - Size 75 Series SS

SS-75 PROBE



PROBE SPECIFICATIONS

Minimum Centers: .075 (1.91)
 Current Rating: 3 amps continuous
 Spring Force: 2.4 or 4.9 oz. @ .050 (1.27) travel
 Typical Resistance: < 25 mΩ
 Maximum Travel: .050 (1.27)
 Working Travel: .050 (1.27)

| Rated Force oz. (g) | Preload oz. (g) | Material |
|---------------------|-----------------|----------|
| 2.4 (68) | 1.7 (48) | SS |
| 4.9 (139) | 3.1 (88) | SS |

MATERIALS

Barrel: Nickel/silver, gold plated
 Spring: Stainless steel, gold plated
 Plunger: Beryllium copper, gold plated over nickel or Duralloy™
 Receptacle: Nickel/silver, gold plated, gold plated post

BeCu PLUNGER TIPS



RECEPTACLE OPTIONS

| Part Number | Style | Receptacle Length | Probe/Receptacle Combined Length | Comments |
|---------------|------------|-------------------|----------------------------------|------------------------------|
| RSS-75-CR | Crimp | 0.695 (17.65) | 0.825 (20.96) | — |
| RSS-75-SC | Solder Cup | 0.695 (17.65) | 0.825 (20.96) | — |
| RSS-75-RP | Round Post | 1.070 (27.18) | 1.200 (30.48) | .375 post length - .025 dia. |
| RSS-75-WW-429 | Wire Wrap | 1.124 (28.55) | 1.254 (31.85) | .429 post length - .025 sq. |

HOW TO ORDER: SPRING CONTACT PROBE

RECEPTACLE

| | | | | | | | | |
|--|-------------------|--|----------------------------|--|----------------------|--------------------------------|--------------------------|---------------------------|
| SS SERIES | 75 SIZE | A TIP STYLE | 2.4 SPRING FORCE | G PLATING OPTIONS | RSS SERIES | 75 SIZE | WW TERMINATION | 429 POST LENGTH |
| SERIES: SS: STANDARD SSX: IMPROVED POINTING ACCURACY | | PLATING OPTIONS: G: GOLD PLATED PLUNGER D: DURALLOY™ PLATED PLUNGER | | TERMINATIONS: CR: CRIMP SC: SOLDER CUP WW: WIRE WRAP RP: ROUND POST | | POST LENGTH: WW: 429 | | |
| SPRING FORCE: 2.4 oz. @ .050 (1.27) TRAVEL 4.9 oz. @ .050 (1.27) TRAVEL | | CRIMPING PLIERS: CPSS75 INSERTION TOOL: RTSS75 | | | | | | |

VIEW UPDATES OF THIS INFORMATION AT WWW.IDINET.COM

Specifications subject to change without notice. Dimensions in inches (millimeters)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru