

ACPL-785E, 5962-9755701EPx, HCPL-7851, 5962-9755701HPx

Hermetically Sealed, Analog Isolation Amplifier

Overview

The Broadcom® reliability data shown represents the high-reliability class of this product family. Both of the products listed use the same LEDs, ICs, DLA-approved packaging materials, processes, stress conditions, and testing per MIL-PRF-38534. Additionally, Broadcom internal processes, material specifications, design standards, and statistical process controls are used. *The data is not transferable to other manufacturers' similarpart types.*

Operating Life Test

For valid system reliability calculations, it is necessary to adjust for the time when the system is not in operation. Note that if you are using MIL-HDBK-217 for predicting component reliability, the results may not be comparable to those given in [Table 2](#) due to different conditions and factors that have been accounted for in MIL-HDBK-217. For example, it is unlikely that your application will exercise all available channels at full rated power with the LEDs always ON as Broadcom testing does. Thus, your application total power and duty cycle must be carefully considered when comparing [Table 2](#) to predictions using MIL-HDBK-217.

Table 1: Demonstrated Operating Life Test Performance

Stress Test Condition	Total Devices Tested	Total Device Hours	Number of Failed Units	Demonstrated MTF (hour) at $T_A = +125^\circ\text{C}$	Demonstrated FITs at $T_A = +125^\circ\text{C}$
$T_A = +125^\circ\text{C}$ $V_{CC} = 5.5\text{V}$ $V_{IN} = \text{N/A}$ $V_{OUT} = \text{N/A}$ $T_J = +150^\circ\text{C}$	360	1,440,000	0	> 1,440,000	< 694

NOTE: Total tested devices include devices that are manufactured in both San Jose and Singapore. Transfer of hermetic optocoupler manufacturing from San Jose to Singapore was completed in 2000.

Definition of Failure

Inability to switch, that is, “functional failure,” is the definition of failure in this data sheet. Specifically, failure occurs when the device fails to switch ON with twice the minimum recommended drive current (but not exceeding the maximum rating) or fails to switch off when there is no input current.

Failure Rate Projections

The demonstrated point mean time to failure (MTTF) is measured at the absolute maximum stress condition. The failure rate projections in Table 2 uses the Arrhenius acceleration relationship, where a 0.43 eV activation energy is used as in the hybrid section of MIL-HDBK-217.

Table 2: Reliability Projections for Devices Listed In Title

Ambient Temperature (°C)	Junction Temperature (°C)	Typical (60% Confidence)		90% Confidence	
		MTTF (Hr/Fail)	FITs (Fail/10 ⁹ Hr)	MTTF (Hr/Fail)	FITs (Fail/10 ⁹ Hr)
125	150	1,571,554	636	625,384	1599
120	145	1,809,345	553	720,011	1389
110	135	2,423,287	413	964,323	1037
100	125	3,293,552	304	1,310,636	763
90	115	4,547,716	220	1,809,718	553
80	105	6,387,578	157	2,541,873	393
70	95	9,138,982	109	3,636,767	275
60	85	13,339,821	75	5,308,448	188
50	75	19,899,490	50	7,918,803	126
40	65	30,395,657	33	12,095,648	83
30	55	47,642,965	21	18,959,042	53
25	50	60,273,251	17	23,985,138	42

Table 3: ESDS Classification per Method 3015, MIL-STD-883

Part Number	ESD Class
5962-9755701HPx, HCPL-7851	1
5962-9755701EPx, ACPL-785E	1

Application Information

The data of Table 1 and Table 2 was obtained on devices with high temperature operating life duration up to 5000 hours. An exponential (random) failure distribution is assumed, expressed in units of FIT (failures per billion device hours), is only defined in the random failure portion of the reliability curve.

Environmental Testing

All high reliability hermetic optocouplers listed meet the 100% screening and quality conformance inspection testing of MIL-PRF-38534 Class H.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Copyright © 2013–2017 by Broadcom. All Rights Reserved.

The term “Broadcom” refers to Broadcom Limited and/or its subsidiaries. For more information, please visit www.broadcom.com.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru