
POWER COMBICON Plugs and Headers PC 6/… for Currents up to 41 A, 10.16 mm Pitch

The PC 6 plug connector features highly conductive metal alloys to offer a current carrying capacity of 41 A at a rated voltage of 1000 V. A double steel spring on the female side offers additional contact reliability especially in the case of extreme fluctuations of power or temperature.
The plugs are also available with a screw flange for vibration-proof connection to the headers, with 2 to 8 positions.
The plugs and headers are coded with the CP-HCC 4. coding profile. The self-adhesive marker cards SK 10/5 are used for labeling (see COMBICON catalog).



Phoenix Contact GmbH & Co. KG • 32823 Blomberg, Germany
Phone +49 52 35 3-00 • Fax +49 52 35 3-4 12 00 • www.phoenixcontact.com


PC 6/…-ST-10,16
10.16 mm Pitch



Note:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON plugs, 10.16 mm pitch, color: green	2	10.16	**PC 6/2-ST-10,16**	**19 13 50 7**	50
	3	20.32	**PC 6/3-ST-10,16**	**19 13 51 0**	
	4	30.48	**PC 6/4-ST-10,16**	**19 13 52 3**	
	5	40.64	**PC 6/5-ST-10,16**	**19 13 53 6**	
	6	50.80	**PC 6/6-ST-10,16**	**19 13 54 9**	
	7	60.96	**PC 6/7-ST-10,16**	**19 13 55 2**	
	8	71.12	**PC 6/8-ST-10,16**	**19 13 56 5**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		
(3) **Screwdriver**, blade: 1.0 x 4.0 x 100 mm, length: 200 mm			**SZS 1,0 x 4,0**	**12 05 06 6**	10

Technical data					
Dimensions		see description			
Pitch	[mm]	10.16			
Hole diameter	[mm]	–			
Pin dimensions	[mm]x[mm]	–			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group	–	I			
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2	
Rated voltage	[V]	1000	1000	1000	
Rated surge voltage	[kV]	8	8	8	
Nominal current / cross section	[A]/[mm²]	41 / 6.0			
Maximum load current / cross section	[A]/[mm²]	41 / 6.0			
Connection capacity					
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.5 - 10.0 / 0.5 - 6.0 / 20 - 7			
Stranded with ferrule without / with plastic sleeve	[mm²]	0.5 - 6.0 / 0.5 -6.0			
Multiple connection (2 conductors with same cross section)					
Solid / stranded	[mm²]	0.5 - 6.0 / 0.5 - 6.0			
Stranded with ferrule with plastic sleeve	[mm²]	0.5 - 2.5			
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 4.0			
Stripping length	[mm]	12			
Internal cylindrical gauge (IEC 60 947-1)		A 5			
Thread		M 4			
Torque	[Nm]	1.2 - 1.5			
Insulating material		PA			
Inflammability class in acc. with UL 94		V0			
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes	UL/CUL:[V]/[A]/AWG	600 / 41 / 20 - 8			
	CSA:[V]/[A]/AWG	–			




PC 6/…-STF-10,16 with Screw Flange 10.16 mm Pitch




HNote:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON plugs, 10.16 mm pitch, color: green, with screw flange	2	10.16	**PC 6/2-STF-10,16**	**19 13 57 8**	50
	3	20.32	**PC 6/3-STF-10,16**	**19 13 58 1**	
	4	30.48	**PC 6/4-STF-10,16**	**19 13 59 4**	
	5	40.64	**PC 6/5-STF-10,16**	**19 13 60 4**	
	6	50.80	**PC 6/6-STF-10,16**	**19 13 61 7**	
	7	60.96	**PC 6/7-STF-10,16**	**19 13 62 0**	
	8	71.12	**PC 6/8-STF-10,16**	**19 13 63 3**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		
(3) **Screwdriver**, blade: 1.0 x 4.0 x 100 mm, length: 200 mm			**SZS 1,0 x 4,0**	**12 05 06 6**	10

Technical data					
Dimensions		see description			
Pitch	[mm]	10.16			
Hole diameter	[mm]	–			
Pin dimensions	[mm]x[mm]	–			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group	–	I			
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2	
Rated voltage	[V]	1000	1000	1000	
Rated surge voltage	[kV]	8	8	8	
Nominal current / cross section	[A]/[mm²]	41 / 6.0			
Maximum load current / cross section	[A]/[mm²]	41 / 6.0			
Connection capacity					
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG	0.5 - 10.0 / 0.5 - 6.0 / 20 - 7			
Stranded with ferrule without / with plastic sleeve	[mm²]	0.5 - 6.0 / 0.5 -6.0			
Multiple connection (2 conductors with same cross section)					
Solid / stranded	[mm²]	0.5 - 6.0 / 0.5 - 6.0			
Stranded with ferrule with plastic sleeve	[mm²]	0.5 - 2.5			
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 4.0			
Stripping length	[mm]	12			
Internal cylindrical gauge (IEC 60 947-1)		A 5			
Thread		M 4			
Torque	[Nm]	1.2 - 1.5			
Insulating material		PA			
Inflammability class in acc. with UL 94		V0			
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes	UL/CUL:[V]/[A]/AWG	600 / 41 / 20 - 8			
	CSA:[V]/[A]/AWG	–			



PC 6/…-G-10,16
10.16 mm Pitch





Note:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON headers,					
10.16 mm pitch, color: green,	2	10.16	**PC 6/2-G-10,16**	**19 13 64 6**	50
plug-in direction parallel to the PCB	3	20.32	**PC 6/3-G-10,16**	**19 13 65 9**	
	4	30.48	**PC 6/4-G-10,16**	**19 13 66 2**	
	5	40.64	**PC 6/5-G-10,16**	**19 13 67 5**	
	6	50.80	**PC 6/6-G-10,16**	**19 13 68 8**	
	7	60.96	**PC 6/7-G-10,16**	**19 13 69 1**	
	8	71.12	**PC 6/8-G-10,16**	**19 13 70 1**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		


Technical data					
Dimensions			see description		
Pitch		[mm]	10.16		
Hole diameter		[mm]	1.7		
Pin dimensions		[mm]x[mm]	1.0 x 1.2		
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		–	I		
Surge voltage category / contamination class		–/–	III / 3	III / 2	II / 2
Rated voltage		[V]	630[1])	1000	1000
Rated surge voltage		[kV]	6	8	8
Nominal current / cross section		[A]/[mm²]	41 / –		
Maximum load current / cross section		[A]/[mm²]	41 / –		
Connection capacity					
Solid / stranded / conductor sizes		[mm²]/[mm²]/AWG	–		
Stranded with ferrule without / with plastic sleeve		[mm²]	–		
Multiple connection (2 conductors with same cross section)					
Solid / stranded		[mm²]	–		
Stranded with ferrule with plastic sleeve		[mm²]	–		
Stranded with TWIN ferrule with plastic sleeve		[mm²]	–		
Stripping length		[mm]	–		
Internal cylindrical gauge (IEC 60 947-1)			–		
Thread			–		
Torque		[Nm]	–		
Insulating material			PA		
Inflammability class in acc. with UL 94			V0		
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes		UL/CUL:[V]/[A]/AWG	300 / 41 / -		
		CSA:[V]/[A]/AWG	–		

[1]) 1000 V on printed circuit board.





PC 6/…-GF-10,16
with Threaded Flange
10.16 mm Pitch




Note:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.


Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON headers,					
10.16 mm pitch, color: green,	2	10.16	**PC 6/2-GF-10,16**	**19 13 71 4**	50
plug-in direction parallel to the PCB,	3	20.32	**PC 6/3-GF-10,16**	**19 13 72 7**	
with threaded flange	4	30.48	**PC 6/4-GF-10,16**	**19 13 73 0**	
	5	40.64	**PC 6/5-GF-10,16**	**19 13 74 3**	
	6	50.80	**PC 6/6-GF-10,16**	**19 13 75 6**	
	7	60.96	**PC 6/7-GF-10,16**	**19 13 76 9**	
	8	71.12	**PC 6/8-GF-10,16**	**19 13 77 2**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		

Technical data					
Dimensions		see description			
Pitch	[mm]	10.16			
Hole diameter	[mm]	1.7			
Pin dimensions	[mm]x[mm]	1.0 x 1.2			
Technical data in accordance with IEC/ DIN VDE					
Insulating material group	–		I		
Surge voltage category / contamination class	–/–	III / 3	III / 2	II / 2	
Rated voltage	[V]	630[1])	1000	1000	
Rated surge voltage	[kV]	6	8	8	
Nominal current / cross section	[A]/[mm²]		41 / –		
Maximum load current / cross section	[A]/[mm²]		41 / –		
Connection capacity					
Solid / stranded / conductor sizes	[mm²]/[mm²]/AWG		–		
Stranded with ferrule without / with plastic sleeve	[mm²]		–		
Multiple connection (2 conductors with same cross section)					
Solid / stranded	[mm²]		–		
Stranded with ferrule with plastic sleeve	[mm²]		–		
Stranded with TWIN ferrule with plastic sleeve	[mm²]		–		
Stripping length	[mm]		–		
Internal cylindrical gauge (IEC 60 947-1)			–		
Thread			–		
Torque	[Nm]		–		
Insulating material			PA		
Inflammability class in acc. with UL 94			V0		
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes	UL/CUL:[V]/[A]/AWG		300 / 41 / -		
	CSA:[V]/[A]/AWG		–		

[1]) 1000 V on printed circuit board.



PCV 6/…-G-10,16
10.16 mm Pitch





Note:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON headers,					
10.16 mm pitch, color: green,	2	10.16	**PCV 6/2-G-10,16**	**19 22 48 8**	50
plug-in direction vertical to the PCB,	3	20.32	**PCV 6/3-G-10,16**	**19 22 49 1**	
	4	30.48	**PCV 6/4-G-10,16**	**19 22 50 1**	
	5	40.64	**PCV 6/5-G-10,16**	**19 22 51 4**	
	6	50.80	**PCV 6/6-G-10,16**	**19 22 52 7**	
	7	60.96	**PCV 6/7-G-10,16**	**19 22 53 0**	
	8	71.12	**PCV 6/8-G-10,16**	**19 22 54 3**	
	9	81.28	**PCV 6/9-G-10,16**	**19 22 55 6**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		


Technical data					
Dimensions			see description		
Pitch		[mm]	10.16		
Hole diameter		[mm]	1.7		
Pin dimensions		[mm]x[mm]	1.0 x 1.2		
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		–	I		
Surge voltage category / contamination class		–/–	III / 3	III / 2	II / 2
Rated voltage		[V]	630[1])	1000	1000
Rated surge voltage		[kV]	6	8	8
Nominal current / cross section		[A]/[mm²]	41 / –		
Maximum load current / cross section		[A]/[mm²]	41 / –		
Connection capacity					
Solid / stranded / conductor sizes		[mm²]/[mm²]/AWG	–		
Stranded with ferrule without / with plastic sleeve		[mm²]	–		
Multiple connection (2 conductors with same cross section)					
Solid / stranded		[mm²]	–		
Stranded with ferrule with plastic sleeve		[mm²]	–		
Stranded with TWIN ferrule with plastic sleeve		[mm²]	–		
Stripping length		[mm]	–		
Internal cylindrical gauge (IEC 60 947-1)			–		
Thread			–		
Torque		[Nm]	–		
Insulating material			PA		
Inflammability class in acc. with UL 94			V0		
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes		UL/CUL:[V]/[A]/AWG	300 / 41 / -		
		CSA:[V]/[A]/AWG	–		

[1]) 1000 V on printed circuit board.





PCV 6/…-GF-10,16 with Threaded Flange 10.16 mm Pitch





Note:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON headers,					
10.16 mm pitch, color: green,	2	10.16	**PCV 6/2-GF-10,16**	**19 22 56 9**	50
plug-in direction vertical to the PCB,	3	20.32	**PCV 6/3-GF-10,16**	**19 22 57 2**	
with threaded flange	4	30.48	**PCV 6/4-GF-10,16**	**19 22 58 5**	
	5	40.64	**PCV 6/5-GF-10,16**	**19 22 59 8**	
	6	50.80	**PCV 6/6-GF-10,16**	**19 22 60 8**	
	7	60.96	**PCV 6/7-GF-10,16**	**19 22 61 1**	
	8	71.12	**PCV 6/8-GF-10,16**	**19 22 62 4**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		

Technical data					
Dimensions			see description		
Pitch		[mm]	10.16		
Hole diameter		[mm]	1.7		
Pin dimensions		[mm]x[mm]	1.0 x 1.2		
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		–	I		
Surge voltage category / contamination class		–/–	III / 3	III / 2	II / 2
Rated voltage		[V]	630[1])	1000	1000
Rated surge voltage		[kV]	6	8	8
Nominal current / cross section		[A]/[mm²]	41 / –		
Maximum load current / cross section		[A]/[mm²]	41 / –		
Connection capacity					
Solid / stranded / conductor sizes		[mm²]/[mm²]/AWG	–		
Stranded with ferrule without / with plastic sleeve		[mm²]	–		
Multiple connection (2 conductors with same cross section)					
Solid / stranded		[mm²]	–		
Stranded with ferrule with plastic sleeve		[mm²]	–		
Stranded with TWIN ferrule with plastic sleeve		[mm²]	–		
Stripping length		[mm]	–		
Internal cylindrical gauge (IEC 60 947-1)			–		
Thread			–		
Torque		[Nm]	–		
Insulating material			PA		
Inflammability class in acc. with UL 94			V0		
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes		UL/CUL:[V]/[A]/AWG	300 / 41 / -		
		CSA:[V]/[A]/AWG	–		


[1]) 1000 V on printed circuit board.





POWER COMBICON Plug-In Block for Direct Mounting, 10.16 mm Pitch

All electronic components are pluggable and easy to maintain. The plug is not connected to the PCB, however, but vice versa.
Plug-in blocks PCU 6/…-STD-10,16with a screw connection and vertical plug-in direction have a base plate with two mounting ears for screwing onto mounting plates or into component housings.
They are available with 2 to 9 positions and a 10.16 mm pitch.
The self-adhesive marker cards SK 10/5 are used for labeling (see COMBICON catalog)




PCU 6/…-STD-10,16
10.16 mm Pitch





Note:
COMBICON plug connectors may only be actuated in the no-load condition. If smaller loads need to be switched for operational reasons, experimental values are available on request.

Description	No. of positions	Dim. a [mm]	Type	Order No.	Pcs./Pkt.
POWER COMBICON plug-in block, 10.16 mm pitch, color: green	2	10.16	**PCU 6/2-STD-10,16**	**19 22 63 7**	50
	3	20.32	**PCU 6/3-STD-10,16**	**19 22 64 0**	
	4	30.48	**PCU 6/4-STD-10,16**	**19 22 65 3**	
	5	40.64	**PCU 6/5-STD-10,16**	**19 22 66 6**	
	6	50.80	**PCU 6/6-STD-10,16**	**19 22 67 9**	
	7	60.96	**PCU 6/7-STD-10,16**	**19 22 68 2**	
	8	71.12	**PCU 6/8-STD-10,16**	**19 22 69 5**	
	9	81.28	**PCU 6/9-STD-10,16**	**19 22 70 5**	
(1) **Coding profile,** is inserted into the recess on the plug and header, insulating material: red			**CP-HCC 4**	**16 00 02 7**	100
(2) **Marker card,** with 10 pcs. 10-section marker strips, white, self-adhesive, for 100 terminal blocks			**SK 10/5** (see COMBICON catalog)		
(3) **Screwdriver**, blade: 1.0 x 4.0 x 100 mm, length: 200 mm			**SZS 1,0 x 4,0**	**12 05 06 6**	10

Technical data					
Dimensions			see description		
Pitch		[mm]	10.16		
Hole diameter		[mm]	–		
Pin dimensions		[mm]x[mm]	–		
Technical data in accordance with IEC/ DIN VDE					
Insulating material group		–	I		
Surge voltage category / contamination class		–/–	III / 3	III / 2	II / 2
Rated voltage		[V]	1000	1000	1000
Rated surge voltage		[kV]	8	8	8
Nominal current / cross section		[A]/[mm²]		41 / 6.0	
Maximum load current / cross section		[A]/[mm²]		41 / 6.0	
Connection capacity					
Solid / stranded / conductor sizes		[mm²]/[mm²]/AWG	0.5 - 10.0 / 0.5 - 6.0 / 20 - 7		
Stranded with ferrule without / with plastic sleeve		[mm²]	0.5 - 6.0 / 0.5 -6.0		
Multiple connection (2 conductors with same cross section)					
Solid / stranded		[mm²]	0.5 - 6.0 / 0.5 - 6.0		
Stranded with ferrule with plastic sleeve		[mm²]	0.5 - 2.5		
Stranded with TWIN ferrule with plastic sleeve		[mm²]	0.5 - 4.0		
Stripping length		[mm]	12		
Internal cylindrical gauge (IEC 60 947-1)			A 5		
Thread			M 4		
Torque		[Nm]	1.2 - 1.5		
Insulating material			PA		
Inflammability class in acc. with UL 94			V0		
Approval data (UL/CUL and CSA)					
Nominal voltage / current / conductor sizes		UL/CUL:[V]/[A]/AWG	–		
		CSA:[V]/[A]/AWG	–		







http://www.phoenixcontact.com
© Phoenix Contact 01.03.02 TNR: 5099540-02

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru