

Low Resistance Metal Element Resistors

LOB Series

- Ultra low resistance values to 0.005Ω
- Available in 1, 3 and 5 watt rated packages
- Tolerances from ±1% to ±5%
- Inherently non-inductive ($\leq 0.02\mu\text{H}$ at 0.5MHz)
- Low temperature coefficient of resistance
- High stability over life



All Pb-free parts comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

Electrical Data

| | | LOB-1 | LOB-3 | LOB-5 |
|--|-------|---------------------|---------------------|---------------------|
| Continuous power dissipation at 25°C in free air | watts | 1 | 3 | 5 |
| Overload power for 5 seconds | watts | 5 | 15 | 25 |
| Resistance range | ohms | R005 to R100 | R005 to R120 | R005 to R100 |
| Maximum working voltage | volts | $\sqrt{1 \times R}$ | $\sqrt{3 \times R}$ | $\sqrt{5 \times R}$ |
| Operating temperature | °C | -55 to 175 | -55 to 175 | -55 to 175 |

* Power Dissipation - The maximum wattage rating depends upon the amount of heat which can be transferred to the surroundings while not exceeding the maximum element temperature. Ambient air temperature, velocity of cooling air, thermal resistance of heat and the temperature of surrounding objects will affect this transfer, this must be taken into account when selecting a resistor.

Physical Data

| Dimensions (mm) | | | | | |
|-----------------|------------|-----------|------------|------------|-------|
| Type | L | D | f | d | C nom |
| LOB-1 | 9.9±0.3 | 3.6±0.2 | 38.1±3.2 | 0.813±0.05 | 33.27 |
| LOB-3 | 14.22±0.25 | 5.33±0.25 | 34.93±3.18 | 0.81±0.05 | 33.27 |
| LOB-5 | 23.37±0.25 | 8.38±0.25 | 31.75±3.18 | 1.02±0.05 | 42.42 |

Description

LOB Series power precision metal element resistors feature resistance values down to 0.005 Ω with virtually no inductance. Available in 1, 3 and 5 watt rated axial leaded packages, these resistors are compatible with automatic insertion equipment.

Construction

LOB Series resistors feature tinned copper leads welded directly to a low temperature coefficient resistance element in a highly automated proprietary process. The leaded resistor elements are then encapsulated in a moulding compound.

Applications

- Switchmode and linear power supplies.
- Automotive current-sensing circuits.
- Instrumentation.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

LOB Series

**Power derating percentage vs
Free air ambient temperature**



**Temperature coefficient of resistance vs
Resistance value**



| Test | MIL-STD 202 | MAX %ΔR* | Unit |
|------------------------|-------------|-------------------|------|
| Load life (2000 hours) | Method 108 | ±1% | %ΔR |
| Thermal shock | Method 107 | ±1% | %ΔR |
| Vibration | Method 204 | ±0.5% | %ΔR |
| Mechanical shock | Method 213 | ±0.5% | %ΔR |
| Dielectric strength | Method 301 | ±0.5% | %ΔR |
| Insulation resistance | Method 302 | >10 ¹¹ | ohms |

*±0.0005 ohm allowance for test/contact error.

Packaging

Resistors are supplied taped and reeled.
Bulk packaging available.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Ordering Procedure

This product has two valid part numbers:

European (Welwyn) Part Number: LOB3-R01JI (LOB3, 10 milliohms $\pm 5\%$, Pb-free)



| 1 | 2 | 3 | 4 | |
|------|----------|----------------|--------------------------------|------------------|
| Type | Value | Tolerance | Packing & Termination Finish | |
| LOB1 | R = ohms | F* = $\pm 1\%$ | I = Standard packing & Pb-free | |
| LOB3 | | H = $\pm 3\%$ | PB = Standard packing & SnPb | |
| LOB5 | | J* = $\pm 5\%$ | LOB1 | Taped, 3500/reel |
| | | * preferred | LOB3 | Taped, 1250/reel |
| | | | LOB5 | Taped, 800/reel |

USA (IRC) Part Number: LOB-3R010FLFSLT (LOB3, 10 milliohms $\pm 5\%$, Pb-free)



| 1 | 2 | 3 | 4 | 5 | |
|-------|----------|---------------|--------------------|------------------|-----------|
| Type | Value | Tolerance | Termination Finish | Packing | |
| LOB-1 | R = ohms | F = $\pm 1\%$ | Omit for SnPb | SLT = Lead Tape* | |
| LOB-3 | | H = $\pm 3\%$ | LF = Pb-free | LOB-1 | 3500/reel |
| LOB-5 | | J = $\pm 5\%$ | | LOB-3 | 1250/reel |
| | | | | LOB-5 | 800/reel |
| | | | | BLK = Bulk | |
| | | | | LOB-1 | 1500/box |
| | | | | LOB-3 | 800/box |
| | | | | LOB-5 | 200/box |

* preferred

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru