


## Small Signal Switching Diodes, High Voltage



### FEATURES

- Silicon epitaxial planar diode
- Fast switching diode in case SOT-23, especially suited for automatic insertion.
- AEC-Q101 qualified
- Base P/N-E3 - RoHS-compliant, commercial grade
- Base P/N-HE3 - RoHS-compliant, AEC-Q101 qualified
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### MECHANICAL DATA

**Case:** SOT-23

**Weight:** approx. 8.8 mg

**Packaging codes/options:**

18/10K per 13" reel (8 mm tape), 10K/box

08/3K per 7" reel (8 mm tape), 15K/box

### PARTS TABLE

| PART  | TYPE DIFFERENTIATION | ORDERING CODE                | TYPE MARKING | INTERNAL CONSTRUCTION | REMARKS       |
|-------|----------------------|------------------------------|--------------|-----------------------|---------------|
| BAS19 | $V_R = 100\text{ V}$ | BAS19-E3-08 or BAS19-E3-18   | A8           | Single diode          | Tape and reel |
|       |                      | BAS19-HE3-08 or BAS19-HE3-18 |              |                       |               |
| BAS20 | $V_R = 150\text{ V}$ | BAS20-E3-08 or BAS20-E3-18   | A81          | Single diode          | Tape and reel |
|       |                      | BAS20-HE3-08 or BAS20-HE3-18 |              |                       |               |
| BAS21 | $V_R = 200\text{ V}$ | BAS21-E3-08 or BAS21-E3-18   | A82          | Single diode          | Tape and reel |
|       |                      | BAS21-HE3-08 or BAS21-HE3-18 |              |                       |               |

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER                                                | TEST CONDITION              | PART  | SYMBOL      | VALUE | UNIT |
|----------------------------------------------------------|-----------------------------|-------|-------------|-------|------|
| Continuous reverse voltage                               |                             | BAS19 | $V_R$       | 100   | V    |
|                                                          |                             | BAS20 | $V_R$       | 150   | V    |
|                                                          |                             | BAS21 | $V_R$       | 200   | V    |
| Repetitive peak reverse voltage                          |                             | BAS19 | $V_{RRM}$   | 120   | V    |
|                                                          |                             | BAS20 | $V_{RRM}$   | 200   | V    |
|                                                          |                             | BAS21 | $V_{RRM}$   | 250   | V    |
| Non repetitive peak forward current                      | $t = 1\text{ }\mu\text{s}$  |       | $I_{FSM}$   | 2.5   | A    |
| Non repetitive peak forward surge current                | $t = 1\text{ s}$            |       | $I_{FSM}$   | 0.5   | A    |
| Maximum average forward rectified current <sup>(1)</sup> | (av. over any 20 ms period) |       | $I_{F(AV)}$ | 200   | mA   |
| DC forward current <sup>(2)</sup>                        |                             |       | $I_F$       | 200   | mA   |
| Repetitive peak forward current                          |                             |       | $I_{FRM}$   | 625   | mA   |
| Power dissipation <sup>(2)</sup>                         |                             |       | $P_{tot}$   | 250   | mW   |

### Notes

<sup>(1)</sup> Measured under pulse conditions; pulse time =  $t_p \geq 0.3\text{ ms}$

<sup>(2)</sup> Device on fiberglass substrate, see layout on next page



| THERMAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                |                  |               |                    |
|------------------------------------------------------------------------------------------------|----------------|------------------|---------------|--------------------|
| PARAMETER                                                                                      | TEST CONDITION | SYMBOL           | VALUE         | UNIT               |
| Thermal resistance junction to ambient air                                                     |                | $R_{thJA}^{(1)}$ | 430           | $^{\circ}\text{C}$ |
| Junction temperature                                                                           |                | $T_j$            | 150           | $^{\circ}\text{C}$ |
| Storage temperature range                                                                      |                | $T_{stg}$        | - 65 to + 150 | $^{\circ}\text{C}$ |
| Operating temperature range                                                                    |                | $T_{op}$         | - 55 to + 150 | $^{\circ}\text{C}$ |

**Note**

(1) Device on fiberglass substrate, see layout drawing below


| ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                        |       |          |      |      |      |               |
|---------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|-------|----------|------|------|------|---------------|
| PARAMETER                                                                                         | TEST CONDITION                                                         | PART  | SYMBOL   | MIN. | TYP. | MAX. | UNIT          |
| Forward voltage                                                                                   | $I_F = 100\text{ mA}$                                                  |       | $V_F$    |      |      | 1.0  | V             |
|                                                                                                   | $I_F = 200\text{ mA}$                                                  |       | $V_F$    |      |      | 1.25 | V             |
| Leakage current                                                                                   | $V_R = 100\text{ V}$                                                   | BAS19 | $I_R$    |      |      | 100  | nA            |
|                                                                                                   | $V_R = 150\text{ V}$                                                   | BAS20 | $I_R$    |      |      | 100  | nA            |
|                                                                                                   | $V_R = 200\text{ V}$                                                   | BAS21 | $I_R$    |      |      | 100  | nA            |
|                                                                                                   | $V_R = V_{Rmax}, T_j = 150\text{ }^{\circ}\text{C}$                    |       | $I_R$    |      |      | 100  | $\mu\text{A}$ |
| Dynamic forward resistance                                                                        | $I_F = 10\text{ mA}$                                                   |       | $r_f$    |      | 5    |      | $\Omega$      |
| Diode capacitance                                                                                 | $V_R = 0, f = 1\text{ MHz}$                                            |       | $C_D$    |      |      | 5    | pF            |
| Reverse recovery time                                                                             | $I_F = I_R = 30\text{ mA}, R_L = 100\text{ }\Omega, i_R = 3\text{ mA}$ |       | $t_{rr}$ |      |      | 50   | ns            |




**LAYOUT FOR  $R_{thJA}$  TEST**

Thickness:


Fiberglass 1.5 mm (0.059 inches)

Copper leads 0.3 mm (0.012 inches)



**PACKAGE DIMENSIONS** in millimeters (inches): **SOT-23**

Foot print recommendation:



Document no.: 6.541-5014.01-4  
Rev. 8 - Date: 23.Sept.2009  
17418



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)