


## Cree® XLamp® XP-E LEDs



### PRODUCT DESCRIPTION

The XLamp XP-E LED combines the proven lighting-class performance and reliability of the XLamp XR-E LED in a package with 80% smaller footprint. The XLamp XP-E LED continues Cree's history of innovation in LEDs for lighting applications with wide viewing angle, symmetrical package, unlimited floor life and electrically neutral thermal path.

Cree XLamp LEDs bring high performance and quality of light to a wide range of lighting applications, including color-changing, portable and personal, outdoor, indoor-directional, transportation, stage and studio, commercial and emergency-vehicle lighting.

### FEATURES

- Available in white, outdoor white, 80-CRI, 85-CRI and 90-CRI white, royal blue, blue, green, amber, red & red-orange
- Maximum drive current: up to 1 A
- Low thermal resistance: as low as 9 °C/W
- Maximum junction temperature: 150 °C
- Wide viewing angle: 115°-130°
- Unlimited floor life at  $\leq 30\text{ °C}/85\%\text{ RH}$
- Reflow solderable - JEDEC J-STD-020C compatible
- Electrically neutral thermal path
- RoHS- and REACH-compliant
- UL-recognized component (E349212)



### TABLE OF CONTENTS

|                                                                   |    |
|-------------------------------------------------------------------|----|
| Characteristics .....                                             | 2  |
| Flux Characteristics - White .....                                | 3  |
| Flux Characteristics - Color .....                                | 4  |
| Relative Spectral Power Distribution.....                         | 6  |
| Relative Flux vs. Junction Temperature .....                      | 7  |
| Electrical Characteristics .....                                  | 8  |
| Thermal Design .....                                              | 9  |
| Relative Flux vs. Current .....                                   | 10 |
| Relative Chromaticity vs. Current and Temperature - Warm White .. | 11 |
| Typical Spatial Distribution.....                                 | 12 |
| Reflow Soldering Characteristics ..                               | 13 |
| Notes.....                                                        | 14 |
| Mechanical Dimensions.....                                        | 15 |
| Tape and Reel .....                                               | 16 |
| Packaging.....                                                    | 17 |

## CHARACTERISTICS

| Characteristics                                                        | Unit    | Minimum | Typical | Maximum |
|------------------------------------------------------------------------|---------|---------|---------|---------|
| Thermal resistance, junction to solder point - white, royal blue, blue | °C/W    |         | 9       |         |
| Thermal resistance, junction to solder point - green                   | °C/W    |         | 15      |         |
| Thermal resistance, junction to solder point - amber, red, red-orange  | °C/W    |         | 10      |         |
| Viewing angle (FWHM) - white                                           | degrees |         | 115     |         |
| Viewing angle (FWHM) - royal blue, blue, green, red, red-orange, amber | degrees |         | 130     |         |
| Temperature coefficient of voltage - white                             | mV/°C   |         | -3.0    |         |
| Temperature coefficient of voltage - royal blue, blue                  | mV/°C   |         | -3.3    |         |
| Temperature coefficient of voltage - green                             | mV/°C   |         | -3.8    |         |
| Temperature coefficient of voltage - red-orange, red                   | mV/°C   |         | -1.8    |         |
| Temperature coefficient of voltage - amber                             | mV/°C   |         | -1.2    |         |
| ESD classification (HBM per Mil-Std-883D)                              |         |         | Class 2 |         |
| DC forward current - white, royal blue, blue, green                    | mA      |         |         | 1000    |
| DC forward current - red-orange, red                                   | mA      |         |         | 700     |
| DC forward current - amber                                             | mA      |         |         | 500     |
| Reverse voltage                                                        | V       |         |         | 5       |
| Forward voltage (@ 350 mA) - white                                     | V       |         | 3.05    | 3.9     |
| Forward voltage (@ 350 mA) - royal blue, blue                          | V       |         | 3.1     | 3.9     |
| Forward voltage (@ 350 mA) - green                                     | V       |         | 3.3     | 3.9     |
| Forward voltage (@ 350 mA) - red-orange, red, amber                    | V       |         | 2.1     | 2.5     |
| Forward voltage (@ 500 mA) - amber                                     | V       |         | 2.3     |         |
| Forward voltage (@ 700 mA) - white                                     | V       |         | 3.3     |         |
| Forward voltage (@ 700 mA) - red-orange, red                           | V       |         | 2.3     |         |
| Forward voltage (@ 1000 mA) - green                                    | V       |         | 3.8     |         |
| Forward voltage (@ 1000 mA) - white, royal blue, blue                  | V       |         | 3.5     |         |
| LED junction temperature                                               | °C      |         |         | 150     |

## FLUX CHARACTERISTICS (T<sub>j</sub> = 25 °C) - WHITE

The following table provides several base order codes for XLamp XP-E LEDs. It is important to note that the base order codes listed here are a subset of the total available order codes for the product family. For more order codes, as well as a complete description of the order-code nomenclature, please consult the XLamp XP Family Binning and Labeling document.

| Color         | CCT Range |          | Base Order Codes<br>Min. Luminous Flux<br>(lm) @ 350 mA |           | Order Code           |
|---------------|-----------|----------|---------------------------------------------------------|-----------|----------------------|
|               | Min.      | Max.     | Group                                                   | Flux (lm) |                      |
| Cool White    | 5000 K    | 10,000 K | Q4                                                      | 100       | XPEWHT-L1-0000-00C01 |
|               |           |          | Q5                                                      | 107       | XPEWHT-L1-0000-00D01 |
|               |           |          | R2                                                      | 114       | XPEWHT-L1-0000-00E01 |
|               |           |          | R3                                                      | 122       | XPEWHT-L1-0000-00F01 |
| Outdoor White | 4000 K    | 5300 K   | Q4                                                      | 100       | XPEWHT-01-0000-00CC2 |
|               |           |          | Q5                                                      | 107       | XPEWHT-01-0000-00DC2 |
|               |           |          | R2                                                      | 114       | XPEWHT-01-0000-00EC2 |
|               |           |          | R3                                                      | 122       | XPEWHT-01-0000-00FC2 |
| Neutral White | 3700 K    | 5300 K   | Q3                                                      | 93.9      | XPEWHT-L1-0000-00BE4 |
|               |           |          | Q4                                                      | 100       | XPEWHT-L1-0000-00CE4 |
|               |           |          | Q5                                                      | 107       | XPEWHT-L1-0000-00DE4 |
| 80-CRI White  | 2600 K    | 4300 K   | P4                                                      | 80.6      | XPEWHT-H1-0000-009E7 |
|               |           |          | Q2                                                      | 87.4      | XPEWHT-H1-0000-00AE7 |
| Warm White    | 2600 K    | 3700 K   | P4                                                      | 80.6      | XPEWHT-L1-0000-009E7 |
|               |           |          | Q2                                                      | 87.4      | XPEWHT-L1-0000-00AE7 |
|               |           |          | Q3                                                      | 93.9      | XPEWHT-L1-0000-00BE7 |
| 85-CRI White  | 2600 K    | 3200 K   | N4                                                      | 62.0      | XPEWHT-P1-0000-006E7 |
|               |           |          | P2                                                      | 67.2      | XPEWHT-P1-0000-007E7 |
|               |           |          | P3                                                      | 73.9      | XPEWHT-P1-0000-008E7 |
|               |           |          | P4                                                      | 80.6      | XPEWHT-P1-0000-009E7 |
| 90-CRI White  | 2600 K    | 3200 K   | N4                                                      | 62.0      | XPEWHT-U1-0000-006E7 |
|               |           |          | P2                                                      | 67.2      | XPEWHT-U1-0000-007E7 |
|               |           |          | P3                                                      | 73.9      | XPEWHT-U1-0000-008E7 |

### Notes:

- Cree maintains a tolerance of  $\pm 7\%$  on flux and power measurements,  $\pm 0.005$  on chromaticity (CCx, CCy) measurements and  $\pm 2$  on CRI measurements.
- Typical CRI for Cool White (5000 K – 10,000 K CCT) is 70.
- Typical CRI for Neutral White (3700 K – 5300 K CCT) is 75.
- Typical CRI for Outdoor White (4000 K - 5300 K CCT) is 70.
- Typical CRI for Warm White (2600 K – 3700 K CCT) is 80.
- Minimum CRI for 80-CRI White is 80.
- Minimum CRI for 85-CRI White is 85.
- Minimum CRI for 90-CRI White is 90.

## FLUX CHARACTERISTICS ( $T_j = 25\text{ }^{\circ}\text{C}$ ) - COLOR

The following table provides several base order codes for XLamp XP-E LEDs. It is important to note that the base order codes listed here are a subset of the total available order codes for the product family. For more order codes, as well as a complete description of the order-code nomenclature, please consult the XLamp XP Family Binning and Labeling document.

| Color      | Dominant Wavelength Range |             |       |             | Base Order Codes<br>Min. Radiant Flux<br>(mW) @ 350 mA |           | Order Code           |
|------------|---------------------------|-------------|-------|-------------|--------------------------------------------------------|-----------|----------------------|
|            | Min.                      |             | Max.  |             | Group                                                  | Flux (mW) |                      |
|            | Group                     | DWL<br>(nm) | Group | DWL<br>(nm) |                                                        |           |                      |
| Royal Blue | D3                        | 450         | D5    | 465         | 14                                                     | 350       | XPEROY-L1-0000-00901 |
|            |                           |             |       |             | 15                                                     | 425       | XPEROY-L1-0000-00A01 |
|            |                           |             |       |             | 16                                                     | 500       | XPEROY-L1-0000-00B01 |

| Color | Dominant Wavelength Range |             |       |             | Base Order Codes<br>Min. Luminous Flux<br>(lm) @ 350 mA |           | Order Code           |
|-------|---------------------------|-------------|-------|-------------|---------------------------------------------------------|-----------|----------------------|
|       | Min.                      |             | Max.  |             |                                                         |           |                      |
|       | Group                     | DWL<br>(nm) | Group | DWL<br>(nm) | Group                                                   | Flux (lm) |                      |
| Blue  | B3                        | 465         | B6    | 485         | K2                                                      | 30.6      | XPEBLU-L1-0000-00Y01 |
|       |                           |             |       |             | K3                                                      | 35.2      | XPEBLU-L1-0000-00Z01 |
|       |                           |             |       |             | M2                                                      | 39.8      | XPEBLU-L1-0000-00201 |

| Color | Dominant Wavelength Range |          |       |          | Base Order Codes<br>Min. Luminous Flux (lm) @ 350 mA |           | Order Code           |
|-------|---------------------------|----------|-------|----------|------------------------------------------------------|-----------|----------------------|
|       | Min.                      |          | Max.  |          |                                                      |           |                      |
|       | Group                     | DWL (nm) | Group | DWL (nm) | Group                                                | Flux (lm) |                      |
| Green | G2                        | 520      | G4    | 535      | P4                                                   | 80.6      | XPEGRN-L1-0000-00901 |
|       |                           |          |       |          | Q2                                                   | 87.4      | XPEGRN-L1-0000-00A01 |
|       |                           |          |       |          | Q3                                                   | 93.9      | XPEGRN-L1-0000-00B01 |
|       |                           |          |       |          | Q4                                                   | 100       | XPEGRN-L1-0000-00C01 |
|       |                           |          |       |          | Q5                                                   | 107       | XPEGRN-L1-0000-00D01 |
|       |                           |          |       |          | R2                                                   | 114       | XPEGRN-L1-0000-00E01 |

Note: Cree maintains a tolerance of +/- 7% on flux and power measurements.

**FLUX CHARACTERISTICS ( $T_j = 25\text{ }^{\circ}\text{C}$ ) - COLOR (CONTINUED)**



| Color | Dominant Wavelength Range |          |       |          | Base Order Codes<br>Min. Luminous Flux (lm) @ 350 mA |           | Order Code           |
|-------|---------------------------|----------|-------|----------|------------------------------------------------------|-----------|----------------------|
|       | Min.                      |          | Max.  |          |                                                      |           |                      |
|       | Group                     | DWL (nm) | Group | DWL (nm) | Group                                                | Flux (lm) |                      |
| Amber | A2                        | 585      | A3    | 595      | M3                                                   | 45.7      | XPEAMB-L1-0000-00301 |
|       |                           |          |       |          | N2                                                   | 51.7      | XPEAMB-L1-0000-00401 |
|       |                           |          |       |          | N3                                                   | 56.8      | XPEAMB-L1-0000-00501 |
|       |                           |          |       |          | N4                                                   | 62.0      | XPEAMB-L1-0000-00601 |
|       |                           |          |       |          | P2                                                   | 67.2      | XPEAMB-L1-0000-00701 |
|       |                           |          |       |          | P3                                                   | 73.9      | XPEAMB-L1-0000-00801 |
|       |                           |          |       |          | P4                                                   | 80.6      | XPEAMB-L1-0000-00901 |

| Color      | Dominant Wavelength Range |          |       |          | Base Order Codes<br>Min. Luminous Flux (lm) @ 350 mA |           | Order Code           |
|------------|---------------------------|----------|-------|----------|------------------------------------------------------|-----------|----------------------|
|            | Min.                      |          | Max.  |          | Group                                                | Flux (lm) |                      |
|            | Group                     | DWL (nm) | Group | DWL (nm) |                                                      |           |                      |
| Red-Orange | O3                        | 610      | O4    | 620      | N3                                                   | 56.8      | XPERDO-L1-0000-00501 |
|            |                           |          |       |          | N4                                                   | 62.0      | XPERDO-L1-0000-00601 |
|            |                           |          |       |          | P2                                                   | 67.2      | XPERDO-L1-0000-00701 |
|            |                           |          |       |          | P3                                                   | 73.9      | XPERDO-L1-0000-00801 |
|            |                           |          |       |          | P4                                                   | 80.6      | XPERDO-L1-0000-00901 |
|            |                           |          |       |          | Q2                                                   | 87.4      | XPERDO-L1-0000-00A01 |




| Color | Dominant Wavelength Range |          |       |          | Base Order Codes<br>Min. Luminous Flux (lm) @ 350 mA |           | Order Code           |
|-------|---------------------------|----------|-------|----------|------------------------------------------------------|-----------|----------------------|
|       | Min.                      |          | Max.  |          | Group                                                | Flux (lm) |                      |
|       | Group                     | DWL (nm) | Group | DWL (nm) |                                                      |           |                      |
| Red   | R2                        | 620      | R3    | 630      | M3                                                   | 45.7      | XPERED-L1-0000-00301 |
|       |                           |          |       |          | N2                                                   | 51.7      | XPERED-L1-0000-00401 |
|       |                           |          |       |          | N3                                                   | 56.8      | XPERED-L1-0000-00501 |
|       |                           |          |       |          | N4                                                   | 62.0      | XPERED-L1-0000-00601 |
|       |                           |          |       |          | P2                                                   | 67.2      | XPERED-L1-0000-00701 |
|       |                           |          |       |          | P3                                                   | 73.9      | XPERED-L1-0000-00801 |

Note: Cree maintains a tolerance of +/- 7% on flux and power measurements.




## RELATIVE SPECTRAL POWER DISTRIBUTION



## RELATIVE FLUX VS. JUNCTION TEMPERATURE ( $I_F = 350 \text{ mA}$ )




## ELECTRICAL CHARACTERISTICS ( $T_j = 25\text{ }^{\circ}\text{C}$ )






## THERMAL DESIGN


The maximum forward current is determined by the thermal resistance between the LED junction and ambient. It is crucial for the end product to be designed in a manner that minimizes the thermal resistance from the solder point to ambient in order to optimize lamp life and optical characteristics.




White




Blue, Royal Blue






Red, Red-Orange






Green




Amber

**RELATIVE FLUX VS. CURRENT ( $T_j = 25\text{ }^{\circ}\text{C}$ )**


**RELATIVE FLUX VS. CURRENT ( $T_j = 25\text{ }^{\circ}\text{C}$ ) (CONTINUED)**

**RELATIVE CHROMATICITY VS. CURRENT AND TEMPERATURE - WARM WHITE**



## TYPICAL SPATIAL DISTRIBUTION



## REFLOW SOLDERING CHARACTERISTICS

In testing, Cree has found XLamp XP-E LEDs to be compatible with JEDEC J-STD-020C, using the parameters listed below. As a general guideline, Cree recommends that users follow the recommended soldering profile provided by the manufacturer of solder paste used.

Note that this general guideline may not apply to all PCB designs and configurations of reflow soldering equipment.



| Profile Feature                                       | Lead-Based Solder | Lead-Free Solder |
|-------------------------------------------------------|-------------------|------------------|
| Average Ramp-Up Rate ( $T_{Smax}$ to $T_p$ )          | 3 °C/second max.  | 3 °C/second max. |
| Preheat: Temperature Min ( $T_{Smin}$ )               | 100 °C            | 150 °C           |
| Preheat: Temperature Max ( $T_{Smax}$ )               | 150 °C            | 200 °C           |
| Preheat: Time ( $t_{Smin}$ to $t_{Smax}$ )            | 60-120 seconds    | 60-180 seconds   |
| Time Maintained Above: Temperature ( $T_{L1}$ )       | 183 °C            | 217 °C           |
| Time Maintained Above: Time ( $t_L$ )                 | 60-150 seconds    | 60-150 seconds   |
| Peak/Classification Temperature ( $T_p$ )             | 215 °C            | 260 °C           |
| Time Within 5 °C of Actual Peak Temperature ( $t_p$ ) | 10-30 seconds     | 20-40 seconds    |
| Ramp-Down Rate                                        | 6 °C/second max.  | 6 °C/second max. |
| Time 25 °C to Peak Temperature                        | 6 minutes max.    | 8 minutes max.   |

Note: All temperatures refer to topside of the package, measured on the package body surface.

## NOTES

### Lumen Maintenance Projections

Cree now uses standardized IES LM-80-08 and TM-21-11 methods for collecting long-term data and extrapolating LED lumen maintenance. For information on the specific LM-80 data sets available for this LED, refer to the public LM-80 results document at [www.cree.com/xlamp\\_app\\_notes/LM80\\_results](http://www.cree.com/xlamp_app_notes/LM80_results).

Please read the XLamp Long-Term Lumen Maintenance application note at [www.cree.com/xlamp\\_app\\_notes/lumen\\_maintenance](http://www.cree.com/xlamp_app_notes/lumen_maintenance) for more details on Cree's lumen maintenance testing and forecasting. Please read the XLamp Thermal Management application note at [www.cree.com/xlamp\\_app\\_notes/thermal\\_management](http://www.cree.com/xlamp_app_notes/thermal_management) for details on how thermal design, ambient temperature, and drive current affect the LED junction temperature.

### Moisture Sensitivity

In testing, Cree has found XLamp XP-C and XP-E LEDs to have unlimited floor life in conditions  $\leq 30\text{ }^{\circ}\text{C}/85\%$  relative humidity (RH). Moisture testing included a 168-hour soak at  $85\text{ }^{\circ}\text{C}/85\%$  RH followed by 3 reflow cycles, with visual and electrical inspections at each stage.

Cree recommends keeping XLamp LEDs in their sealed moisture-barrier packaging until immediately prior to use. Cree also recommends returning any unused LEDs to the resealable moisture-barrier bag and closing the bag immediately after use.

### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as amended through June 8, 2011. RoHS Declarations for this product can be obtained from your Cree representative or obtained from the Product Ecology section of [www.cree.com](http://www.cree.com).

### REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notices of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Cree representative to insure you get the most up-to-date REACH Declaration. Historical REACH banned substance information (substances restricted or banned in the EU prior to 2010) is also available upon request.

### UL Recognized Component

Level 4 enclosure consideration. The LED package or a portion thereof has been investigated as a fire and electrical enclosure per ANSI/UL 8750.

### Vision Advisory Claim


WARNING: Do not look at exposed lamp in operation. Eye injury can result. See LED Eye Safety at [www.cree.com/xlamp\\_app\\_notes/led\\_eye\\_safety](http://www.cree.com/xlamp_app_notes/led_eye_safety).

### Intellectual Property

For remote phosphor applications, a separate license to certain Cree patents is required.

### MECHANICAL DIMENSIONS ( $T_A = 25\text{ }^{\circ}\text{C}$ )




All measurements are  $\pm .13\text{ mm}$  unless otherwise indicated.



## TAPE AND REEL

All Cree carrier tapes conform to EIA-481D, Automated Component Handling Systems Standard.


All dimensions in mm.






### PACKAGING

#### Unpackaged Reel



Label with Cree Bin Code, Qty, Reel ID


#### Packaged Reel



Label with Cree Order Code, Qty, Reel ID, PO #

Label with Cree Bin Code, Qty, Reel ID

#### Boxed Reel



Label with Cree Order Code, Qty, Reel ID, PO #

Label with Cree Bin Code, Qty, Reel ID

Patent Label (on bottom of box)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)