


# Transmissive Optical Sensor with Phototransistor Output



## FEATURES

- Package type: leaded
- Detector type: phototransistor
- Dimensions (L x W x H in mm): 11.9 x 6.3 x 10.8
- Gap (in mm): 3.1
- Typical output current under test:  $I_C = 4$  mA (TCST1103)
- Typical output current under test:  $I_C = 2$  mA (TCST1202)
- Typical output current under test:  $I_C = 0.5$  mA (TCST1300)
- Daylight blocking filter
- Emitter wavelength: 950 nm
- Lead (Pb)-free soldering released
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC


**RoHS**  
COMPLIANT

## DESCRIPTION

The TCST1103, TCST1202, and TCST1300 are transmissive sensors that include an infrared emitter and phototransistor, located face-to-face on the optical axes in a leaded package which blocks visible light. These part numbers include options for aperture width.

## APPLICATIONS

- Optical switch
- Photo interrupter
- Counter
- Encoder

## PRODUCT SUMMARY

| PART NUMBER | GAP WIDTH (mm) | APERTURE WIDTH (mm) | TYPICAL OUTPUT CURRENT UNDER TEST <sup>(1)</sup> (mA) | DAYLIGHT BLOCKING FILTER INTEGRATED |
|-------------|----------------|---------------------|-------------------------------------------------------|-------------------------------------|
| TCST1103    | 3.1            | 1                   | 4                                                     | Yes                                 |
| TCST1202    | 3.1            | 0.5                 | 2                                                     | Yes                                 |
| TCST1300    | 3.1            | 0.25                | 0.5                                                   | Yes                                 |

### Note

- Conditions like in table basic characteristics/coupler

## ORDERING INFORMATION

| ORDERING CODE | PACKAGING | VOLUME <sup>(1)</sup>      | REMARKS                 |
|---------------|-----------|----------------------------|-------------------------|
| TCST1103      | Tube      | MOQ: 1020 pcs, 85 pcs/tube | Without mounting flange |
| TCST1202      | Tube      | MOQ: 1020 pcs, 85 pcs/tube | Without mounting flange |
| TCST1300      | Tube      | MOQ: 1020 pcs, 85 pcs/tube | Without mounting flange |

### Note

- MOQ: minimum order quantity

## ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25$ °C, unless otherwise specified)

| PARAMETER                 | TEST CONDITION                          | SYMBOL    | VALUE         | UNIT |
|---------------------------|-----------------------------------------|-----------|---------------|------|
| <b>COUPLER</b>            |                                         |           |               |      |
| Total power dissipation   | $T_{amb} \leq 25$ °C                    | $P_{tot}$ | 250           | mW   |
| Ambient temperature range |                                         | $T_{amb}$ | - 55 to + 85  | °C   |
| Storage temperature range |                                         | $T_{stg}$ | - 55 to + 100 | °C   |
| Soldering temperature     | Distance to package: 2 mm; $t \leq 5$ s | $T_{sd}$  | 260           | °C   |



| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                           |           |       |                    |
|-------------------------------------------------------------------------------------------------|-------------------------------------------|-----------|-------|--------------------|
| PARAMETER                                                                                       | TEST CONDITION                            | SYMBOL    | VALUE | UNIT               |
| <b>INPUT (EMITTER)</b>                                                                          |                                           |           |       |                    |
| Reverse voltage                                                                                 |                                           | $V_R$     | 6     | V                  |
| Forward current                                                                                 |                                           | $I_F$     | 60    | mA                 |
| Forward surge current                                                                           | $t_p \leq 10\text{ }\mu\text{s}$          | $I_{FSM}$ | 3     | A                  |
| Power dissipation                                                                               | $T_{amb} \leq 25\text{ }^{\circ}\text{C}$ | $P_V$     | 100   | mW                 |
| Junction temperature                                                                            |                                           | $T_j$     | 100   | $^{\circ}\text{C}$ |
| <b>OUTPUT (DETECTOR)</b>                                                                        |                                           |           |       |                    |
| Collector emitter voltage                                                                       |                                           | $V_{CEO}$ | 70    | V                  |
| Emitter collector voltage                                                                       |                                           | $V_{ECO}$ | 7     | V                  |
| Collector peak current                                                                          | $t_p/T = 0.5$ , $t_p \leq 10\text{ ms}$   | $I_{CM}$  | 200   | mA                 |
| Power dissipation                                                                               | $T_{amb} \leq 25\text{ }^{\circ}\text{C}$ | $P_V$     | 150   | mW                 |
| Junction temperature                                                                            |                                           | $T_j$     | 100   | $^{\circ}\text{C}$ |


**ABSOLUTE MAXIMUM RATINGS**

Fig. 1 - Power Dissipation Limit vs. Ambient Temperature

| BASIC CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                              |          |             |      |      |      |      |
|----------------------------------------------------------------------------------------------|----------------------------------------------|----------|-------------|------|------|------|------|
| PARAMETER                                                                                    | TEST CONDITION                               | PART     | SYMBOL      | MIN. | TYP. | MAX. | UNIT |
| <b>COUPLER</b>                                                                               |                                              |          |             |      |      |      |      |
| Current transfer ratio                                                                       | $V_{CE} = 5\text{ V}$ , $I_F = 20\text{ mA}$ | TCST1103 | CTR         | 10   | 20   |      | %    |
|                                                                                              |                                              | TCST1202 | CTR         | 5    | 10   |      | %    |
|                                                                                              |                                              | TCST1300 | CTR         | 1.25 | 2.5  |      | %    |
| Collector current                                                                            | $V_{CE} = 5\text{ V}$ , $I_F = 20\text{ mA}$ | TCST1103 | $I_C$       | 2    | 4    |      | mA   |
|                                                                                              |                                              | TCST1202 | $I_C$       | 1    | 2    |      | mA   |
|                                                                                              |                                              | TCST1300 | $I_C$       | 0.25 | 0.5  |      | mA   |
| Collector emitter saturation voltage                                                         | $I_F = 20\text{ mA}$ , $I_C = 1\text{ mA}$   | TCST1103 | $V_{CEsat}$ |      |      | 0.4  | V    |
|                                                                                              | $I_F = 20\text{ mA}$ , $I_C = 0.5\text{ mA}$ | TCST1202 | $V_{CEsat}$ |      |      | 0.4  | V    |
|                                                                                              | $I_F = 20\text{ mA}$ , $I_C = 0.1\text{ mA}$ | TCST1300 | $V_{CEsat}$ |      |      | 0.4  | V    |
| Resolution, path of the shutter crossing the radiant sensitive zone                          | $I_{Crel} = 10\text{ \% to }90\text{ \%}$    | TCST1103 | s           |      | 0.6  |      | mm   |
|                                                                                              |                                              | TCST1202 | s           |      | 0.4  |      | mm   |
|                                                                                              |                                              | TCST1300 | s           |      | 0.2  |      | mm   |

| <b>BASIC CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                                        |      |           |      |      |      |               |
|-----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|------|-----------|------|------|------|---------------|
| PARAMETER                                                                                           | TEST CONDITION                                                                         | PART | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
| <b>INPUT (EMITTER)</b>                                                                              |                                                                                        |      |           |      |      |      |               |
| Forward voltage                                                                                     | $I_F = 60\text{ mA}$                                                                   |      | $V_F$     |      | 1.25 | 1.6  | V             |
| Junction capacitance                                                                                | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$                                                |      | $C_j$     |      | 50   |      | pF            |
| <b>OUTPUT (DETECTOR)</b>                                                                            |                                                                                        |      |           |      |      |      |               |
| Collector emitter voltage                                                                           | $I_C = 1\text{ mA}$                                                                    |      | $V_{CEO}$ | 70   |      |      | V             |
| Emitter collector voltage                                                                           | $I_E = 10\text{ }\mu\text{A}$                                                          |      | $V_{ECO}$ | 7    |      |      | V             |
| Collector dark current                                                                              | $V_{CE} = 25\text{ V}$ , $I_F = 0\text{ A}$ , $E = 0\text{ lx}$                        |      | $I_{CEO}$ |      |      | 100  | nA            |
| <b>SWITCHING CHARACTERISTICS</b>                                                                    |                                                                                        |      |           |      |      |      |               |
| Turn-on time                                                                                        | $I_C = 2\text{ mA}$ , $V_S = 5\text{ V}$ ,<br>$R_L = 100\text{ }\Omega$ (see figure 2) |      | $t_{on}$  |      | 10   |      | $\mu\text{s}$ |
| Turn-off time                                                                                       | $I_C = 2\text{ mA}$ , $V_S = 5\text{ V}$ ,<br>$R_L = 100\text{ }\Omega$ (see figure 2) |      | $t_{off}$ |      | 8    |      | $\mu\text{s}$ |




Fig. 2 - Test Circuit for  $t_{on}$  and  $t_{off}$ 


Fig. 3 - Switching Times


**BASIC CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 4 - Forward Current vs. Forward Voltage




Fig. 5 - Relative Current Transfer Ratio vs. Ambient Temperature




Fig. 6 - Collector Dark Current vs. Ambient Temperature




Fig. 9 - Current Transfer Ratio vs. Forward Current




Fig. 7 - Collector Current vs. Forward Current




Fig. 10 - Turn-off/Turn-on Time vs. Collector Current




Fig. 8 - Collector Current vs. Collector Emitter Voltage




Fig. 11 - Relative Collector Current vs. Displacement




Fig. 12 - Relative Collector Current vs. Displacement







Fig. 13 - Relative Collector Current vs. Displacement

**PACKAGE DIMENSIONS** in millimeters


Drawing-No.: 6.550-5039.01-4


Issue: 2; 10.11.98

96 12094

weight: ca. 0.80g



**TUBE DIMENSIONS** in millimeters



With rubber stopper  
Tolerance:  $\pm 0.5\text{mm}$   
Length:  $575 \pm 1\text{mm}$

Drawing-No.: 9.700-5100.01-4

Issue: 1; 25.02.00

20252

## Packaging and Ordering Information


| PART NUMBER   | MOQ <sup>(1)</sup> | PCS PER TUBE | TUBE SPEC. (FIGURE) | CONSTITUENTS (FORMS) |
|---------------|--------------------|--------------|---------------------|----------------------|
| CNY70         | 4000               | 80           | 1                   | 28                   |
| TCPT1300X01   | 2000               | Reel         | <sup>(2)</sup>      | 29                   |
| TCRT1000      | 1000               | Bulk         | -                   | 26                   |
| TCRT1010      | 1000               | Bulk         | -                   | 26                   |
| TCRT5000      | 4500               | 50           | 2                   | 27                   |
| TCRT5000L     | 2400               | 48           | 3                   | 27                   |
| TCST1030      | 5200               | 65           | 5                   | 24                   |
| TCST1030L     | 2600               | 65           | 6                   | 24                   |
| TCST1103      | 1020               | 85           | 4                   | 24                   |
| TCST1202      | 1020               | 85           | 4                   | 24                   |
| TCST1230      | 4800               | 60           | 7                   | 24                   |
| TCST1300      | 1020               | 85           | 4                   | 24                   |
| TCST2103      | 1020               | 85           | 4                   | 24                   |
| TCST2202      | 1020               | 85           | 4                   | 24                   |
| TCST2300      | 1020               | 85           | 4                   | 24                   |
| TCST5250      | 4860               | 30           | 8                   | 24                   |
| TCUT1300X01   | 2000               | Reel         | <sup>(2)</sup>      | 29                   |
| TCZT8020-PAER | 2500               | Bulk         | -                   | 22                   |

### Notes

<sup>(1)</sup> MOQ: minimum order quantity

<sup>(2)</sup> Please refer to datasheets

### TUBE SPECIFICATION FIGURES



With rubber stopper

Tolerance:  $\pm 0.5\text{mm}$

Length:  $575 \pm 1\text{mm}$

Drawing-No.: 9.700-5097.01-4

Issue: 1; 25.02.00

15198

Fig. 1




Drawing-No.: 9.700-5139.01-4  
Issue: 1; 10.05.00

Drawing refers to following types: TCRT 5000

15210


Fig. 2



Drawing-No.: 9.700-5178.01-4  
Issue: 1; 25.02.00

15201

Fig. 3




With rubber stopper  
Tolerance:  $\pm 0.5\text{mm}$   
Length:  $575 \pm 1\text{mm}$

Drawing-No.: 9.700-5100.01-4  
Issue: 1; 25.02.00

15199

Fig. 4



With stopper pins  
Tolerance:  $\pm 0.5\text{mm}$   
Length:  $575 \pm 1\text{mm}$

Drawing-No.: 9.700-5140.01-4  
Issue: 1; 25.02.00

15202

Fig. 5



Drawing-No.: 9.700-5205.01-4  
Issue: 1; 25.02.00

15196

Fig. 6



Drawing-No.: 9.700-5245.01-4  
Issue: 1; 25.02.00

15195

Fig. 7



Fig. 8



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)