



**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

**BASIC CHARACTERISTICS**

| Parameter  | Condition              |                  | Min.   | Typ.   | Max.             |
|--|------------------------|------------------|--|--------|------------------|
| Input Voltage Range <sup>(3)</sup>   | nom. Vin = 230VAC      |                  | 90VAC<br>100VDC  | 230VAC | 264VAC<br>375VDC |
| Input Current  | 115VAC<br>230VAC       |                  |  |        | 400mA<br>270mA   |
| Inrush Current   | 2ms max.               | 115VAC<br>230VAC |  |        | 30A<br>50A       |
| No load Power Consumption  | 115VAC/230VAC          |                  |  |        | 470mW            |
| Input Frequency Range  | AC Input               |                  | 47Hz   |        | 440Hz            |
| Minimum Load   | Single, Dual<br>Triple |                  | 0%   | 10%    |                  |
| Hold-up Time   | 115VAC/230VAC          |                  | 13ms   |        |                  |
| Internal Operating Frequency   |                        |                  |  | 100kHz |                  |
| Output Ripple and Noise <sup>(4)</sup>   | 20MHz BW               | Noise<br>Ripple  | <0.5% Vout + 50mVp-p max.<br><0.2% Vout + 40mVp-p max. |        |                  |
| <p><b>Notes:</b></p> <p>Note3: The products were submitted for safety files at AC-Input operation</p> <p>Note4: Measurements are made with a 0.1µF and 47µF MLCC across output (low ESR)</p> |                        |                  |  |        |                  |

**REGULATIONS**

| Parameter  | Condition             |                          | Value   |
|--|-----------------------|--------------------------|---|
| Output Accuracy  |                       |                          | ±2.0% max.  |
| Line Regulation  | low line to high line | Single, Dual<br>Triple   | ±0.5% typ.<br>±1.0% typ. (+5Vout) / ±5.0 typ. (±Vout)           |
| Load Regulation <sup>(5)</sup>   | 10% to 100% load      | Single<br>Dual<br>Triple | 1.0% typ.<br>3.0% typ.<br>2.0% typ. (+5Vout) / 5.0 typ. (±Vout) |
| <p><b>Notes:</b></p> <p>Note5: Operation below 10% load will not harm the converter, but specifications may not be met</p> |                       |                          |   |

**PROTECTIONS**

| Parameter                      | Type       |                     | Value                      |
|--------------------------------|------------|---------------------|----------------------------|
| Short Circuit Protection (SCP) |            |                     | Hiccup mode, auto recovery |
| Over Voltage Protection (OVP)  |            |                     | zener diode clamp          |
| Over Current Protection (OCP)  |            |                     | 105% typ.                  |
| Isolation Voltage              | I/P to O/P | tested for 1 minute | 3kVAC                      |
| Leakage Current                |            |                     | 0.25mA max.                |

**Notes:**

- Note6: Refer to local safety regulations if input over-current protection is also required. Recommended fuse: slow blow type
- Note7: An external MOV is recommended. The varistor should comply with IEC-61051-2. e.g. 14S471K series



**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

| ENVIRONMENTAL               |                                  |                                      |                                  |
|-----------------------------|----------------------------------|--------------------------------------|----------------------------------|
| Parameter                   | Condition                        |                                      | Value                            |
| Operating Temperature Range | @ natural convection 0.1 m/s     | full load<br>refer to derating graph | -25°C to +50°C<br>-25°C to +70°C |
| Temperature Coefficient     |                                  |                                      | ±0.02%/K typ.                    |
| Operating Humidity          | non-condensing                   |                                      | 95% RH max.                      |
| MTBF                        | according to MIL-HDBK-217F, G.B. | +25°C                                | >400 x 10 <sup>3</sup> hours     |

**Derating Graph**

(@ Chamber and natural convection 0.1 m/s)



**SAFETY AND CERTIFICATIONS**

| Certificate Type (Safety)   | Report / File Number | Standard  |
|---|----------------------|---|
| Information Technology Equipment, General Requirements for Safety | E196683              | UL60950-1, 2nd Edition, 2007<br>CAN/CSA-C22.2 No. 60950-1-07, 2nd Edition, 2007 |
| Information Technology Equipment, General Requirements for Safety |                      | EN60950-1:2006 + A2:2013  |
| EAC Safety of Low Voltage Equipment                               | RU-AT.49.09571       | TP TC 004/2011  |
| RoHS2+  |                      | RoHS-2011/65/EU + AM-2015/863   |

| EMC Compliance  | Condition | Standard / Criterion   |
|---|-----------|------------------------|
| Electromagnetic Compatibility of Multimedia Equipment – Emission Requirements                   |           | EN55032:2015, Class B  |
| Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurement |           | EN55024:2010 + A1:2015 |
| Limits for Harmonic Current Emissions   |           | EN61000-3-2: 2014      |
| Limitation of Voltage Fluctuations/Flicker in Low-Voltage Systems                               |           | EN61000-3-3: 2013      |

**DIMENSION AND PHYSICAL CHARACTERISTICS**

| Parameter         | Type              | Value                           |
|-------------------|-------------------|---------------------------------|
| Material          | case              | epoxy with fibreglass (UL94V-0) |
| Dimension (LxWxH) | standard          | 70.0 x 48.0 x 22.0mm            |
|                   | with suffix "-ST" | 111.9 x 64.6 x 27.5mm           |
| Weight            | standard          | 122g typ.                       |
|                   | with suffix "-ST" | 197g typ.                       |

continued on next page

Specifications (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

Dimension Drawing (mm)



Pin Connections

| Pin # | Single     | Dual       | Triple     |
|-------|------------|------------|------------|
| 1     | FG         | FG         | FG         |
| 2     | VAC in (N) | VAC in (N) | VAC in (N) |
| 3     | VAC in (L) | VAC in (L) | VAC in (L) |
| 4     | no Pin     | no Pin     | -Vout      |
| 5     | -Vout      | -Vout      | Com        |
| 6     | no Pin     | Com        | +Vout      |
| 7     | +Vout      | +Vout      | +5V Rtn    |
| 8     | no Pin     | no Pin     | +5Vout     |

Tolerance: xx.x=  $\pm 0.5$ mm  
xx.xx=  $\pm 0.25$ mm

Screw Terminal Module "ST" version



Screw terminal information

| # | Single     | Dual       | Triple     |
|---|------------|------------|------------|
| 1 | FG         | FG         | FG         |
| 2 | VAC in (N) | VAC in (N) | VAC in (N) |
| 3 | VAC in (L) | VAC in (L) | VAC in (L) |
| 4 | NC         | NC         | -Vout      |
| 5 | -Vout      | -Vout      | Com        |
| 6 | NC         | Com        | +Vout      |
| 7 | +Vout      | +Vout      | +5V Rtn    |
| 8 | NC         | NC         | +5Vout     |

7.5mm Pitch  
suitable wire: 24-12AWG (0.5-2.5mm<sup>2</sup>)  
wire stripping length: 7mm typ.  
recommended tightening torque: 0.5Nm  
NC = No Connection  
FC = Fixing Centers  
Tolerance: xx.x=  $\pm 0.5$ mm  
xx.xx=  $\pm 0.25$ mm

**Specifications** (measured @ Ta= 25°C, nom. Vin, full load and after warm-up unless otherwise stated)

| PACKAGING INFORMATION       |                   |                   |                       |
|-----------------------------|-------------------|-------------------|-----------------------|
| Parameter                   | Type              |                   | Value                 |
| Packaging Dimension (LxWxH) | cardboard box     | standard          | 260.0 x 70.0 x 42.0mm |
|                             |                   | with suffix "-ST" | 119.0 x 64.0 x 54.0mm |
| Packaging Quantity          | standard          |                   | 3pcs                  |
|                             | with suffix "-ST" |                   | 1pcs                  |
| Storage Temperature Range   |                   |                   | -40°C to +85°C        |
| Storage Humidity            | non-condensing    |                   | 95% RH                |

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)