THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	NEW DRAWING	08FEB2016	NK	RH



POSITION 1



POSITION 2







EXPLODED VIEW

ASSEMBLED VIEW



PANEL CUTOUT
MAX.PANEL THICKNESS: 10.00[.394]



SPECIFICATIONS

CONTACT RATING: SILVER: 3A @ 250 VAC RESISTIVE
GOLD: 0.4VA @ 20VDC OR PEAK AC
INSULATION RESISTANCE: 1,000MΩ MIN AT 500VDC
DIELECTRIC STRENGTH: 2,000V RMS @ SEA LEVEL
CONTACT RESISTANCE: 50 mΩ MAX @ 1A 12VDC (INITIAL VALUE)
ELECTRICAL LIFECYCLES: 50,000 MAKE AND BREAK CYCLES AT FULL LOAD

ACTUATION FORCE: SP: 2.5±1 NEWTON, DP: 3.5±1 NEWTON
ACTUATION TRAVEL: 3.2mm
SEALED PER IP67, IK10 (STAINLESS)
OPERATING TEMPERATURE: −20°C TO +55°C
MECHANICAL LIFECYCLES: MOMENTARY: 1,000,000 CYCLES
LOCKING: 500,000 CYCLES
HARDWARE TORQUE: 5−14 N−m

MATERIALS

BUSHING: STAINLESS STEEL
BASE: PBT (UL 94−V0), PC (UL 94−V2)
ACTUATOR: STAINLESS STEEL, PC
SEALING: O−RING (SILICONE)
TERMINAL/CONTACT: COPPER BASE, SILVER/GOLD PLATED
HEX NUT: BRASS BASE, NICKEL PLATED

1 ALL MATERIAL AND FINISHES SHALL COMPLY WITH EU DIRECTIVE 2002/95/EC OF 27JAN2003 (ROHS)

2213766

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -

MATERIAL -
FINISH -

DWN NAGALAKSHMI K 08FEB2016
CHK HILL RYAN 08FEB2016
APVD HILL RYAN 08FEB2016
PRODUCT SPEC —
APPLICATION SPEC —
WEIGHT —

TE Connectivity

NAME
ANTI−VANDAL SWITCH 19mm
POWER LOGO LED

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-2213766	—

CUSTOMER DRAWING | SCALE 6:1 | SHEET 1 OF 3 | REV A

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	—	—









POSITION 1



POSITION 2





THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN NAGALAKSHMI K 08FEB2016	TE Connectivity
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± – 1 PLC ± – 2 PLC ± – 3 PLC ± – 4 PLC ± – ANGLES ± –	CHK HILL RYAN 08FEB2016	NAME ANTI–VANDAL SWITCH 19mm POWER LOGO LED
		APVD HILL RYAN 08FEB2016	
		PRODUCT SPEC —	
		APPLICATION SPEC —	SIZE A2 / CAGE CODE 00779 / DRAWING NO C-2213766 / RESTRICTED TO —
MATERIAL –	FINISH –	WEIGHT –	CUSTOMER DRAWING / SCALE NTS / SHEET 2 OF 3 / REV A

2213766

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION -,- .
© COPYRIGHT - By - ALL RIGHTS RESERVED.

POLE/THROW	CONTACT	LED COLOUR	LED VOLTAGE	TE DESCRIPTIVE PN	TE PART NUMBER
DOUBLE POLE–MOMENTARY	SILVER	WHITE	24V	AV1920P124Q04	4–2213766–3
	GOLD	WHITE	12V	AV1920P112R04	4–2213766–2
	SILVER	WHITE	12V	AV1920P112Q04	4–2213766–1
SINGLE POLE–LOCKING	GOLD	BLUE	24V	AV1911P724R04	4–2213766–0
	SILVER	BLUE	24V	AV1911P724Q04	3–2213766–9
	GOLD	BLUE	12V	AV1911P712R04	3–2213766–8
	SILVER	BLUE	12V	AV1911P712Q04	3–2213766–7
	GOLD	GREEN	24V	AV1911P624R04	3–2213766–6
	SILVER	GREEN	24V	AV1911P624Q04	3–2213766–5
	GOLD	GREEN	12V	AV1911P612R04	3–2213766–4
	SILVER	GREEN	12V	AV1911P612Q04	3–2213766–3
	GOLD	YELLOW	24V	AV1911P524R04	3–2213766–2
	SILVER	YELLOW	24V	AV1911P524Q04	3–2213766–1
	GOLD	YELLOW	12V	AV1911P512R04	3–2213766–0
	SILVER	YELLOW	12V	AV1911P512Q04	2–2213766–9
	GOLD	RED	24V	AV1911P324R04	2–2213766–8
	SILVER	RED	24V	AV1911P324Q04	2–2213766–7
	GOLD	RED	12V	AV1911P312R04	2–2213766–6
	SILVER	RED	12V	AV1911P312Q04	2–2213766–5
	GOLD	WHITE	24V	AV1911P124R04	2–2213766–4
	SILVER	WHITE	24V	AV1911P124Q04	2–2213766–3
	GOLD	WHITE	12V	AV1911P112R04	2–2213766–2
	SILVER	WHITE	12V	AV1911P112Q04	2–2213766–1
SINGLE POLE–MOMENTARY	GOLD	BLUE	24V	AV1910P724R04	2–2213766–0
	SILVER	BLUE	24V	AV1910P724Q04	1–2213766–9
	GOLD	BLUE	12V	AV1910P712R04	1–2213766–8
	SILVER	BLUE	12V	AV1910P712Q04	1–2213766–7
	GOLD	GREEN	24V	AV1910P624R04	1–2213766–6
	SILVER	GREEN	24V	AV1910P624Q04	1–2213766–5
	GOLD	GREEN	12V	AV1910P612R04	1–2213766–4
	SILVER	GREEN	12V	AV1910P612Q04	1–2213766–3
	GOLD	YELLOW	24V	AV1910P524R04	1–2213766–2
	SILVER	YELLOW	24V	AV1910P524Q04	1–2213766–1
	GOLD	YELLOW	12V	AV1910P512R04	1–2213766–0
	SILVER	YELLOW	12V	AV1910P512Q04	2213766–9
	GOLD	RED	24V	AV1910P324R04	2213766–8
	SILVER	RED	24V	AV1910P324Q04	2213766–7
	GOLD	RED	12V	AV1910P312R04	2213766–6
	SILVER	RED	12V	AV1910P312Q04	2213766–5
	GOLD	WHITE	24V	AV1910P124R04	2213766–4
	SILVER	WHITE	24V	AV1910P124Q04	2213766–3
	GOLD	WHITE	12V	AV1910P112R04	2213766–2
	SILVER	WHITE	12V	AV1910P112Q04	2213766–1
DOUBLE POLE–LOCKING	GOLD	BLUE	24V	AV1921P724R04	8–2213766–0
	SILVER	BLUE	24V	AV1921P724Q04	7–2213766–9
	GOLD	BLUE	12V	AV1921P712R04	7–2213766–8
	SILVER	BLUE	12V	AV1921P712Q04	7–2213766–7
	GOLD	GREEN	24V	AV1921P624R04	7–2213766–6
	SILVER	GREEN	24V	AV1921P624Q04	7–2213766–5
	GOLD	GREEN	12V	AV1921P612R04	7–2213766–4
	SILVER	GREEN	12V	AV1921P612Q04	7–2213766–3
	GOLD	YELLOW	24V	AV1921P524R04	7–2213766–2
	SILVER	YELLOW	24V	AV1921P524Q04	7–2213766–1
	GOLD	YELLOW	12V	AV1921P512R04	7–2213766–0
	SILVER	YELLOW	12V	AV1921P512Q04	6–2213766–9
	GOLD	RED	24V	AV1921P324R04	6–2213766–8
	SILVER	RED	24V	AV1921P324Q04	6–2213766–7
	GOLD	RED	12V	AV1921P312R04	6–2213766–6
	SILVER	RED	12V	AV1921P312Q04	6–2213766–5
	GOLD	WHITE	24V	AV1921P124R04	6–2213766–4
	SILVER	WHITE	24V	AV1921P124Q04	6–2213766–3
	GOLD	WHITE	12V	AV1921P112R04	6–2213766–2
	SILVER	WHITE	12V	AV1921P112Q04	6–2213766–1
DOUBLE POLE–MOMENTARY	GOLD	BLUE	24V	AV1920P724R04	6–2213766–0
	SILVER	BLUE	24V	AV1920P724Q04	5–2213766–9
	GOLD	BLUE	12V	AV1920P712R04	5–2213766–8
	SILVER	BLUE	12V	AV1920P712Q04	5–2213766–7
	GOLD	GREEN	24V	AV1920P624R04	5–2213766–6
	SILVER	GREEN	24V	AV1920P624Q04	5–2213766–5
	GOLD	GREEN	12V	AV1920P612R04	5–2213766–4
	SILVER	GREEN	12V	AV1920P612Q04	5–2213766–3
	GOLD	YELLOW	24V	AV1920P524R04	5–2213766–2
	SILVER	YELLOW	24V	AV1920P524Q04	5–2213766–1
	GOLD	YELLOW	12V	AV1920P512R04	5–2213766–0
	SILVER	YELLOW	12V	AV1920P512Q04	4–2213766–9
	GOLD	RED	24V	AV1920P324R04	4–2213766–8
	SILVER	RED	24V	AV1920P324Q04	4–2213766–7
	GOLD	RED	12V	AV1920P312R04	4–2213766–6
	SILVER	RED	12V	AV1920P312Q04	4–2213766–5
	GOLD	WHITE	24V	AV1920P124R04	4–2213766–4

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	–	SEE SHEET 1	–	–	–

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL –

FINISH –

DWN NAGALAKSHMI K 08FEB2016
CHK HILL RYAN 08FEB2016
APVD HILL RYAN 08FEB2016
PRODUCT SPEC –
APPLICATION SPEC –
WEIGHT –

TE Connectivity

NAME
ANTI–VANDAL SWITCH 19mm
POWER LOGO LED

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C–2213766	–

CUSTOMER DRAWING | SCALE NTS | SHEET 3 OF 3 | REV A

2213766

1471–9 (1/15)

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru