

## 734AS3P Coax - Bundled 734 Plenum Telecommunication Coax



For more Information  
please call

1-800-Belden1



### General Description:

3-20 AWG solid bare copper conductors, foam FEP insulation, Beldfoil® shield (100% coverage) plus a tinned copper braid shield (85% coverage), Flamarrest® jacket. Banana Peel®.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
3	20	Solid	BC - Bare Copper	0.034

Total Number of Conductors: 3

#### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (in.)	Dia. (in.)
Teflon	FFEP - Foam Fluorinated Ethylene Propylene	0.058	0.148

#### Fillers

Fillers: Extruded PVC Spline

#### Inner Shield

Inner Shield Material:

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000
2	Braid	Braid	TC - Tinned Copper	85.000

#### Inner Jacket

Inner Jacket Material:

Inner Jacket Trade Name	Inner Jacket Material	Nom Wall (in.)	Nom. Dia. (in.)
Flamarrest(R)	LS PVC - Low Smoke Polyvinyl Chloride	0.015	0.213

#### Overall Cable

Overall Nominal Diameter: 0.475 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

Bulk Cable Weight: 106 lbs/1000 ft.

Min. Bend Radius (Each Coax): 2.100 in.

Min. Bend Radius (Overall): 4.750 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 11/06/2008

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Other Specification: Telcordia Specification GR-139-Core

## 734AS3P Coax - Bundled 734 Plenum Telecommunication Coax

### Flame Test

UL Flame Test:	NFPA 262 Plenum Flame Test (UL910)(FT6)
C(UL) Flame Test:	FT6

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Impedance (Ohm)
75.000

#### Nom. Inductance:

Inductance (µH/ft)
0.095

#### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.300

#### Nominal Velocity of Propagation:

VP (%)
80.000

#### Nominal Delay:

Delay (ns/ft)
1.270

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
10.100

#### Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
3.000

#### Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.024	0.290
4.224	0.540
17.184	1.110
22.368	1.270
25.920	1.370
69.632	2.290
77.760	2.430
137.088	3.310

#### Max. Operating Voltage - UL:

Voltage
300

#### Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
15.000	95.000	30.000

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
734AS3P 0081000	1,000 FT	120.000 LB	GRAY		BONDED FILLER COMPOSITE
734AS3P 008500	500 FT	53.000 LB	GRAY		BONDED FILLER COMPOSITE

Revision Number: 1    Revision Date: 09-04-2013

© 2017 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification.

## 734AS3P Coax - Bundled 734 Plenum Telecommunication Coax

Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.  
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)