



**POWER MATE
TECHNOLOGY CO.,LTD.**

FKC05-SERIES



UL E193009
TUV R3-50007936
CB JPTUV-003641
CE MARK


- 5 WATTS OUTPUT POWER
- 2:1 AND 4:1 WIDE INPUT VOLTAGE RANGE
- INTERNATIONAL SAFETY STANDARD APPROVAL
- FIVE-SIDED SHIELD
- HIGH EFFICIENCY UP TO 84%
- STANDARD 24 PIN DIP PACKAGE & SMD TYPE PACKAGE
- FIXED SWITCHING FREQUENCY

The FKC05 series offer 5 watts of output power from a package in an IC compatible 24pin DIP configuration without derating to 71°C ambient temperature and pin to pin compatible with FKC03 series. FKC05 series have 2:1 wide input voltage of 9-18, 18-36 and 36-75VDC. FKC05-W series have 4:1 ultra wide input voltage of 9-36 and 18-75VDC. The FKC05 features 1600VDC of isolation, short-circuit protection and as well as five sided shielding. All models are particularly suited to telecommunications, industrial, mobile telecom and test equipment applications.

TECHNICAL SPECIFICATION

All specifications are typical at nominal input, full load and 25°C otherwise noted

OUTPUT SPECIFICATIONS			
Output power			5 Watts max
Voltage accuracy	Full load and nominal Vin		± 2%
Minimum load (Note 1)			10% of FL
Line regulation	LL to HL at Full Load		± 0.2%
Load regulation	25% to 100% FL	Single Dual	± 0.5% ± 1%
Cross regulation(Dual)	Asymmetrical load 25% / 100% FL		± 5%
Ripple and noise	20MHz bandwidth		50mVp-p
Temperature coefficient			± 0.02% / °C, max
Transient response recovery time	25% load step change		200uS
Over load protection	% of FL at nominal input		170% typ
Short circuit protection			Continuous, automatics recovery
INPUT SPECIFICATIONS			
Input voltage range	FKC05	12V nominal input	9 – 18VDC
		24V nominal input	18 – 36VDC
		48V nominal input	36 – 75VDC
	FKC05-W	24V nominal input	9 – 36VDC
		48V nominal input	18 – 75VDC
Input filter			Pi type
Input surge voltage 100mS max		12V input	36VDC
		24V input	50VDC
		48V input	100VDC
Input reflected ripple (Note 2)		Nominal Vin and full load	20mAp-p
Start up time		Nominal Vin and constant resistor load	600mS typ



GENERAL SPECIFICATIONS			
Efficiency			See table
Isolation voltage	Input to Output		1600VDC, min
	Input (Output) to Case	DIP SMD	1600VDC, min 1000VDC, min
Isolation resistance			10 ⁹ ohms, min
Isolation capacitance			300pF, max
Switching frequency			300KHz, typ
Approvals and standard			IEC60950, UL1950, EN60950
Case material			Nickel-coated copper
Base material			Non-conductive black plastic
Potting material			Epoxy (UL94-V0)
Dimensions			1.25 X 0.80 X 0.40 Inch (31.8 X 20.3 X 10.2 mm)
Weight	DIP		16g (0.55oz)
	SMD		18g (0.62oz)
MTBF (Note 3)			3.165 x 10 ⁶ hrs
ENVIRONMENTAL SPECIFICATIONS			
Operating temperature range	Standard		-25°C~+85°C (with derating)
	M1 (Note 4)		-40°C~+85°C (non-derating)
	M2 (W series)		-40°C~+85°C (with derating)
Maximum case temperature			+100°C
Storage temperature range			-55°C ~ +105°C
Thermal impedance	Nature convection		20°C/watt
Thermal shock			MIL-STD-810D
Vibration			10~55Hz, 10G, 30minutues along X,Y and Z
Relative humidity			5% to 95% RH
EMC CHARACTERISTICS			
Conducted emissions	EN55022		Class A
Radiated emissions	EN55022		Class A
ESD	EN61000-4-2		Perf. Criteria2
Radiated immunity	EN61000-4-3		Perf. Criteria2
Fast transient	EN61000-4-4		Perf. Criteria2
Surge	EN61000-4-5		Perf. Criteria2
Conducted immunity	EN61000-4-6		Perf. Criteria2




Model Number	Input Range	Output Voltage	Output Current	Input Current ⁽⁵⁾	Eff ⁽⁶⁾ (%)	Capacitor ⁽⁷⁾ Load max
FKC05-12S33	9 – 18 VDC	3.3 VDC	1000mA	382mA	76	2200uF
FKC05-12S05	9 – 18 VDC	5 VDC	1000mA	563mA	78	1000uF
FKC05-12S12	9 – 18 VDC	12 VDC	470mA	603mA	82	220uF
FKC05-12S15	9 – 18 VDC	15 VDC	400mA	649mA	81	150uF
FKC05-12D05	9 – 18 VDC	± 5 VDC	± 500mA	563mA	78	± 680uF
FKC05-12D12	9 – 18 VDC	± 12 VDC	± 230mA	597mA	81	± 100uF
FKC05-12D15	9 – 18 VDC	± 15 VDC	± 190mA	594mA	84	± 68uF
FKC05-24S33 (W)	18 – 36 (9 – 36) VDC	3.3 VDC	1000mA	194mA (191mA)	75 (76)	2200uF
FKC05-24S05 (W)	18 – 36 (9 – 36) VDC	5 VDC	1000mA	285mA (278mA)	77 (79)	1000uF
FKC05-24S12 (W)	18 – 36 (9 – 36) VDC	12 VDC	470mA	305mA (309mA)	81 (80)	220uF
FKC05-24S15 (W)	18 – 36 (9 – 36) VDC	15 VDC	400mA	325mA (312mA)	81 (84)	150uF
FKC05-24D05 (W)	18 – 36 (9 – 36) VDC	± 5 VDC	± 500mA	274mA (282mA)	80 (78)	± 680uF
FKC05-24D12 (W)	18 – 36 (9 – 36) VDC	± 12 VDC	± 230mA	288mA (295mA)	84 (82)	± 100uF
FKC05-24D15 (W)	18 – 36 (9 – 36) VDC	± 15 VDC	± 190mA	308mA (297mA)	81 (84)	± 68uF
FKC05-48S33 (W)	36 – 75 (18 – 75) VDC	3.3 VDC	1000mA	98mA (100mA)	74 (73)	2200uF
FKC05-48S05 (W)	36 – 75 (18 – 75) VDC	5 VDC	1000mA	143mA (138mA)	77 (79)	1000uF
FKC05-48S12 (W)	36 – 75 (18 – 75) VDC	12 VDC	470mA	151mA (155mA)	82 (80)	220uF
FKC05-48S15 (W)	36 – 75 (18 – 75) VDC	15 VDC	400mA	162mA (160mA)	81 (82)	150uF
FKC05-48D05 (W)	36 – 75 (18 – 75) VDC	± 5 VDC	± 500mA	141mA (145mA)	78 (76)	± 680uF
FKC05-48D12 (W)	36 – 75 (18 – 75) VDC	± 12 VDC	± 230mA	147mA (151mA)	82 (80)	± 100uF
FKC05-48D15 (W)	36 – 75 (18 – 75) VDC	± 15 VDC	± 190mA	154mA (159mA)	81 (79)	± 68uF

Note

1. The FKC05 (W) series required a minimum 10% loading on the output to maintain specified regulation. Operation under no-load condition will not damage these devices, however they may not meet all listed specification.
2. Simulated source impedance of 12uH. 12uH inductor on series with + Vin.
3. BELLCORE TR-NWT-000332. Case I: 50% Stress, Temperature at 40°C. (Ground fixed and controlled environment)
4. M1 version is more efficient, therefore, it can be operated in a more extensive temperature range than standard and M2 version
5. Maximum value at nominal input voltage and full load of standard type.
6. Typical value at nominal input voltage and full load
7. Test by minimum Vin and constant resistor load.
8. There is no pin at PIN10 & PIN15 for FKC05-W series

Suffix-SMD



DIP PIN CONNECTION

PIN	SINGLE	DUAL	PIN	SINGLE	DUAL
2	- INPUT	- INPUT	23	+ INPUT	+ INPUT
3	- INPUT	- INPUT	22	+ INPUT	+ INPUT
9	NC	COMMON	16	- OUTPUT	COMMON
10	NC(Note 8)	NC(Note 8)	15	NC(Note 8)	NC(Note 8)
11	NC	- OUTPUT	14	+ OUTPUT	+ OUTPUT

SMD PIN CONNECTION

PIN	SINGLE	DUAL	PIN	SINGLE	DUAL
2	- INPUT	- INPUT	23	+ INPUT	+ INPUT
3	- INPUT	- INPUT	22	+ INPUT	+ INPUT
9	NC	COMMON	16	- OUTPUT	COMMON
10	NC	NC	15	NC	NC
11	NC	- OUTPUT	14	+ OUTPUT	+ OUTPUT
Others	NC	NC	Others	NC	NC

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru