

1		2		3		4		5		6																																																																																																																																																																																																																																			
STD OPTION WITH ACCESSORY OPTION						LAY OUT OF 50P CONNECTOR						<table border="1"><thead><tr><th rowspan="2">SHELL SIZE</th><th rowspan="2">P</th><th rowspan="2">S</th><th colspan="10">DIMENSIONS</th></tr><tr><th>A</th><th>B</th><th>C</th><th>D</th><th>E</th><th>F</th><th>G</th><th>H</th><th>J</th><th>K</th><th>L</th></tr></thead><tbody><tr><td rowspan="2">50</td><td>P</td><td>S</td><td>66.65</td><td>66.65</td><td>52.68</td><td>52.30</td><td>61.11</td><td>61.11</td><td>11.08</td><td>10.62</td><td>14.99</td><td>14.99</td><td>11.09</td><td>11.21</td><td>5.85</td><td>5.85</td><td>55.07</td><td>55.07</td><td>13.31</td><td>13.31</td><td>1.50</td><td>1.10</td><td>1.0</td><td>0.8</td></tr><tr><td>P</td><td>S</td><td>68.94</td><td>68.94</td><td>55.30</td><td>54.71</td><td>63.50</td><td>63.50</td><td>8.23</td><td>7.77</td><td>12.17</td><td>12.17</td><td>11.09</td><td>11.21</td><td>6.05</td><td>6.05</td><td>57.45</td><td>57.45</td><td>10.46</td><td>10.46</td><td>1.50</td><td>1.10</td><td>1.0</td><td>0.8</td></tr><tr><td rowspan="2">37</td><td>P</td><td>S</td><td>52.65</td><td>52.65</td><td>38.84</td><td>38.25</td><td>47.04</td><td>47.04</td><td>8.23</td><td>7.77</td><td>12.17</td><td>12.17</td><td>11.07</td><td>11.21</td><td>5.85</td><td>5.85</td><td>41.02</td><td>41.02</td><td>10.46</td><td>10.46</td><td>1.10</td><td>1.10</td><td>0.8</td><td>0.8</td></tr><tr><td>P</td><td>S</td><td>38.76</td><td>38.76</td><td>25.12</td><td>24.54</td><td>33.32</td><td>33.32</td><td>8.23</td><td>7.77</td><td>12.17</td><td>12.17</td><td>10.99</td><td>11.21</td><td>5.85</td><td>5.85</td><td>27.25</td><td>27.25</td><td>10.46</td><td>10.46</td><td>1.10</td><td>1.10</td><td>0.8</td><td>0.8</td></tr><tr><td rowspan="2">25</td><td>P</td><td>S</td><td>30.43</td><td>30.43</td><td>16.79</td><td>16.21</td><td>24.99</td><td>24.99</td><td>8.23</td><td>7.77</td><td>12.17</td><td>12.17</td><td>10.99</td><td>11.21</td><td>5.85</td><td>5.85</td><td>19.02</td><td>19.02</td><td>10.46</td><td>10.46</td><td>1.10</td><td>1.10</td><td>0.8</td><td>0.8</td></tr><tr><td>P</td><td>S</td><td>30.43</td><td>30.43</td><td>16.79</td><td>16.21</td><td>24.99</td><td>24.99</td><td>8.23</td><td>7.77</td><td>12.17</td><td>12.17</td><td>10.99</td><td>11.21</td><td>5.85</td><td>5.85</td><td>19.02</td><td>19.02</td><td>10.46</td><td>10.46</td><td>1.10</td><td>1.10</td><td>0.8</td><td>0.8</td></tr><tr><td rowspan="2">15</td><td>P</td><td>S</td><td>+0,76 A 0</td><td>+0,76 A 0</td><td>+0,25 B 0</td><td>+0,25 B 0</td><td>±0,12 C</td><td>±0,12 C</td><td>+0,25 D 0</td><td>+0,25 D 0</td><td>+0,76 E 0</td><td>+0,76 E 0</td><td>F MAX</td><td>F MAX</td><td>+0,15 G 0</td><td>+0,15 G 0</td><td>+0,51 H 0</td><td>+0,51 H 0</td><td>+0,51 J 0</td><td>+0,51 J 0</td><td>±0,2 K</td><td>±0,2 K</td><td>+0,22 L 0</td><td>+0,22 L 0</td></tr><tr><td>P</td><td>S</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>						SHELL SIZE	P	S	DIMENSIONS										A	B	C	D	E	F	G	H	J	K	L	50	P	S	66.65	66.65	52.68	52.30	61.11	61.11	11.08	10.62	14.99	14.99	11.09	11.21	5.85	5.85	55.07	55.07	13.31	13.31	1.50	1.10	1.0	0.8	P	S	68.94	68.94	55.30	54.71	63.50	63.50	8.23	7.77	12.17	12.17	11.09	11.21	6.05	6.05	57.45	57.45	10.46	10.46	1.50	1.10	1.0	0.8	37	P	S	52.65	52.65	38.84	38.25	47.04	47.04	8.23	7.77	12.17	12.17	11.07	11.21	5.85	5.85	41.02	41.02	10.46	10.46	1.10	1.10	0.8	0.8	P	S	38.76	38.76	25.12	24.54	33.32	33.32	8.23	7.77	12.17	12.17	10.99	11.21	5.85	5.85	27.25	27.25	10.46	10.46	1.10	1.10	0.8	0.8	25	P	S	30.43	30.43	16.79	16.21	24.99	24.99	8.23	7.77	12.17	12.17	10.99	11.21	5.85	5.85	19.02	19.02	10.46	10.46	1.10	1.10	0.8	0.8	P	S	30.43	30.43	16.79	16.21	24.99	24.99	8.23	7.77	12.17	12.17	10.99	11.21	5.85	5.85	19.02	19.02	10.46	10.46	1.10	1.10	0.8	0.8	15	P	S	+0,76 A 0	+0,76 A 0	+0,25 B 0	+0,25 B 0	±0,12 C	±0,12 C	+0,25 D 0	+0,25 D 0	+0,76 E 0	+0,76 E 0	F MAX	F MAX	+0,15 G 0	+0,15 G 0	+0,51 H 0	+0,51 H 0	+0,51 J 0	+0,51 J 0	±0,2 K	±0,2 K	+0,22 L 0	+0,22 L 0	P	S																						
SHELL SIZE	P	S	DIMENSIONS																																																																																																																																																																																																																																										
			A	B	C	D	E	F	G	H	J	K	L																																																																																																																																																																																																																																
50	P	S	66.65	66.65	52.68	52.30	61.11	61.11	11.08	10.62	14.99	14.99	11.09	11.21	5.85	5.85	55.07	55.07	13.31	13.31	1.50	1.10	1.0	0.8																																																																																																																																																																																																																					
	P	S	68.94	68.94	55.30	54.71	63.50	63.50	8.23	7.77	12.17	12.17	11.09	11.21	6.05	6.05	57.45	57.45	10.46	10.46	1.50	1.10	1.0	0.8																																																																																																																																																																																																																					
37	P	S	52.65	52.65	38.84	38.25	47.04	47.04	8.23	7.77	12.17	12.17	11.07	11.21	5.85	5.85	41.02	41.02	10.46	10.46	1.10	1.10	0.8	0.8																																																																																																																																																																																																																					
	P	S	38.76	38.76	25.12	24.54	33.32	33.32	8.23	7.77	12.17	12.17	10.99	11.21	5.85	5.85	27.25	27.25	10.46	10.46	1.10	1.10	0.8	0.8																																																																																																																																																																																																																					
25	P	S	30.43	30.43	16.79	16.21	24.99	24.99	8.23	7.77	12.17	12.17	10.99	11.21	5.85	5.85	19.02	19.02	10.46	10.46	1.10	1.10	0.8	0.8																																																																																																																																																																																																																					
	P	S	30.43	30.43	16.79	16.21	24.99	24.99	8.23	7.77	12.17	12.17	10.99	11.21	5.85	5.85	19.02	19.02	10.46	10.46	1.10	1.10	0.8	0.8																																																																																																																																																																																																																					
15	P	S	+0,76 A 0	+0,76 A 0	+0,25 B 0	+0,25 B 0	±0,12 C	±0,12 C	+0,25 D 0	+0,25 D 0	+0,76 E 0	+0,76 E 0	F MAX	F MAX	+0,15 G 0	+0,15 G 0	+0,51 H 0	+0,51 H 0	+0,51 J 0	+0,51 J 0	±0,2 K	±0,2 K	+0,22 L 0	+0,22 L 0																																																																																																																																																																																																																					
	P	S																																																																																																																																																																																																																																											
NOTE:-- 1) INSIDE DIMENSIONS OF THE MALE AND OUTSIDE DIMENSIONS OF THE FEMALE CONNECTOR 2) ALL ACCESSORIES SHOWN IN ASSEMBLY OPTIONS SHOULD BE ORDERED SEPARATELY																																																																																																																																																																																																																																													
ASSEMBLY OPTIONS FEMALE SCREW LOCK EXTENDED TYPE ORD CODE 8630-01-061 FEMALE SCREW LOCK EXTERNAL THREAD ORD CODE 8630-01LF M3 M3 MALE LEVER LOCK ORD CODE 8630-3427(EABC) CONNECTOR WITH SPECIAL RIVETTED FEMALE SCREW LOCK ORD CODE 8630-3428(D) CLINCH NUT PREFIX: 0 - UNC4-40 L - M3 WITH SHIELDING TERMINATION FINGERS OPTION: H FEMALE LEVER LOCK ORD CODE 8630-3425(EABC)																																																																																																																																																																																																																																													
VIEW OF MATING FACE																																																																																																																																																																																																																																													
TECHNICAL SPECIFICATIONS SHELLS : MATT TIN / ZINC PLATED STEEL INSULATOR MATERIAL : SELF EXTINGUISHING THERMOPLASTIC - UL CLASS 94 V0 CONTACTS DIA ON ACTIVE AREA : Ø1 MM. CONTACTS MATERIAL : COPPER ALLOY CONTACT PLATING : GXT / GOLD OVER NICKEL (ACTIVE ZONE) FOR LEAD FREE PLATING : TIN OVER NICKEL (TERMINATION ZONE) OPERATING TEMPERATURE : -55°C +125°C OPERATING CURRENT : 5 A PER CONTACT CONTACT RESISTANCE : ≤10m Ω INSULATION RESISTANCE : ≥5000M Ω MAXIMUM VOLTAGE : 1000 V.r.m.s MECHANICAL ENDURANCE : 200 MATINGS (For 64 code) 500 MATINGS (For 65 code). DAMP HEAT : 21 DAYS. WIRE SIZE : 0.6 MM² (AWG 20) MAX.																																																																																																																																																																																																																																													
ORDERING INFORMATION SERIES : D B V 25 P 0 64 H T X B XXX LF SHELL SIZE : E,A,B,C,D OPTIONS : BLANK-STANDARD F - FLOAT MOUNTING L - CLINCH NUT (M3) O - CLINCH NUT (UNC) V - FEM. SCREW LOCK HEX. (UNC) NO.OF CONTACTS : 09,15,25,37,50 CONTACTS : P - PIN S - SOCKET TERMINATION TYPE : 0 - SOLDER BUCKET LEAD FREE : SPECIAL CODES INSULATOR COLOUR : BLANK- NATURAL B - BLACK DIMPLES : X-ON MALE CONNECTORS ONLY SHELL PLATING : BLANK-ZINC T-STD. TIN over Cu OPTIONS : BLANK - STD H - WITH SHIELDING TERMINATION FINGERS CONTACT PLATING : 64 - 200 Mating cycles 65 - 500 Mating cycles																																																																																																																																																																																																																																													
mat'l. code SEE NOTE 4 surface ISO 1302 tolerance ISO 406 ISO 1101 projection product family D-SUB title D- SUB SOLDER BUCKET CONNECTOR (WITH ASSEMBLY OPTIONS) dwg no sheet 1 of 1 size A3 type Product Customer Drawing																																																																																																																																																																																																																																													
ltr ecn no dr date tolerances unless otherwise specified angles linear scale revision sheet index																																																																																																																																																																																																																																													

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru