

# 9200 NVMe SSDs

# MTFDHAL1T6TCU, MTFDHAL1T9TCT, MTFDHAL3T2TCU, MTFDHAL3T8TCT, MTFDHAL6T4TCU, MTFDHAL7T6TCT, MTFDHAL8TATCW, MTFDHAL11TATCW

# **Features**

- Micron<sup>®</sup> 3D NAND Flash
- PCIe<sup>®</sup> Gen3: U.2 ×4
- NVMe<sup>™</sup> 1.2
- Capacity<sup>1</sup>
  - 9200 ECO: 11.0TB, 8.0TB
  - 9200 PRO: 1.92TB, 3.84TB, 7.68TB
  - 9200 MAX: 1.6TB, 3.2TB, 6.4TB
- Endurance (total bytes written)<sup>1</sup>
  - 1.6TB: Up to 8.8PB
  - 1.92TB: Up to 3.5PB
  - 3.2TB: Up to 17.5PB
  - 3.84TB: Up to 7.0PB
  - 6.4TB: Up to 35.1PB
  - 7.68TB: Up to 14.0PB
  - 8.0TB: Up to 11.7PB
  - 11.0TB: Up to 16.1PB
- 512 and 4096 byte sector sizes
- Power: <5W idle, 25W power limited, or unlimited
- · Surprise insertion/surprise removal (SISR) and hot-plug capable
- Power-backed cache
- Steady state performance<sup>1, 2</sup> (varies by capacity and form factor)
  - Sequential 128KB read: 2.85-3.15 GB/s
  - Sequential 128KB write: 1.9-2.3 GB/s
  - Random 4KB read: 700K–770K IOPS
  - Random 4KB write: 130K–280K IOPS
- Latency to media performance, typical (QD = 1) READ: 92–150µs<sup>3</sup>, WRITE: 21µs
- Reliability
  - MTTF: 2 million hours<sup>4</sup>
  - Field-upgradable firmware
  - UBER: <1 sector per 10<sup>17</sup> bits read
- SMBus for drive management
- End-to-end data path protection
- SMART command set support
- Cryptographic erase<sup>5</sup>
- FlexPro (flexible over provisioning)

- Temperature<sup>6</sup>
  - 0°C to 80°C SMART temperature
  - 0°C to 35°C ambient for U.2
  - Temperature protection
- Mechanical/electrical
  - U.2: 69.85 × 15.00 × 100.5mm, 12V (-6%/+8%)
- Shock
  - U.2: 1500g @ 0.5ms
- Vibration: 3.1 G<sub>RMS</sub> 5–800Hz @ 30 min/axis

# **Controller Features**

- NVMe controller
  - Number of queues: 128 SQ/CQ pairs
  - Weighted round robin with urgent arbitration
- Interrupt coalescing
- NVMe command set attributes
  - Completion queue entry size: 16 bytes
  - Submission queue entry size: 64 bytes
- 4KB Atomic operations
  - Notes: 1. User capacity: 1GB = 1 billion bytes; 1TB = 1 trillion bytes; 1PB = 1 peta bytes.
    - 2. Steady state as defined by SNIA Solid State Storage Performance Test Specification Enterprise v1.1.
    - 3. READ latency varies by capacity.
    - 4. Based on population statistics that are not relevant to individual units and a T<sub>CASE</sub> of 60°C.
    - 5. 4K sector size support only.
    - 6. Operating temperature is the drive case temperature as measured by the SMART temperature. See air flow recommendations.

CCMTD-731836775-10493 9200\_u2\_nvme\_pcie\_ssd.pdf - Rev. E 10/17 EN

Micron Technology, Inc. reserves the right to change products or specifications without notice. © 2016 Micron Technology, Inc. All rights reserved. Products and specifications discussed herein are subject to change by Micron without notice.



# **Native Drivers**

- Microsoft Windows Server<sup>®</sup> 2016
- Red Hat<sup>®</sup> Enterprise Linux (RHEL) 6.5+
- CentOS<sup>®</sup> 6.5+
- SUSE<sup>®</sup> Linux Enterprise Server 11 SP4, 12+
- Ubuntu<sup>®</sup> 12.04.03+, 14.04+
- VMware<sup>®</sup> 5.5, 6.0+

# **Custom Drivers**

- Microsoft Windows Server 2012 R2, Hyper-V (recommended)
- RHEL 6.1-6.4
- CentOS 6.1-6.4
- SUSE Linux Enterprise Server 11 SP1-SP3

# **Part Numbering Information**

The Micron<sup>®</sup> 9200 SSD is available in different configurations and capacities. Visit www.micron.com for a list of valid part numbers.

# Figure 1: Part Number Chart



**Warranty**: Contact your Micron sales representative for further information regarding the product, including product warranties.



# **General Description**

The Micron 9200® NVMe SSD Series is Micron's flagship performance product line. These products utilize a Gen3 PCIe interface, the innovative Non-Volatile Memory Express protocol and Micron's own high-speed NAND to provide high throughput and IOPS, very low latency, and consistent quality of service. The 9200 product line has Micron's FlexPro<sup>™</sup> firmware architecture which allows you to actively tune capacity to optimize drive performance and endurance and is available in high capacities up to 11 TBs. Reliability assurance measures include cyclic redundancy checks (CRC), end-toend data path protection, capacitor-backed power loss protection and Micron's extensive validation, quality and reliability testing. It features thermal monitoring and protection, SMART attributes for status polling and SMBus for out-of-band management.

The Micron 9200 has three endurance classes: the PRO for read-centric use at roughly 1 drive writes per day (DWPD); and the MAX for mixed-use workloads at about 3 DWPD; and the ECO for less than 1 DWPD. The PRO version comes in 1.92TB, 3.84TB, and 7.68TB capacities, while the MAX is sized at 1.6TB, 3.2TB, 6.4TB, and the ECO in 8.0TB and 11.0TB.

# **Logical Block Address Configuration**

The number of logical block addresses (LBAs) reported by the device ensures sufficient storage space for the specified capacity.

### Table 1: LBA Count in Accordance with IDEMA LBA1-03

Capacity	512-Byte Sector LBA Count	4KB Sector LBA Count
1.6TB	3,125,627,568	390,703,446
1.92TB	3,750,748,848	468,843,606
3.2TB	3.2TB 6,251,233,968 781,404,246	
3.84TB	7,501,476,528	937,684,566
6.4TB	12,502,446,768	1,562,805,846
7.68TB	15,002,931,888	1,875,366,486
8.0TB	15,628,053,168	1,953,506,646
11.0TB	21,488,565,168	2,686,070,646



# Performance

### **Table 2: Drive Performance**

	9200 (T	ECO B)		9200 PRO (TB)	1		9200 MA) (TB)	C	
Specification	8.0	11.0	1.92	3.84	7.68	1.6	3.2	6.4	Unit
Sequential read (128KB I/O size)	3.15	3.15	2.85	3.15	3.15	2.85	3.15	3.15	GB/s
Sequential write (128KB I/O size)	2.3	2.25	1.9	2.3	2.3	1.9	2.3	2.3	-
Random read (4KB I/O size)	740K	770K	700K	770K	750K	700K	770K	770K	IOPS
Random write (4KB I/O size)	135K	130K	185K	170K	160K	255K	280K	270K	
Mixed 70/30 read/write (4KB I/O size)	320K	330K	325K	355K	355K	370K	445K	450K	

Notes: 1. Performance specifications shown are with power limiting off. See Electrical Characteristics section for more details.

- 2. The stated specifications are preliminary.
- 3. Performance is steady state as defined by SNIA Solid State Storage Performance Test Specification Enterprise v1.1.
- 4. Performance may vary up to 10% over life of drive.

### Table 3: Latency

Specification	Queue Depth = 1	Unit
READ latency (TYP) 1.6TB–3.84TB	92	μs
READ latency (TYP) 6.4TB-8TB	101	
READ latency (TYP) 11TB	105	
WRITE latency (TYP) all capacities	21	

Note: 1. Quality of service is measured using random 4KB workloads, QD = 1 at steady state.



# **Functional Description**

### **Mean Time to Failure**

The mean time to failure (MTTF) for the device can be calculated based on the component reliability data using the methods referenced in the Telcordia SR-322 reliability prediction procedures for electronic equipment and measured during reliability demonstration test.

#### Table 4: MTTF

Capacity	MTTF (Operating Hours)
All	2.0 million

### Endurance

SSD endurance is dependent on many factors, including: usage conditions applied to the drive, drive performance and capacity, formatted sector size, error correction codes (ECCs) in use, internal NAND PROGRAM/ERASE cycles, write amplification factor, wear-leveling efficiency of the drive, over-provisioning ratio, valid user data on the drive, drive temperature, NAND process parameters, and data retention time.

The device is designed to operate under a wide variety of conditions, while delivering the maximum performance possible and meeting enterprise market demands.

While actual endurance varies depending on conditions, the drive lifetime can be estimated based on capacity, assumed fixed-use models, ECC, and formatted sector size. Lifetime estimates for the device are shown in the following tables in total bytes written.

Model	Capacity (TB)	Total Bytes Written (PB)
9300 500	8.0	11.7
9200 ECO	11.0	16.1
9200 PRO	1.92	3.5
	3.84	7.0
	7.68	14.0
	1.6	8.8
9200 MAX	3.2	17.5
	6.4	35.1

#### Table 5: Total Bytes Written

Note: 1. Values shown are based on system modeling.



# **Data Retention**

Data retention refers to the capability of the SSD media (that is, NAND flash) to retain programmed data. The three primary factors that affect data retention are:

- Power-on/power-off state: Data retention generally improves when the SSD is in use (that is, not shelved in a power-off state).
- Temperature: Data retention decreases as the temperature increases.
- Number of PROGRAM/ERASE cycles on the media: When the SSD ships from the factory, it is typically able to retain user data for up to 5 years in a powered-off state.

Data retention is guaranteed for three months at 40°C (MAX), which assumes worstcase power and media wear (the SSD remains in a powered-off state and has reached end of life).

# **Wear Leveling**

The device uses sophisticated wear-leveling algorithms to maximize endurance by distributing PROGRAM/ERASE cycles uniformly across all blocks in the array. Both static and dynamic wear leveling are utilized to optimize the drive's lifespan.

Both types of wear leveling aim to distribute "hot" data away from blocks that have experienced relatively heavy wear. Static wear leveling accomplishes this by moving data that has not been modified for an extended period of time out of blocks that have seen few PROGRAM/ERASE cycles and into more heavily worn blocks. This frees up fresher blocks for new data while reducing expected wear on tired blocks. Dynamic wear leveling, by contrast, acts on in-flight data to ensure it is preferentially written to the least-worn free blocks rather than those closer to the end of their rated life. These techniques are used together within the controller to optimally balance the wear profile of the NAND array.

### **Firmware Update Capability**

The SSD supports firmware updates as defined by the NVMe specification. When a download operation completes, an ACTIVATE command must be issued.

### **Power Loss Subsystem and Rebuild**

The SSD supports an unexpected power loss with a power-backed write cache. No user data is lost during an unexpected power loss. When power is subsequently restored, the SSD returns to a ready state within a maximum of 120 seconds.

### Boot

The 9200 is not intended to be a bootable device. Boot functionality is not validated by Micron, and any use in this manner is done at the user's own risk. Please visit Micron.com to find other SSD products that are recommended for boot.

### **SMBus Sideband Management**

If the system management bus (SMBus) is configured to be enabled, the SSD uses the SMBus interface for presenting product data, monitoring drive health, checking drive status before power-up, and error posting.



Protocol supported: Enterprise SSD Form Factor interface with its accompanying vital product data (VPD) definition.

Management data and vital product data may be accessed at fixed addresses with  $+3.3V_{AUX}$  prior to powering up the drive completely. This data continues to be available at this fixed address when the drive is fully powered up.

#### **Table 6: Out of Band Management Details**

Out of Band Protocol	SMBUS Address	Alternate Address (due to bit shift)	Data
Enterprise SSD Form Factor	0x53	0xA6	Vital product data (VPD)
NVMe Management Interface 1.0	0x6A	0xD4	Subsystem management data (SMD)

Notes: 1. SMBUS addresses will appear at an alternate address in certain tools due the inclusion of direction bit in the SMBUS spec.

2. Out of band management is disabled by default.

### Table 7: Vital Product Data (VPD) Structure

Address	#Bytes	Function	Value	Byte Offset	Description
0x53	3	Class code	02h	0	Device type and programming interface
(7bit)			08h	1	
			01h	2	
	2	ID	44h	3	PCI-SIG vendor ID (0x1344 is assigned to
			13h	4	Micron)
	20		Varies	5–24	Serial number
	40		Varies	25–64	Model number
	1	PCle port0 capabilities	03h	65	Maximum link speed
	1		04h/08h	66	Maximum link width (04h if U.2, 08h if HHHL)
	1	PCle port1 capabilities	00h	67	Maximum link speed
	1		00h	68	Maximum link width
	1	Initial power requirements	08h	69	12V Power rail initial power requirement (W)
	2	Reserved	0	70–71	-
	1	Maximum power require- ments	24h	72	12V power rail maximum power require- ment (W)
	2	Reserved	0	73–74	-
	2	Capability list pointer	4Dh	75	16b address offset pointers to start of ca-
			00h	76	pability list, see Capability List Pointer ta- ble



# **Table 8: Capability List Pointer**

Address	#Bytes	Value	Byte Offset	R/W	Description
0x004D	2	A5h	0	RO	PCI-SIG vendor specific capability
		00h	1		
	2	00h	2	RO	Pointer to next capability
		00h	3		
	2	44h	4	RO	PCI-SIG vendor ID (0x1344 is assigned to
		13h	5		Micron)
	2	0000h	6–7	RO	Reserved
	2	Varies	8	RO	Temperature value (Celsius), little-endian
		Varies	9	RO	format. For example, byte[8:9] = 29h 00h indicates the temperature is 41°C



# **Electrical Characteristics**

Stresses greater than those listed may cause permanent damage to the device. This is a stress rating only, and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

#### **Table 9: Power Consumption**

	9200	9200 ECO (TB)		9200 PRO (TB)		9200 MAX (TB)			
Specification	8.0	11.0	1.92	3.84	7.68	1.6	3.2	6.4	Unit
Active reads (Maximum RMS)		25 <sup>2</sup>						W	
Active writes (Maximum RMS)		25 <sup>2</sup>							
128K sequential reads (Average RMS)	19	21	17	19	19	17	19	19	
128K sequential writes (Average RMS)	20	20	18	20	20	18	20	20	
4K random reads (Average RMS)	17	17	16	16	17	16	16	17	
4K random writes (Average RMS)	20	21	18	21	20	18	20	21	
Mixed 70/30 read/write (Average RMS)	19	20	17	20	18	16	20	17	

Notes: 1. Average power consumption.

2. 25W power limiting by VU command.

### **Table 10: Operating Voltage**

Electrical Characteristic	Value	
12V power rail	Operating voltage	12Vdc (±8%)
	MAX/MIN rise time	10–100ms
	MAX/MIN fall time	<5s
	Inrush current (typical peak)	3.0A
	MAX average current (RMS)	2.5A
3.3V <sub>AUX</sub> power rail	Operating voltage	3.3V (–8% to 8%)
	MAX/MIN rise time	50ms/1ms
	MAX/MIN fall time	5s/1ms
	MAX average current	20mA



# **Environmental Conditions**

#### **Table 11: Temperature and Airflow**

Temperature and Airflow	2.5" U.2	Notes
Operating temperature (as indicated by the SMART temper- ature attribute)	0°C to 85°C	1
Operating ambient temperature	Ambient: 0°C to 35°C; Case: 0°C to 70°C	2
Operating airflow	450 LFM at 25°C ambient	3, 4
Storage temperature	–40°C to 85°C	5
Humidity	25% to 95% noncondensing	

Notes: 1. If SMART temperature exceeds 75°C (SMART composite), write performance will be throttled.

- 2. Temperature of air impinging on the SSD.
- 3. Airflow must flow along the length of the drive parallel to and through any cooling fins.
- 4. Airflow is measured upstream of the drive before any acceleration as the air goes around the drive.
- 5. Contact Micron for additional information.

#### **Table 12: Shock and Vibration**

Shock and Vibration	2.5" U.2
Shock (nonoperational)	1500G at 0.5ms half-sine
Vibration (nonoperational)	3.1 G <sub>RMS</sub> 5–800Hz at 30 min/axis

Note: 1. Shock and vibration ratings refer to the ability to withstand stress events only. Prolonged or repeated exposure to conditions listed or greater stresses may result in permanent damage to the device. Functional operation of the device under these conditions is not implied. See warranty for more information.



# **Supported Commands**

### **NVMe Admin Command Set**

The 9200 supports the following mandatory NVMe admin commands, as described in the NVMe 1.2 specification:

- Delete I/O submission queue
- Create I/O submission queue
- Get log page
- Delete I/O completion queue
- Create I/O completion queue
- Identify
- Abort
- Set features
- Get features
- Asynchronous event request

The following optional NVMe admin commands are also supported:

- Firmware activate
- Firmware image download
- Format NVM
- · Security Send
- Security Receive

### NVMe I/O Command Set

The 9200 supports the following mandatory NVMe I/O commands, as described in the NVMe 1.2 specification:

- Write
- Read
- Flush

The following optional NVMe I/O commands are also supported:

- Dataset management
- Deallocate

### Log Pages

The Get Log Page command can be used to retrieve the following logs:

- 01h Error information
- 02h SMART / health information
- 03h Firmware slot information
- CAh Vendor Unique SMART
- 05h Command Effects Log



# **SMART and Health Information**

The SSD supports SMART/Health log information as defined in the NVMe specification as well as extended health information. These logs persist through power cycles and reflect lifetime data.

### Table 13: SMART/Health Information (Log Identifier 02h)

Bytes	Name	Description
0	Critical warning	Indicates critical warnings for the state of the controller. Each bit corre- sponds to a critical warning type; multiple bits may be set. If a bit is cleared to 0, the critical warning does not apply. Critical warnings may result in an asynchronous event notification to the host.
		• Bit 00: If set to 1, the available spare space has fallen below the threshold.
		• Bit 01: If set to 1, the temperature has exceeded a critical threshold.
		• Bit 02: If set to 1, the device reliability has been degraded due to sig- nificant media-related errors or any internal error that degrades de- vice reliability.
		• Bit 03: If set to 1, the media has been placed in read-only mode.
		• Bit 04: If set to 1, the volatile memory backup device has failed. This field is only valid if the controller has a volatile memory backup solution.
		Bits 07:05 Reserved
2:1	Temperature	Contains the temperature of the overall device (controller and NVM in- cluded) in units of Kelvin. If it exceeds the temperature threshold, an asynchronous event may be issued to the host. For the 9100, the value reported is the maximum temperature measured on either the board or controller.
3	Available spare	Contains a normalized percentage (0–100%) of the remaining available spare capacity, beginning at 100% and decreasing.
4	Available spare threshold	When the available spare falls below the threshold indicated in this field, an asynchronous event may be issued to the host. The value is indicated as a normalized percentage (0–100%). Threshold is set to 5%.
5	Percentage used	Contains a vendor-specific estimate of the percentage of the device life used based on the actual device usage and the manufacturer's predic- tion of device life. A value of 100 indicates that the estimated endurance of the device has been consumed, but may not indicate a device failure. Refer to the JEDEC JESD218 standard for SSD device life and endurance measurement techniques.
31:6	Reserved	Reserved
47:32	Data units read	Contains the number of 512-byte data units the host has read from the controller; this value does not include metadata. This value is reported in thousands (that is, a value of 1 corresponds to 1000 units of 512 bytes read) and is rounded up. When the LBA size is a value other than 512 bytes, the controller shall convert the amount of data read to 512-byte units.



### Table 13: SMART/Health Information (Log Identifier 02h) (Continued)

Bytes	Name	Description
63:48	Data units written	Contains the number of 512-byte data units the host has written to the controller; this value does not include metadata. This value is reported in thousands (that is, a value of 1 corresponds to 1000 units of 512 bytes written) and is rounded up. When the LBA size is a value other than 512 bytes, the controller shall convert the amount of data written to 512-byte units. For the NVM command set, logical blocks written as part of write operations shall be included in this value. Write uncorrectable commands shall not impact this value.
79:64	Host read commands	Contains the number of read commands issued to the controller.
95:80	Host write commands	Contains the number of write commands issued to the controller. For the NVM command set, this is the number of write commands.
111:96	Controller busy time	Contains the amount of time the controller is busy with I/O commands. The controller is busy when there is a command outstanding to an I/O queue (specifically, a command was issued via an I/O submission queue tail doorbell write and the corresponding completion queue entry has not been posted yet to the associated I/O completion queue.) This val- ue is reported in minutes.
127:112	Power cycles	Contains the number of power cycles.
143:128	Power on hours	Contains the number of power-on hours. This does not include time that the controller was powered and in a low-power state condition.
159:144	Unsafe shutdowns	Contains the number of unsafe shutdowns. This count is incremented when a shutdown notification (CC.SHN) is not received prior to loss of power.
175:160	Media errors	Contains the number of occurrences where the controller detected an unrecovered data integrity error. Errors such as uncorrectable ECC, CRC checksum failure, or LBA tag mismatch are included in this field.
191:176	Number of error info log entries	Contains the number of error information log entries over the life of the controller.
511:192	Reserved	Reserved

# **Vendor Unique SMART**

In addition to the standard SMART log, the 9200 provides the following details in a vendor unique log:

### Table 14: Vendor Unique SMART Attributes (Log Identifier CAh)

Bytes	Name	Description
0:1	F9 - NAND_writes_1GiB	Raw value reports the number of writes to NAND in 1 GiB increments.
3:4	Normalized value	
5:11	Current raw value	
12:13	FA - NAND_reads_1GiB	Raw value reports the number of reads to NAND in 1 GiB increments.
15:16	Normalized value	
17:23	Current raw value	



#### Table 14: Vendor Unique SMART Attributes (Log Identifier CAh) (Continued)

Bytes	Name	Description		
24:25	EA - Thermal throttle status	Raw value indicates throttle status and total throttling time.		
27:28	Normalized value	Byte 0: If set to 1, throttling is active; if set to 0, throttling is not active		
29:35	Current raw value	Bytes 1–4: Total throttling time in minutes since power on Bytes 5: Reserved		
36:37	E7 - Temperature	Raw value reports the maximum and minimum temperature in Kelvin		
39:40	Normalized value	over the lifetime of the device.		
41:47	Current raw value	Byte 0–1: The maximum temperature sampled from the temperature sensor Bytes 2–3: The minimum temperature sampled from the temperature		
		Bytes 4–5: The current temperature sampled from the temperature sen- sor		
48:49	E8 - Power consumption	Raw value reports the maximum and minimum average power con- sumption in watts.		
51:52	Normalized value			
53:59	Current raw value	Bytes 0–1: The maximum power consumption Bytes 2–3: The minimum power consumption Bytes 4–5: The average power consumption		
60:61	AF - Power loss protection	Normalized value reports the power loss protection status. 100 indi-		
63:64	Normalized value	cates protection was successful. 0 indicates protection failed. A power		
65:71	Current raw value	toss failure indicator will persist until a Format NVM command is ex		

### **Get/Set Features**

The following features can be configured or retrieved using NVMe SET FEATURES and GET FEATURES commands:

- 02h Power management (Commands are accepted but values are not returned. A custom power governor feature is utilized for power management.)
- 04h Temperature threshold
- 05h Set error recovery
- 07h Number of queues (Maximum supported is 128 for both submission and completion queues.)
- 08h Interrupt coalescing
- 09h Interrupt vector configuration
- 0Bh Asynchronous event configuration
- D4h Device initiated thermal



# **Interface Connectors**

The host interface connector conforms to the PCIe Electromechanical Specification.

A mechanical indent is used to separate the PCIe power pins from the differential signal contacts. The pins are numbered below in ascending order from left to right. Side B refers to component side. Side A refers to the solder side.

# **U.2 Pin Assignments**

The U.2 2.5" form factor follows the SFF-8639 specification and supports built-in latching.

Pin	Name	Description	Pin	Name	Description
S1	GND	Ground	E7	REFCLK0+	PCle REFCLK 0 p
S2		DNC	E8	REFCLK0-	PCle REFCLK 0 p
53		DNC	E9	GND	Ground
S4	GND	Ground	E10	PETp0	PCle TX Lane 0 p
S5		DNC	E11	PETn0	PCle TX Lane 0 n
S6		DNC	E12	GND	Ground
S7	GND	Ground	E13	PERn0	PCle RX Lane 0 n
E1	REFCLK1+	DNC	E14	PERp0	PCle RX Lane 0 p
E2	REFCLK1-	DNC	E15	GND	Ground
E3	3.3Vaux	3.3V auxiliary power	E16	RSVD	Reserved
E4	PERST1#	DNC	S8	GND	Ground
E5	PERST0#	PCIe Fundamental Reset	S9		DNC
E6	RSVD	Reserved	S10		DNC
P1		DNC	S11	GND	Ground
P2		DNC	S12		DNC
Р3		DNC	S13		DNC
P4	lfDet_N	Interface detect	S14	GND	Ground
P5	GND	Ground	S15	RSVD	Reserved
P6	GND	Ground	S16	GND	Ground
P7		DNC	S17	PETp1	PCle TX Lane 1 p
P8		DNC	S18	PETn1	PCle TX Lane 1 n
P9		DNC	S19	GND	Ground
P10	PRSNT_N	Presence detect	S20	PERn1	PCle RX Lane 1 n
P11	Activity	Activity signal from the drive	S21	PERp1	PCle RX Lane 1 p
P12	Hot-Plug	Ground	S22	GND	Ground
P13	+12V_pre	12V power	S23	PETp2	PCle TX Lane 2 p
P14	+12V	12V power	S24	PETn2	PCle TX Lane 2 n
P15	+12V	12V power	S25	GND	Ground
			S26	PERn2	PCle RX Lane 2 n

### Table 15: PCIe Interface Connector Pin Assignments (U.2 Form Factor)



Pin	Name	Description	Pin	Name	Description
			S27	PERp2	PCle RX Lane 2 p
			S28	GND	Ground
			E17	РЕТр3	PCle TX Lane 3 p
			E18	PETn3	PCle TX Lane 3 n
			E19	GND	Ground
			E20	PERn3	PCle RX Lane 3 n
			E21	PERp3	PCle RX Lane 3 p
			E22	GND	Ground
			E23	SMCLK	SMBus clock
			E24	SMDAT	SMBus data
			E25	DualPortEn_N	Dual port enable

#### Table 15: PCIe Interface Connector Pin Assignments (U.2 Form Factor) (Continued)

Notes: 1. PRSNT\_N is open and IfDet\_N is grounded to indicate PCIe support.

2. DualPortEn\_N pin should be left un-connected or un-driven by the system to enable single port operation with all 4 lanes. If this pin is asserted (driven low) by the system, the SSD will function as PCIe x2 lane only.



# **PCIe Header**

#### Figure 2: 9200 MAX PCIe Header



### Figure 3: 9200 PRO PCIe Header





### Figure 4: 9200 ECO PCIe Header





# **Physical Configuration**

Micron's 9200 conforms to PCI Express CEM and SFF-8639 specifications.





Note: 1. Length does not include 0.3 connector protrusion.



# Compliance

The device complies with the following specifications:

- CE (Europe): EN 55022 Class B, EN 55024, RoHS
- UL: UL-60950-1, 2nd Edition
- BSMI (Taiwan): Approval to CNS 13438 Class B
- RCM (Australia, New Zealand): AS/NZS CISPR22 Class B
- KCC RRL (Korea): Approval to KN32 Class B, KN 35
- W.E.E.E.: Compliance with EU WEEE directive 2012/19/EC. Additional obligations may apply to customers who place these products in the markets where WEEE is enforced.
- TUV (Germany): Approval to IEC60950/EN60950
- V<sub>CCI</sub> (Japan): 2015-04 Class B, CISPR22
- IC (Canada): ICES-003 Class B, CISPR22 Class B
- This Class B digital apparatus complies with Canadian ICES-003.
- Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada

# **FCC Rules**

This equipment has been tested and found to comply with the limits for a digital device, pursuant to part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference ence by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

# References

- PCI Express CEM Specification V2.0
- PCI Express Specification V3.0
- SFF-8639
- IDEMA Specification
- Telcordia SR-322 Procedures
- NVM Express Specification revision 1.2



# Appendix A

# **Identify Data Structures**

### Table 16: Identify Controller Data Structure

Identify Controller Data Structure Bytes	DS <sup>1</sup>	Default Value	M/0 <sup>2</sup>	Feature Name	Description
1:0	F	0x1344	М	PCI vendor ID (VID)	Contains the company vendor identifier that is assigned by the PCI SIG.
3:2	F	0x1344	М	PCI subsystem vendor ID (SSVID)	Contains the company vendor identifier that is assigned by the PCI SIG for the subsystem.
23:4	V	varies	М	Serial number (SN)	Contains the serial number for the NVM sub- system.
63:24	V	varies	М	Model number (MN)	Contains the model number for the NVM subsystem.
71:64	V	varies	М	Firmware revision (FR)	Contains the currently active firmware revision for the NVM subsystem.
72	F	0x1	М	Recommended arbitration burst (RAB)	This is the recommended arbitration burst size.
75:73	F	0x75-0xA0-0x00	М	IEEE OUI identifier (IEEE)	Contains the organization unique identifier (OUI) for the controller vendor.
76	х	0x0	0	Controller multi-path I/O and namespace sharing capabili- ties (CMIC)	This field specifies multi-path I/O and name- space sharing capabilities of the controller and NVM subsystem.
77	F	0x20	М	Maximum data transfer size (MDTS)	Supports MDTS of 128K.
79:78	F	0x1	М	Controller ID (CNTLID)	This field contains the controller ID of the controller whose status is reported in this data structure.
83:80	F	0x00010200	М	Version (VER)	This field indicates the version of the NVM express specification 1.2 that the controller implementation supports.
95:92	V	0x1	М	Optional asynchronous events supported (OAES)	This field indicates the optional asynchro- nous events supported by the controller.
239:96	_	-	_	_	Reserved

Notes: 1. DS = Data structure; F = Fixed; V = Variable; X = Both

2. M/O = Mandatory/Optional



### **Table 17: Identify Namespace Data Structure**

Bvtes	DS <sup>1</sup>	Default Value	M/O <sup>2</sup>	Feature Name	Description
512	F	0x55	M	Submission queue entry size (SQES)	Required and maximum submission queue entry size is 32 bytes
513	F	0x44	М	Completion queue entry size (CQES)	Required and maximum submission queue entry size is 16 bytes
515:514	-	-	-	_	Reserved
519:516	F	0x1	М	Number of namespaces (NN)	Supports up to 32 namespaces
521:520	F	0x14	М	Optional NVM command support (ONCS)	Supports dataset management and write un- correctable optional NVMe commands
523:522	F	0x0	М	Fused operation support (FUSES)	Fused commands not supported
524	F	0x4	М	Format NVM attributes (FNA)	Secure/Crypto erase not supported
525	F	0x1	М	Volatile write cache (VWC)	Volatile write cache is present
527:526	F	0x0	М	Atomic write unit normal (AWUN)	Atomic write size for controller during nor- mal equals to 4K bytes
529:528	F	0x0	М	Atomic write unit power fail (AWUPF)	Indicates the atomic write size for the con- troller during a power fail condition equals 512 bytes
530	Х	0x0	М	NVM vendor specific com- mand configuration (NVSCC)	Not supported
531	-	-	-	_	Reserved
533:532	F	0x0	М	Atomic compare and write unit (ACWU)	Not supported
535:534	-	-	-	_	Reserved
539:536	F	0x0	0	SGL support (SGLS)	Not supported
703:540	-	-	-	-	Reserved
I/O comman	d set at	tributes	-		
2047:704	-	-	_	-	Reserved

Notes: 1. DS = Data structure; F = Fixed; V = Variable; X = Both

2. M/O = Mandatory/Optional



# **Revision History**

Rev. E – 10/17	
	Removed HHHL through the data sheet
	Updated Drive Performance table and Latency table in Performance
	Updated Power Consumption table
	Corrected PCIe header information
Rev. D – 8/17	
	• Updated Drive Performance table, Latency table, and Quality of Service table in Per- formance section
	• Updated Out of Band Management Details table in SMBus Sideband Management: Added NVMe Management Interface 1.0
	• Updated Power Consumption table in Electrical Characteristics: Changed Idle power specification
	• Updated Temperature and Airflow table in Environmental Conditions: Changed Operating ambient temperature specification and Operating airflow specification
	Updated Shock and Vibration table
Rev. C – 7/17	
	Updated Part Number Chart
	Updated formatting
Rev. B – 1/17	
	• Updated figure 1
	Updated formatting
Rev. A - 10/16	
	Initial release

8000 S. Federal Way, P.O. Box 6, Boise, ID 83707-0006, Tel: 208-368-4000 www.micron.com/products/support Sales inquiries: 800-932-4992

Micron and the Micron logo are trademarks of Micron Technology, Inc.

All other trademarks are the property of their respective owners.

This data sheet contains minimum and maximum limits specified over the power supply and temperature range set forth herein.

Although considered final, these specifications are subject to change, as further product development and data characterization sometimes occur.



#### ООО "ЛайфЭлектроникс"

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru

#### www.lifeelectronics.ru