


### 4.7 mm×3.5 mm SMD Light Touch Switches

Type: **EVQP2/EVQP9/EVQ3P2**




#### ■ Features

- External dimensions : 4.7 mm×3.5 mm,  
Height : Middle Push Travel 2.5 mm  
Short Push Travel 2.1 mm, 2.5 mm
- High operating force and long operational life
- High mountability with J-bent (4 terminals)

#### ■ Recommended Applications

- Operation switches for portable electronic equipment  
(Mobile phones, Digital still cameras, Camcorders,  
Portable audio players, etc.)
- Keyless entry systems (automotive)
- Car audio equipment

#### ■ Explanation of Part Numbers










#### ■ Specifications

| Travel Type                   |                                 | Middle Push Travel                                                                       | Short Push Travel                                                                                                                                           |
|-------------------------------|---------------------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                          |                                 | Snap action / Push-on V DC type SPST                                                     |                                                                                                                                                             |
| Electrical                    | Rating                          | 10 $\mu$ A 2 V DC to 20 mA 15 V DC (Resistive load)                                      |                                                                                                                                                             |
|                               | Contact Resistance              | 100 m $\Omega$ max.                                                                      |                                                                                                                                                             |
|                               | Insulation Resistance           | 100 M $\Omega$ min. (at 100 V DC)                                                        |                                                                                                                                                             |
|                               | Dielectric Withstanding Voltage | 250 V AC (1 minute)                                                                      |                                                                                                                                                             |
|                               | Bouncing                        | 10 ms max. (ON, OFF)                                                                     |                                                                                                                                                             |
| Mechanical                    | Operating Force                 | 2.5 N, 3.5 N, 5.0 N                                                                      | 1.0 N, 1.6 N, 2.4 N, 3.5 N, 4.0 N, 5.0 N                                                                                                                    |
|                               | Travel                          | 0.70 mm $\pm$ 0.20 mm                                                                    | 0.25 mm <sup>+0.05</sup> <sub>-0.15</sub> mm                                                                                                                |
| Endurance                     | Operating Life                  | 2.5 N: 1,000,000 cycles min.<br>3.5 N: 500,000 cycles min.<br>5.0 N: 200,000 cycles min. | 1.0 N, 1.6 N: 1,000,000 cycles min.<br>2.4 N: 500,000 cycles min.<br>3.5 N: 200,000 cycles min.<br>4.0 N: 200,000 cycles min.<br>5.0 N: 200,000 cycles min. |
| Operating Temperature         |                                 | -40 °C to +85 °C                                                                         |                                                                                                                                                             |
| Storage Temperature           |                                 | -40 °C to +85 °C (Bulk)<br>-20 °C to +60 °C (Taping)                                     |                                                                                                                                                             |
| Minimum Quantity/Packing Unit |                                 | 4,000 pcs. Embossed Taping (Reel Pack)                                                   |                                                                                                                                                             |
| Quantity/Carton               |                                 | 20,000 pcs.                                                                              |                                                                                                                                                             |







Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.  
Should a safety concern arise regarding this product, please be sure to contact us immediately.

### ■ Dimensions in mm (not to scale)







|                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                 |        |                  |                  |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|--------|------------------|------------------|
| No. 1                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                 |        |                  |                  |
| EVQP2<br>EVQ3P2                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                 |        |                  |                  |
| Middle push travel<br>With J-bent terminals<br>Without<br>Ground Terminal          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                 |        |                  |                  |
|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                 |        |                  |                  |
|                                                                                    | <div>(General dimension tolerance±0.2)</div> <div></div> <div></div> <div></div> <div></div> <div>Circuit diagram</div> <div></div> <div></div> <div>PWB land pattern for reference</div> |                 |        |                  |                  |
| Part Numbers                                                                       | Ground Terminal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Operating Force | Height | Push Plate Color | Operating Life   |
| EVQP2H02B                                                                          | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 2.5 N           | 2.5 mm | Blue             | 1,000,000 cycles |
| EVQP2K02Q                                                                          | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 3.5 N           | 2.5 mm | Gray             | 500,000 cycles   |
| EVQ3P202K                                                                          | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 5.0 N           | 2.5 mm | Black            | 200,000 cycles   |

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.  
Should a safety concern arise regarding this product, please be sure to contact us immediately.

### ■ Dimensions in mm (not to scale)


|                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |        |                  |                  |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|--------|------------------|------------------|
| No. 2                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |        |                  |                  |
| EVQP2<br>EVQ3P2                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |        |                  |                  |
| Middle push travel<br>With J-bent terminals<br>With<br>Ground Terminal             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |        |                  |                  |
|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                 |        |                  |                  |
|                                                                                    | <div>(General dimension tolerance : <math>\pm 0.2</math>)</div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div><div>Land pattern plan</div><div>We recommend to connect the GND land shown in the switch spec. with the GND of your P.C.B for withstanding electric-static discharge.</div></div> |                 |        |                  |                  |
| Part Numbers                                                                       | Ground Terminal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Operating Force | Height | Push Plate Color | Operating Life   |
| EVQP2B02B                                                                          | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 2.5 N           | 2.5 mm | Blue             | 1,000,000 cycles |
| EVQP2D02Q                                                                          | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3.5 N           | 2.5 mm | Gray             | 500,000 cycles   |
| EVQP2F02K                                                                          | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 5.0 N           | 2.5 mm | Black            | 200,000 cycles   |

### ■ Dimensions in mm (not to scale)

|                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |          |                  |                  |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|------------------|------------------|
| No. 3                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |          |                  |                  |
| EVQP2<br>EVQP9                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |          |                  |                  |
| Short push travel<br>With J-bent terminals<br>Without<br>Ground Terminal          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |          |                  |                  |
|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                 |          |                  |                  |
|                                                                                   | <p>(General dimension tolerance±0.2)</p> <div><p>Circuit diagram</p><p>PWB land pattern for reference</p></div> |                 |          |                  |                  |
| Part Numbers                                                                      | Ground Terminal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Operating Force | H=Height | Push Plate Color | Operating Life   |
| EVQP2002M                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1.0 N           | 2.1 mm   | White            | 1,000,000 cycles |
| EVQP2002W                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1.0 N           | 2.5 mm   | White            | 1,000,000 cycles |
| EVQP2202M                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1.6 N           | 2.1 mm   | White            | 1,000,000 cycles |
| EVQP2202W                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 1.6 N           | 2.5 mm   | White            | 1,000,000 cycles |
| EVQP2402M                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2.4 N           | 2.1 mm   | White            | 500,000 cycles   |
| EVQP2402W                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2.4 N           | 2.5 mm   | White            | 500,000 cycles   |
| EVQP2602M                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3.5 N           | 2.1 mm   | White            | 200,000 cycles   |
| EVQP2602W                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 3.5 N           | 2.5 mm   | White            | 200,000 cycles   |
| EVQP9W02W                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 4.0 N           | 2.5 mm   | White            | 200,000 cycles   |
| EVQP9P02M                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 5.0 N           | 2.1 mm   | White            | 200,000 cycles   |
| EVQP9P02W                                                                         | Without                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 5.0 N           | 2.5 mm   | White            | 200,000 cycles   |


Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.  
Should a safety concern arise regarding this product, please be sure to contact us immediately.

### ■ Dimensions in mm (not to scale)




| Part Numbers | Ground Terminal | Operating Force | H=Height | Push Plate Color | Operating Life   |
|--------------|-----------------|-----------------|----------|------------------|------------------|
| EVQP2P02M    | With            | 1.0 N           | 2.1 mm   | White            | 1,000,000 cycles |
| EVQP2P02W    | With            | 1.0 N           | 2.5 mm   | White            | 1,000,000 cycles |
| EVQP2R02M    | With            | 1.6 N           | 2.1 mm   | White            | 1,000,000 cycles |
| EVQP2R02W    | With            | 1.6 N           | 2.5 mm   | White            | 1,000,000 cycles |
| EVQP2T02M    | With            | 2.4 N           | 2.1 mm   | White            | 500,000 cycles   |
| EVQP2T02W    | With            | 2.4 N           | 2.5 mm   | White            | 500,000 cycles   |
| EVQP2V02M    | With            | 3.5 N           | 2.1 mm   | White            | 200,000 cycles   |
| EVQP2V02W    | With            | 3.5 N           | 2.5 mm   | White            | 200,000 cycles   |
| EVQP9H02M    | With            | 5.0 N           | 2.1 mm   | White            | 200,000 cycles   |
| EVQP9H02W    | With            | 5.0 N           | 2.5 mm   | White            | 200,000 cycles   |

### ■ Recommended Reflow Soldering Conditions



### ● Embossed Carrier Taping



Taping condition : Lack of products in the middle of taping should be one MAX, but total quantity specified in the specifications should be secured.


Peeling off strength of top tape : It should be within 0.2N to 1.0N at 165 degree in peeling off angle.

Joint of carrier tape : One joint per one reel may exist.


Unit: mm

| Part No. | Height | A       | B       | W        | F       | E         | $P_1$   | $P_2$   | $P_0$   | $D_0$ Dia.                        | $t_1$   | $t_2$   |
|----------|--------|---------|---------|----------|---------|-----------|---------|---------|---------|-----------------------------------|---------|---------|
| EVQP2    | 2.1    | 6.0±0.2 | 4.7±0.2 | 12.0±0.3 | 5.5±0.1 | 1.75±0.10 | 8.0±0.1 | 2.0±0.1 | 4.0±0.1 | 1.5 <sup>+0.1</sup> <sub>-0</sub> | 0.3±0.1 | 2.7±0.2 |
| EVQP9    | 2.5    |         |         |          |         |           |         |         |         |                                   |         |         |
| EVQ3P2   |        |         |         |          |         |           |         |         |         |                                   |         |         |

### ■ Recommended Shape of Test Pole



### ■ Recommended Operating Conditions



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Panasonic:

[EVQ-P2002W](#) [EVQ-P2202W](#) [EVQ-3P2F02K](#) [EVQ-P2402M](#) [EVQ-P2T02M](#) [EVQ-P2K02Q](#) [EVQ-P2402W](#) [EVQ-P2B02B](#) [EVQ-P2202M](#) [EVQ-P2V02M](#) [EVQ-3P202K](#) [EVQ-P2002M](#) [EVQ-P2602M](#) [EVQ-P2602W](#) [EVQ-P2D02Q](#) [EVQ-P2F02K](#) [EVQ-P2H02B](#) [EVQ-P2P02M](#) [EVQ-P2P02W](#) [EVQ-P2R02M](#) [EVQ-P2R02W](#) [EVQ-P2T02W](#) [EVQ-P2V02W](#) [EVQ-P9P02M](#) [EVQ-P9H02W](#) [EVQ-P9P02W](#) [EVQ-P9H02M](#) [EVQ-P9W02W](#) [EVQ-P9102M](#) [EVQ-P9102W](#) [EVQ-P9W02M](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)