



### Main

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCA LUCB LUCC LUCD LUCL LUCM
Device application	Communication
Range compatibility	TeSys TeSys U LUB non reversing power base TeSys TeSys U LU2B reversing power base

### Complementary

Function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	Open style connector
Bus type	DeviceNet
Communication port protocol	CAN2.0A CAN2.B
Addressing	0...63
Current consumption	1.5 mA at 24 V DC 20...28 V
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	1 2 dedicated to starter-controller coil operation
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GL fuse 2 A
Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	0.2 in (5 mm) open style DeviceNet 0.15 in (3.81 mm)
Connections - terminals	Screw clamp terminals 2 cable 0 in <sup>2</sup> (0.75 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0...0 in <sup>2</sup> (0.14...1 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0...0 in <sup>2</sup> (0.14...1 mm <sup>2</sup> ) - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0...0 in <sup>2</sup> (0.25...0.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0...0 in <sup>2</sup> (0.25...1 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0...0 in <sup>2</sup> (0.14...0.5 mm <sup>2</sup> ) - cable stiffness: rigid - without cable end Screw clamp terminals 2 cable 0...0 in <sup>2</sup> (0.14...0.75 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0...0 in <sup>2</sup> (0.25...0.34 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end BUS 1 cable 0...0 in <sup>2</sup> (0.2...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end BUS 1 cable 0...0 in <sup>2</sup> (0.25...2.5 mm <sup>2</sup> ) - cable stiffness: rigid - without cable end BUS 1 cable 0...0 in <sup>2</sup> (0.25...2.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end BUS 2 cable 0...0 in <sup>2</sup> (0.14...0.5 mm <sup>2</sup> ) - cable stiffness: rigid - without cable end BUS 2 cable 0...0 in <sup>2</sup> (0.25...1 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end BUS 2 cable 0...0 in <sup>2</sup> (0.5...1.5 mm <sup>2</sup> ) - cable stiffness: flexible - with cable end

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

	BUS 2 cable 0...0 in <sup>2</sup> (0.5...1.5 mm <sup>2</sup> ) - cable stiffness: flexible - without cable end
Associated cable type	AWG 26...AWG 16 screw clamp terminals AWG24...AWG16 BUS
Tightening torque	1.77...2.21 lbf.in (0.2...0.25 N.m) flat Ø 2.5 mm 4.42...5.31 lbf.in (0.5...0.6 N.m) flat Ø 3.5 mm

## Environment

standards	IEC 62026-1
ambient air temperature for operation	-13...131 °F (-25...55 °C)
IP degree of protection	IP20 IEC 60529

## Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)